


Optics issues for Phase 1 and Phase 2 upgrades



Massimo Giovannozzi, CERN

- Outline:
 - Option for Phase 1 and 2 upgrades.
 - Development and issues of Phase 1 upgrade studies.
 - Issues of Phase 2 upgrade studies.
 - Conclusions and outlook.

Acknowledgements: AB and AT colleagues contributing to the upgrade studies

LHC IR Upgrade options - I


- Phase 1: consolidation of 'ultimate' performance with $L > 10^{34} \text{cm}^{-2} \text{s}^{-1}$
 - Large aperture NbTi triplet magnets using existing spare dipole cables.
 - The goal is also of introducing additional margins for the LHC operation.
 - No modifications of the experiment interface and cryogenic infrastructure.
 - Opening the option for operation with $\beta^* = 0.25 \text{ m}$ and the LHC 'ultimate' beam.

LHC IR Upgrade options - II

- Phase 2: ambitious upgrade of luminosity with $L \sim 10^{35} \text{cm}^{-2}\text{s}^{-1}$
 - Aims at operation beyond ultimate luminosity (the goal is integrated L).
 - Implies operation in extremely radiation hard environment (35 MGy/year).
 - Less than 1 year lifetime for magnets with nominal triplet layout!
 - New magnet technology and /or special protection / absorber elements.

The path to Phase 1 layout - I


- Technological challenge of large aperture quadrupoles (see presentation of E. Todesco): where are the limits of gradient vs. aperture?



From E. Todesco, J.-P. Koutchouk,
LUMI' 06 Proceedings

The path to Phase 1 layout - II



- Huge parameter space: semi-analytical approaches and fitting to determine Twiss parameters vs. free parameters



From E. Todesco, J.-P. Koutchouk, LUMI' 06 Proceedings.

The path to Phase 1 layout - III

- Huge parameter space: analytical approaches applied to a slightly simplified system to fix the overall optical parameters prior to detailed analysis are needed.



R. De Maria, LHC Project Report 1051.

08/11/2007

M. Giovannozzi – CARE-HHH-APD IR'07


6

The path to Phase 1 layout - IV

- Guidelines for the optical design:
 - Aperture is the first requirement. General criterion:
 - $33 \sigma + 12 \text{ mm}$ needed in the triplets
 - Open question: how much aperture margin do we need? And what is the best use of it, e.g.
 - Mitigation of energy deposition issues (still to be studied in details, see presentation by E. Wildner).
 - Mitigation (but not solution!!!) of impedance issues due to collimators.
 - Keep β_{max} under control (impact on chromaticity, off-momentum beta-beating and single-particle dynamic aperture).

The path to Phase 1 layout - V


- A word on off-momentum beta-beating:
 - Nominal LHC:
 - $3/8 \cdot 10^{-4} \Delta p/p \rightarrow 10\%/30\%$
 - Correction means (see S. Fartoukh LHC Project Report 308)
 - Phasing IPs
 - Chromatic sextupoles (32 families/beam)
 - NB: off-momentum beta-beating can be corrected only in one half of the machine.



The path to Phase 1 layout - VI

- Apart on aperture, off-momentum beta-beating has an **impact on collimation performance**.
- How to choose in which half of the machine the beating has to be corrected?
 - **Driving criterion:** avoid that a secondary collimator becomes a primary one.

FOR the nominal LHC the correction should be made between IR5 and IR1.



The path to Phase 1 layout - VII

- Concerning field quality issues, it is worth mentioning that:
 - Recently a useful result was obtained concerning the dependence of the triplets field quality on aperture (E. Todesco et al. LHC Project report 1010).

$$\sigma(b_n, a_n; \alpha\phi, d, \alpha R_{ref}) = \frac{1}{\alpha} \sigma(b_n, a_n; \phi, d, R_{ref})$$


- The impact of these scaling laws on dynamic aperture clearly observed (see presentation by R. Tomás).
- Hardware constraints such as modularity (optimize the tooling and the spares) have to be considered.

The path to Phase 1 layout - VIII

- Putting everything together:

Detailed discussion of the four optics under consideration for the Phase 1 upgrade by R. de Maria.

From R. de Maria LIUWG presentation 18/10/07



The path to Phase 1 layout - IX

- Usually the focus is always on the triplets, but the long straight section needs also revision and detailed analysis (see S. Fartoukh LIUWG presentation 27/09/07):
 - D1 (warm design): its aperture has to be increased!
 - Modification to the current design proposed (J.-P. Koutchouk and D. Tommasini): very cost-effective.
 - Should a cold D1 be considered?
 - D2, Q4, Q5: a rotation of the beam screens should fix the aperture issues. Possibility of designing a two-aperture Q4 with increased aperture assessed (E. Todesco).
 - The rest of the long straight section is essentially compatible with Phase 1 upgrade requirements.

The path to Phase 1 layout - X


- Next steps:
 - Convergence to a smaller number of optics candidates (two). Each should be studied in terms of:
 - Overcome the observed limitations in the optics.
 - Provide a complete solution compatible with the hardware constraints (cryostats parameters, instrumentation).
 - Study tunability of the optics.
 - Study injection optics.
 - Study squeeze sequence.
 - Evaluate the performance of a flat beam option.
 - Beam-beam simulations.
 - Collimation performance.

The beneficial effect of flat beams - I

Potential of Flat Beam: Aperture

- Triplet beam screen orientation for H/V crossing

Round beam configuration (V-crossing in ATLAS, H-crossing in CMS) Flat beam configuration (H-crossing in ATLAS, V-crossing in CMS)



→ In all cases, the average b-b separation is set to $9.5 \cdot \sigma_{x/y}$ (for H/V crossing)

→ Find the optimum between beam-screen and beam aspect ratio

The beneficial effect of flat beams - II

Conclusions

- The LHC experimental insertions are very **flexible**.
- Extremely good **Field Quality** of the triplet magnets.
 - will allow to produce and test a large variety of flat beam collision optics:
 $\sqrt{\beta_x^* / \beta_y^*} \equiv r = 1/2 \rightarrow 2$ (range given by the triplet beam screen aperture).
 - if needed, will allow V-H, H-V, V-V or H-H crossing scheme with round-round, flat-flat, round-flat or flat-round beam optics in IR1 and IR5.
- While strong (parasitic) beam-beam limitations occur at nominal intensity, **staging the IP beam aspect ratio with intensity** allows
 1. To **push the lumi by up to 20%** at max. β^* (aperture saturated) and medium intensity: **< 60% of nom. intensity** → see flat beam case 4, with $r \sim 1.7$.
 2. **Up to ~ 80% of the nominal intensity**, to **enlarge the triplet aperture by 15%** ($n1=8$ instead of 7) at constant lumi, e.g. in case of direct or indirect problem (impedance) related to collimation → see case 5a, with $r \sim 1.45$.
 3. To **enlarge the b-b separation by ~ 15-20%** at **full intensity**, constant aperture but slightly reduced lumi, e.g. in case of unexpected beam-beam related difficulties → see case 5b, with $r \sim 1.45$ and b-b sep. of $\sim 11\sigma$.

Phase 2: introduction - I

- Current studies look for a 10-fold increase in the peak luminosity. Two options (doubling the bunch number not possible):
 - **ES (25 ns):** Low β^* (11 cm – 14 cm) with ‘ultimate’ beam parameters requiring significant hardware modifications in the IR & detector regions.
 - **LPA (50 ns):** operation with larger than ‘ultimate’ beam intensities and ‘flat bunches’ but without modifications in the detector regions.

Phase 2: introduction - II

- Additional measured required for a Phase 2 upgrade:
 - Upgrade of the cryogenic plants for IR1 and IR5 (additional new plants).
 - Improved shielding and protection of triplet magnets.
 - Both Phase 2 options require additional measures that go beyond magnet.
 - R&D and that could benefit already the Phase 1 upgrade.

Phase 2: optics concept

R. De Maria, LHC Project Report 1051

distance to IP	l^*	(m)	23	13
quad length	$l(Q1-Q3)$	(m)	7.3	9.3
quad length	$l(Q2)$	(m)	6.5	6.8
total quad length	l_q	(m)	27.5	32.1
triplet length	l_t	(m)	34.1	38.7
Gradient Q1	G_1	(T/m)	166	169
Gradient Q2	G_2	(T/m)	166	169
Gradient Q3	G_3	(T/m)	166	141
B peak estimate	B_p	(T)	13.7	13.5
Aperture	ϕ	(m)	0.150	0.145
β funct. in IP	β^*	(m)	0.142	0.112
Max β funct. in Q1-Q3	β_{\max}	(m)	18700	16800


J.-P. Koutchouk *et al.*, PAC07.

Additional changes in the long straight section (see S. Fartoukh LIUWG presentation 27/09/07):

- Beam screen rotation in D2, Q4, Q5.
- Q4, Q5 must be replaced with large aperture magnets.
- 120-130 mm gap requested for D1 (cold D1 might be the only possible option).
- 95-100 mm aperture requested for D2 (Warm D2, e.g. MBW type, might be the only possible option).


08/11/2007

M. Giovann




Additional measures for Phase 2 - I

Minimizing the luminosity loss due to the crossing angle:



The crossing angle results at the IP in an increase of the effective cross section and thus a reduction of the luminosity.

Assuming a constant normalized beam separation the reduction factor decreases with decreasing β^* !




$$F = \frac{1}{\sqrt{1 + \phi^2}}; \quad \phi \equiv \frac{\theta_c \sigma_z}{2\sigma_x} \quad \text{Piwinski angle}$$

Additional measures for Phase 2 - II

Minimizing the luminosity loss due to the crossing angle at the IP:

Compensate the long range beam-beam effects, thus allowing a smaller angle




- New proposal and technology, requiring MDs (USLARP & CERN@)
- Could potentially reduce the required crossing angle
- Similar proposal for head-on collisions: electron lens

Additional measures for Phase 2 - III

Minimizing the luminosity loss due to the crossing angle at the IP:

Reduce the crossing angle at the IP via dipole magnets deep inside the detectors (slim dipole option)




- Requires magnet integration inside the detectors.
- Impact on detector performance and physics reach.
- Requires new magnet technology.
- Implies beam-beam studies (numerical and experimental).

Additional measures for Phase 2 - IV

Minimizing the luminosity loss due to the crossing angle at the IP:

Bunch rotation via crab cavities. It implies a new technology for protons.




- Requires high precision RF technology and control.
- Currently used in KEK B-factory.
- No experience with operation in proton machines (noise).
- Requires prototyping and machine studies (lead time and resources).

Additional measures for Phase 2 - V

Minimizing the luminosity loss due to the crossing angle at the IP:

Bunch rotation via crab cavities. It implies a new technology for protons.



Compensate the head-on beam-beam force by additional e-/p⁺ interactions (opposite sign of the p⁺/p⁺ beam-beam force).

- Development of a prototype ‘electron lens’ at FNAL.
- This new tool is currently studied / tested in Tevatron (and RHIC in 2008).
- Still open issues: Tevatron observes significant operation improvements (lens as a fast quadrupole), but no successful operation as beam-beam lens.

Additional measures for Phase 2 - VI

Operation with large Piwinski angle:


- 40% higher luminosity for flat bunch profile.
 - Increased luminosity lifetime.
 - Does the flat bunch remain flat (proved in injectors for short times)?

Luminosity leveling (see talks by J.-P. Koutchouk and G. Sterbini):

- Can it be performed in real operation?

Phase 2 luminosity potential reach

average luminosity [$10^{34} \text{ cm}^{-2} \text{ s}^{-1}$]



- Average luminosity over one physics run assuming optimum run length.
- Estimates done without luminosity leveling.
- Phase 2 might provide average luminosity increase by a factor 3 to 4 in most optimistic scenario.

Conclusions and outlook

- Phase 1:
 - Essentially new magnets are required, only.
- Phase 2:
 - New magnets are required and (not all together):
 - wire compensators
 - integrated dipole magnets
 - crab cavities
 - electron lens
 - Flat beam operation
 - Luminosity leveling
 - Magnets TAS, absorbers, and masks

All additional measures for the Phase 2 upgrade could benefit the Phase 1 upgrade. They should be launched before Phase 2!