

A multitude of Magnets for HL-LHC, and beyond

or: "Be fruitful and multiply, and fill the Tunnel, and subdue the Bosons" (Genesis, 1:28)

Luca.Bottura@cern.ch for TE-MSC

Superconducting Technologies for Next Generation of Accelerators



CERN - GLOBE of Science and Innovation
4-5 December 2012



Outline

- Magnet overview for HL-LHC
- Ideas for an implementation
- Other needs for LHC
- Beyond LHC




Outline

- Magnet overview for HL-LHC
- Ideas for an implementation
- Other needs for LHC
- Beyond LHC




Magnet geography for HL-LHC







The LHC most affected zone (MAZ)




300 m x 4 +... : about 1.5 km long accelerator, pushed performance in a high radiation environment: 10...100 MGy



The MAZ in real life

D1, towards DFBX





A catalog of magnet units

Magnet type	Name	Quantity	Peak Field (T)	Coil bore (mm)	Length (m)	Energy (MJ)	Deadline (year)
Twin Dipole	DS-MB	1020	11	60	11 (2×5.5)	11	2017/202
Quadrupole	Low-β Q1/Q2/Q3	16	1213	150	8-10	12	2020
Dipole	D1	4	5	160	8	6	2020
Twin Dipole	D2	4	35	100 (?)	5-10	?	2019
Twin Quadrupole	Q4	4	8	8590	4.5	1.2	2019
Twin Quadrupole	Q5	4	8?	70	4.5	0.6	2019


NOTE

Most of the above units must be intended as cryostated cold masses, containing multiple single magnets (e.g. Q2), suitable (TBD) corrector packages (orbit, trims, field errors) and the transitions/interconnections to the next magnet/feedbox



IR-quadrupoles: MQXC


Material		NbTi
Aperture	(mm)	120
Gradient	(T/m)	118
Current	(A)	12850
Temperature	(K)	1.9
Peak field	(T)	8.1




- Self-locking collars, porous insulation
- Result of EU-financed SLHC-PP development, R&D approaching completion
- Lengths and quantities:
 - Q1/Q3: 9.5 m magnets (8 magnets + 2 spares)
 - Q2: 2 x 8 m magnets (8 magnets + 2 spares)
 - A total of some 20 magnets to be produced




Why do we go for Nb₃Sn?





1 mm, 192 tubes PIT from **Bruker EAS**




Year

0.7 mm, 108/127 stack RRP from **Oxford OST**



DS: collimators & 11 T dipoles




LS2 2017-18: IR-2 (demonstration)

LS3 2020: IR7/8, IR1/5 as part of HL-LHC (TBC)

CERN

DS-MB


Material		Nb₃Sn
Aperture	(mm)	60
Field	(T)	10.8
Current	(A)	11850
Temperature	(K)	1.9
Peak field	(T)	11.3




- Twin aperture, collared coils
- R&D in collaboration with Fermi National Laboratory (Chicago, IL)
- Lengths and quantities:
 - LS2: 4 x 2 x 5.5 m magnets (8 magnets + 2 spares)
 - LS3: 16 x 2 x 5.5 m magnets (32 magnets + 3 spares)
 - A total of some 45 magnets to be produced



11 T (MBHSP01) test results at FNAL





Quench performance short of the 11 T objective. Some deviations observed between expected and measured field quality

There is work to do




See the talk of M. Karppinen



IR-quadrupoles: MQXF


Material		Nb ₃ Sn
Aperture	(mm)	150
Gradient	(T/m)	140
Current	(A)	17300
Temperature	(K)	1.9
Peak field	(T)	12.2



- Bladder-and-key structure
- Common R&D with US to develop model (2014) and prototype (2015)
- Lengths and quantities:
 - $-Q1/Q3: 2 \times 4 \text{ m magnets (16 magnets + 2 spares)}$
 - Q2: 2 x 6.8 m magnets (8 magnets + 2 spares)
 - A total of some 30 magnets to be produced




HQ cold test in SM18





D1 separation dipole

Material		NbTi
Aperture	(mm)	160
Field	(T)	5.2
Current	(A)	11000
Temperature	(K)	1.9
Peak field	(T)	6.1




- Single layer coil, large iron saturation (stray field), large forces on the coil/structure
- R&D in collaboration with Japan (KEK)
- Lengths and quantities:
 - D1: 7.7 m magnets (4 magnets + 2 spares)
 - A total of 6 magnets to be produced



D2 recombination dipole

Material		NbTi
Aperture	(mm)	90100
Field	(T)	o(4)
Current	(A)	
Temperature	(K)	1.9
Peak field	(T)	




- Single layer coil, large iron saturation (stray field), large forces on the coil/structure
- R&D in collaboration with BNL (US)
- Lengths and quantities:
 - D2: o(10) m magnets (4 magnets + 2 spares)
 - A total of 6 magnets to be produced



MS-quadrupoles: Q4

Material		NbTi
Aperture	(mm)	90
Gradient	(T/m)	120
Current	(A)	16188
Temperature	(K)	1.9
Peak field	(T)	5.9



- Single layer coil using LHC-type2 cable (spare)
- R&D in collaboration with CEA-Saclay
- Lengths and quantities:
 - Q4: 4.5 m magnets (4 magnets + spares)
 - A total of 6 magnets to be produced




Correctors


- At present, the corrector layout for HL-LHC is not finalized, however ...
- ... we have a fairly good idea from the existing LHC, and the Phase-I (SHLC-PP) study:

	Current	Integrated strength (field)	Coil Aperture
MCXB (B_1/A_1)	+/- 2.4 kA	1.5 Tm	140 mm
MQXS (A ₂)	+/- 2.4 kA	0.55 Tm@40 mm	140 mm
$MCXT(B_6)$	+/- 120A	0.075 Tm @ 40 mm	140 mm
$MCXO(B_4)$	+/- 120A	0.035 Tm @ 40 mm	140 mm
MCXSO (A ₄)	+/- 120A	0.035 Tm @ 40 mm	140 mm
MCXSS (A ₃)	+/- 120A	0.055 Tm @ 40 mm	140 mm
MCXS (B ₃)	+/- 120A	0.055 Tm @ 40 mm	140 mm




A zoo of correctors






MCXB (single layer): design and winding trials

MCXBH+V (nested): concept





6 units

MCBX with nested high-order correctors

MQSX (single layer): concept

MCXS, MCXSS MCXO, MCXSO: prototype (CIEMAT)

MCXT



Outline

- Magnet overview for HL-LHC
- Ideas for an implementation
- Other needs for LHC
- Beyond LHC



An industrial action for HL-LHC

- CERN must have all technologies in hand to insure the long-term exploitation of the LHC (includes tooling)...
- However, CERN does not need to build all components that enter in the LHC!
- At present, US is proposing the largest contribution to the HL-LHC construction (o(250 MCHF))...
- However, a large share is not covered!
- CERN is launching an industrial action to attract EU-industries on-site, to develop Nb₃Sn magnet technology for HL-LHC, and prepare for the magnet construction in the period 2016-2020
- We are convinced that this R&D can have far-reaching consequences on SC magnet technology



Outline


- Magnet overview for HL-LHC
- Ideas for an implementation
- Other needs for LHC
- Beyond LHC




SC links By courtesy of A.Ballarino, CERN

HTS tapes

Round wires








 Φ = 75 mm Itot =190 kA @ 25 K (2 imes 95 kA)


 Φ = 60 mm Itot =100 kA @ 25 K (2 imes 50 kA)



Repositioning the converters in the cavern

See also the talk of A. Ballarino

Removal of the converters from the cavern






Removal/installation

- The LHC-IR region is crowded, limited access, and will be activated by LS3
- Removal of magnets would result in relatively high dose, unless performed using (closely controlled) remote handling tools
- New magnets will have to survive (10 times) harsher conditions and remote handling should be planned from the
 - Design and manufacturing features
 - Associated RH tools and machines





start



Other magnet needs



- 15 dipoles and 4 quadrupoles will be exchanged during LS1
- Some 25 magnets to be re-built, a few (10?) to be prepared for installation during LS2
- Irradiation dose of magnets next to collimators (MBW, MQW) is of concern – shielding!
- Spare coils, new spare magnets (4+4) to be built for installation during LS2

LHC is a living machine



Outline

- Magnet overview for HL-LHC
- Ideas for an implementation
- Other needs for LHC
- Beyond LHC



Is there a physics beyond the LHC?





Also on the www: HE-LHC Scope

http://indico.cern.ch/conferenceDisplay.py?confId=97971

- "[...] a 33 TeV centre-of-mass energy proton—proton accelerator in the LHC tunnel [...] and the need for new injectors, possibly with 1 TeV energy". (The High-Energy Large Hadron Collider, CERN—2011—003, also EuCARD—Conf—2011—001)
- Technicolor, Supersymmetry, Extra dimensions: "[...] the need to explore the high energy frontier will remain. We will always be able to make that case, today and tomorrow". (Elements of a Physics Case for a High-Energy LHC, J.D. Wells, pp. 1-5, CERN-2011-003, 2011)
- "A project on the scale and innovation level of the HE-LHC has a long preparation lead time". (CERN Accelerator Strategy, S. Myers, pp. 6, CERN-2011-003, 2011)












A really high field dipole

- Engineering extrapolation is difficult, but does not seem impossible
- May require a genetic mutation in the art of SC magnet design an construction








By courtesy of E. Todesco



Program FP7: EuCARD2 - May 2013


Develop 10 kA class HTS accelerator cable using Bi-2212 and YBCO. Test stability, magnetization, and strain tolerance



Build a 5 T, 40 mm bore HTS

accelerator quality
dipole as a technology
demonstration









Low-field magnets – a new frontier?

Injection field	(T)	0.14
Injection current	(A)	500
Flat-top field	(T)	1.8
Flat-top current	(A)	5800
Ramp time	(s)	1.1
Field ramp-rate	(T/s)	1.5
Good field region	(mm²)	42 x 30
AC loss	(W/m)	< 2





New concepts for improved energyefficiency have been tested, with typical parameters range of interest for the CERN injector complex



Summary

- The physics case for an HL-LHC is strong: it would be utterly unreasonable to scrap the upgrade of a machine that is producing physics at the frontier of our knowledge
- The magnet challenges are many, they are tough, they are motivating, and they open a new window onto large scale applications of superconductivity
- And there is more, beyond magnets for HL-LHC
- This is why we want to make sure you are on board in this new adventure!

