

... for a brighter future



UChicago
Argonne



A U.S. Department of Energy laboratory managed by UChicago Argonne, LLC

Status of the APS RF Systems

Ali Nassiri Accelerator Systems Division Advanced Photon Source



Workshop on High Power RF

Outline

- Introduction
- Technical Systems
- Highlights
- Beam Instability
- RF Operational Statistics
- Summary







Short into to APS



- 7 GeV, 102 mA x-ray synchrotron operating since 1995
- 31 insertion devices (ID) beamlines and 24 bending magnet beamlines
- >3,000 users per year
- >98% availability, 9
- 3.1 nmm eff. emittance, 1%coupling
- Flexible bunch patterns and lattice





Injector Configuration









Linac RF

- S-Band Linac
- 450 MeV Linac
- Thermionic rf gun
 - 1.6-cell, π mode
 - Macropulse current 1A, 4.5 MeV
 - Emittance ~ 5 π mm-mrad (rms)





BNL/ATF photocathode

L2

Wave Guide Switching System

L1

- ~200 pC/bunch
- 300-A peak
- 3 πmm-mrad (rms)
- 5 MeV
- 119-MHz Nd:Glass laser
- 260 fs Up-conversion IR to UV
- 400 μJ pulse (~1.5 ps FWHM)





March 25, 2008





Linac RF System Enhancements

- Built and installed a Signal Filtering Chassis (SFC) in all modulators which significantly improved the overall reliability by reducing the amount of unnecessary trips caused by noise.
- Designed, built and installed saturating chokes in series with the thyratrons to delay the thyratron current pulse and reduce switch losses for increased thyratron lifetime.
- Installed new thyratron trigger units with grid pre-pulsing for improved thyratron stability and lifetime.
- Installed new arc detectors viewing the klystron windows, which features increased diameter, radiation resistant, optical fiber and greater circuit gain..



Signal Filtering Chassis



Saturating Choke







Linac RF System Enhancements (2)

- Built a high-voltage "Corona Test Cage" for testing the reliability of high-voltage rf components.
- Implemented new high-voltage cable connectors in all modulators to reduce corona discharge and prevent highvoltage cable failures.
- A "Roll-Around" spare klystron oil tank with klystron was built to reduce operational down-time when a klystron replacement is required.
- Designed, built and installed easy-toremove "End of Line" clipper assemblies in all modulators for improved downtime.



Spare "Roll-Around" klystron / Tank



End of Line Clipper Assembly





Particle Accumulator Ring (PAR)

- Accumulates charge from the linac
 - Reduces need for high charge gun (5× reduction)
 - Can routinely provide 5 nC/pulse
 - Can potentially reach operating envelope of 10 nC/pulse
- Compresses bunch from 10-30 ns to 2.8 ns to provide "pure" injection into booster synchrotron
 - Reduces need for short-pulse gun (10×reduction)
- Fundamental RF system @9.8 MHz
 - Design is 40 kV, routinely operates at ~31 kV (325 MeV)
- Harmonic RF system @117 MHz
 - Design is 30 kV, routinely operates at ~27 kV (325 MeV)







PAR RF Cavities



- Plunger-loaded reentrant coaxial structure.
- 1.6 m in length with a radius of 0.72 m and an accelerating gap of 13 cm.
- Reentrant type coaxial cavity.
- 60 cm in length with the outer conductor diameter of 1m and the inner conductor diameter of 30 cm.



CERVIC VINCOV

March 25, 2008

9

Ferrite tuners are used for both cavitiesCopper housing with toroidal ferrite cores.



	Toshiba M4C21A	Stackpole C/14
O. D. (inches)	8.0	8.0
I. D. (inches)	5.0	5.0
Height (inches)	1.0	1.0
Initial permeability	42	12.5
Magnetic loss tangent	0.0085	
Curie temperature (°C)	340	510
Saturation magnetization (gauss)		2100
Dielectric constant	13.0 @40MHz	10.5
Dielectric loss tangent	0.0003 @40MHz	





PAR RF System Enhancements (2)

- Replaced obsolescent pulse generators driving the harmonic par with VXI based arbitrary function generators, achieving a major improvement in controllability of the generators and stability of the compressed pulse.
- Provided extensive support for the par bunch cleaning design, installation, and commissioning effort, including evaluation of mixers, low and high power amplifiers, and variable phase shifters/ delay lines, arranging packaging, and defining interfaces and spares.
- Ensured equal performance of the back up harmonic par power amplifier by upgrading the high voltage power supply with a new power transformer identical to the one in the alternate triode tube amplifier system.



Original Function Generator



New VXI-based Function Generator





PAR High Power RF Switching Systems

- Switching system controlled by operators using EPICS control screens.
- Both fundamental par and harmonic par uses a high power rf switching system. The LLRF drive to the tube amplifier and the high power rf switch, switch simultaneously.
- Operators can quickly switch high power rf amplifier systems in the event of a failure therefore increasing availability or improving down-time.



Fundamental Par High Power RF Switching

March 25, 2008





APS Operating Modes, 102 mA

Multi bunch 324 / 1296 24 Singlet Hybrid with singlet 1 + 8*711.37 nsec x 324 / 2.84 nsec x 1296 8x7 (86 mA) 153 nsec 1.59 μs 1x1 (16 mA) **APS FY 2008** Long Range Operations Schedule Current 45.0 102.5 Run 2008-01 Run 2007-03 Run 2008-02 Lifetime 6 44.5 Shutters 102.0 44.0 5 ue 43.5 d O (hours) (mA) 4 s 43.0 42.5 42.5 101.5 Current Lifetime 3 $4 \rightarrow$ 2 1.01.0 42.0 41.5 100.5 41.0 '2246h 21 d1 86 22d0h 22d12h Time starting Fri Mar 21 13:37:09 2008 User Operation in standard lattice Weekends Lab Holidays SOM Periods Machine Studies User Operation in Reduced Horizontal Beam 1 Hybrid Fill - (singlet) Maintenance Lattice (RHB) 4 324 Singlets - Non Top-Up Shifts set aside for Studies/ Machine Intervention as Needed Plot generated Sat Mar 22 14:49:09 CDT 2008 Top-Up Operations is standard unless indicated in fill pattern Fill pattern is 24 singlets unless otherwise indicated by number



Status of the APS RF Systems



Multibunch Instability at high current

- APS storage ring is normally operated with 102 mA
- A number of high-current studies were carried out to determine MBI limits.
- The longitudinal MB instability is dominated by the rf cavity HOMs and the CBI threshold.
- Beam stable with 324 bunches (200 mA)
- CBI threshold is 245 mA
- With 24 bunches (above 160 mA)
 - Several components approaching temperature limits
 - Ceramic kicker chambers
 - HOM dampers
 - No CBI observed at this current
- Transverse MBI are mostly driven by the resistive wall impedance
 - Cure: rely on the chromaticity to stabilize the transverse MBI.







Multibunch Instability at high current (2)

- Kicker chamber redesign
 - Mitigate excessive heating



Argonne A. Nassiri

Status of the APS RF Systems



Multibunch Instability at high current (3)

- HOM Dampers
 - Rf cavity HOMs have been long known to potentially drive longitudinal CBIs in the APS
 - Instability is stongly bunch-pattern dependent
 - In 24-bunch operation, the lowest monopole 540-MHz HOM was found to drive CBI at a threshold of about 85 mA
 - Typical cure
 - Detuning the offending cavities
 - Adjusting the cooling water temperature
 - However, it became more difficult to find stable operating points for all cavities.
 - HOM dampers were designed and installed in one sector (38)
 - It provide a de-Qing factor of about 8





CWRF2008 March 25, 2008

Longitudinal Limits

- We can stably store 164 mA in 24 bunches. No CBIs.
- We concluded that the HOM dampers have raised the threshold by at least 60%
- However, several SR components are approaching temperature limits above ~160 mA.
- With 324 bunches, the beam is stable up to a CBI threshold of ~245 mA
- The dominate mode numbers are 36, 78, and 151
 - 538 MHz, 1211 MHz, 915 MHz





CWRF

March 25, 2008



352 MHz RF System Layout

Five 352-MHz/1MW

- RF1-RF4 for storage ring (CW)
- RF5 for booster (ramped)

Waveguide Switching System provides:

- Easy switch to hot standby system
- RF3 backup for RF5 in Booster service
- Parallel-klystron mode for storage ring operation greater than 150mA
- RF1 feeding power to 350-MHz RF Test Stand

Waveguide shutters provide personnel safety isolation in waveguide.





352 MHz RF Switching Scheme





Status of the APS RF Systems



8

2MW POWER SYSTEM FOR SR & BOOSTER









March 25, 2008

19





RF System Components

Waveguide Switching System



Waveguide Switch



PLC Control



Waveguide Shutters



Waveguide Phase Shifter

Klystrons and Power Supplies



352-MHz/1MW CW Klystron







2 MW DC Klystron Power Supply

One Sector of Storage Ring RF Cavities



VXI Analog Low-Level RF Electronics





Status of the APS RF Systems





Highlights

Mar 2002 : 130mA storage ring operation demonstrated.

aa

- Apr 2002: Successful user run at 130mA.
- Sept 2003: Successful demonstration of parallel-klystron operation involving all four storage-ring rf systems – 115mA stored.
- Dec 2003: 225mA storage ring operation demonstrated utilizing parallel-klystron operation.
- Apr 2005: 150mA storage ring operation after Sector 38 HOM damper installation.
- Apr 2005: Demonstrated storage-ring bunch shortening utilizing rf phase modulation technique.
- Aug 2005 250mA storage ring operation
- Oct 2006: Successful use of RF3 in Booster-mode for one week while repairs on RF5 were completed.
- Oct 2007: 200 kW operation of a single-cell cavity with dual coupler



352 MHz RF System Enhancements

Installed 60Hz ripple-rejection boards to reduce noise on storage ring rf.

- Reduce beam motion
- Installed WR2300 waveguide shutters.
 - Enhanced personnel safety at test stand, and allowed smoother transition to RF3-Booster operating mode
- Upgraded RF Source equipment rack.
 - Improved overall reliability and mean-time-to-repair
- Designed and implemented new feedback card design.
 - Improved overall reliability
- Upgraded computers in rf system power supplies.







352 MHz RF System Enhancements (2)

- Installed E-Probe HOM dampers in Sector 38 rf cavities
- Upgrade storage ring rf cavity blower controls
 - Improved overall reliability
- Installed PLC interlock system upgrades at three storage ring rf system
 - Improved overall reliability
- Matching Transformer 1400V:13.2kV:
 - Installed cooling fan and control system
 - Added proper winding support and blocking material
 - Removed multiple core grounds.

SCR Regulator:

- Installed water metering and interlocks
- Installed additional ground bus
- Modified phase isolation barriers
- Installed "star" distribution ground system
- Manufactured spare Gun Anode Regulator cards.

Crowbar:

Argonne

- Installed VESDA smoke detectors
- Added smoke detection interlock system
- Installed Crowbar Stack video monitoring and distribution
- Enhanced the di/dt circuitry.

A. Nassiri





Operational Statistics

Booster and SR RF

	<u>% Downtime</u>	MTBF
FY 2002	0.58%	98.4hr
FY 2003	0.44%	198.9hr
FY 2004	0.13%	464.8hr
FY 2005	0.27%	493.3hr
FY 2006	0.84%	195.0hr
FY 2007	0.39%	339.3hr
Argonne A. Nassiri	Status of the APS RF Systems	CWRF2008 28-0 America 2008 Control Control Statement



Operational Statistics (2)

SR Power System





* Faults

Faulty circuit breaker: 1

Water load wiring: 1

Crowbar fired: 3

klystron ma instability: 4

RF4 intermittent opto-coupler 5







Operational Statistics (3)







Status of the APS RF Systems



March 25, 2008 26

RF Operational Statistics (4)







Status of the APS RF Systems





RF Operational Statistics (5)





SR RF down time statistics.

Major contributors to the SR down time.



Status of the APS RF Systems





К

Summary

- The APS RF system reliability is world-class and perform equally well compared to 3rd generation light sources worldwide.
- Proactive approach to maintenance to minimize rf downtime.
- Incremental improvements, enhancement, and upgrades to maintain a steady reliability to meet operational demand.
- Systems degradation, components aging and obsolescence makes it difficult to maintain long-term high operational reliability, over 200 hrs MTBF, and higher beam uptime.
- Significant investment is needed to address long term rf systems aging and obsolescence issues. We are addressing this in the context of the APS upgrade. Smart investment.
- We will focus our efforts on:
 - Maintain a highly reliable rf systems in support of the APS operation.
 - Develop in-house SRF expertise and establish an R&D test facility in support of the APS upgrade and other SRF related applications.
 - Develop in-house expertise in digital LLRF and controls.
 - Exploring collaboration opportunities for the development of rf systems with other light source facilities



