

Fabric Infrastructure and Operations

CERN**IT** Department

CPU Efficiency

Ulrich Schwickerath WLCG GDB, 5th March 2008




CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it



Outline

CERN**IT** Department

Job efficiency (CPU/Wall time) for CERN in 2008





CPU Efficiency - 2



CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it



Possible Reasons - I

- Error trapping in SEAL
 - Hitting eg. LHCb jobs which got stuck in the system

--> Fixed





CERN

Department




CERN IT Department CH-1211 Genève 23 Switzerland www.cern.ch/it

Possible Reasons - II

Job Overhead

- Middleware overhead
 - Measure the overhead for a "hello world" job; calculate minimum cpu time for 85% efficiency
 - Is 30,000 8 minute jobs sensible? This also causes heavy load on the batch system.

 Sandbox timeouts were 5h15. Being improved at CERN: maximum wait is now just...
... 1h15 minutes!!!





CERN IT Department CH-1211 Genève 23 Switzerland www.cern.ch/it

Possible Reasons - III



- Data fetch/upload overhead
 - Local SE<->local disk
 - Job recall from tape (shouldn't happen!)
 - Optimum policy for reading from SE or from local disk
 - » Will depend on fraction of data read
 - » Need instrumentation in experiment framework to measure the data copy overhead
 - WN<->remote SE
 - Need instrumentation in experiment framework to understand time spent here.



CERN

Department



Possible Reasons - IV



• Pilot Job Framework overheads

- "wasted time" between "joblets"?

- Can be up to 10 minutes in some cases for one framework. Worker node is idle in this time.
- Need instrumentation of framework to measure
 - Time to start first joblet
 - Time between joblets
 - Added in DIRAC 3.
- Does this explain difference between site and experiment view of efficiency?
 - Or do experiments only measure efficiency for successful joblets? This would introduce a bias










Possible Reasons - V



Example: Alice joblet efficiency in the past 4 weeks



CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it

CPU Efficiency - 7





CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it

Possible Reasons - VI



Example: ALICE production jobs in the past 4 weeks

Significant number of killed and exited jobs: - are they counted ? - what happened to them ? - need instrumentation of FW RRDTOOL λobs 20 k TOB number HL. 10 k \Box ETIK Ϋ. 0 -Week 06 Week 07 Week 09 Week 08 Done State aver: 3.2k max:10.8k min:1.3 curr:42.6

Exit State aver:	:377.1 max:5.5k	: min:0.0 cu	rr:179.3m
Killed Jobs aver	r:363.8 max:5.5	k min:0.0 c	urr:179.3m
Killed Pending a	aver:57.6 max:8	60.4 min:0.0	curr:609.6m
CPU Time exceeded	l aver:1.2 max	:9.5 min:0.0	curr: 0. 0
📒 Run Time exceeded	l aver:11.6 ma	x:153.8 min:	0.0 curr:0.0

CPU Efficiency - 8



Possible Reasons - VII




- Naturally inefficient (I/O bound) jobs
 - Real world example from LHCb
 - Read 20GB of input data
 - Extract raw data within 288.94s of CPU time
 - Write out 1.6GB of output data (WAN transfer to Rutherford)
 - Estimated theoretical wall time: 31min
 - Maximum of 15% CPU/Wall time possible.
- What fraction of the overall workload do these represent? How can they be scheduled to improve overall efficiency?
 - Tag jobs as I/O bound? How is this passed from WMS to local scheduler?
 - Overall cpu/wall time ratio would not be improved, but sites can schedule I/O intensive jobs to improve box efficiency.
 - Schedule network optimized ?
 - Sites could provide dedicated queues for CPU bound jobs with more powerful machines behind CPU Efficiency 9



CERN IT Department CH-1211 Genève 23 Switzerland www.cern.ch/it

Grid/Local job comparisons



Local jobs appear to be more efficient for CMS and ATLAS.

Department

CERN

For LHCb and Alice Grid jobs are more efficient than local jobs

Why?

Need to instrument the experiment frameworks

CPU Efficiency - 10


CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it





Grid Production/User jobs

CERN



00:00

aver:13.9

06:00

min:0.0

max:57.5

LHCb production jobs clearly improved over the last 4 weeks.

Good! But why?

Other LHCb grid jobs less efficient. Why ?

CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it ø

GRID Job Efficiency

18:00

CPU Efficiency - 11

12:00

curr:45.3





CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it

More information needed from CERNIT Department

Key Message:

• need instrumentation so we understand where these differences come from.





Proposals



- Instrumentation in experiment frameworks to
 - Time job is waiting for data
 - Time between end of one joblet and start of the next
 - Other?
 - Agree common logging format by when?
 - Implement by when? April?
- Remove biases in experiment measurements of efficiency. All jobs should be considered.
- Review in May and June GDBs before and after CCRC

CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it

CPU Efficiency - 13





CERN IT Department CH-1211 Genève 23 Switzerland WWW.cern.ch/it

Conclusions



- There is not one single reason for bad CPU/Wall time ratios. There are improvements, but will they be permanent? We need to find out where exactly the time is spent.
- This can only be done together with the experiments.





Acknowledgements



Many thanks to everybody who helped to prepare this presentation, and in particular to Latchezar Betev and Philippe Charpentier who kindly provided inputs and material.

CERN IT Department CH-1211 Genève 23 Switzerland www.cern.ch/it



