

IAPP Mid-Term Review

27 Sep 2012 Pauli Piirainen



Background

- Bachelor of Science 1994
- Working experience: Ocotec (Finland), Nokia Networks (Finland), Viasystems (China)
- Sweco/Lewel Group (Finland) 2003 ->
 - Various customer projects e.g. for NSN, Huawei, PKC
 - Mostly in Base Station mechanical design projects/maintenances teams
 - Current project is Radio Base Station design for Ericsson in R&D mechanical team
 - Strong sheet metal and assembling experience



Project in Cern 10.2010 – 09.2011

- The main task in this project was to be involved in CERN RF structure production and two-beam teams in charge of manufacturing the X-band RF structures for the CLIC study.
- This included taking part in the present development and design work being done for the CLIC RF structure development.
- The work consisted of CATIA 3D-design work in co-operation with other researchers and designers working on the CLIC project.
- Design work concentrates on the modelling of high accuracy RF parts, supporting components and components for related technical systems necessary for a proper functionality of the CLIC module.






TD26 CLEX Structure

Design report

P. Piirainen







06-Sep-2011

CLIC RF Structure





TD26 CLEX Super Accelerating Structure is an accelerating module with compact couplers and silicon carbide (SiC)damping material integrated. It consists of two accelerating structures bonded together and several features are integrated to meet RF and physical requirements for the structure.


The main task was to continue the engineering design for the TD26 CLEX structure and the following issues needed to be considered:

- Mechanical design of the wakefield monitors
- Mechanical design of the cooling system
- Mechanical design of the vacuum manifolds
- Mechanical design of the interconnections
- Implementation of the alignment features






- Super Accelerating Structure (SAS) has been formed by brazing two Accelerating Structure (AS) together







Main components and subassemblies for SAS, which will be assembled together




06-Sep-2011

CLIC RF Structure







REGULAR CELL




- Cell shape accuracy 0.005 mm
- Flatness accuracy 0.001 mm
- Cell shape roughness Ra 0.025 μm













- Shape accuracy 0.02 mm
- Shape roughness Ra 0.1 μm







Vacuum Manifold design, 6 different types








Compact Coupler Design

Compact couplers and new design waveguides have been integrated to the disk structure



06-Sep-2011


CLIC RF Structure





Wakefield Monitor Design

Wakefield monitors with feedthroughs have been integrated to the structure




06-Sep-2011 CLIC RF Structure





Cooling System Design

- Cooling system has been integrated to vacuum manifolds
- External piping has been implemented with standard fittings and pipes









Damping and Alignment Design

Damping material has been integrated to the vacuum manifolds and WFM waveguides Alignment inserts have been included to design









Interconnection Design

Super Accelerating Structure has been designed so that it is able to assemble to adjacent structures with flexible interconnections

Interconnection with bellow, flange and chain clamp

O6-Sep-2011

CLIC RF Structure


(BE/RF)





Supporting System


Super Accelerating Structure has been fitted on the girder





ASSEMBLY PROCEDURE







ASSEMBLY PROCEDURE



KIITOS! MERCI!

THANK YOU!