



**High
Luminosity
LHC**

D1 Design at 150 mm Aperture and Plans

T. Nakamoto, Q. Xu, M. Sugano, H. Kawamata,
M. Iio, T. Ogitsu, K. Sasaki, N. Kimura, M. Yoshida, A. Yamamoto,
E. Todesco


3rd Joint HiLumi LHC-LARP Annual Meeting
11-15 November 2013, Daresbury Laboratory

The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.




Objective: New D1


- For HL-LHC upgrade, needs for new Inner Triplet system at IR1 & IR5.
 - Large aperture (150 mm) HF Quadrupoles, corrector package and D1.
- New beam separation dipole (D1) should be accommodated with large aperture IT Quads; which will need *a large aperture (large beam size) and 50 % increase in original integrated field (distance btw D1-D2 shortened).*




Schematic layout of the LHC



Current D1 (MBXW) at IR1 & IR5




Schematic layout of the IR



New superconducting D1

Design Parameter Change

- Coil aperture of D1 (NbTi) was once set to be **160 (=150+10) mm** until April 2013.
 - Extra space (+10mm) reserved for additional thicker beam shielding to suppress heat deposition
- Radiation simulation results for D1
 - First result for D1 with 150 mm aperture with beam shielding of tungsten
 - Peak dose in lifetime: a few 10 MGy
 - Peak heat deposition: 1-2mW/cm³
 - Additional beam shielding will be unnecessary...



New coil aperture of 150 mm in May 2013

- Requirements for the HX cooling was relaxed...
 - Free Area 130 cm², or
 - Free area 100cm² + 2 x φ49 mm HX holes

New iron cross section:

Free area >130 cm² + 2 x φ49 mm HX holes

- Availability: **NbTi LHC MB outer cable**

R. van Weelderen (March 2013)

	Variant 1	Variant 2	Variant 3/4
Power limit with max HX holes of 80 mm	550 W (Q1-D1) vapour velocity constraint	550 W (Q1-D1) vapour velocity constraint	550 W (Q1-Q3) ~60 W (CP-D1) 710 W Area constraint
Q1-Q3 HXs	2x80 mm holes	2x80 mm holes	2x80 mm holes
Q1-Q3 Free Area	~150 cm ²	~150 cm ²	~150 cm ²
Q1-Q3 Cryostat Pumping line	97-100 mm	97-100 mm	97-100 mm
CP HXs	none	2x80 mm holes	None or 2x49-80 mm holes
CP Free Area	>100 cm ²	~150 cm ²	~100 cm ²
CP Cryostat Pumping line	none	97-100 mm	~100 mm
D1 HXs	none	none	2x49-80 mm holes
D1 Free Area	>100 cm ²	~130 cm ²	~100 cm ²
D1 Cryostat Pumping line	none	none	~100 mm
Phase Separator & Pumping Entries/exits	1) Q1-end 2) Q3-CP	1) Q1-end 2) CP-D1	1) Q1-end 2) Q3-CP 3) CP-D1 or Q3-CP
QRL-jumpers	Q3-CP SM	CP-D1 SM	Q3-CP SM

Design Variants for D1 150

L_{mech} is longer.
Conflict with test cryostat.

Concern about higher local stress in coil and yoke.


	Option A: LL70	Option B: LL80
Bore diameter	150 mm	
# of turns	44 (4 + 8 +13 +19)	
Nominal field (dipole)	5.22 T	5.97 T
Magnetic length *	6.7 m	5.9 m
Operating current	11 kA	13 kA
Injection current	~ 0.7 kA	~ 0.84 kA
Field homogeneity	<0.01% ($R_{ref}=50$ mm)	<0.01% ($R_{ref}=50$ mm)
Peak field in the coil (2D)	6.0 T	6.9 T
Load line ratio (2D)	9% @ 1.9 K / 90% @ 4.2 K	80% @ 1.9 K
Inductance (low / nominal field)	5.7 / 5.2 mH/m	5.7 / 5.1 mH/m
Stored energy	294 kJ/m	391 kJ/m
Peak field/central field	1.15	1.16
Lorenz force X/Y (1st quadrant)	1.3/0.5 MN/m	1.7/0.7 MN/m
Outer dia. of iron yoke	550 mm	550 mm
Inner dia. of iron yoke	222 mm	222 mm
Strand diameter	0.825 mm	0.825 mm
Cu/Non-Cu ratio	1.95	1.95
Cable dimension / insulation	15.1* 1.48mm² / 0.16 mm (radial) 0.145 (azimuthal)	15.1* 1.48mm² / 0.16 mm (radial) 0.145 (azimuthal)
No. of strands	36	36
Keystone angle	0.9 °	0.9 °
Superconductor current density	1710 A/mm ²	1954 A/mm ²
Total length of the cable	618 m (Coil length ~7.1 m)	548 m (Coil length ~6.3 m)

Latest Design Parameters of D1: Option C

- Coil ID: **150 mm**
- Integrated field: **35 T m** (26 Tm at present LHC)
 - 5.59 T at 12 kA. $L_{coil}=6.3$ m
- T_{op} : **1.9 K** by Hell cooling
- Op. point (2D coil): **75 %**
- Coil layout: **1 layer of 15.1 mm cable**
 - Better cooling. Saving space for iron yoke.
- Conductor: **Nb-Ti LHC MB outer cable**
- Structure: **Collared yoke structure by keying**
 - RHIC dipole, LHC MQXA, J-PARC SCFM
 - Enhancing iron material for stray field issue
- Field quality: $< 10^{-4}$ at $R_{ref} = 50$ mm
- Cold mass OD: $550 + 10 \times 2 = 570$ mm
- Cryostat OD: **914 mm**, same as MB cryostat
- Radiation, energy deposition:

A few 10 MGy, 1~2 mW/cm³


- ◆ **Stress management**
- ◆ **High saturation, stray field, flux return cryostat**
- ◆ **Radiation resistance, cooling capability**




2D Cross Section

- Same cross section for iron yoke for the Option C and Option A.
- The total void area in the iron yoke: **154 cm²**
- **2 x ϕ 50 mm holes** reserved for HX


Option C (75% at load line in 2D)



Option A (70 %)




IBI flux density (T)



ROXIE_{10.2}


Variation of Multipole Coefficients: b_3 (2D)




Variation of Multipole Coefficients: b_5 and higher (2D)

- Similar behaviors of Option C and A.
- Both of them look acceptable.


LL75 Option C



LL70 Option A



Transfer Function





Stray Field of the Magnet

stray field at the outer surface of the iron cryostat for the two design options with 150 mm aperture.

Cryostat thickness: 12 mm.




Cryostat outer diameter: 914 mm.



Mechanical Analysis for Option C: Key insertion




Shear stress in lock-keys is not included

Key slots: below 220 MPa in most areas >> feasible



Remove load from the yoke shoulder and insert the load-key; The gap between top and bottom yokes keep closed at both ends.



Mechanical Analysis: After excitation (110 % I_{nom})



Coil Stress at Each Step


◆ 150 mm aperture, Option C (LL75) with 110% of the nominal current.

- At Assembly: $\sigma_{Pole_Ave.}$ of 70 MPa, $\sigma_{MP_Ave.}$ of ~95 MPa
- At excitation: $\sigma_{Pole_Ave.}$ of ~5 MPa, $\sigma_{MP_Ave.}$ of 90 MPa
- Peak stress below 150 MPa





Coil End Design by ROXIE

- **Objectives:**
 - keep compact coil ends,
 - compensation of field integral of multipoles,
 - lower peak field.
- 1 subdivision of CB3 in Return End to reduce peak field: 2 + 6 turn
 - 3 % higher peak field in the end
- Iron covers the whole coil ends.
- Layer jump modeled by CAD >> Simplified “Bricks” model in ROXIE




Peak Field in the Coil End

- Peak field moved from Block 3 to Block 1 by subdivision.
- Peak field of 6.75 T >> operating point for Option C is **78 %** (75 % in 2D coil).



Field Integral & Magnet Length: Option C (LL75)

*For Mechanical Coil Length: 6.416 m (-3209 < z < +3207)





Field Integral	Return End (-4000 < z < -2041)	S.S. (-2041 < z < +2041 mm)	Lead End: (+2041 < z < +4000 mm)	Total (Tm)	Ratio of integral (unit)
B1	6.1715	22.8779	6.1711	35.2204	10000
B3	-0.0156	0.0090	-0.0138	-0.0205	-5.82
B5	-0.0019	-0.0003	-0.0004	-0.0025	-0.71
B7	0.0009	-0.0005	0.0011	0.0016	0.44
A1	0.0000	0.0002	-0.0046	-0.0044	-1.26
A3	0.0000	0.0000	0.0014	0.0014	0.40

- A large B_3 of 0.009 Tm (+4 unit) generated in S.S. due to the end effects while the one in 2D is almost zero.
- The integral of B_3 (-6 unit) could be minimized by adjusting B_3 in S.S. to a certain value.
- Other multipoles less than 1 unit looks acceptable except A_1 .
- The whole magnet length estimate: **6.92 m**
>> Acceptable for the vertical cold test at KEK


Radiation Resistant Materials R&D

- New radiation resistant GFRPs (w/ S-2 Glass or T-Glass) are baseline for **coil wedges, end spacers**.
 - Cyanate Ester & Epoxy
 - BT (Bismaleimide Triazine)
 - BMI (Bismaleimide)
- Trial production has been made: **prepreg sheets, laminated plates and pipes**.
- Backup plan (in case of higher dose) would be metallic parts with **Polyimide coating by "Vapor Deposition Polymerization"** technology.
- Irradiation test by electron and gamma rays
 - Gamma rays (Co^{60}), 2 MeV electron at JAEA Takasaki
 - 30 MeV electron at KUR

Ordinary SC coils (J-PARC SCFM) with G10 (epoxy + E glass) end spacers and wedges.




BT-GFRP pipe for end spacers and pipe (φ160, L1000)



Backup Plan: Polyimide coating on

After irradiation of 10MGy with 30 MeV electron beam





RT Gamma-ray Irradiation Tests

- All new GFRPs (CE&Epoxy, BT, and BMI) shows good radiation resistance up to **100 MGy**.
- Ordinary G10 (MQXA) already showed significant degradation at **10 MGy**.


GFRP (S2 glass & BT resin) will be adopted for the new D1

Gamma ray irradiation test at RT, in vacuum.

Rate: 13.9-15.6 kGy/hr. Evaluation test at RT. GFRP made by ARISAWA.




After irradiation of 13 MGy



Flexural strength test (G10, 30MGy)



2m-long Model Magnet - Overview

Single-layer coil, 4-split spacer collars, collared yoke by keying



2m-long Model Magnet Development – Status

- Coil design ($\phi 150\text{mm}$, 75%) will be finalized soon.
- Engineering, drawing ongoing.
 - Reuse of available tooling and jigs for J-PARC SCFM.
- NbTi SC cable with standard Apical insulation (220 m x 4) to be delivered from CERN in Jan. 2014.
- Radiation resistant GFRP (plates, pipes) from ARISAWA for wedges and end spacers to be delivered in Jan. 2014.
- Practice coil winding anticipated in March 2014.
- Discussion with vendors, JFE Steel (EFE steel) and Nippon Steel & Sumikin Stainless Steel (YUS130S), started. Supply even for the model magnets.
- Fine blanking for spacer collars and iron yokes will be adopted for the full-scale prototypes and a production.
 - Combination of laser cut and machining will be adopted for the 2m long models.
- Mechanical short model in spring 2014.
- Renovation of development area.
- Modification and consolidation of the vertical cryostat, bus lines, and the 15kA PC.



Plans (or Prospect...)

JFY2013 (until March 2014)

- Practice coil winding. Mechanical short model

JFY2014

- 1st 2m long model magnet. Cold test in vertical cryostat at 1.9K.

Beyond this, new funding for the construction (including R&D) is necessary.

JFY2015 (*Tentative plan...*)

- 2nd 2m long model magnet, if necessary.
- Major consolidation in cryogenics. New construction of a horizontal cold-test bench. (Otherwise, horizontal cold test at SM18/CERN??)

JFY2016

- One full-scale prototype magnet by a manufacturer

JFY2017

- One full-scale prototype cryostat by a manufacturer

JFY2018

- A series production of the magnets and the cryostats (5 or 6 sets including the spare) to be completed by 2022.

*Presumably, horizontal cold testing at KEK will determine the production rate...²¹

Budget
supported by
ATLAS-Japan

Summary

- Conceptual design study for the new D1 has been made for Option C: *φ150mm, 35 Tm, load line ratio of 75 % in 2D (78 % in total)*.
 - Nominal field of 5.59 T at 12 kA, with a peak field of 6.75 T (78% at 1.9K).
 - Field quality in 2D along excitation is acceptable and successfully optimized at nominal current under high saturation effect.
 - Coil end effects are still observed at S.S. of the full-scale model and further optimization on field integral of B_z would be necessary.
 - The whole magnet length of 6.9 m will fit to the vertical cryostat at KEK.
 - Mechanical analysis: this option is feasible.
 - To be addressed: quench protection studies.
- 2-m long practice coil winding in JFY2013, followed by a 30-cm long mechanical short model.
 - Engineering work underway. Procurement started.
 - New radiation resistant GFRP (S-2 glass & BT resin) adopted for wedges, end spacers.
 - Renovation of development area, consolidation of cold test stand ongoing.
 - Collaboration (support) with CERN: NbTi cable, QPH, fabrication of collar & yoke, etc.
- LHC/ATLAS upgrade review at KEK in this Nov. Funding proposal for construction (+ R&D) starting from JFY2014 will be submitted.