



# Cryogenics of the 60 GeV LHeC

Friedrich Haug

CERN

Technology department

LHeC Workshop, Chavannes-de-Bogis, Jan. 20-21, 2014




# Contents....

...largely based on the LHeC Conceptional Design Report

- ERL layout (Linac-Ring)
- Cryomodule principle
- Power consumption of ERL
- Parameters for cryo power
- Ring-Ring version
- Comparison with CERN accelerator plants
- *Detector cryogenics*



# Two e-accelerator versions: Linac-Ring, Ring-Ring






# Linac-Ring Cryogenics (ERL)



## Basic concept



### Racetrack

(ERL) Energy Recovery Linac  
2 linacs, 1 km length each  
3-pass, 60 GeV, 8 mA

For more details see talk of  
Frank Zimmermann


## Proposal based on CDR

### Cryomodule

8 cavities + Quad  
~ 15 m length  
118 cryomodules


### Cavities

5-cell      1.04m length  
> 721 MHz, CW operated  
**Power diss. 32 W @ 2K**  
for 21.2 MV/m  
(based on  $Q_0 = 2.5E10$ )




Proposed cryomodule configuration and cryostat similar to XFEL

# Basic Lay-out





# Basic Lay-out



Sectorisation: Eight 250 m long strings. Eight dedicated cryoplants

# Lay-out Cryoplants

**ERL**




Cooling requirements dominated by dynamic losses at 2 K  
(other loads neglected here for simplicity)

Lay-out is based on LHC cryogenic principles  
with split cold boxes (surface cold box and  
underground cold box with cold compressors).

Refrigerator units of approx. 5 kW @ 2 K  
assumed. To be designed. Technology and  
experience: LHC, CEBAF (JLAB).



# Lay-out Cryoplants




On surface refrigerator cold boxes



Underground  
Cold box

Distribution

On surface



Split cold boxes (see  
LEP2, LHC (4.2K on  
surface, 2K in tunnel)

Total (minimum) cooling power;


**84 kW @ 4.2 K (no contingency)**

**Cryoplants proposed**

**8 x 10.5 kW @ 4.2 K**

R&D cavities ongoing. Expectance  
improved Q values....

# Basic refrigerator lay-out





# Summary Parameters (CDR)



Parameter	Value
Two linacs	length 1 km
5-cell cavities	length 1.04 m
Number	944
Cavities/ cryomodule	8
Number cryomodules	118
Length cryomodule	14 m
Voltage per cavity	21.2 MV
R/Q	$285\Omega$
Cavity $Q_0$	$2.5 \cdot 10^{10}$
Operation	CW
Bath cooling	2 K
Cooling power/cav.	32 W @ 2 K
Total cooling power (2 linacs)	30 kW @ 2 K



# Summary Parameters (CDR)




Parameter	Value
Number of Refrigerators	8
1/COP @ 2 K	700
Minimum cooling capacity/refrigerator	10 kW @ 4.5 K
Contingency	none
Minimum total cooling power	80 kW @ 4.5 K
Grid power consumption	21 MW



# Cryo power = f(parameters)

- Power consumption dominated by dynamic load (CW operation)
- Power consumption inverse proportional to  $Q_o$
- Lower temperatures: increase in  $Q_o$
- Cavity frequency ...etc. (reference is made to SRF experts in this field...)

Cavity dynamic load




Cavity dynamic load



# Ideal work for refrigeration

Inverse coefficient of performance

$$COP_{Inv,ideal} = 1/COP_{ideal} = COP_{ideal}^{-1}$$




Units of work required to produce one unit (1 W) of refrigeration of an ideal machine. Equation used

$$\frac{W}{\dot{Q}} = \frac{T_0 - T}{T} \quad \begin{matrix} [Watts] \\ [Watt] \end{matrix}$$

Gas	Normal boiling point [K]	Ideal work for refrigeration [W/W]
Oxygen (O <sub>2</sub> )	90.18	2.3
Argon	87.28	2.4
Air	78.80	2.8
Nitrogen (N <sub>2</sub> )	77.36	2.9
Neon	27.09	10.1
Hydrogen (H <sub>2</sub> )	20.27	13.8
Helium-4	4.21	70.3

# Power = f(parameters)


Gas	Normal boiling point [K]	Ideal work for refrigeration [w/w]
Helium-I	4.21	70.3
Helium-II	2.0	150
Helium-II	1.8	167
Helium-II	1.6	187



But in addition Carnot efficiency becomes smaller, hence, real inverse COP unproportionally large

$$COP_{real}^{-1} = COP_{ideal}^{-1} / \eta_{Carnot}$$

Size, complexity and cost of refrigerators and systems increase unproportionally with decreasing temperatures







# Using the LHC tunnel: Ring-Ring Version



Principle: use LHC tunnel for additional new electron Ring accelerator

Superconducting cavities for acceleration

Normal conducting low-field magnets to guide electrons of 60 GeV





# Ring-Ring Cryogenics



## SC Cavities for the bypasses

2-cell	721 MHz
Length	0.42 m
Acc. Field	12 MV/m
Operation	CW mode
Operation temp.	2 K
Dissip.	4 W

## Cryomodules

nr. of cavities	8
Length	10 m

## Location and number of cryomodules

CMS side	8
ATLAS left	3
ATLAS right	3


## SC Cavities for the Injector

9-cell	1.3 GHz
(ILC/XFEL type)	
Length	1 m
Acc. Field	23 MV/m
Operation	pulsed mode

## Cryomodules



nr. of cavities	8
Length	12.2 m
Nr. of modules	12

*(exact copy of XFEL)*





# Ring-Ring Cryogenics





LHC ATLAS Detector with complex cryogenic system.  
NO CHANCE to use this plant for LHeC.

Cryomodules location

Site	Cryoplant power
ATLAS left	1.2 kW @ 4.2 K
ATLAS right	1.2 kW @ 4.2 K

# Ring-Ring Cryogenics

## 10 GeV 3-pass injector



<u>Site</u>	<u>Cryoplant power</u>
Injector	2.0 kW @ 4.2 K
CMS	3.0 kW @ 4.2 K
ATLAS left	1.2 kW @ 4.2 K
ATLAS right	1.2 kW @ 4.2 K
<b>2 K operation of cryomodules</b>	



# Comparison (cryogenics only)

## LEP2 (cryo for SRF cavities 5 MV/m)

4 Acc points. 4 Cryoplants 12 kW @ 4.5 K.

4.5 K bath cooling (already split principle). Upgraded later for use at LHC...

## LHC (cryo for sc bending magnets)

8 Cryoplants 18 kW @ 4.5 K + 8 cold boxes 1.8 K. Largely for LHC sc magnet cooling at 1.9 K. Grid power consumption appr. 40 MW (with ATLAS and CMS detector cryoplants)

## LHeC ERL (cryo for SRF cavities > 20 MV/m)

**Linac-Ring version:** 2 accel. strings 1 km each. 8 cryoplants

2 K bath cooling, 8 x 10 kW @ 4.5 K.

Grid power consumption appr. >21 MW (+ contingency...)

**LHeC Ring-Ring version:** 2 acceleration points (IP 1, 5), 4 cryoplants,

2 K bath cooling, total < 8 kW @ 4.5 K


Ring-Ring only appr. 1/10 of  
ERL power + use of LHC infra  
(= small LEP2 at 2 K)




# Detector Cryogenics

SC solenoid (3.5 T) and two dipoles on one support cylinder  
diam. 2 m, 9.5 m length  
**Cryoplant: 300 W @ 4.5 K**

Liquid Argon calorimeter  
12 m<sup>3</sup>  
Corresponds to appr.  
1/8 of Atlas Calorimeter Volume



# Detector Cryogenics




**Liquid Argon  
Calorimeter**

**Principle flow-  
scheme of the LN2  
(87 K) cooling system**

**LN2 Cryostat and  
phase separator**

**Redundant  
centrifugal pumps**

# Detector Cryogenics



SC bus integrated in transfer line

**SC Solenoid and dipoles**

**Principle flow-scheme**

**He Cryostat and phase separator**

**Redundant centrifugal pumps**

**Similar to Atlas Test Facility Hall 180**



# Thanks for your attention