

# Fast Cycled superconducting Magnets (FCM) for PS2

---

WAMSDO, May 23<sup>rd</sup>, 2008

Presented by L. Bottura

on input from G. Kirby, M. Karppinen, L. Oberli, R. Maccaferri,

C. Maglioni, V. Parma, D. Richter, G. de Rijk, L. Rossi,

W. Scandale, L. Serio, D. Tommasini



# Outline

---

- Motivation
- Superconducting magnet design
- R&D target and issues
- Medium term plan
- Conclusions and perspectives




# Outline

---

- Motivation
- Superconducting magnet design
- R&D target and issues
- Medium term plan
- Conclusions and perspectives

# The LHC Accelerator Chain



PS was built in 1959




SPS was commissioned in 1976

# PS2: Magnet Requirements


- PS2 will be an accelerator with a length of  $\approx 1.3$  km
  - Injection at 3.5 GeV
  - Extraction at 50 GeV
  - 200 dipoles
    - Nominal field: 1.8 T
    - Ramp-rate: 1.5 T/s
    - Magnet mass:  $\approx 15$  tons
  - 120 quadrupoles
    - Nominal gradient 16 T/m
    - Ramp-rate: 13 T/ms
    - Magnet mass:  $\approx 4.5$  tons
- Average electric power  $\approx 15$  MW
  - The magnets require  $\approx 7.5$  MW, i.e. about 50 % of the total consumption

Modest requirements


The location of the new PS2



dipole



quadrupole






# Outline


---

- Motivation for the study
- **Superconducting magnet design**
- R&D target and issues
- Medium term plan
- Conclusions and perspectives

# Iron Dominated SC Dipole




# Comparison of Dipole Designs



Magnet length	470	3 m
Number of magnets		200
<b>Iron weight</b>		<b>10 tons</b>
Peak current @ 1.8 T		5300 A
Current rise rate		4830 A/s
Number of turns		2x10
Inductance		7 mH

**Peak voltage** 34 V




Magnet length	535	3 m
Number of magnets		200
<b>Iron weight</b>		<b>15 tons</b>
Peak current @ 1.8 T		5775 A
Current rise rate		5260 A/s
Number of turns		2x9
Inductance		6 mH
Resistance		1.7 mΩ
RMS Current		3990 A
Power consumption		27 kW


**Peak voltage** 41 V




# Iron Dominated SC Quadrupole



# Comparison of quad designs



Magnet length	1.75 m
Number of magnets	120
<b>Iron weight</b>	<b>2.8 tons</b>
Peak current @ 16 T/m	4600 A
Current rise rate	3830 A/s
Number of turns	4x6
<b>Inductance</b>	<b>2.2 mH</b>
<b>Peak voltage</b>	<b>8 V</b>



Magnet length	1.75 m
Number of magnets	120
<b>Iron weight</b>	<b>4.4 tons</b>
Peak current @ 16 T/m	1200 A
Current rise rate	1000 A/s
Number of turns	4x23
<b>Inductance</b>	<b>35 mH</b>
Resistance	26.7 mΩ
RMS Current	830 A
Power consumption	18 kW
<b>Peak voltage</b>	<b>67 V</b>

# Cost comparison - investment

## ■ NC magnets

- Dipoles: 30 MCHF
- Quadrupoles: 9 MCHF
- Testing: 1 MCHF
- Auxiliaries: 1.5 MCHF

## ■ Power converters

- Total: 19.3 MCHF

## ■ Cooling and ventilation

- Total: 1.1 MCHF

## ■ **Total cost: 61.9 MCHF**

## ■ SC magnets

- Dipoles: 21.3 MCHF
- Quadrupoles: 6.6 MCHF
- Testing: 3.2 MCHF
- Auxiliaries: 4 MCHF

## ■ Cryogenics

- Plant + lines: 13.5 MCHF
- **Building: 3.1 MCHF<sup>(1)</sup>**

## ■ Power converters

- Total: 15 MCHF

## ■ Cooling and ventilation

- **Total: 1.1 MCHF<sup>(2)</sup>**

## ■ **Total cost: 67.8 MCHF**

<sup>(1)</sup> Scaled to 1/2 of estimate for the 15 kW plant

<sup>(2)</sup> Assume the same as for NC magnets, benefiting from lower power requirement

Installed power of NC PS2 by courtesy of M. Benedikt



# Power requirements

<b>Electrical consumption</b>	<b>NC</b>	<b>SC</b>
Main Magnets	7.5 MW	0 MW
RF	2 MW	2 MW
Other systems	3 MW	3 MW
Cryoplant	0 MW	<b>1.3 MW</b>
Water cooling station	1.2 MW	0.4 MW
Ventilation	0.5 MW	0.5 MW
Climatisation	0.4 MW	0.4 MW
<b><i>Total consumption</i></b>	<b><i>14.6 MW</i></b>	<b><i>7.6 MW</i></b>



## Cost comparison - operation

---

### ■ NC magnets

- Energy: 14.6 MW \* 6000 hrs/yr
- Energy cost<sup>(1)</sup>: 3.8 MCHF/yr

### ■ SC magnets

- Energy: 7.6 MW \* 6000 hrs/yr
- Energy cost<sup>(1)</sup>: 1.9 MCHF/yr
- Cryo maintenance: 0.3 MCHF/yr

■ Total cost: 3.8 MCHF/yr

■ Total cost: 2.2 MCHF/yr

*bottom line*

---

*Estimated  $\approx 7$  MW saving, half of the  $\approx 15$  MW projected power consumption of the PS2 complex, which corresponds to 1.6 MCHF/yr at the present cost of electricity*

<sup>(1)</sup> Assuming 40 CHF/MWh




# Outline

---

- Motivation
- Superconducting magnet design
- **R&D target and issues**
- Medium term plan
- Conclusions and perspectives

# A Broader Perspective





# FCM R&D Objectives

---

- Build and test a demonstrator that:
  - **Achieves PS2 nominal conditions** ( $B=1.8$  T,  $dB/dt = 1.5$  T/s) and the  **$\Pi=7$  T<sup>2</sup>/s target** ( $B=1.8$  T,  $dB/dt \approx 4$  T/s)
  - Demonstrates the **low-loss properties of the SC magnet option** (1 W/m of magnet for the PS2 nominal conditions)
    - Address strand and cable R&D issues, relevant to both PS2 and SPS+
    - Prototype of the of **coil, cryostat, supports** relevant for a PS2
  - Various other **side results**, such as a demonstration of the *cooling scheme*, *quench detection* and *protection*, ramped *field quality* and its *measurement*



# First Step: Short Dipole Model

28/Apr/2008 18:40:53

Surface contours: BMOD

2.877575E+00

2.500000E+00


2.000000E+00

1.500000E+00


1.000000E+00

5.000000E-01

0.000000E+00



# Critical Issues Identified to Date






# Superconducting Strand and Cable

- NbTi strand, *modest* critical current
  - $I_c > 460 \text{ A @ } 4.2 \text{ K and } 2 \text{ T}$
  - $J_c > 2500 \text{ A/mm}^2 \text{ @ } 4.2 \text{ K and } 5 \text{ T}$  (below LHC standard)
- **Low-loss strand and cable**
  - $D_{\text{eff}} < 3 \mu\text{m}$  ( $\approx 3 \dots 4 \mu\text{m}$  achieved on LHC strands)
    - **45 mJ/cm<sup>3</sup> of NbTi for a +/- 1.5 T cycle**
  - strand  $\tau < 1 \text{ ms}$  ( $\approx 0.1 \text{ ms}$  achieved with resistive barriers on previous productions)
    - **9.5 mJ/cm<sup>3</sup> of NbTi for a +/- 1.5 T cycle at 1 T/s**
  - Cable  $n\tau < 2 \text{ ms}$  (corresponds to  $R_a \approx 100 \mu\Omega$  and  $R_c \approx 10 \text{ m}\Omega$ )
    - **9.5 mJ/cm<sup>3</sup> of NbTi for a +/- 1.5 T cycle at 1 T/s**
- Force-flow cooled cable
  - Stability advantage, robust against perturbations, for reliable operation, small He inventory, good voltage insulation properties, *classical* winding techniques

# Nb-Ti Wire: Low Hysteresis Loss




Design and prototyping work in progress on a strand with:


$D_{\text{strand}}$  0.6 mm  
 $D_{\text{filament}}$   $\approx 2.5 \mu\text{m}$   
 Cu/**CuMn**/NbTi  $\approx 1.8 / \approx 0.4 / 1$

# Force-Flow Cooled Cables

- Low current (5...7 kA)
- The first short models will be based on existing cables. A cable re-design is in progress
  - Larger hydraulic diameter for cooling efficiency
  - Co-wound copper strands for protection
  - Reduction of AC loss, depending on present status




Internally cooled cable  
Prototype from VNIKP




$$P \approx \frac{2 ND^2 L_p}{\pi R_a} \left( \frac{dB}{dt} \right)^2$$

$$R_a \approx 75 \dots 200 \mu\Omega$$




# Coil Winding & Support Concept



# Coil Support Structure

Vertical load path: 0.8 tons/m




Horizontal load path: 1.6 tons/m


Through posts to the iron

**Composites and fibers to  
avoid eddy currents**

*Make the coil self-supporting...*



Stiffened coil



77 K structure




Horizontal straps and *toblerone* iron


# Cryostat and Supports

- Conflicting requirements of mechanical rigidity vs. low heat input

Support feet



Tensioned rods or straps








# Outline

---

- Motivation for the study
- Superconducting magnet design
- R&D target and issues
- **Medium term plan**
- Conclusions and perspectives

# Plan for FCM R&D





# Outline

---

- Motivation for the study
- Superconducting magnet design
- R&D target and issues
- Medium term plan
- **Conclusions and perspectives**


# Conclusions and perspectives

- This is a challenging bet: we are trying to displace normal conducting magnet technology from its *proprietary domain*.
- We have to prove that our SC alternative is:
  - Equally reliable
  - Equally robust
  - More efficient



The rise of  
*hadron  
therapy  
synchrotrons*

**This is a worthy  
effort, not only for the  
Beauty of Science !**





# Outline

---

- Motivation for the study
- Superconducting magnet design
- R&D target and issues
- Medium term plan
- Conclusions
- **Additional information**



# Assumptions for cost analysis

---

- SC magnet construction:
  - Iron yoke (warm): 6.6 CHF/kg
  - Superconducting coil: 250 CHF/kg
  - Cryostat: 25 kCHF/magnet
  - Magnet testing: 10 kCHF/magnet
- SC auxiliaries:
  - Quench detection & protection: 1 MCHF total
  - Current leads and bus-bars: 3 MCHF total
- Power converters costs are taken identical to previous analysis
- Cooling and ventilation costs are assumed equal for NC and SC because of the reduced SC power requirement
- Buildings cost for cryogenic plant are assumed to be reduced for the lower installed power
- Operation:
  - Cryogenic operation is run by CERN (as power converters)
  - Electricity is quoted at 40 CHF/MWh




# Is HTS an option ?

---

- The use of HTS materials would affect:
  - Construction cost
    - Coil more expensive, cryostat simpler, smaller cryogenic installation (at best liquid nitrogen)
  - Operation
    - A larger margin to improve robustness
    - The cryogenic load can be removed at higher operating temperature, which requires lower installed power
  - Changes in the cost estimates for the SC PS2:
    - Investment cost reduced by 5 ... 10 MCHF
    - Installed power reduced by 1 MW
    - Operation cost reduced by 0.25 MCHF/year

Marginal gain with respect to previous figures (10 %)  
could be beneficial for the overall reliability

# Nb-Ti Wire: Moderate Coupling





# Magnet Projects and Related R&D

