


LARP

Nb₃Sn Quadrupole Designs for the LHC Upgrades



Context

LARP

- LARP is preparing Nb₃Sn quadrupoles for Phase 2 upgrade. Several series have already been designed and tested:

- SQ=> subscale quadrupole model with 90 T/m gradient and 110 mm aperture relying on racetrack and implementing alignment

- TQ => - 1-meter 90 mm aperture

- ~ 12 T peak field, ~ 200 T/m gradient


- The LQ series is under construction

- LQ => scale up of TQ, 3.6 m long, 240 T/m short sample gradient at 4.5 K

- Next step: reaching 14 – 15 T peak field at 1.9 K with accelerator quality features for LHC luminosity upgrades


- Large aperture, alignment (field quality), cooling


=> 1-meter model HQ: 110 / 140 mm aperture, 230 / 200 T/m gradient



LARP

HQ goals and R&D issues





LARP

HQ Design study

⇒ A **range of apertures** have been considered: from 110 mm to 140 mm


- detailed study of 114 mm and 134 mm


⇒ **Several magnetic cross-sections** have been compared in terms of:

- Gradient
- Peak field
- Field quality
- Pole angle (windability)
- Maximum stress in the coil for a given mechanical structure

⇒ **Strong relation** between the **coil magnetic design** and the **mechanical stress distribution** in the coil

- Role of the **Lorentz forces** distribution between the 2 layers







LARP

HQ magnetic cross-sections

Courtesy of V. Kashikhin



134 mm aperture



Cable parameters

15 mm wide


1.405 mm mid-thickness

0.11 mm insulation

$J_c(12\text{ T}, 4.2\text{ K}) = 3000\text{ A/mm}^2$

	114 mm aperture	134 mm aperture
Quench gradient at 1.9 K	234 T/m	201 T/m
Quench peak field at 1.9 K	15.39 T	15.66 T
Quench current at 1.9 K	19.18 kA	18.17 kA
F_θ Layer 1 / Layer 2	2.5 / 2.99 MN/m	2.7 / 3.4 MN/m
Stored energy	1.31 MJ/m	1.69 MJ/m

130 mm Aperture Quadrupoles for the LHC Luminosity Upgrade, F. Borgnolutti, E. Todesco, PAC07



Lorentz forces distribution and mechanical behavior

LARP

TQS (1-meter)


- 90 mm aperture
- 12 T peak field
- 240 T/m
- F_{θ} Layer 1 = -1.5 MN/m
- F_{θ} Layer 2 = -1.02 MN/m

LQS (3.6-meter)


- 90 mm aperture
- 12 T peak field
- 240 T/m
- F_{θ} Layer 1 = -1.5 MN/m
- F_{θ} Layer 2 = -1.02 MN/m

HQ (1-meter)


- 114 mm aperture
- 15 T peak field
- 230 T/m
- F_{θ} Layer 1 = -2.5 MN/m
- F_{θ} Layer 2 = -2.99 MN/m




Key
optimization



Xsection
optimization



=> Improvement of the cross-section to avoid layer 2 overloading



LARP


HQ Mechanical structure Design concept and Guideline

Design concept

- Coil sub-assembly (coil + pad) at very low pre-stress
- Assembly at room temperature with **keys and bladders**
- Axial loading with axial rods
- Final pre-stress provided by an aluminum shell during cool-down

Guideline


- Full contact between pole and coil at short sample (200 – 230 T/m)
- **Optimization** of the mechanical stress in the coil during **bladder operation**: bladder location
- **Optimization** of the mechanical stress in the coil **after cool-down and during excitation**: key location
- Alignment with gradual implementation



HQ Mechanical structure based on LQ structure


LARP

114 mm aperture




- 550 mm outer diameter
- 25 mm Al shell
- 43 mm iron pad

134 mm aperture



- 15 mm Al bolted collars
- Iron pads
- Iron yoke
- 45 mm diameter axial rods

- 584 mm outer diameter
- 32 mm Al shell
- 53 mm iron pad




LARP

HQ – Mechanical Structure

114 mm aperture


Components

- Aluminum bolted collars
 - alignment feature
 - needs to remain in compression from assembly to operating conditions
 - intercept preload (~ 20 %)
- Iron pads and yoke
- Iron master => alignment
- 45 mm diameter axial rods => axial preload
- 25 mm aluminum shell => azimuthal preload
- Cooling area




Assembly


- 50 mm bladders located outside the key span
- 42 MPa pressure (550 + 50 microns clearance for 230 T/m)



LARP

HQ – Alignment







LARP

HQ – Mechanical analysis

Azimuthal stress in the coil for a 114 mm aperture



=> Reasonable stresses in the coil even at short sample





LARP

Work in Progress

Magnetic 3D


-Study of coil-relative end position

-Study of iron field contribution



=> Work in progress





LARP

HQ – Cable optimization




Test winding samples


Variation of the keystone angle, width, thickness...

Up to now, 8 cables evaluated

Micrographs analyzed for each sample

- Edge deformation – strand distortion
- Deformation of the sub-elements
- Barrier
- Size of the facets on the surface of the cable





LARP

HQ – Cable optimization


Winding tests

EDM part return end


Rapid Prototype (RP) part lead end



114 mm aperture mandrel




134 mm aperture mandrel



Ongoing tests:

Winding tests on 114 mm mandrel with RP pole pieces








LARP

Work in progress

Winding Table

Initial parametric design of coil and spacers for both layers






LARP


Work in progress


Tooling design

Winding tooling




Curing tooling






LARP

HQ – CAD Model





Summary

LARP

- ⇒ A **range of apertures** have been considered: from 110 mm to 140 mm
 - detailed study of 114 mm and 134 mm

- ⇒ Optimization of the cable in progress => iteration on the magnetic cross-section

- ⇒ For each aperture, a **mechanical structure** is under study in order to provide:
 - ⇒ support up to the short sample limit of the magnet
 - ⇒ alignment
 - ⇒ cooling

- ⇒ **Tooling** design is in progress, **End parts design** under study
- ⇒ **3D** computations have been started

