

Updating the LISE++ Software and Future Upgrade Plans

M.P. Kuchera, O.B. Tarasov, D. Bazin, B.M. Sherrill, K.V. Tarasova National Superconducting Cyclotron Laboratory, Michigan State University

Introduction

Production of new isotopes is at the intensity frontier of nuclear physics. The associated science address the stability, origin, and content of atomic nuclei. Scientific programs range from tests of the Standard Model to exploration of the origin and evolution of the chemical elements in the universe. Leading facilities in this effort include RIKEN in Japan, TRIUMF in Canada, GSI in Germany, GANIL in France, JINR in Russia, and ISOLDE at CERN. New large scale facilities under development include FAIR in Europe, FRIB in the United States, and others in countries including China, France, Korea, and Italy. Many of these facilities produce rare isotope beams by in-flight production and separation of a projectile beam on a target, followed by a spectrometer for in-flight fragment selection. Simulation of isotope production at these facilities is crucial for experimentalists in this field.

What is the LISE⁺⁺ Software Suite?

LISE⁺⁺ is the predominant isotope production and simulation software used at many of the facilities mentioned above. The software has two primary uses: experiment planning and spectrometer design.

The former uses the LISE⁺⁺ software to simulate the production transmission and yields of desired projectile fragments through a spectrometer [1]. LISE⁺⁺ provides models for reaction mechanisms for isotope production : projectile fragmentation, fusion-residual, fusionfission, coulomb fission, and abrasion-fission. For spectrometer design, construction of a spectrometer is implemented through the use of material and optical "blocks". These "blocks" can consist of detector and target materials, dipole magnets, and other materials commonly used in these experiments...

Friystal calculator			
	A Element Z Q	after/into Si 513 micron	
File Options Experiment Settings Physics Models Calculations Utilities 1D-Plot 2D-Plot Databases Help			
		Energy Remain C 114.91 MeV/u	
	Stable Ion mass = 21 9622 arm	Enumit and 1E0.0E Make	
Projectile 40Ar18+ 50 MaVin 1 not	ion mass = 51.3655 dem	Energy Loss 1 136.65 Mev	
Eragment 32S16+		Energy Strag.(sigma) 0.054194 MeV/u	
To Target 191Ta 46V 47V 48V 49V 50V 51V 52V 53V	Energy C 119.879 MeV/u Energy C 119.7417 AMeV	Angular Strag (sigma) 1 6622 mrad	
	Brho C 3,24885 Tm TKE C 3831.73 MeV	(plane)	
Brho ▲ 39 _{Ti} 40 _{Ti} 41 _{Ti}		Lateral spread (sigma) 0.085182 microns	
	Erho C 452.276 MJ/C Velocity C 13.9022 cm/ns	Brho (for Q=Z) 3.1768 Tm	
QUI Q017-1TA QUAD Contribution Contribution 40 S	P C 15583.7 MeV/c Beta C 0.4637264		
2018 standard 1s:289 Tm		Equilibrium values for material "Si"	
	p_trnspt C 0.97398 GeV/C Gamma C 1.128696	Charge State <q> 16</q>	
2020 standard 1.8289 Tm	After • Stripper	dQ (sigma) 0.02	
	Energy Remain. E-Loss	Thiskey 1 C107 mg/cm2	
S □ z022 standard 129e-7 6 25e-2 4.07e+1 7 23e M 700 407e+06 c010eed 000 00	Block Z\Thickness MeV/u MeV MeV <q></q>	Thickness 1.6107 hig/cm2	
D1 Brho 0% 0.389% 24.499% 82.96 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0% 0%	FP PIN Si 513 micron 114.91 3672.9 158.85 16.00		
S 2030 Standard S 2050 5EL4 cm 2956-4 271ee0 7ee2 137e-4 164e (b)	M ED Cha Ci E00 minute 100.02 (2512.2) 150.02 10.00		
	rr_sta 51500 micron 103.32 3513.3 153.62 16.00	Hange and Energy Loss to 51	
	FP_Sta Si 1000 micron 99.408 3177.4 335.86 16.00	Range dRange (sigma)	
	M FP_Sta Si 1000 micron 88.032 2813.8 363.6 16.00	C 1690.27 2 5605 materia	
	FP Sta Si 1000 micron 75 463 2412 1 401 74 16 00	1030.37 1 3.3603 mg/cm2	
2/369-3 9/1e+0 2/3e+3 2/59+4 3/14e+4 1/24e+4 1/9/e Add 0.014% 3/441% 41.276% 60.982% 20.407% 4/467% 0.743 + 400		C 7282.33 15.339 micron	
28p 29p 30p 31p 32p 33p 34p A	FP_Sta Si 1000 micron 61.113 1953.4 458.7 16.00		
G S X 40 378% 54 023% 18 769% 5 345% 1 238% 0 243	FP_SCI C9H10100 mm 0 0 1953.4 0.00	Energy Remain. 0.000 MeV/u	
27 Si 28 Si 29 Si 30 Si 31 Si 32 Si 33 S		Material Mislances 1690.4 mg/cm2	

Updates and Future Plans

To ensure longevity of the LISE⁺⁺ program for future operating systems, the LISE++ program will be transported to a modern graphics framework. Additional benefits include providing a 64-bit application, cross-platform compatibility, and the ability to take advantage of computational advances.

The calculations of beam transport and isotope production are becoming more computationally intense with the new large scale facilities. For example, the 90 m long FRIB separator will have around fifty magnetic elements and ten points of beam interactions with matter. In order to perform the calculations in acceptable time, numerical optimization and parallel methods will be applied.

Qt was chosen as the graphics framework for its feature set and widespread use in cross-platform C++ applications

Future plans include improved numerical optimization methods in areas such as ion optics and reaction models. Lastly, integration with control systems are planned.





Fig. 1: The LISE⁺⁺ main GUI with a ⊿E vs Total Kinetic Energy particle identification simulation plot overlaid.

	for energy rest 7282.3 micron
Print ? Help X Quit	Calculation method of Energy Losses 2 Energy straggling 1 Charge States 3 Angular straggling 1

Fig. 2: The physical calculator is a widely used utility in the LISE⁺⁺ framework. It calculates the energy loss through an unlimited number of material "blocks".

framework transportation, verify the new code, then implement improvements.

Fig. 3: Horizontal space envelope of the A1900 fragment separator at NSCL calculated with LISE++. This represents the beam ray paths through the spectrometer.

Motivation for Update

The current version of LISE⁺⁺ is available on the Windows operating system with 32 bit compilation. The program was developed within the Borland C++ framework. In order to update the software to meet demands of the new large scale facilities, the software will be converted to a new development environment. Since 1998, the code has grown immensely. It started on MS-DOS with 14 C++ files and less than 10,000 lines of code and grew to 606 files on MS Windows today. With over 350 thousand lines of code, this is a significant undertaking and the verification and validation of the conversion is a very important process.

Current Progress

The first release of the new LISE++ software suite was the LISE++ Utilities Package, released March 4, 2015. This is a cross platform transportation of the satellite utilities in LISE framework to Qt. The package consists of five stand-alone programs useful for experiment design.

Work is now underway to convert the entire LISE⁺⁺ program to Qt with ISO C++ Standard.

mpound nucleus excitation energ

The NSCL is funded in part by

Michigan State University and

the National Science

Foundation

-value of reaction (MeV) mpound nucleus recoil energy oound nucleus recoil velocity (

Units Converter

Fig. 5: The application on the left side is the LISE++ Utilities Package which launches the Qt ISO C++ versions of the satellite utilities. On the right side is an example of a PACE4 calculation using the new



Download

LISE++ : http://lise.nscl.msu.edu/download/ **LISE++ Qt Utilities:** http://lise.nsl.msu.edu/porting

package.

7

UCLEAR SCIENCE and SECURITY CONSORTIUM

References

[1] LISE++ : Radioactive beam production with inflight separators O.B.Tarasov, D.Bazin, NIM B 266 (2008) 4657-4664 http://lise.nscl.msu.edu

MICHIGAN STATE

<u>UNIVERSIT</u>

300.00	If BarFac is negative, its absolute value will be taken as a factor to multiply the Sierk barrier.			
143.089	ARATIO 1 Ratio of the Fermi gas level density parameter 'LITTLE-A' at the saddle point to the ground state value. The saddle point level density is determined by g.s. 'LITTLE-A' * ARATIO.			
-73.191 83.721	FACLA 10 level density parameter = MASS/FACLA if r if == 0 Gilbert and Cameron value used.	not zero.		
9.698e-01	IDIST			
3 734-117	 = 0 brief, schematic results of particle spectra and list of evaporated (= 1 detailed angular and energy distribution of residual nuclei and evap = 2 detailed(1) + transmission coefficients for particle emission 	residual) nuclei porated particles	Limits of residual yields (in %) to show angular and energy distributions	
		24 DA	Low limit 2	
	• = 0 compound nucleus is initially M=0 states and the Z-axis is the recoi	il axis		
	○ = 1 compound nucleus is initially M=J states and the z-axis is perp. to	recoil direction	High limit 100	
	ITRAC - (controls the degree of event traceback)	Particle analysis		
	• = 0 produces compact traceback, summed over all residues		Nucleus gate	
	= 1 detailed traceback leading to each individual isotope separately	neutron ?	Use Use	
	NOSHL	proton	Z = 10	
	= 0 uses AME2003 values (A&W&T, NPA 729, 2003, pp. 336-676) = 1 uses I vsekil massese with shell correction	🗌 alpha	A = 20	
	216.28 143.089 -73.191 83.721 9.698e-01 <u>3.733e-02</u>	100.00 If BarFac is negative, its absolute value will solute value will solute value. The saddle point level density parameter state value. The saddle point level density parameter states and list of evaporated (100.00 If BarFac is negative, its absolute value will be taken as a factor to multip 216.28 Ratio of the Fermi gas level density parameter 'LITTLE-A' at the saddle p 143.089 state value. The saddle point level density is determined by g.s. 'LITTLE-73.191 83.721 Image: state value. The saddle point level density is determined by g.s. 'LITTLE-73.191 83.721 Image: state value. The saddle point level density is determined by g.s. 'LITTLE-73.191 9.698e-01 Image: state value. The saddle point level density is determined by g.s. 'LITTLE-73.191 9.698e-01 Image: state value. The saddle point level density is determined by g.s. 'LITTLE-73.191 9.698e-01 Image: state value. The saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point level density is determined by g.s. 'LITTLE-73.191 9.698e-01 Image: state value. The saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point level density parameter'LITTLE-A' at the saddle point level density parameter 'LITTLE-A' at the saddle point	

ACKNOWLEDGEMENTS AND DISCLAIMER:

This material is based upon work supported by the Department of Energy National Nuclear Security Administration under Award Number: DE-NA0000979 through the Nuclear Science and Security Consortium and the US National Science Foundation under Grants No. PHY-06-06007, No. PHY-10-68217, and No. PHY-11-02511.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or limited, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.