



**High
Luminosity
LHC**

Vacuum interfaces and crab cavities (SPS/LHC)

**V. Baglin (TE-VSC)
on behalf of WP12**

**4th Joint HiLumi LHC-LARP Annual Meeting
KEK – 17-21 November 2014**



The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.




Outline

1. COLDEX in SPS
2. Crab cavities in SPS
3. Crab cavities in LHC
4. Conclusion

1. COLDEX in SPS

Motivation: HL-LHC Inner Triplets

- Extrapolation for the HL-LHC of Run 1 observations **predicts** large heat load due to **electron cloud** on the beam screen of the inner triplets
- This increase of heat load will be accompanied by increase of background to the experiments
- To reduce the heat load to ~ 200 W on the beam screen, **amorphous carbon** (a-C) **coating** is proposed (SEY ~ 1.1)
- This base line must be **validated** at cryogenic temperature with LHC type beams





G. Iadarola, G. Rumolo
3rd Joint HiLumi LHC-LARP Annual Meeting, Daresbury
11-15/01/2013

What is COLDEX ?

COLD (Bore) **EX**(periment) – installed at CERN-SPS (BA4)

Mimics the LHC cold bore and beam screen section, for electron cloud studies



- Mitigate the electron cloud build-up with **amorphous carbon coating**
- Operate in the BS in the 40 to 60 K temperature range
- Reduce background to experiments


- Refurbishment of COLDEX : strong support and commitment of many CERN groups: **TE-CRG, BE-OP, BE-ABP, TE-EPC, EN-ICE**

COLDEX Scientific Objectives

- Accumulate beam time with:
 - a-C coating on Cu (HL-LHC inner triplets & matching section)
- Studies with LHC type beams of:
 - Pressure increase
 - Gas composition
 - Heat load
 - Electron flux
- Study multipacting triggering vs:
 - BS temperature
 - Beam structure and bunch intensity
- Study the impact of BS temperature:
 - 5-20 K for HL-LHC matching section
 - 40-60 K for HL-LHC inner triplets
- Studies of operational impact of:
 - Gas pre-condensation, H₂, CH₄, H₂O, CO and CO₂: simulates long term operation and impact of quenches
 - Temperature oscillations / excursion

Current schedule

- Study long term behaviour during “scrubbing runs”:
 - 9 days in 2014 + 7 days in 2015 → 15 days with a-C copper coated beam screen




- Specific studies during “Injector Complex MD block”: 1 shift of 8 h
 - None in 2014 + some blocks (5 ?) → still to be defined in 2015
- Remark: COLDEX needs to be moved in/out so not compatible with floating injector MD where LHC beam has priority


Preliminary results

- a-C beam screen held at 50 K, 5 k then 10 K while cold bore ~ 4K
- LHC type beams circulating in SPS (3-9/11/2014):
 - Heat load < 1 W/m
 - Pressure rise < 5 10⁻⁹ mbar
 - Main gas is H₂

~2.2 m, ID 67 beam screen
Internally coated with amorphous carbon



COLDEX - 2014 SPS Scrubbing Run 1 - 06/11/2014
Residual Gas Analyser 1 (COLDEX)
CB 4.5 K - BS 50 K



R. Salemme, IEFC, 14/11/2014

2. Crab Cavities in SPS

Current Schedule (tbc)



- The SPS crab cavity tests bench is proposed to be installed in BA4
- The schedule was **revised** for this meeting and needs to be approved (A . Macpherson private communication, 14/11/2014)
- Preparatory work in 2015-2016 YETS
- Installation of crab infrastructure to start by December 2016 (EYETS) :
 - RF power installation
 - Supporting table
 - New cryogenic cooling system at 2 K
 - **New vacuum bypass** (Jan 2017)
- COLDEX could operate during **2015, 2016** (tbc)

Impact of Schedule

- This implies:
 - Dec 2016, removal of COLDEX (in a non destructive way): Time estimate ~ 1 week
 - Installation of a new vacuum system to accommodate the crab cavity test bench
- Potential impact on the COLDEX scientific program (HL-LHC and also FCC)
- The location of the SPS crab cavity test bench in BA4 was driven by the presence of a cryogenic system (4.2 K) and the presence of a bypass system, but, following studies, both systems have to be replaced by new ones.
 - Other location might be envisaged e.g. BA5 which is very similar to BA4
 - This would open the possibility for CERN to possess TWO beam test stations operating at cryogenic temperature: an advantage for HL-LHC but also FCC

Layout

- Operating pressure $\sim 10^{-10}$ mbar with beams: a detailed **computational analysis** is needed
- Similarly to LHC, **NEG coated** vacuum chambers between V1 and V2 (except CC module !)
 - Differential pumping system between V1/V2 and module
 - If needed, a-C coating or solenoids could be implemented elsewhere



- A new layout must be defined by **June 2015** to complete the design of the “Y” chamber and start the procurement of components

SM18 preparation



- Vertical test bench for cavities to be refurbish by March 2015
 - Industrial support
 - Material defined (mobile pumping group, bakeout, RGA)
 - Quoted launched
 - Budget defined

- Horizontal test bench located in bunker for modules needs to be operational for 2016

3. Crab Cavities in HL-LHC

Crab Cavities

- Operating pressure $\sim 10^{-10}$ mbar with beams
- 2 designs with bulk Nb operating at 2 K
- Vacuum instrumentation on the modules is under definition
- Drawings and leak detection procedures needs to be validated by VSC



Cryomodules for the DQW (left) and RFD (right) cavities respectively

Courtesy R. Calaga, O. Capatina

Crab Cavities

- Bulk Nb treatment is well **defined** (EDMS 1389669):
 - 150 micron chemical etching, 600 deg heat treatment, 10-20 micron chemical etching, high pressure water rinsing and finally a 120 deg bake
- **Impact of the electron cloud** in the CC modules must be evaluated:
 - Nb cavity itself
 - Inter-cavity tube
 - Module cold warm transition

Samples needed for qualification

1.1 < Nb film SEY < 1.7





FIGURE 2 SEY vs PE energy of a Nb thin film as a function of heating temperature at 1 h heating time (left plot) and as a function of heating time at 150 °C (right plot)

N. Hilleret *et al.*, Appl. Phys. A 79, 1085-1091 (2003)

Electron conditioning




N. Hilleret *et al.* EPAC 2000, Vienna, Austria



Layout –D2-Q4

side view




C4.R5



LHCLSXH_0010


A typical VA__

- Room temperature (except CC modules): bakeable and **NEG coated**
- 4 Sectorised CC modules:
 - **Standard** sectorisation valves (VA__), length 655 mm, at extremity
 - **Specific** sectorisation assembly, length 400, between modules. To be defined & designed. 2 beam line:
 - 2 roughing valve
 - 3 sector valve (beam interlocked)
 - 3 penning gauges + 2 ion pump + 2 pirani gauges



Layout –D2-Q4: 2nd beam pipe


- The 2nd beam pipe is held at 2 K and has cold warm transition (CWT) !
- Current material is Nb, diameter limited by space
- In LHC, maximum length without beam screen is < 1 m (to be revised for HL-LHC)
- Detailed studies are needed to comply with vacuum stability and pressure level



4. Conclusions

Conclusions

- COLDEX has started data taking to validate WP12 a-C coating base line:
 - should operate in 2015 and 2016
- SPS layout with crab cavities needs to be validated by mid-2015 to complete design and start procurement of components
- Crab cavity vacuum layout in HL-LHC is under definition
- Dedicated studies are needed to:
 - understand the impact of electron cloud
 - design the 2nd beam pipe of the module




High Luminosity LHC

**Thank you for
your attention**



The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.





High Luminosity LHC



The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.

