




Laser-based Emittance Measurements for H- Beams

BI Day 2014

T. Hofmann, E. Bravin, U. Raich,
F. Roncarolo, F. Zocca (CERN)








G. Boorman, A. Bosco, S. Gibson,
K. Kruchinin (RHUL)



Thank you for your attention!

Thomas Hofmann
CERN – Beam Instrumentation (BE/BI/PM)
thomas.hofmann@cern.ch

This project has received funding from the European Union's Seventh Framework Programme for research, technological development and demonstration under grant agreement no 289191






Laser-based Emittance Measurements for H- Beams

BI Day 2014





T. Hofmann, E. Bravin, U. Raich,
F. Roncarolo, F. Zocca (CERN)

G. Boorman, A. Bosco, S. Gibson,
K. Kruchinin (RHUL)



Thank you for your attention!

Thomas Hofmann
CERN – Beam Instrumentation (BE/BI/PM)
thomas.hofmann@cern.ch



Conclusions

Status

- A novel instrument based on a fiberlaser and diamond detector for emittance measurement of H-beams was successfully commissioned.
- Comparison with the slit and grid system showed good agreement at the LINAC4 3 MeV beam

Outlook


- Further tests 12 MeV LINAC4 beam are currently ongoing.
- Instrument design for final location at 160 MeV, including electron collection for profile measurement

LA.NET

This project has received funding from the European Union's Seventh Framework Programme for research, technological development and demonstration under grant agreement no 289191



LINAC4



Conventional method for emittance measurement (**slit & grid**) is not working at this energy, due to the particle range.




Foreseen emittance measurement at 160 MeV:
"3 profile method"

Limitations:

- Maximum pulse length: 100 μ s (400 μ s nominal)
- Space charge disturbance
- Destructive



Concept



State of the art



Laser Diagnostics at SNS



Beam Energy: 2.5 MeV ... 1 GeV

Beam Current: 38 mA

Laser Pulse Energy: 50 mJ

Laser Pulse Width: 10 ns

- ① MEBT Laser Bunch Shape Monitor
- ② SCL Laser Wire Profile Monitor
- ③ HEBT Laser Emittance System




Y. Liu et al., Laser based diagnostics for measuring H- beam parameters, Proc. PAC 2011, New York, NY, USA

Challenge: 250m long free-space laser delivery

Test-Setup

3 MeV / 12 MeV Diagnostic Test bench




Laser diameter:
150 μm



H⁻ Beam


$\sigma = 1 \dots 3 \text{ mm}$




Laser source



Manlight ML30-PL-R-TKS
(commercial available)




Laser	Fiberlaser (used in tests)	Nd-YAG (as reference)
Energy per pulse	0.1 mJ	50 mJ
Diameter	$\sim 150 \mu\text{m}$	$\sim 200 \mu\text{m}$
P_{strip} @ 160 MeV for H ⁻ crossing Laser	0.1 %	> 99 %
t_{pulse}	80 ns	5...10 ns
Repetition rate	10...100 kHz	< 20 Hz
Beam transport	Fiber	Free Space




Laser source




Manlight ML30-PL-R-TKS
(commercial available)





Klystron Hall




Shaft to L4
Tunnel, for laser
transport

Laser Room


Test-Setup

3 MeV / 12 MeV Diagnostic Test bench




Diamond Strip Detector

- Prototype -



Ref: CIVIDEC Instrumentation, Austria




- High sensitivity ($\sim 10^4 e^- / H^0$)
- High bandwidth (< ns)
- Radiation tolerant ($10^{15} cm^{-2}$)
- Strip electrodes for spatial resolution

Results

Diamond detector raw signals


Laser pulse & diamond signal compared



- Laser stripped H₀ clearly arriving at diamond detector
- Very linear response of diamond detector

Macropulse level


preliminary results - 12 MeV commissioning



- Diamond signal proportional to beam current
(in contrast to signal decrease at 3 MeV tests)


Comparison with Slit & Grid

Beam profile



$$\sigma_{\text{Laser}} = 1.49 \text{ mm} \quad \sigma_{\text{Slit/Grid}} = 1.36 \text{ mm}$$


Emittance



Disagreement: < 2 %

F. Roncarolo et al., Transverse profile and emittance measurements with a laser stripping system during the CERN LINAC4 commissioning at 3 and 12 MeV, Proc. LINAC14, Geneva, Switzerland


Laser pulse & diamond signal compared



- Laser stripped H0 clearly arriving at diamond detector
- Very linear response of diamond detector

Macropulse level

preliminary results - 12 MeV commissioning




- Diamond signal proportional to beam current
(in contrast to signal decrease at 3 MeV tests)

Results

Diamond detector raw signals


Laser pulse & diamond signal compared



- Laser stripped H₀ clearly arriving at diamond detector
- Very linear response of diamond detector

Macropulse level


preliminary results - 12 MeV commissioning



- Diamond signal proportional to beam current
(in contrast to signal decrease at 3 MeV tests)


Comparison with Slit & Grid

Beam profile



$$\sigma_{\text{Laser}} = 1.49 \text{ mm} \quad \sigma_{\text{Slit/Grid}} = 1.36 \text{ mm}$$


Emittance



Disagreement: < 2 %


F. Roncarolo et al., Transverse profile and emittance measurements with a laser stripping system during the CERN LINAC4 commissioning at 3 and 12 MeV, Proc. LINAC14, Geneva, Switzerland

Beam profile





$$\sigma_{Laser} = 1.49 \text{ mm} \quad \sigma_{Slit/Grid} = 1.36 \text{ mm}$$

Emittance



Emittance



Disagreement: < 2 %

F. Roncarolo et al., Transverse profile and emittance measurements with a laser stripping system during the CERN LINAC4 commissioning at 3 and 12 MeV, Proc. LINAC14, Geneva, Switzerland

Conclusions

Status

- A novel instrument based on a fiberlaser and diamond detector for emittance measurement of H-beams was successfully commissioned
- Comparison with the slit and grid system showed good agreement at the LINAC4 3 MeV beam

Outlook

- Further tests 12 MeV LINAC4 beam are currently ongoing
- Instrument design for final location at 160 MeV, including electron collection for profile measurement




Laser-based Emittance Measurements for H- Beams

BI Day 2014





T. Hofmann, E. Bravin, U. Raich,
F. Roncarolo, F. Zocca (CERN)

G. Boorman, A. Bosco, S. Gibson,
K. Kruchinin (RHUL)



Thank you for your attention!

Thomas Hofmann
CERN – Beam Instrumentation (BE/BI/PM)
thomas.hofmann@cern.ch



Conclusions

Status

- A novel instrument based on a fiberlaser and diamond detector for emittance measurement of H-beams was successfully commissioned.
- Comparison with the slit and grid system showed good agreement at the LINAC4 3 MeV beam

Outlook

- Further tests 12 MeV LINAC4 beam are currently ongoing.
- Instrument design for final location at 160 MeV, including electron collection for profile measurement

This project has received funding from the European Union's Seventh Framework Programme for research, technological development and demonstration under grant agreement no 289191

LA.NET

