

Conceptual Specifications review: Layouts in LSS 4, ATLAS, CMS, LHCb, ALICE, Collimator bypass assembly and insulation vacuum system

V. Baglin (TE-VSC)

11th HL-LHC Technical Committee CERN – 2nd September 2014



The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.



• Thanks to everybody for their comments

• Dead line to implement them ?



HL-LHC LSS4 layout EDMS 1361099

- Ensure vacuum performances:
 - ACS < 10⁻¹⁰ mbar with beams
 - Bakeout temperature to 200°C (300°C) for NEG (St.St)
 - Heating rate = 50 °C / h
- Vacuum sectorisation & instrumentation
- Interface to other systems:
 - variants minimisation
 - Offsets / transitions included into equipments
 - Circular apertures
- Cryogenic temperature : only new ACS
- Re-use of standard LHC interfaces

HL-LHC ATLAS vacuum system (1/2) EDMS 1361088

- From Q1L1 to Q1R1, Q1 excluded
- Valve sectorisation:
 - At Q1 to decouple warm to cryogenic temperature (interlocked)
 - Between TAS-Q1 to decouple experiment/machine (not interlocked)
- Q1-TAS:
 - Pumping system (L1 only, R1 need to be installed)
 - Pure Ne/pumping injection (L1 only, R1 need to be installed)
 - Rupture disk
 - Remote tooling
 - Robust component, "quick" flanges
- Permanent bakeout system (compatible with other systems)

4

HL-LHC ATLAS vacuum system (2/2) EDMS 1361088

- Experimental cavern:
 - Permanent bakeout
 - TAS area to be redesigned wrt to ALARA
 - Al chambers for radioactivity reasons
 - Conflat bolted technology, "quick flange" type connection in hot radiation areas, no sliding RF fingers
 - Remote alignment of chambers (avoid people during WTS)
 - Ne venting during long stops (> 10 days)
- Assumptions:
 - Same central chamber since LS1.
 - TAS to be exchanged implies venting / re-commissionnning



of the ATLAS vacuum system

HL-LHC CMS vacuum system (1/2) EDMS 1361089

- From Q1L5 to Q1R5, Q1 excluded
- Valve sectorisation:
 - At Q1 to decouple warm to cryogenic temperature (interlocked)
 - Between TAS-Q1 to decouple experiment/machine (not interlocked)
- Q1-TAS:
 - Pumping system (L&R installed)
 - Pure Ne/pumping injection (L&R installed)
 - Rupture disk
 - Remote tooling
 - Robust component, "quick" flanges
- Permanent bakeout system (compatible with other systems)

6

HL-LHC CMS vacuum system (2/2) EDMS 1361089

- Experimental cavern:
 - No permanent bakeout: tbd if needed for ALARA
 - TAS area to be redesigned wrt to ALARA
 - Al chambers for radioactivity reasons
 - Conflat bolted technology, "quick flange" type connection in hot radiation areas, no sliding RF fingers
 - Remote alignment of chambers (avoid people during WTS)
 - Ne venting during long stops (> 10 days)
- Assumptions:
 - Same central chamber since LS1
 - Al chambers installed during LS2: no intervention between TAS5L and TAS5R during LS3
 - TAS to be exchanged during LS3 implies venting / recommissionnning of the CMS vacuum system



HL-LHC LHCb vacuum system (1/2) EDMS 1361090 • From Q1L8 to Q1R8, Q1 excluded

- Valve sectorisation:
 - At Q1 to decouple warm to cryogenic temperature (interlocked)
 - Between Cavern-Q1 to decouple experiment/machine (not interlocked)
- Q1-cavern:
 - Rupture disk
- LHCb vacuum sectors:
 - Requires a complete NEG re-activation in case of opening



HL-LHC LHCb vacuum system (2/2) EDMS 1361090

- Experimental cavern:
 - VELO has a gas balance system operating at atmospheric pressure and UHV. Used to perform Ne venting
 - VELO system must be baked to 180-200°C (@50 °C / h) to suppress electron cloud
 - Al chambers preferred for radioactivity reasons
 - Conflat bolted technology, "quick flange" type connection in hot radiation areas, no sliding RF fingers
 - Remote alignment of chambers (avoid people during WTS)
- Assumptions:
 - Part of the detector to be equipped with permanent bakeout during LS2.
 - New VELO and VCDBV installed during LS2: no vacuum (mechanical, bakeout, NEG activation) interventions in the cavern during LS3



HL-LHC ALICE vacuum system (1/2) EDMS 1361091 • From Q1L2 to Q1R2, Q1 excluded

- Valve sectorisation:
 - At Q1 to decouple warm to cryogenic temperature (interlocked)
 - Between Cavern-Q1 to decouple experiment/machine (not interlocked)
- Q1-Cavern:

uminosity

- Pumping system (R2 only)
- Pure Ne/pumping injection (R2 only)
- Rupture disk

HL-LHC ALICE vacuum system (2/2) EDMS 1361091

- Experimental cavern:
 - RB24 vacuum sector with a manual valve on the left side of ALICE central chamber
 - RB26 vacuum chambers equipped with permanent bake out system
 - Al chambers preferred for radioactivity reasons
 - Conflat bolted technology, "quick flange" type connection in hot radiation areas, no sliding RF fingers
 - Remote alignment of chambers (avoid people during WTS)
- Assumptions:
 - New central chamber installed during LS2: no vacuum (mechanical, bakeout, NEG activation) interventions in the cavern during LS3



HL-LHC Collimator-bypass assembly EDMS 1361087

- Install in some dispersion areas
- Room temperature collimator
- Vacuum sectorisation & instrumentation of both beam pipes
- RF ball compatible
- Bake able room temperature lines
- "quick flange" type connection, integrated functionalities to gain lenght
- Re-use of standard LHC interfaces
- New design, with continuous beam screen on 2nd pipe, under study
- Assumptions:
 - Installation around IP2 during LS2.
 - Installation areas during LS3 will be defined by WP5 (collimation)



HL-LHC Insulation vacuum system EDMS 1361095

- LSS1 and LSS5
- He leak rate, at component level, < 10⁻¹⁰ mbar.l/s
- Permanent turbo-molecular pumping
- Compatible with LHC insulation system
- Re-use of LHC standard
- In high radiation areas, specific seals have to be foreseen to replace Viton in NBR







The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.

