

# FCC-hh

# INJECTION AND EXTRACTION

---

Wolfgang Bartmann, CERN

with many inputs from

M. Atanasov, M.J. Barnes, J. Borburgh, T. Fowler, B. Goddard, W. Herr,  
T. Kramer, A. Lechner, M. Meddahi, R. Ostojic, R. Schmidt, D. Schulte

FCC week, 23<sup>th</sup>-27<sup>th</sup> March 2015

# Outline

- FCC injection
  - Machine protection consideration
  - Kicker rise time specification
  - Septum strength
  - Optics and overall insertion length
- FCC dump system
  - Extraction locations and link with collimation
  - Insertion overview and alternative concepts
  - Dump block limitations
- Summary
  - Challenges
  - Study directions and R&D programs
  - Timeline


# FCC-hh parameters

Beam parameters	Unit	Injection	Extraction
Kinetic energy	TeV	3.3	50
$\beta_{rel}$		$\approx 1$	$\approx 1$
$\gamma_{rel}$		3518	53290
Revolution period	$\mu s$	333	333
Magnetic rigidity	T.m	11011	166785
# bunches		10600	10600
Transverse emittances	$\mu m$	2.2	2.2
Total beam energy	GJ	0.65	8.5

Table 1: Beam parameters at FCC injection and extraction.


# Injection concept

- Fast bunch-to-bucket transfer
- A total of 650 MJ beam energy to transfer
- For HL-LHC with an injected beam energy of **~5 MJ reach limit of injection protection devices**
- **Transfer beam from HEB to FCC in stages**
- 50 – 70 bunches per transfer
  - Gives a total of ~200 injections to fill FCC
  - ~60 injections to transfer a full LHC bunch train
- Time required for the injection process
  - Have to wait for re-synchronisation between machines (~10 ms for LHC-FCC case)
  - Total time required to inject one LHC bunch train ~0.5 s
  - Would need 3 - 4 LHC trains to fill FCC




# Constraints for FCC filling scheme

- Beam transfer from HEB to FCC is machine protection limited
- Aim to fill 80% of FCC
- Assume about 3  $\mu\text{s}$  for abort gap
- 280 ns rise time for injection kicker rise time



# FCC Injection Schematic



Massless septum as active injection protection?

# Injection septum strength






Figure 3: Kick angle and integrated field of septum and kicker as a function of the half cell length.

# Injection straight optics

- Increase regular half cell length from 100 m to 150 m in injection insertion
  - Relax magnet strengths, make space for instrumentation and protection devices
- Maximum betas of 620 m – why not go higher?
- Total injection insertion requires about 500 m for septum, kicker and internal dump
- Further protection downstream is required





# Injection HW


<b>Hardware parameters</b>	<b>Unit</b>	<b>Kicker</b>	<b>Septum</b>
Deflection	mrad	0.29	12.3
Integrated field	T.m	3.2	134
Available system length	m	120	90
Rise time	$\mu$ s	0.28	-
Flattop length	$\mu$ s	2.25	$\geq 2.25$
Flattop stability	%	$\pm 0.5$	$\pm 0.5$
GFR h/v	mm	18/18	18/18

Table 2: Parameters of kicker and Lambertson septum at FCC injection for a halfcell length of 125 m.

# FCC Extraction

# FCC Extraction

- Two separated extraction insertions
- Sequence of collimation and extraction systems
  - If betatron cleaning is separated would be ideal to have collimation downstream extraction
  - Protection of downstream machine and experiments in case of asynchronous dump



# Dump insertion – LHC scaled

Extraction kicker:

- 0.13 mrad, **22 T.m**
- 110 m drift

Enlarged quadrupole:


- 9 mm offset

Bump (not in LHC):

- 9 mm
- 0.3 mrad, **50 T.m**

Extraction septum:

- 17 mm septum width
- 150 m drift to clear blade
- 50 m for protection devices +2 bumpers
- **200 m available length**
- 1.7 mrad, **284 T.m, 1.42 T**





# Dump insertion alternatives

## SSC like


- Septum is part of extraction bump
- Use field free channel of septum to extract
- Need strong, good field quality septum

- Asymmetric insertion optics

- Avoid asynchronous dumps by accepting single kicker erratic
- High segmentation of kicker system (200-300 modules)
- Asymmetric optics
  - to reduce oscillation from single kicker failure (small hor beta)
  - to reduce kicker strength and dilute beam at absorbers (high betas at septum)




# Requirements for special quadrupoles



Enlarged quadrupole

Triple chamber quadrupole?

Beam offset:  
Injection up to 18 mm  
Extraction up to 9 mm




# Dump block limitations

- Assume 1.5 km dump line without active dilution
  - 400  $\mu\text{m}$  rms beam size at dump
- Assuming graphite (1.2-1.77 g/cm<sup>3</sup>)
  - Limit in energy density such that peak temperature of  $\sim 1500^\circ\text{C}$  not exceeded
  - Minimum of  $\sim 1.8$  mm separation between bunches  $\rightarrow$  requires min of 20 m linear sweep length!
- Actively dilute beam in dump line (beta function of 100 km)
  - 2.0 mm rms beam size
  - Still need  $\sim 1.5$  mm separation between bunches - **not much gain from active dilution**

See talk by A. Lechner:  
Energy deposition  
challenges

	Unit	25 ns	5 ns
Bunch population		1e11	0.2e11
# bunches		10600	53000
Transv. emittance normalised	$\mu\text{m}$	2.2	0.44
Spotsize at dump (rms) for 1.5 km dump line	mm	0.4 - 1.6	0.2 - 0.7
Total beam energy	GJ	8.5	8.5
Average power (5 h fills)	kW	500	500



# Summary

- Challenges
- Study direction and R&D programs
- Timeline



# Challenges

- Beam energy at HEB-FCC transfer and FCC injection
- Fast injection kicker field rise and recharging
- Injection protection: passive, maybe also active
- Asynchronous dump mitigation
  - Kicker system segmentation
  - Kicker generators: ultra-reliable triggering
- Asynchronous dump protection devices
- Dump absorber
- Beam dilution
- Special insertion magnets
- Limited access possibilities: hot spares, remote handling
- Controls and electronics: remote, compact, reliable, radiation hardness
- Power consumption/recycling
- Constraints on filling schemes from injection and dump

# Study directions and R&D programs

- **Conceptual**
  - Separate extraction systems and link to other systems
  - Failure mitigation (retriggering or segmented kicker system, #abort gaps)
  - Beam dilution
  - Minimize impact of injection and extraction on FCC filling scheme
- **Kicker system**
  - Generator: fast field rise time, short pulses and fast generator recharging; semiconductor switches
  - Magnet: Beam screen and ferrite cooling
  - Segmentation and built-in redundancy
- **Septa:**
  - High field Lambertson with high saturation material shims and NC or SC coils
  - Massless septum to deflect mis-kicked beam into dedicated injection dump channel
  - Superconducting septum
- **Electronics**
  - Radiation to electronics mitigation
  - Ultra-high reliability triggering and synchronisation concepts for highly segmented systems
- **Dump absorber and passive protection devices:**
  - Study new materials and concept of sacrificial absorbers
  - Beam dilution requirements

# Timeline

- 2015:
  - Detailed R&D program proposal for kicker generator, kicker and septum magnet, electronics
  - Finalize conceptual studies for injection, extraction and failure mitigation
  - Specify kicker systems, septa and special insertion magnets
- 2016:
  - Finalize linear optics of injection and dump lines; dilution pattern
  - Specify passive protection devices and massless septum for injection protection
- 2017:
  - Finish error studies, specify power converter stability and field homogeneities
  - Measurement report of individual components for kicker generators; design report prototype
  - Finished design of kicker beam screen and ferrite cooling; radiation hard sensor board developed
- 2018:
  - Finish prototype construction of kicker generator, kicker beam screen and septum
  - **CDR write-up**
- 2019:
  - Document prototype testing results of kicker generator, magnet, electronics and septa magnets