



Contribution ID: 52

Type: **Poster Presentation**

## Modeling Thermal Parasitic Load Lines for an Optical Refrigerator

*Monday, 29 June 2015 14:00 (2 hours)*

Optical refrigeration is currently the only completely solid state cooling method capable of reaching cryogenic temperatures from room temperature. Optical cooling utilizing Yb:YLF as the refrigerant crystal has resulted in temperatures lower than 123K measured via a fluorescence thermometry technique. However, to be useful as a refrigerator this cooling crystal must be attached to a sensor or other payload. The phenomenology behind laser cooling, known as anti-Stokes fluorescence, has a relatively low efficiency which makes the system level optimization and limitation of parasitic losses imperative. We propose and model a variety of potential designs for a final optical refrigerator, enclosure and thermal link; calculate conductive and radiative losses, and estimate direct fluorescence reabsorption. We generate parasitic load-lines; these curves define temperature-dependent minimum heat lift thresholds that must be achieved to generate useful cooling.

**Primary author:** MARTIN, Kyle (ATA/AFRL)

**Co-authors:** Mr DODSON, Christopher (Air Force research labs); Mr SCHOMACKER, Jason (Rensselaer Polytechnic Institute); Mr FRASER, Thomas (air force research labs)

**Presenters:** Mr DODSON, Christopher (Air Force research labs); Mr FRASER, Thomas (air force research labs)

**Session Classification:** C1PoJ - Novel Concepts and New Devices I

**Track Classification:** CEC-17 - Novel Concepts and New Devices