

# Importance of PURESAFE for the FAIR facility

Helmut Weick, GSI CERN Geneva, 19. Jan. 2015

- Overview FAIR / Super-FRS
- Radiation Areas
- Robot Handling
- Engineering Management








## FAIR - Facility for Antiproton and Ion Research



material science, bio physics




### **FAIR Construction Site**




## Super-FRS - Overview -





beam

Maintenance requires remote handling



#### **Radiation Areas Intervention Planning**

#### **Existing GSI:**

- Grid of radiation monitors in the halls for prompt dose.
- Systematic tables of many measurement points along beamline, activation measured shortly after beam time and later, allows comparison with past and some extrapolation.

#### **Examples of more information needed:**

Unforeseen beam losses before main beam dump

Areas behind

**FRS** target

S. Damianovic

-> Too high radiation to neighboring area,

no maintenance work possible at the same time.



Work on FRS target ladders.
on outside, but inside?

s much on history of usage.



#### **Radiation Areas Intervention Planning**



beam time, FLUKA

FAIR requires more care and planning, also easier access to information.


Simulations can predict radiation levels, provided sufficient input. Measurements are necessary, automated measurements helpful. Intervention planning with dose prediction wanted.

→ Combine information,

Software for analysis and visualisation (T. Fabry RP13)

Integrate in planning tool (M. Baudin RP2)


Full benefit requires data base of configuration materials, beams, and an evaluation including the tasks.



#### **Open the Black Box**

Most interesting things are mounted inside vacuum chambers. Super-FRS will use at many positions inserts into the beam: shaped energy degraders, many different tracking detectors. Drawings exist, but not close to device, interaction can be unclear. Visualize also things not directly visible (e.g. radiation).

→ augmented reality, H. Martinez (RP11)



#### **Use of Robotics**



Industrial standard robots are available at large variety, with low price compared to specially constructed manipulators.

**Mobility is important** 

- Speed is less an issue repetitions are few, time limited by other things
  - get robot out off prompt radiation
  - service many positions, monitor large areas

- **Controls are important communication in heavily shielded tunnels,** 
  - autonomous motion can help, but for rare use also manual remote control possible
  - position adjustment in environment

**Tools** 

- for normal robots devices must be adapted
- detailed intervention / handling planning needed
- teaching

Maintenance Safety

- maintain robot itself (modular ?),
- power management, rescue scenarios

### Remote Handling in Open Tunnel




robot at existing FRS target at GSI





concepts, F. Amjad (RP9)




#### Many steps solved/ to be solved before

IMoro as test device, safe path planning with obstacles (R. Oftadeh, RP14)

autonomous positioning for better precision (M. Aref, RP10)

Communication with WLAN relais on robots, (R. Parasuraman RP6)

Power management (RP 6, 8,14)



Wide spread need for smaller surveillance robot.

Tasks: Visual inspection, dose rate measurements, leak testing ...

Not only radiation is hazardous environment, Super-conducting magnets at current are pressure vessels with a lot of energy stored.

Here also modular concepts can be important (P. S. Pagala, RP8)





# The safe approach with shielding plugs minimize RH at beamline place, RH in hot cell

target area: from beamline to hot cell shielding flask target plug on crane (60t) shielding

develop design/techniques for manipulators and robots (L. Orona RP7)



#### **Engineering Management**



Accelerator facilities are a different kind of product. Interaction of many:

Civil construction ←→ Accelerators ←→ Experiments ←
→ Safety/approving authorities ←→ Funding Agencies

Our OpenSE draft demands definition of Project Team and of the Stakeholders. That is now the case for FAIR@GSI, more after merger of GSI and FAIR.

OpenSE also comes with systems engineering guidelines.

Many technical guidelines exist for FAIR, but only directly on equipment.

In Puresafe **RAMS** (Reliability, Availability, Maintainability, Safety) is one of the words used most.

Configuration management (CM) (M. Niknam RP5),

Risk management (D. Imran Khan RP1),

Product Life Cycle Management (PLM) (M. Lintala RP4), information

"CM and PLM were added very late in the (FAIR) project", Oliver Kester, 16.1.2015 Maturity models like CM<sup>3</sup> can help to define goals.

Innovation model, (J. Hyppölä RP3), analysis in EU projects and big facilities

#### **Summary / Conclusion**







Learned extended possibilities in planning and visualisation.

Large information gain in field of robotics.

Possibility of more future collaboration with experts.

Engineering management was so far involved only as example, but can also benefit.

ESRs are a gain for all of us.



