

FELIX

: the detector readout
upgrade of the ATLAS experiment

Soo Ryu

Argonne National Laboratory, sryu@anl.gov

(on behalf of the FELIX group)

FELIX group



John Anderson, Soo Ryu, Jinlong Zhang



Hucheng Chen, Kai Chen, Francesco Lanni



Andrea Borga, Henk Boterenbrood, Frans Schreuder, Jos Vermeulen



Lorne Levinson, Julia Narevicius, Alex Roich



Benedetto Gorini, Markus Joos, Giovanna Lehmann, Jorn Schumacher ,
Wainer Vandelli


Brief about FELIX

- What is FELIX ?
 - Front End Link Interface eXchange
 - the new ATLAS Readout for Run4(2023)
 - a heterogeneous switch
- Why we change?
 - Upon the change of link protocol on FE side from S-Link to GBT-Link
 - To introduce Commercial Off-The-Shelf (COTS) products → convenient to scale up the electronic components

GBT-link : radiation hard bi-directional optical link protocol developed by CERN
<https://espace.cern.ch/GBT-Project/GBT-FPGA/default.aspx>


aspx

ATLAS TDAQ : Current (2015)



FE : Front-End
 ROD : Read Out Driver
 ROS : Read Out System (buffer)
 HLTPU: High Level Trigger
 Processing Unit


ATLAS TDAQ : Run4 (2023)



ROD-like features can be implemented in **downstream of FELIX** either in software or in hardware

FE : Front-End
 ROS : Read Out System (buffer)
 HLTPU: High Level Trigger Processing Unit

Feature and functionality



A new TDAQ architecture based on FELIX will become


1. Scalable
2. Heterogeneous

Routing of multiple traffic types:
 (physics events, detector control, configuration, calibration, monitoring)
 Reconfigurable data path
 Multicasting, Cloning, QoS



Automatic failover and load balancing
 Trigger data, LHC clock distribution

E-link: variable-width logical link on top GBT. Can be used to logically separate different streams on a single link.

FELIX Architectural View




Development Platform




High Tech
Global 710

Xilinx Virtex 7
CXP module : 12ch




Mellanox
ConnectX-3 EN


40Gbps x 2port



FELIX Functional View




FELIX demonstrator test results




- Split functional Test
 - Forwarding trigger signal and LHC clock (TTC – CR – GBT – FE)
 - PCI DMA performance
 - Network throughput
- Combined test : Full FPGA chain

Trigger/Clock Forwarding test




- **Split functional Test**
 - **Forwarding trigger signal and LHC clock (TTC – CR – GBT – FE)**
 - PCI DMA performance
 - Network throughput
- Combined test : Full FPGA chain

Trigger/Clock Forwarding test




TTC data
 Level 1 Trigger





- Constant latency : 247 ns (including cable delay : 5 ns)
- Jitter in LHC clock
 - @ HTG710 : 6.5 ps
 - @ GBTx chip : 9 ps

PCIe DMA performance



- **Split functional Test**
 - Forwarding trigger signal and LHC clock
 - **PCI DMA performance**
 - a. **PCIe – Memory : throughput test**
 - b. **Data Emulator – PCIe – Memory : stability test**
 - Network throughput
- Combined test : Full FPGA chain

PCIe DMA performance




Stable readout from PCIe card possible over long timespan

Network throughput test




- **Split functional Test**
 - Forwarding trigger signal and LHC clock
 - PCI DMA performance
 - **Network throughput (Memory – Pipeline – NIC – Switch – PC)**
- Combined test : Full FPGA chain

Network throughput test



- Input from files
- Hardware limit : 40 Gbps
- **Achieved maximum throughput for large data fragments : 36 Gbps**
- Need more efforts for smaller fragments

Full FPGA chain test




- **Combined test : Full FPGA chain**

- Data Emulator – GBT – FE – CR – PCIe – Memory
- pseudo data loop back through Front End forwarded to host memory
- FE and FELIX are synced in LHC clock
- Received data is matched to the generated data


Summary & Outlook

- Summary
 - FELIX is a new readout system of ATLAS DAQ for the next LHC runs
 - FELIX is a heterogeneous switch
 - First integration test is done and achieved reasonable results
- Upcoming Tasks
 - Establish multiple GBT link design and clocking scheme
 - Implement all functionality (TTC Busy, HDLC encode/decode ...)
 - Prove no data congestion between GBT and Central Router
 - Optimize host software functionality and performance
- UC Irvine is going to join for software development
- Production and test plan
 - A few FELIX prototypes will be produced and tested with several prototypes for new detector components foreseen for Run4



Back up

Evolution of Readout Architecture




ROD (readout driver) : is an off-detector end point that processes incoming data to send via ethernet


FELIX routes physics data to off-detector endpoint through industry standard network.

ROD-like functionality can be implemented either in software or in dedicated hardware.


ATLAS TDAQ : Run3 (2019)



FELIX Firmware Design



Development team



FPGA Firmware development



Time, Trigger & Control



Giga-bit Transceiver (GBT)




PCIe DMA engine



Central Router

Software development



- Independent implementation
- First integration efforts in May 2015