

Process Control Strategy for ITER CS Operation (C-PREST)

R. Maekawa, S. Takami(NIFS), A. Iwamoto(NIFS),

H-S. Chang, A. Forgeas, M. Chalifour

Presented at CHATS 2015

Bologna, Italy

Sep. 14, 2015


ITER disclaimer

The views and opinions expressed herein do not necessarily reflect those of the ITER organization

ITER Cryogenic System

Cryoplant 25kW x3 CBs


Nominal operation - 75 kW
The maximum power - 110 kW (utilization of LHe tank)



Design value for HX

Target for process simulator development

Mirror Plant





Outline

- Objective
- Simulation model
- Dynamic simulation
 - Nominal operation
 - Impact on cold circulator/compressor
 - Cold circulator
 - » feedback Anti-Surge-Control
 - Cold compressor
 - » feedback ASC
 - » Mitigation by Circulator speed
- Conclusion

Objective


- Identify potential risks during 15MA baseline operation
 - CS IM → Risk of surge for circulator
 - POS → Wide operation range for compressor (5-16kW)



CB: Co
 CTCB: C
 Termina
 Cold Co
 SHe LHe h
 Cold C
 CS m

15 MA Baseline-nominal

- Requirement → Constant SHE supply to CS
- Neglecting the impact on circulator & compressor
 - Ideal performance w/o surge/choke
 - Assessment of operation range




ASC: Anti-Surge Controller
 PT: Pressure Transmitter
 MC: Mitigation Control


ASV: Anti-Surge Valve
 LC: Level Controller
 FT: Flow Transmitter

IV_S: Isolation Valve Supply
 PC: Pressure Controller

IV_R: Isolation Valve Return
 HX: Heat Exchanger



- | | |
|-----------------|-------------------------------|
| 1 = Pump Casing | 4 = Bearing housing |
| 2 = Impeller | 5 = Shaft |
| 3 = Shaft seal | 6 = Lubricating oil reservoir |





CENTRIFUGAL TYPE CIRCULATOR/COMPRESSOR

Centrifugal type cold circulator/comp.



Characteristic Curve for circulator/comp. normalized



$$\Pi_1 = \frac{dP}{D^2 n^2}$$

Operation boundary



- Surge/choke
- Self protection sequence


From http://www.theturboforums.com/turbotech/img_21_principle_g.jpg

<http://www.grc.nasa.gov/WWW/5810/rvc/swift.htm>

Centrifugal type cold compressor


- Imposed boundary condition at the discharge side!
- Limited operation range





15 MA BASELINE-NOMINAL



Dynamic heat load (Plasma Operation State)



- 8 MJ in 1800 s
 - 50% deposition within 70 s

Impact on the Cooling loop


- Substantial variation of P and T
 - Identical pressure/temp. profiles after 2nd pulse
 - "stability of operation"




Regulation at LHe subcooler

✓ Good tracking performance against huge variation of process values

LHe Level




PRESSURE



HX & Cryoplant



- Thermal energy dissipation at HX → sizing
- Resulting heat load to Cryoplant




Process control-nominal operation

- ✓ Demonstrate satisfactory tracking performance w/
a classical PI control
 - Feasibility of sustaining CS operation

- OPEN ISSUE
 - Assessment of cold Circulator/Compressor...





IMPACT ON CENTRIFUGAL TYPE COLD CIRCULATOR AT IM




Cold circulator- flow blockage

- ✓ Risk to go into surge at the IM due to drastic P increase
 - Driving operation point in a short time, a few seconds



Impact at the onset of CS pulse



Anti-Surge-Control (ASC)





- Feedback control-pressure head
 - ASC
 - » 100 ms sampling PLC
 - » Time lag 0.7s of valve response






Feedback control

- Utilization of circulator pressure head to take control action on ASV
 - Shows a good tracking w/ less demanding operation range
 - Feasibility w/ real system 100 ms sampling rate w/ 0.7 s time lag





CS IM- SURGE RISK



✓ Good tracking performance w/ a classical feedback

- Regulation of pressure head leads to better boundary establishment for circulator
- Temporary reduction of \dot{m} will not impact CS operation
 - Robustness of magnetic bearing could sustain the operation





IMPACT ON COLD COMPRESSOR DURING DWELL



Cold compressor- ASC




- ✓ Demanding wide operation range w/ imposed discharge pressure
 - Challenging to adapt substantial dynamic heat load from 5-16 kW
 - Lack of mass-flow rate to achieve required compression ratio
- ASC is inevitable w/ the current CC design





Cold compressor operation-ASV

- Recycle mass-flow rate via ASV
 - Impose lower boundary of speed





Control strategy-Cold compressor



A classical PI should give satisfactory result due to the long characteristic-time of process → POS






Compensation of efficiency

- "~40% more compression work" compared w/ nominal

• POSSIBLE SOLUTION...


- Design needs to take different approach for adapting wide operation range
- Having dedicated compressor → technical challenge



MITIGATION TO REDUCE THE IMPACT ON COLD COMPRESSOR

Mitigation-Thermal Energy

- Cold circulator speed to regulate the cold compressor
- Imposing upper bound of cold compressor speed



ASC: Anti-Surge Controller
PT: Pressure Transmitter
MC: Mitigation Control

ASV: Anti-Surge Valve
LC: Level Controller
FT: Flow Transmitter



IV_S: Isolation Valve Supply
PC: Pressure Controller

IV_R: Isolation Valve Return
HX: Heat Exchanger



Mitigation-Cold compressor regulation

- Thermal energy mitigation leads to comparable effect on cold compressor boundary set-up
 - Imposing upper bound of HX energy dissipation with circulator speed






Impact on operation field

- ✓ Mitigation demonstrate satisfactory performance
- Impose optimized boundary condition (well confined range)
 - Practical approach for the operation

✓ Optimal operating point selection




Conclusion

- ✓ 15 MA reference
 - Nominal operation
 - Disclose the potential risk for machinery
 - Identify the impact on circulator/compressor
 - Feedback control demonstrated satisfactory results
 - Confirmation w/ real system to ensure fast control response
 - (CS-IM: Robustness of magnetic bearing withstand the temporary reduction of mass-flow rate...)
 - Mitigation could provide better stability of cold compressor operation
 - ✓ - Stability of CS conductor will not be the issue as reducing the mass-flow rate (confirmed by D.B on Sep9, 2015)

SUPPLEMENT SLIDES



Cryogenic Process REal-time SimulaTor

- C-PREST
 - 2003: Start development based on Visual Modeler® (omega simulation)
 - 10kW helium refrigerator (NIFS)
 - 2010: SHe forced-flow cooling loop under dynamic heat load (ITER)
 - Validation with test conducted at CEA-Grenoble
 - 2013: TF structure cooling loop → Mitigation
 - Benchmarked w/ SUPERMAGNET, VINCENTA & 4C
 - 2014: Development of CICC model
 - Validation w/ test results of CSMC (JAEA in 2000)
 - Data analysis w/ 2015 data for CSMC
 - 2015: CS model and process study



Active ASC



- Time lag shows some impact on the opening
 - Optimization of opening- valve characteristics
 - Temporary increasing bypass flow (circulator + back-flow)






Operation Field

- Confine the operation range but...
 - Extending the operation points to the other end...
 - Too much opening with 50%
 - Optimization w/ a real set-up





New configuration

- Two independent LHe baths
 - Saturated
 - Subcooled-reduce the demand of cold compressor operation



Modeling approach

- CICC based on CSTR model
 - Integration of 20 layers to achieve real-time computation (12 modules in the model)
 - Spatial discretization 70 in each module



Open issue

- FD-sizing case for HX-impact on the CC design
 - Implementation of Mitigation Scheme
- Quench Scenario...