

Fundamental Power Coupler at CERN

WWFPC01, CERN, Geneva, 23-24 June 2015, Eric Montesinos, CERN-BE-RF

Outline

Past, present and future projects


Windows for FPC at CERN

Statistics

Conditioning processes, test boxes, resonant rings

R&D programmes

Past, present & future projects



Frequency & Power levels

Coupler	Frequency [MHz]	Operation	TW [kW]	SW [kW]
LEP 2	352	CW	375	500
SPS 2	200	CW	500	-
LHC	400	CW	550	575
ESRF-SOLEIL-APS	352	CW	300	200
SPL 1-2-3	704	2 ms – 50 Hz	1000-1000-1500	600-1000-1500
Linac 4	352	2 ms – 1 Hz	-	1000
Design				
Crab	400	CW	100	100
LIU 200	200	CW	1000	-
LIU 800	800	CW	250	-
LHC 2	400	CW	600	600
LHC crab	400	CW	100	100

Ceramics



LHC cylindrical

400 MHz
500 kW
CW
TW + SW

ESRF-SOLEIL-APS

352 MHz

SPL

704 MHz




SPL coaxial disk

704 MHz
1000 kW
2 ms – 50 Hz
TW + SW

Crab Cavities

400 MHz



Linac 4 disk

352 MHz
1000 kW
1ms – 2Hz
TW + SW

Cylindrical windows



Initial design LEP 2

Brazing has been improved

- 2 mm copper collars instead of 0.5 mm kovar collars
- Less losses & better cooling

Electron Beam Welding

- More precise
- Perfect electrical continuity (no need of RF contacts)



Cylindrical windows

Initial design LEP 2

Brazing has been improved

- 2 mm copper collars instead of 0.5 mm kovar collars
- Less losses & better cooling

Electron Beam Welding

- More precise
- Perfect electrical continuity (no need of RF contacts)




Cylindrical windows

Distance between rings limits the peak power due to surface flashover rating along the ceramic

These ceramics are part of the matching system, reduces the RF peak power limit

End of a cycle... except if we again have to go to variable couplers




SPL couplers
TW 1000 kW were ok
SW 600 kW were arcing

Cylindrical windows

Distance between rings limits the peak power due to surface flashover rating along the ceramic

These ceramics are part of the matching system, reduces the RF peak power limit

End of a cycle... except if we again have to go to variable couplers




Coaxial disk windows

Easier to manufacture

- Titanium external flange
- Ceramic coaxial disk (quite thick to be robust even if with few losses)
- Copper inner tube
- Easier TiOx sputtering
- EBW on the inner copper tube side
- Standard vacuum seals on the Titanium flange outer side

Simple design used as a new baseline for several project

‘Cyclotronic’ air cooling




Coaxial disk windows

Easier to manufacture

- Titanium external flange
- Ceramic coaxial disk (quite thick to be robust even if with few losses)
- Copper inner tube
- Easier TiOx sputtering
- EBW on the inner copper tube side
- Standard vacuum seals on the Titanium flange outer side

Simple design used as a new baseline for several project

‘Cyclotronic’ air cooling



Disk windows

Robust and compact (in length) design




- 12 kg ceramic
- 400 mm diameter
- 25 mm thickness

As simple as possible

- 1-2-3-4 : Ceramic assembly
- 5 : spacer
- 6 : Helicoflex seal
- 7-8 : Stainless Steel flanges

Massive stainless Steel flanges, not copper plated



More difficult design than it looks like because of the two shapes: cylindrical and rectangular, with integrated screws



Disk windows

Robust and compact (in length) design

- 12 kg ceramic
- 400 mm diameter
- 25 mm thickness




As simple as possible

- 1-2-3-4 : Ceramic assembly
- 5 : spacer
- 6 : Helicoflex seal
- 7-8 : Stainless Steel flanges



Massive stainless Steel flanges, not copper plated

More difficult design than it looks like because of the two shapes: cylindrical and rectangular, with integrated screws



Ceramics

Whatever the shapes, all our ceramics are specified regarding the same Technical Specification since 1996, 'RF Windows for the LHC'

<http://cds.cern.ch/record/91419?ln=fr>


They are all Al_2O_3 minimum 99.5 % purity, with MoMn metallization with Ni diffused to a depth of between 5 – 10 μm

Whatever the coupler and the frequency, vacuum side is Titanium sputtered in house and at CERN we only have TiO_x sputtering

Ceramics

R&D Program launched in collaboration with KEK to test a new Kyocera ceramic that would not need any sputtering process

Comparison will be made with 'traditional' ceramic in order to validate the results



New Kyocera alumina Test at KEK

(K. Iwamoto, KYOCERA Corporation)

(E. Kako, KEK)

(S. Michizono, A. Yamamoto, High Energy Accelerator Research Organization)

Statistics

Coupler	Number	Lifetime [years]	Number of fault	Machine stop
LEP 2	288	5	2	0
LHC	16	7	0	0
SPS 200 – 1	16	24	2	2 x 3 days
SPS 200 – 2	16	14	0	0
SPS 800	8	35	0	0



LEP 2 couplers fault were small cracks in the ceramic, not detected during operation, only lowering the performance of the cavities

LEP 2 & LHC results with the DC polarisation always ON ! (mandatory with LHC couplers)

Conditioning process

Since 1998 at CERN, pulse mode conditioning process under vacuum loop control



- A first direct vacuum loop (red) ensures RF is never applied if pressure exceeds 5.0×10^{-7} mbar
- This interlock vacuum threshold is to protect the couplers, but also to have an as short as possible conditioning time
- The settings are adjusted to have minimum attenuation under 1.0×10^{-8} mbar and maximum attenuation over 2.5×10^{-7} mbar (~ 40 dB dynamic range with the attenuator)



Conditioning process

Since 1998 at CERN, pulse mode conditioning process under vacuum loop control

- A second vacuum loop (blue), cpu controlled, executes the automated process
- Always starts, under vacuum control, with very short pulses of $20\ \mu\text{s}$ every 20 ms
- Power level is increased using short pulses up to full power passing slowly through all power levels to avoid “de-conditioning”
- Same procedure repeated for initially short then longer and longer pulses up to the maximum length




Conditioning process

Safe but very slow process

More than 40 pairs have been processed

Ok for prototyping, but not for large series production




LHC coupler processing: 6 weeks 24/7
for two couplers

Test boxes

A way to speed up the process, several test boxes in series

Example of Linac 4 windows processing

- 50 – 100 – 200 – 600 μs / 2 Hz
- 16 phase steps
- 1 MW @ 352 MHz
- 5 weeks 7/24 with 1 test box
- 6 weeks 7/24 with 2 test boxes




Test boxes

A way to speed up the process, several test boxes in series

Example of Linac 4 windows processing

- 50 – 100 – 200 – 600 μs / 2 Hz
- 16 phase steps
- 1 MW @ 352 MHz
- 5 weeks 7/24 with 1 test box
- 6 weeks 7/24 with 2 test boxes




Resonant ring(s)

A way under study to minimize cost is the resonant ring solution

Three options are under study

- One ring with one coupler (to re-start with something)
- One ring with several pairs of couplers
- A double resonant ring

Only TW test, to be compare to SW




Resonant ring(s)

A way under study to minimize cost is the resonant ring solution

Three options are under study

- One ring with one coupler (to re-start with something)
- One ring with several pairs of couplers
- A double resonant ring

Only TW test, to be compare to SW




Resonant ring(s)

A way under study to minimize cost is the resonant ring solution

Three options are under study

- One ring with one coupler (to re-start with something)
- One ring with several pairs of couplers
- A double resonant ring

Only TW test, to be compare to SW



3D printing

Initially used for
mechanical qualification

R&D programme with
Grenoble INP for an all in
one metallic and plastic
printing, including cooling
channels



Clean room assembly

Cern restarted its SRF programme

From next year we will assemble couplers in-house for SPL project



Next steps

Several FPC projects are in the pipeline

LIU 200 already started

LIU 800 already started

LHC 2 from 2016

LHC Crab from 2017

FCC from 2016

for which your help and your advice will be very welcomed

Thank you very much

