Analysis Services in the PI project

AppArea, 9 April 2003

Andreas Pfeiffer

CERN/EP

Work packages in PI

- **PI started in mid Nov'02 (Vincenzo Innocente)**
  - Review with experiments to define workplan
  - Project proposal to SC2 end Jan'03
- **Analysis Services**
  - Status: active
- **Analysis Environment**
  - Status: on hold (mainly) by PEB
- **Pool & Grid PI**
  - Status: on hold pending RTAG by SC2
- **Event & Detector Visualization**
  - Status: on hold until May by SC2
- **Infrastructures & Documentation**
  - Status: active

Analysis Services

- **AIDA**
  - Review, adapt, extend Interface to Data Analysis
- **Root implementation of AIDA**
  - Provide an implementation of the Interfaces to Data Analysis, as defined by the previous work package, based on Root.
- **AIDA interface to SEAL and POOL services**
  - Use SEAL and POOL to provide AIDA with services such as object whiteboard and persistency.
- **Blueprint compliant Analysis tool set**
  - On Hold by SC2 till May 03
- **Resources**
  - Lorenzo Moneta (also SEAL)
  - Andreas Pfeiffer (also CMS)

Milestone 1: AIDA Proxy layer

- **"Value semantics" for AIDA objects**
  - Implemented using the "Proxy" pattern, very easy !
  - Based only on AIDA Interfaces
    ➔ ***no dependency on a given implementation***
  - Initially "hiding" of AIDA object management, later: use of SEAL whiteboard
- **Keeping the functionality and signatures of AIDA**
  - "re-shuffling" of factory methods to object ctors
- **Examples on how to use with web-docs**
  - Exist since March 24, as ***PI_0_0_7*** release tag
- **Will be basis for user-review and further evaluation**
  - Any feedback will be propagated to AIDA team

AIDA_Proxy in more detail

- Proxy to IHistogram1D

```
class Histogram1D : public IHistogram1D {
  public:
    // Constructor following the factory-create method (example)
    Histogram1D(std::string title, int nBins, double xMin, double xMax);
    // as an example the fill method:
    bool  fill ( double x, double weight = 1. )
          { if (rep == 0) return 0;
            else return rep-> fill ( x , weight ); }
    // other methods are also mostly inlined …
  private:
    IHistogram1D * rep;
};
```

Example: Histogram

```
#include <iostream>
#include <cstdlib>
#include <memory>

#include "AIDA_Proxy/AIDA_Proxy.h"
#include "AIDA/AIDA.h“

int main( int, char** ) {
  // Creating a histogram
  PI_AIDA::Histogram1D h1( "Example histogram.", 50, 0, 50 );

// Filling the histogram with random data
  std::srand( 0 );
  for ( int i = 0; i < 1000; ++i ) {
    h1.fill( 50 * static_cast<double>( std::rand() ) / RAND_MAX );
  }
```

```
// Printing some statistical values of the histogra
  std::cout << "Mean:" << h1.mean() << std::end
  std::cout << "RMS:" << h1.rms() << std::endl;

// Printing the contents of the histogram
const AIDA::IAxis& xAxis = h1.axis();
  for ( int iBin = 0; iBin < xAxis.bins(); ++iBin ) {
    std::cout << h1.binMean( iBin )
              << "       " << h1.binEntries( iBin )
              << "       " << h1.binHeight( iBin )
              << std::endl;
  }
  return 0;
}
```

Example: Fitting a histogram

```
// create and fill the histogram …
// Creating the function which is going to be fitted with the histogram data
AIDA::Function gaussFun("G");
// set parameters to starting values
gaussFun.setParameter("mean" , 50.);
gaussFun.setParameter("sigma", 10.);
gaussFun.setParameter("amp"  , 10.);
// Creating the fitter (ChiSquare by default)
AIDA::Fitter fitter;   // or:   fitter("UnbinnedML")
// Perform the fit
AIDA::IFitResult& fitResult = *( fitter.fit( h1, gaussFun ) );
// Print the fit results
std::cout << "Fit result : chi2 / ndf : " << fitResult.quality() << " / " << fitResult.ndf()
     << std::endl;
for ( unsigned int i = 0; i < par.size(); ++i ) {
  std::cout << fitResult.fittedParameterNames()[i]
            << " = " << fitResult.fittedParameters()[i]
            << " +/- " << fitResult.errors()[i]
            << std::endl;
}
```

Example: Tuple (I)

```
// Defining the description of the tuple columns
std::string description = "int nTracks; double beamEnergy; bool
    goodTrigger;";

// Define a “tuple-in-a-tuple”
description += "Tuple{ double px, py, pz, mass } p;";

// Creating the actual tuple in memory
AIDA::Tuple tuple( "id", "example tuple", description );
```

Example: Tuple (intermediate)

```
// these will be used in the filling … so they are listed for completeness
DRand48Engine randomEngine;
RandGauss rBeamEnergy( randomEngine, 90, 5 );
RandGauss rTracksSpread( randomEngine, 0, 2 );
RandGauss rMomentum( randomEngine, 0, 3 );
RandGauss rMass( randomEngine, 1, 0.1 );


// Filling the tuple, for performance get the indices first …
int i_nTracks = tuple.findColumn( "nTracks" );
int i_beamEnergy = tuple.findColumn( "beamEnergy" );
int i_goodTrigger = tuple.findColumn( "goodTrigger" );
int i_p = tuple.findColumn( "p" );
```

Example: Tuple (II)

```
const double tracksPerEnergy = 0.5;
for ( unsigned int i = 0; i < 1000; ++i ) {
  double beamEnergy = rBeamEnergy.fire();
  int numberOfTracks = static_cast<int>( tracksPerEnergy * beamEnergy + rTracksSpread.fire() );
  tuple.fill( i_nTracks, numberOfTracks );
  tuple.fill( i_beamEnergy, beamEnergy );
  tuple.fill( i_goodTrigger, ( (rMomentum.fire() > 0)?true:false) );
  AIDA::ITuple* tp = tuple.getTuple( i_p );
  for ( int iTrack = 0; iTrack < numberOfTracks; ++iTrack ) {
    tp->fill( 0,  rMomentum.fire() );
    tp->fill( 1,  rMomentum.fire() );
    tp->fill( 2,  rMomentum.fire() );
    tp->fill( 3, rMass.fire() );
    tp->addRow();
   }
   tuple.addRow();
 }
```

Near term plans

- **Various small changes**
  - Namespace PI_AIDA for Proxies
  - Use of SEALs plugin manager to allow parallel use of several implementations
- **First *public* release (V-0.1.0, planned for April 11)**
- **User review (see later)**
  - **Need feedback on what exists now !**
- **Next steps**
  - Continue to work on Root implementation
  - Add remaining functionality (according to user review) to Proxy layer
    - Projections, …
  - Integrate tests with CppUnit and Oval

Further plans (I)

- **Prototyping on integration with other frameworks**
  - SEAL – object whiteboard
  - POOL – object persistency
  - hippoDraw – visualisation
  - Expt frameworks – volunteers ?
- **Enhance AIDA**
  - User review (see later)
  - ErrorPropagation Functor to allow correct (and/or user specified) treatment of error propagation in profile histos and DataPointSets

Further plans (II)

- **Review "Developer level" Interfaces**
  - Adapt to use SEALs object whiteboard and POOL persistency
  - Re-implement Proxies using this
    - Transparent to the user !
  - Propose to AIDA team

- **Design "Canned ANalysis" objects (CANs)**
  - Container to hold various "related" AIDA objects
    - Histo(s) for data, Histo(s) for MC, Fit(s) to either ...
  - Gather user-requirements first

User Review of AIDA

- Review of AIDA (Proxies) by users in the experiments
  - Need feedback on what exists now !
    - Concentrate on the Interfaces, *not* on the implementations (or on performance (yet))
- Questions to be answered:
  - Are the interfaces complete ?
  - What features would you like to add/change ?
  - Are the methods and signatures clear enough ?
  - What are the specific needs (use-cases) for the CANs ?
  - …
- Identify contact people in the experiments !