

Constrained Markovian MC for QCD initial state PDF evolution

First prototypes

S. Jadach

and

M. Skrzypek

stanislaw.jadach@ifj.edu.pl

HNINP-PAS, Cracow, Poland

The problem

- Markovian MC implementing the QCD evolution equations is basic ingredient of all QCD parton shower MCs

The problem

- Markovian MC implementing the QCD evolution equations is basic ingredient of all QCD parton shower MCs
- Unconstrained Markovian, with kernels being an essential input from QCD, can only be used for FSR (inefficient for ISR)

The problem

- Markovian MC implementing the QCD evolution equations is basic ingredient of all QCD parton shower MCs
- Unconstrained Markovian, with kernels being an essential input from QCD, can only be used for FSR (inefficient for ISR)
- A remedy is the “backward Markovian” of Sjostrand (Phys.Lett. 157B, 1985)

The problem

- Markovian MC implementing the QCD evolution equations is basic ingredient of all QCD parton shower MCs
- Unconstrained Markovian, with kernels being an essential input from QCD, can only be used for FSR (inefficient for ISR)
- A remedy is the “backward Markovian” of Sjostrand (Phys.Lett. 157B, 1985)
- However, backward Markovian does not solve QCD evolution eqs. It merely exploits their solutions which come from non-MC methods. Disadvantage?? Advantage??

The problem

- Markovian MC implementing the QCD evolution equations is basic ingredient of all QCD parton shower MCs
- Unconstrained Markovian, with kernels being an essential input from QCD, can only be used for FSR (inefficient for ISR)
- A remedy is the “backward Markovian” of Sjostrand (Phys.Lett. 157B, 1985)
- However, backward Markovian does not solve QCD evolution eqs. It merely exploits their solutions which come from non-MC methods. Disadvantage?? Advantage??
- **Is it possible to invent an efficient MC algorithm for constrained Markovian providing *own* MC solutions for QCD evolution eqs?**

The solution

- We claim that we have found a class of solutions of the above long-standing problem

The solution

- We claim that we have found a class of solutions of the above long-standing problem
- In the introductory exercise Markovian MC `EvolveMC` was found to agree with `QCDnum16` to within 0.2%,
see [Acta Phys.Polon. B35 \(2004\)745](#)

The solution

- We claim that we have found a class of solutions of the above long-standing problem
- In the introductory exercise Markovian MC `EvolveMC` was found to agree with `QCDnum16` to within 0.2%, see *Acta Phys.Polon. B35 (2004)745*
- Recently we have constructed the 1-st prototype of the efficient *constrained Markovian MC* (solution IIB). It agrees with `EvolveMC` to within 0.2%

The solution

- We claim that we have found a class of solutions of the above long-standing problem
- In the introductory exercise Markovian MC `EvolveMC` was found to agree with `QCDnum16` to within 0.2%, see *Acta Phys.Polon. B35 (2004)745*
- Recently we have constructed the 1-st prototype of the efficient *constrained Markovian MC* (solution IIB). It agrees with `EvolveMC` to within 0.2%
- Next step: Prototyping, testing and documenting the entire family of constrained MC algorithms that we see

The solution

- We claim that we have found a class of solutions of the above long-standing problem
- In the introductory exercise Markovian MC `EvolveMC` was found to agree with `QCDnum16` to within 0.2%, see *Acta Phys.Polon. B35 (2004)745*
- Recently we have constructed the 1-st prototype of the efficient *constrained Markovian MC* (solution IIB). It agrees with `EvolveMC` to within 0.2%
- Next step: Prototyping, testing and documenting the entire family of constrained MC algorithms that we see
- Next-next step: looking for applications in the full scale (4-momenta) parton shower MCs. Obvious candidates: DY-type and DIS processes

The solution

- We claim that we have found a class of solutions of the above long-standing problem
- In the introductory exercise Markovian MC `EvolveMC` was found to agree with `QCDnum16` to within 0.2%, see *Acta Phys.Polon. B35 (2004)745*
- Recently we have constructed the 1-st prototype of the efficient *constrained Markovian MC* (solution IIB). It agrees with `EvolveMC` to within 0.2%
- Next step: Prototyping, testing and documenting the entire family of constrained MC algorithms that we see
- Next-next step: looking for applications in the full scale (4-momenta) parton shower MCs. Obvious candidates: DY-type and DIS processes