

Performance of the Collimation System during 2015

Evian Workshop on LHC Beam Operation

December 16th, 2015

R. Bruce, M. Fiascaris, H. Garcia, P. Hermes, A. Mereghetti, D. Mirarchi,
R. Kwee, S. Redaelli, E. Quaranta, A. Rossi, R. Rossi, B. Salvachua,
P. Theodoropoulos, G. Valentino, A. Valloni, J. Wagner

thanks also to:



*G. Baud, A. Danisi, M. Donze, J. F. Fuchs, M. Gasior, A. Masi, D. Missiaen,
J. Olexa, J. Wenninger*

- **Recap: LS1 changes**
- **System commissioning**
 - HW & beam commissioning
- **System performance**
 - Collimation cleaning
 - Issues encountered during the year
- **Embedded BPM collimators**
- **Commissioning plans for 2016**
- **Conclusions**

Recap: LS1 changes


- **Important collimation upgrade program with 30% of the system changed.**
 - New collimators with embedded BPMs (IR1, IR2, IR5, IR8 and IR6).
 - Improved TCL layouts in IR1 and IR5.
 - Installation of additional passive absorbers in IR3.
 - Improved IR8 layout: replacement of 2-in-1 beam collimators by single-beam collimators.
 - Removal and re-installation of 3 primary collimators in IR7 due to ventilation work, and replacement of 1 primary collimator IR7 due to heating problems.

TCSP jaw






Recap: LS1 changes




Recap: LS1 changes

- **Controls and instrumentation upgrade**
- Upgrade of rack configuration, improved monitoring + middleware controls upgrade to FESA3.



Recap: LS1 changes

- Controls and instrumentation upgrade
- Upgrade of rack configuration, improved monitoring + middleware controls upgrade to FESA3.




- During Run 1, EM interference from nearby quads found to affect some IR3 collimator LVDTs. 10 sensors on 5 collimators now replaced with a new design (I2PS) (A. Danisi):







2015 HW commissioning



- New devices: updating of configuration databases, logging, LSA parameters etc
- LVDT calibration, interlock response to power cut & PRS reboot, RBAC
- Collimator temperature interlock tests
- Machine protection tests: 86 collimators x 18 limits = **1548 tests** executed in 2 days.
 - ➡ First major test campaign since 2011.
- Collimators imported into AccTesting in Jan 2015, tests implemented as sign-only for now.

2015 HW commissioning



- New devices: updating of configuration databases, logging, LSA parameters etc
- LVDT calibration, interlock response to power cut & PRS reboot, RBAC
- Collimator temperature interlock tests
- Machine protection tests: 86 collimators x 18 limits = **1548 tests** executed in 2 days.
 ➡ First major test campaign since 2011.
- Collimators imported into AccTesting in Jan 2015, tests implemented as sign-only for now.



2015 beam commissioning

- **Beam-based collimator alignment**

- Required to measure the beam centers and sizes at the collimator locations for OP settings generation.
- Initially done only with BLM-based technique due to unavailability of DOROS BPM electronics.
- Feedback loop for BLM and BPM-based alignment moved to FESA class in LS1.
- Alignment time for all 86 collimators now down to 4 hours from ~20 hours in 2010.



2015 beam commissioning

- Collimator settings used throughout standard $\beta^* = 80$ cm machine cycle:

Coll Family	Injection [σ]	Flat Top [σ]	Squeezed [σ]	Physics [σ]
TCP IR3	8.0	15.0	-	-
TCSG IR3	9.3	18.0	-	-
TCLA IR3	12.0	20.0	-	-
TCP IR7	5.7	5.5	-	-
TCSG IR7	6.7	8.0	-	-
TCLA IR7	10.0	14.0	-	-
TCSP IR6	7.5	9.1	-	-
TCDQ IR6	8.0	9.1	-	-
TCT IR1/2/5/8	13/13/13/13	37/37/37/37	13.7/37/13.7/15	-
TCL 4/5/6 IR1/5	parking	parking	parking	15/15/parking*

*When TOTEM inserted, TCLs in IP5 @ 15/35/20.

2015 beam commissioning

- Collimator settings used throughout standard $\beta^* = 80$ cm machine cycle:

Coll Family	Injection [σ]	Flat Top [σ]	Squeezed [σ]	Physics [σ]
TCP IR3	8.0	15.0	-	-
TCSG IR3	9.3	18.0	-	-
TCLA IR3	12.0	20.0	-	-
TCP IR7	5.7	5.5	-	-
TCSG IR7	6.7	8.0	-	-
TCLA IR7	10.0	14.0	-	-
TCSP IR6	7.5	9.1	-	-
TCDQ IR6	8.0	9.1	-	-
TCT IR1/2/5/8	13/13/13/13	37/37/37/37	13.7/37/13.7/15	-
TCL 4/5/6 IR1/5	parking	parking	parking	15/15/parking*

*When TOTEM inserted, TCLs in IP5 @ 15/35/20.

Left [mm]	IP7	Right [mm]
1.35	TCP.D6L7.B1	-0.9
1.23	TCP.C6L7.B1	-1.79
1.73	TCP.B6L7.B1	-0.82

down to 2.2 mm
gap in IR7!

Validation of settings

- We need to validate the settings determined from beam-based alignments using loss maps.
- Loss map validation strategy:
 - ➡ Initially, require 3 fills per point in the machine cycle.
 - ➡ Post-TS2 and proposal to keep also for 2016:

	Betatron Lossmaps	POSITIVE off-momentum	NEGATIVE off-momentum	Asynchronous Dump	Fills
INJECTION	YES	YES	YES	YES	3
FLAT TOP	YES	ALTERNATE SIDE	ALTERNATE SIDE	Cancelled?	1
SQUEEZE	YES	ALTERNATE SIDE	ALTERNATE SIDE	Recommend to keep it	2-3
COLLISIONS	YES	YES	YES	YES	3

B. Salvachua


Validation of settings

- We need to validate the settings determined from beam-based alignments using loss maps.
- Loss map validation strategy:
 - ➔ Initially, require 3 fills per point in the machine cycle.
 - ➔ Post-TS2 and proposal to keep also for 2016:


	Betatron Lossmaps	POSITIVE off-momentum	NEGATIVE off-momentum	Asynchronous Dump	Fills
INJECTION	YES	YES	YES	YES	3
FLAT TOP	YES	ALTERNATE SIDE	ALTERNATE SIDE	Cancelled?	1
SQUEEZE	YES	ALTERNATE SIDE	ALTERNATE SIDE	Recommend to keep it	2-3
COLLISIONS	YES	YES	YES	YES	3

B. Salvachua

betatron losses B1 4000GeV hor norm IR7 (2012.07.01, 05:41:31)




Betatron losses B1 6500 GeV Horizontal 2015-6-2 13:09:15



D. Mirarchi + A. Mereghetti




Validation of settings





Validation of settings




- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.

Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
 - In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➡ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).


Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
- In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➡ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).
- Possible to reduce # fills required in several validations in collisions later on in the year, from 3 to 1:




Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
- In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➡ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).
- Possible to reduce # fills required in several validations in collisions later on in the year, from 3 to 1:




Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
- In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➔ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).
- Possible to reduce # fills required in several validations in collisions later on in the year, from 3 to 1:




Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
- In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➔ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).
- Possible to reduce # fills required in several validations in collisions later on in the year, from 3 to 1:




Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
- In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➡ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).
- Possible to reduce # fills required in several validations in collisions later on in the year, from 3 to 1:




Validation of settings

- In 2012: validation efficiency bottleneck for betatron loss maps removed with ADT blow-up.
- In 2015: bottleneck for off-momentum loss maps greatly mitigated with new Java application sending real-time trims up to 150 Hz (instead of 500 Hz via LSA) with 12.5 Hz BLM feedback
- ➔ thanks also to RF for support with controlled emittance blow-up (see talk by H. Timko).
- Possible to reduce # fills required in several validations in collisions later on in the year, from 3 to 1:




Cleaning performance

Run I




Cleaning performance

Run I




Run 2




B. Salvachua

Cleaning performance

Run 1



Run 2




B. Salvachua

➡ Worse cleaning than in 2012, but continue stable performance with only one full alignment per year!




Collimation with heavy ions




Collimation with heavy ions

- Cleaning worse than protons as expected (almost single stage).
- Higher losses in B1 H TCT in IR2 could be connected to observations of higher background in ALICE.

BI H collisions - full ring



BI H collisions - IR7




A. Mereghetti


Collimation with heavy ions

- Cleaning worse than protons as expected (almost single stage).
- Higher losses in B1 H TCT in IR2 could be connected to observations of higher background in ALICE.

BI H collisions - full ring



BI H collisions - IR7




A. Mereghetti

- Possible mitigation measures were tested (e.g. asymmetric IR7 TCP settings) and likely to work
 - ➡ After tracking simulations, EOF study done in shade of IP2 polarity switch validation (P. Hermes, R. Bruce).
 - ➡ Not implemented due to time constraints (as requested from ALICE).




Issues encountered in the year



Issues encountered in the year


- Fault statistics for the collimation system



- System with 2nd least contribution to LHC downtime!
- E.g. LVDT glitches, temperature interlocks, issues with β^* limits

Issues encountered in the year


- Fault statistics for the collimation system



- System with 2nd least contribution to LHC downtime!
- E.g. LVDT glitches, temperature interlocks, issues with β^* limits
- Survey and alignment:**
 - TCLA.D6R7.B2:** large offset of +3 mm wrt other IR7 collimators discovered during beam commissioning. Survey measurements done but not possible to correct in TS. Collimator stable and we could correct for the offset with the right settings. Fiducialization measurement and re-alignment foreseen for YETS.
 - TCL.6L5.B2:** Tilt of > 2 mrad observed during beam commissioning (400% measured-to-nominal beam size ratio). Fixed in TS2.
 - No impact on OP, able to workaround using appropriate settings.




Collimator BPMs: Commissioning





- Motivation for installation:
 - ➡ Faster alignment ➡ respond more quickly to IR configuration changes
 - ➡ Reduce orbit margins in the TCSP-TCTP hierarchy: more room to push β^*
- DOROS BPM electronics available for IP1 during beam commissioning, then all collimators available for MD in July.
- Final version of acquisition software with automatic calibration of gains and offsets in electronics available after TS2.

- Motivation for installation:
 - ➡ Faster alignment ➡ respond more quickly to IR configuration changes
 - ➡ Reduce orbit margins in the TCSP-TCTP hierarchy: more room to push β^*
- DOROS BPM electronics available for IP1 during beam commissioning, then all collimators available for MD in July.
- Final version of acquisition software with automatic calibration of gains and offsets in electronics available after TS2.




- Motivation for installation:
 - ➡ Faster alignment ➡ respond more quickly to IR configuration changes
 - ➡ Reduce orbit margins in the TCSP-TCTP hierarchy: more room to push β^*
- DOROS BPM electronics available for IP1 during beam commissioning, then all collimators available for MD in July.
- Final version of acquisition software with automatic calibration of gains and offsets in electronics available after TS2.

BLM-based alignment IP1 and 5 in 2012





BPM-based alignment IP1 and 5 in 2015




- Motivation for installation:
 - ➡ Faster alignment ➡ respond more quickly to IR configuration changes
 - ➡ Reduce orbit margins in the TCSP-TCTP hierarchy: more room to push β^*
- DOROS BPM electronics available for IP1 during beam commissioning, then all collimators available for MD in July.
- Final version of acquisition software with automatic calibration of gains and offsets in electronics available after TS2.

BLM-based alignment IP1 and 5 in 2012




1 hour vs 2 min.

BPM-based alignment IP1 and 5 in 2015







Collimator BPMs: Fill-to-fill stability





Collimator BPMs: Fill-to-fill stability

- Dynamic parts of the cycle:** Trends correlated with standard BPMs nearby: feed-forward into collimator functions for 2016?




Collimator BPMs: Fill-to-fill stability

- Dynamic parts of the cycle:** Trends correlated with standard BPMs nearby: feed-forward into collimator functions for 2016?




- Stable beams:** Intra-fill stability better than inter-fill stability.



400 μm
spread



A. Valloni




- **Combined ramp & squeeze during p-p reference run @ 2.51 TeV**
 - first experience with CRS with orbit measurements directly at the collimators.
 - data are useful input for possible CRS implementation in 2016.
 - to be compared in detail to MADX simulations and see if we have a good understanding of the dynamic behaviour.






Collimator BPMs: Interlocks





Collimator BPMs: Interlocks





- Direct monitoring of the orbit at the TCSPs and TCTPs would need to be interlocked if we are going to reduce the orbit margins to reduce the β^* .

Collimator BPMs: Interlocks

- Direct monitoring of the orbit at the TCSPs and TCTPs would need to be interlocked if we are going to reduce the orbit margins to reduce the β^* .
- Interlock threshold scan performed to determine number of dumps, data from ~ 50 fills after TS2 taken w.r.t. a reference fill, look at individual interlocks vs combined TCTP-TCSP interlock.



Collimator BPMs: Interlocks

- Direct monitoring of the orbit at the TCSPs and TCTPs would need to be interlocked if we are going to reduce the orbit margins to reduce the β^* .
- Interlock threshold scan performed to determine number of dumps, data from ~ 50 fills after TS2 taken w.r.t. a reference fill, look at individual interlocks vs combined TCTP-TCSP interlock.
- Suggestions for interlock implementation:
 - ➔ Dynamic parts (ramp & squeeze): feed-forward collimator functions should eliminate any transients.
 - ➔ Assuming we will not try to manually correct better than the OFB e.g. in adjust: we can set a conservative limit of 1σ in TCTP-TCSP interlock at which we are very unlikely to dump.
 - ➔ Already big improvement from current 1.9σ in TCSP-TCTP orbit margin (see R. Bruce for translation into β^*).



Collimator BPMs: Interlocks


- Direct monitoring of the orbit at the TCSPs and TCTPs would need to be interlocked if we are going to reduce the orbit margins to reduce the β^* .
- Interlock threshold scan performed to determine number of dumps, data from ~50 fills after TS2 taken w.r.t. a reference fill, look at individual interlocks vs combined TCTP-TCSP interlock.
- Suggestions for interlock implementation:
 - ➡ Dynamic parts (ramp & squeeze): feed-forward collimator functions should eliminate any transients.
 - ➡ Assuming we will not try to manually correct better than the OFB e.g. in adjust: we can set a conservative limit of 1σ in TCTP-TCSP interlock at which we are very unlikely to dump.
 - ➡ Already big improvement from current 1.9σ in TCSP-TCTP orbit margin (see R. Bruce for translation into β^*).



- Require 100% BPM FESA class reliability for interlocks (minor availability issues being mitigated).



Commissioning plans for 2016



Commissioning plans for 2016

- For the embedded BPM collimators, with the final DOROS electronics software in place since TS2, will have to repeat several tests with beam (*1 - 2 shifts*):
 - ➡ BLM vs BPM alignment cross-checks
 - ➡ Collimator scans to measure BPM non-linearities
 - ➡ Tests of BPM interlock implementation
 - ➡ Ideally done as soon as nominal bunch is available to fully profit for standard alignments after.

Commissioning plans for 2016

- For the embedded BPM collimators, with the final DOROS electronics software in place since TS2, will have to repeat several tests with beam (*1 - 2 shifts*):
 - ➡ BLM vs BPM alignment cross-checks
 - ➡ Collimator scans to measure BPM non-linearities
 - ➡ Tests of BPM interlock implementation
 - ➡ Ideally done as soon as nominal bunch is available to fully profit for standard alignments after.
- Require usual alignments + validation at 4 points in the machine cycle (injection, ramp, squeeze, collisions).
 - ➡ 3 shifts for alignments + 3 shifts for validation
 - ➡ Would like to test possibility of BLM-based alignment feedback @ 50 Hz (up from 12.5 Hz)

Commissioning plans for 2016


- For the embedded BPM collimators, with the final DOROS electronics software in place since TS2, will have to repeat several tests with beam (*1 - 2 shifts*):
 - ➡ BLM vs BPM alignment cross-checks
 - ➡ Collimator scans to measure BPM non-linearities
 - ➡ Tests of BPM interlock implementation
 - ➡ Ideally done as soon as nominal bunch is available to fully profit for standard alignments after.
- Require usual alignments + validation at 4 points in the machine cycle (injection, ramp, squeeze, collisions).
 - ➡ 3 shifts for alignments + 3 shifts for validation
 - ➡ Would like to test possibility of BLM-based alignment feedback @ 50 Hz (up from 12.5 Hz)
- We do not require dedicated commissioning for CRS except the re-alignment at flat top.

Commissioning plans for 2016

- For the embedded BPM collimators, with the final DOROS electronics software in place since TS2, will have to repeat several tests with beam (*1 - 2 shifts*):
 - ➡ BLM vs BPM alignment cross-checks
 - ➡ Collimator scans to measure BPM non-linearities
 - ➡ Tests of BPM interlock implementation
 - ➡ Ideally done as soon as nominal bunch is available to fully profit for standard alignments after.
- Require usual alignments + validation at 4 points in the machine cycle (injection, ramp, squeeze, collisions).
 - ➡ 3 shifts for alignments + 3 shifts for validation
 - ➡ Would like to test possibility of BLM-based alignment feedback @ 50 Hz (up from 12.5 Hz)
- We do not require dedicated commissioning for CRS except the re-alignment at flat top.
- Don't plan major changes to the control software, so we will only repeat a subset of MP tests that ensures that each IP BIC is tested.




Summary & Conclusions





Summary & Conclusions



- Huge HW and beam commissioning effort after coming out from LS1 with changes to 30% of the system.
- ➡ Special thanks to all involved in the equipment groups.

Summary & Conclusions

- Huge HW and beam commissioning effort after coming out from LS1 with changes to 30% of the system.
 - ➡ Special thanks to all involved in the equipment groups.
- The collimation system continues to perform as well as it has during Run 1 in terms of cleaning, stability and availability.

Summary & Conclusions

- Huge HW and beam commissioning effort after coming out from LS1 with changes to 30% of the system.
 - ➡ Special thanks to all involved in the equipment groups.
- The collimation system continues to perform as well as it has during Run 1 in terms of cleaning, stability and availability.
- A few issues along the way in particular related to tunnel alignment which have / are being solved during a technical stop.

Summary & Conclusions

- Huge HW and beam commissioning effort after coming out from LS1 with changes to 30% of the system.
 - ➡ Special thanks to all involved in the equipment groups.
- The collimation system continues to perform as well as it has during Run 1 in terms of cleaning, stability and availability.
- A few issues along the way in particular related to tunnel alignment which have / are being solved during a technical stop.
- Already using the embedded BPM collimators for fast alignment
 - ➡ experience gained during 2015 MD will come in handy during the commissioning next year.
 - ➡ hope to also profit from them to reduce the TCSP-TCTP collimator margins as one of the ingredients to push the β^* reach in 2016.
 - ➡ Dedicated commissioning time will be needed especially if they will be used for interlocks.