



Injector Linac Experiences at KEKB / SuperKEKB

Kazuro Furukawa
Injector Linac, KEK
<kazuro.furukawa@kek.jp>



SuperKEKB overview

KEKB Injector Linac

SuperKEKB Injector Linac Progress

Operation

Mission of electron/positron Injector in SuperKEKB

◆ 40-times higher Luminosity

❖ 20-times higher collision rate with nano-beam scheme

❏ → Low-emittance even at first turn

→ Low-emittance beam from Linac

❏ → Shorter storage lifetime

❖ Twice larger storage beam

→ Higher beam current from Linac

◆ Linac challenges

❖ Low emittance e-

❏ with high-charge RF-gun

❖ Low emittance e+

❏ with damping ring


❖ Higher e+ beam current

❏ with new capture section

❖ Emittance preservation


❏ with precise beam control

❖ 4+1 ring simultaneous injection





SuperKEKB master schedule



Akai, Mar.2016.



Required injector beam parameters

Stage	KEKB (final)		Present Phase-I		SuperKEKB (final)	
Item	e+	e-	e+	e-	e+	e-
Energy	3.5 GeV	8.0 GeV	4.0 GeV	7.0 GeV	4.0 GeV	7.0 GeV
Bunch charge	Primary e- 10nC → 1 nC	1 nC	Primary e- 8nC → 0.4 nC	1 nC	Primary e-10nC → 4 nC	5 nC
Norm. Emittance ($\gamma\beta\epsilon$) (μrad)	2100	200	2400	150	100/20 (Hor./Ver.)	50/20 (Hor./Ver.)
Energy spread	0.125%	0.125%	0.5%	0.5%	0.1%	0.1%
No. of Bunch / Pulse	2	2	2	2	2	2
Repetition rate	50 Hz		25 / 50 Hz		50 Hz	
Simultaneous top-up injection	3 rings (KEKB e-/e+, PF)		No top-up		4+1 rings (SuperKEKB e-/e+, DR, PF, PF-AR)	





SuperKEKB overview
KEKB Injector Linac
SuperKEKB Injector Linac Progress
Operation




KEKB

- ◆ 1995-1999: Construction
- ◆ 1999-2010: Operation
- ◆ KEKB B-Factory
 - ❖ Electron-Positron Asymmetric Collider
 - ❖ Pursue study on CP-violation in B-meson system
 - ❖ ~3km dual ring:
 - ❏ Electron (8GeV - 1.4A)
 - ❏ Positron (3.5GeV - 1.8A)
 - ❏ Achieved world highest luminosity 2.1×10^{34}
 - ❏ Shared injection to light sources, PF and PF-AR









Operated with SC Crab Cavities





KEKB Operation Improvement (base of SuperKEKB)



red: beam current (e-, e+)
 purple: vacuum (e-, e+)
 yellow: luminosity
 green: integrated luminosity


May.2000

Apr.2003

Dual Bunch e+

Feb.2005
Continuous
Injections

Dec.2008
Crab Cavities and
Simultaneous Injection



Keeps world
luminosity record

Operation Improvements (1)

◆ Many slow closed feedback loops for beam

- ❖ Beam orbit, energy, and often device
- ❖ Until related hardware was stabilized
- ❖ Also useful when studying beams

◆ Tolerance study to understand fluctuations

- ❖ For example, single-parameter tolerance to keep 90% of beam transmission
- ❖ Good reference to consider the beam stability

◆ Fight against discharges in structures

- ❖ Especially at 1st cavities after gun and positron target
- ❖ Solenoids, beam loss, etc.
- ❖ Optimization for rf power and shorter rf pulse



Operation Improvements (2)

- ◆ **Dual bunches in a pulse for higher beam charge**
 - ❖ 50 Hz x 2 bunches doubled the injection beam
 - ❖ Especially for positron
- ◆ **Faster beam switching, continuous injection**
 - ❖ Between electron / positron and for light sources
 - ❖ Magnet hysteresis consideration
- ◆ **Even faster simultaneous injections**
 - ❖ Pulse-to-pulse modulation at 50 Hz (20 ms)
 - ❖ ~150 parameters were switched in KEKB for 3 beams
 - ❖ ~250 parameters in SuperKEKB for 4 beams



SuperKEKB at 2002

- ◆ Some consideration on upgrade for SuperKEKB was presented already in 2002
- ◆ Much different from present form, but this shows a project needs a long lead time

Present Status and Future Upgrade of KEK e⁻ Linac

Linac / Ring Upgrade for SuperKEKB

- ◆ for Precise Measurement of *B*-meson System Parameters and Search for New Physics (ex. SUSY)

SuperKEKB : Luminosity of $10^{35} \text{ cm}^{-2} \text{ s}^{-1}$

with Major Upgrade of Linac and Ring

- ◆ Luminosity Increase
 - (1) Squeezing **Beta** at Interaction Region (by factor of 3.3)
 - (2) Increasing e⁻ and e⁺ **Beam Current** (by factor of 3.3)
 - (3) **Exchanging Energies** of e⁻ and e⁺ (to cure e⁻ cloud issues)
- ◆ for Linac
 - (3) is the Major Challenge, as well as (2)Two Schemes are Considered
 - (a) **Higher Gradient** with C-band Structures
 - (b) **Recirculation** of Positron

- ❖ **Later,**
- ❖ **Energy exchange was rejected**
- ❖ **Nano-beam scheme was employed**

K.Furukawa, Linac2002, Aug.2002.



SuperKEKB overview
KEKB Injector Linac

**SuperKEKB Injector Linac Progress
Operation**

Mission of electron/positron Injector in SuperKEKB

◆ 40-times higher Luminosity

❖ 20-times higher collision rate with nano-beam scheme

❏ → Low-emittance even at first turn

→ Low-emittance beam from Linac

❏ → Shorter storage lifetime

❖ Twice larger storage beam

→ Higher beam current from Linac

◆ Linac challenges

❖ Low emittance e-

❏ with high-charge RF-gun

❖ Low emittance e+

❏ with damping ring


❖ Higher e+ beam current

❏ with new capture section

❖ Emittance preservation

❏ with precise beam control

❖ 4+1 ring simultaneous injection






Linac Schedule Overview

RF-Gun e- beam commissioning at A,B-sector

e- commiss. at A,B,J,C,1

e+ commiss. at 1,2 sector (FC, DCS, Qe- 50%)
e- commiss. at 1,2,3,4,5 sector

Phase1: high emittance beam for vacuum scrub
Phase2,3: low emittance beam for collision






Required injector beam parameters

Stage	KEKB (final)		Present Phase-I		SuperKEKB (final)	
	e+	e-	e+	e-	e+	e-
Beam	e+	e-	e+	e-	e+	e-
Energy	3.5 GeV	8.0 GeV	4.0 GeV	7.0 GeV	4.0 GeV	7.0 GeV
Stored current	1.6 A	1.1 A	1 A	1 A	3.6 A	2.6 A
Life time	150 min.	200 min.	100 min.	100 min.	6 min.	6 min.
Bunch charge	Primary e-10nC → 1 nC	1 nC	Primary e- 8nC → 0.4 nC	1 nC	Primary e-10nC → 4 nC	5 nC
Norm. Emittance ($\gamma\beta\varepsilon$) (μrad)	2100	200	2400	150	100/20 (Hor./Ver.)	50/20 (Hor./Ver.)
Energy spread	0.125%	0.125%	0.5%	0.5%	0.1%	0.1%
No. of Bunch / Pulse	2	2	2	2	2	2
Repetition rate	50 Hz		25 / 50 Hz		50 Hz	
Simultaneous top-up injection (PPM)	3 rings (KEKB e-/e+, PF)		No top-up		4+1 rings (SuperKEKB e-/e+, DR, PF, PF-AR)	

Subjects to Consider




◆ Have to consider too many subjects !

◆ Phronesis needed (Greek: Practical wisdom, Ability to understand the Universal Truth)

Linac Upgrade Progress towards SuperKEKB (1)

◆ High-charge low-emittance RF gun development

- ❖ QTWSC cavity and Ir₅Ce photo cathode developments
- ❖ Laser development is underway




◆ Positron generator commissioning

- ❖ Good agreement with the simulation results
- ❖ Will solve discharge issues



◆ Precise alignment for emittance preservation

- ❖ Recovering after large earthquake in 2011
- ❖ Reaching specification of 0.1~0.3mm
- ❖ Longer term stability will be solved




◆ Utility upgrade during FY2014


- ❖ for electricity (+1.5MW) and cooling water (+1400L/min)

Linac Upgrade Progress towards SuperKEKB (2)

- ◆ **High-power microwave modulator upgrades**
- ◆ **Low-level RF controls/monitor upgrades**
 - ❖ Pulse-to-pulse modulation (PPM) between 4+1 rings
 - ❖ More spaces for increased number of devices
- ◆ **Beam instrumentation**
 - ❖ Large/small aperture beam position monitors (BPM)
 - ❖ Precise/fast and synchronized BPM readout system
 - ❖ Wire scanners and beam loss monitors
 - ❖ Streak cameras
 - ❖ (Deflectors, etc.)
- ◆ **Event-based control and timing system upgrades**
 - ❖ Combination of MRF & SINAP modules
 - ❖ Essential for PPM operation
 - ❖ Precise timing & synchronized controls
 - ❖ Bucket selection at DR and MR




SINAP event modules



Beam wire scanner

Positron generation for SuperKEKB



New positron capture section after target with

Flux concentrator (FC) and large-aperture S-band structure (LAS)

Satellite bunch (beam loss) elimination with velocity bunching

Pinhole (2mm) for passing electrons beside target (3.5mm)

Recently, facing discharge difficulties at maximum field



RF-Gun development strategy for SuperKEKB

◆ Cavity : Strong electric field focusing structure

❖ Disk And Washer (DAW) ⇒ 3-2, A-1(test)

❖ Quasi Traveling Wave Side Couple (QTWSC) ⇒ A-1

⇒ Reduce beam divergence and projected emittance dilution

◆ Cathode : Long term stable cathode

❖ Middle QE ($QE=10^{-4}\sim 10^{-3}$ @266nm)

❖ Solid material (no thin film) ⇒ Metal composite cathode

⇒ Started with LaB_6 (short life time)

⇒ Ir_5Ce has very long life time and $QE>10^{-4}$ @266nm

◆ Laser : Stable laser with temporal manipulation

❖ Fiber laser oscillator / amplifier = Yb doped

❖ LD pumped laser medium ⇒ Nd / Yb doped


❖ Temporal manipulation ⇒ Yb doped

⇒ Minimum energy spread

Energy spread reduction using temporal manipulation






M. Yoshida

Energy spread of 0.1% is required for SuperKEKB synchrotron injection.



RF Gun Result Example

5.6 nC bunch charge was observed.




Q-scan emittance measurement

x	y
32.7 ± 3.1 mm-mrad	10.7 ± 1.4 mm-mrad


Emittance Preservation

- ◆ Offset injection may solve the issue
- ◆ Orbit have to be maintained precisely
- ◆ Mis-alignment should be $<0.1\text{mm}$ locally, $<0.3\text{mm}$ globally

Mis-alignment leads to Emittance blow-up



Orbit manipulation compensates it



Sugimoto et al.




Pulse-to-pulse modulation

◆ Four PPM virtual accelerators for SuperKEKB project

Based on Dual-tier controls with EPICS and event-system

Independent parameter sets for each VA (20ms)
>200 parameters for equipment controls
many more for beam controls

maybe with additional PPM VA of stealth beam for measurement






SuperKEKB overview
KEKB Injector Linac
SuperKEKB Injector Linac Progress
Operation





Injector Linac Operation History



Routine maintenance was important to improve the reliability (Failure rate includes rf trips)





Injector Linac Energy Management





Beam Manipulation Study

At 180-deg arc



Optics design with $R56 = 0$ and -0.6 for bunch compression

BPM will be replaced with 5-times better resolution





Streak camera should follow

Measurement of dispersion functions for $R56 = 0$ and -0.6
Soon with timing measurement by streak camera

Linac Optics Measurement / Management

- ◆ Wire scanner is used to manage twiss parameters along linac
- ◆ ~6 sets of wire scanners will be installed



- ◆ Wire scanner measurements performed everyday
- ◆ If necessary (if Bmag is large), re-matching is performed by operator
- ◆ For pulse-to-pulse vertical measurement, X-band deflector will be installed

Typical Phase-1 Daily Operation

More than 300mA stored this week in the both e-/e+ rings

In daytime increases beam current, and performs optics studies


In night time continue vacuum scrubbing

No collision yet





Collision expected at the end of 2017

HER	.324 [A]	1163 [bunches]	Vacuum Scrubbing
LER	.370 [A]	1576 [bunches]	
Luminosity	.000 (now)	.000 (peak in 24H @4:01) [/nb/sec]	
Integ. Lum.	.0 (Fill)	.0 (Day)	.0 (24H) [/pb]

Maintenance 04/21 09:00-17:00
 Stop beam operation 04/28 09:00
 Resume beam operation 05/06 09:00



Examples of Operational Panels






Radiation control licenses

- ◆ **Step-by-step upgrade of beam limits**
- ◆ **Final goal in linac is 1250/625 nA before/after target**
- ◆ **License applications**
 - ❖ **Fall.2013. 10 nA at #28 dump, 1250 nA at #A2 dump**
 - ❖ **Spring 2014. New utility rooms, 50 nA at #61 straight dump**
 - ❖ **Jun.2015. 200 nA at #15 target**
 - ❖ **Early 2016. 800 nA at #15 target, 625 nA at #61**
 - ❖ **Sometime 2017.(?) 1250 nA at #15 target**
- ◆ **Shield, shield, shield, shield ...**
 - ❖ **Gun, 180deg-arc, Target, Electron stopper, Collimator, etc.**

Recent Works



Positron generator at #15 region

Iron shield

Positron generator complex



Guns at #A1 region

Thermionic gun for high-current beam

RF gun for low-emittance beam

Summary

- ◆ We learned a lot during KEKB construction and operation
- ◆ It contributed to achieve the world highest luminosity
- ◆ Injection into SuperKEKB is another challenge with higher beam charge and lower emittance
- ◆ Steady progress towards designed injection beam in steps
 - ❖ Alignment: almost confident on the required precision (0.1-mm local, 0.3-mm global), need to maintain for longer term
 - ❖ Positron generator: another license test, need discharge analysis
 - ❖ Thermionic gun: re-commissioned, working
 - ❖ RF gun: following recommendations at review meetings
 - ❖ Need much more radiation shield
- ◆ Will balance between final beam quality and progressive operation
- ◆ Will select optimized route depending on available resources
- ◆ With some Phronesis we may enjoy beam commissioning




Conference papers at <<http://www-linac.kek.jp/linac/>>



Floor vertical movement

in a half year from summer to winter

Higo et al.



Preparation of Thermionic Gun

◆ Refurbished and recommissioned

- ❖ Raise by 75cm not to conflict with straight RF-gun


 - ✧ As well as angled RF-gun

- ❖ ~ Jun.2015.

◆ Beside RF gun, thermionic gun may serve



- ❖ electrons in phase-I

- ❖ primary electron for positron generation in phase-II and later



SADscripts

◆ Many machine diagnostic and correction/feedback tools



SADScript

◆ Mathematica-like Language

- ❖ Not Real Symbolic Manipulation (Fast)
- ❖ EPICS CA (Synchronous and Asynchronous)
CaRead/CaWrite[], CaMonitor[], etc.
- ❖ (SQL Database)
- ❖ Tk Widget
- ❖ Canvas Draw and Plot (Mathematica-like Plot)
 - ✧ High quality plots to be used in publications
- ❖ KFrame on top of Tk
- ❖ Data Processing (Fit, Modeling, FFT, Optimization, ...)
- ❖ Inter-Process Communication (Exec, Pipe, etc)
System[], OpenRead/Write[], BidirectionalPipe[], etc.
- ❖ Greek Letter
- ❖ Full Accelerator Modeling Capability (this the main part, of course)
- ❖ Also Used for non-Accelerator Applications
- ❖ Other institutes depend on MAD, XAL, but very different architecture