

Hub- and Site-cooling of MRI Magnets using Mobile Cryogenic System

S. K. Gandla and A. Mortensen

Talk Outline



1. Introduction to MRI cooldowns.
2. Site- and hub-cooling concepts.
3. MRI magnet pre-cooler for site- and hub-cooling.
4. Results from using the MRI magnet pre-cooler.

MRI helium consumption

- MRI amounts to ~ **20% of global helium consumption**. Logistics and pre-cooling helium losses are a **significant contribution** to this consumption.
- **4K cold mass** of a large bore superconducting MRI ~ **few tons**.
- Global sales of superconducting MRI magnets: **few thousands/year**.



Current Technology Cold-shipping MRI Magnets


- Existing cooling technologies for precooling MRI magnets at the factory
 - **Liquid nitrogen.**
 - **Closed Loop Mechanical Cooler.**
- MRI magnet is **filled with liquid helium (4K) at factory.** Boil-off loss reduced with **helium recovery system**

Cold-shipping to Customer

- The liquid helium acts as a **cold storage buffer** to keep magnet cold until it arrives at customer.



Helium boil-off while in transit




Alternative logistics options for superconducting MRI magnets

Cold-ship to customer



Warm-ship to local hub (Hub-cooling)



Warm-ship to customer (Site-cooling)




Magnet cold-ship characteristics

- Magnet cryostat boils off helium during transit to customer site.
- Transit duration has to be kept to a minimum (sometimes airfreighted)

Warm-ship advantages


- Zero transit helium boil-off (site-cooling) or significantly reduced transit helium boil-off (hub-cooling).
- No time constraint on the transit time.
- Increased flexibility in mode of transport.

Closed loop helium gas circuit between MRI magnet helium vessel and a cryocooler used for MRI magnet pre-cooling



Cryocooler main requirements.

- Duration of pre-cooling ~ 1 week, i.e., ~1 kW cooling power needed.
- Operate with electrical power, water cooling, and helium process gas only.
- Save liquid helium by pre-cooling magnet to < 30 K.



Realisation of Cryocooler

Cryocooler main components

Helium gas cooling

- 4 single stage coldheads (Sumitomo CH-110LT).
- Custom copper heat-exchangers.
- 4 helium compressors (Sumitomo F-70).

Forced helium gas flow

- Cryogenic gas centrifugal fan.


Cleaning of helium circuit

- Scroll pump.

Performance

- Cooling capacity: 1.4 kW (@293 K)


(More information see: S. Gandla, R. Longworth, 'Mobile Refrigeration System for Precool and Warmup of Superconducting Magnet', CEC/ICMC 2017)



Realisation of Cryocooler: Software Control

Software control main Features


- Automated protocols
- Manual controls for individual components of the cryocooler (touch screen)
- Remote monitoring of the cryocooler.
- Automatic pressure regulation



Controller with
Industrial PC

F-70H
Compressor



Screen shot of control screen





Manual controls for individual
components of the cryocooler
(touch screen)

Automated
protocols for
push-button
control.


Site/Hub-cooling Steps: Evac + Charge




Site-cooling Steps: Pre-cooling



Site/hub-cooling steps: Magnet liquid helium fill



Test: Liquid helium cooling from ~20K to 4K




Test results

- Duration of initial fill: 15 minutes.
- Helium dewar loss: 17 kg (~ 140L).
- MRI Magnet mass gain: 13.5 kg (80% efficiency).
- Almost immediate liquid helium collection in MRI.



Site/hub-cooling steps: Magnet liquid helium fill



Overall helium fill efficiency

- **No additional helium loss** is incurred in cooling from 20K to 4K.
- **80 % liquid helium mass transfer efficiency** (helium syphon efficiency).
- **No liquid helium boil off** after the helium fill as magnet thermal shield < 100K.



Hub-cooling in Brazil



- Magnets for the Brazilian market warm-ship by sea from Shenzhen, China (**Factory**) to Joinville, Brazil (**Hub**) for local assembly.
- Magnets are pre-cooled and liquid helium filled at factory.



- Hub-cooling using a prototype cryocooler was introduced in 2015.
- Since 2015 **majority of MRI magnets for Brazil market have been hub-cooled.**
- **Cryocooler saves > 1000 L liquid helium per MRI magnet compared to liquid nitrogen pre-cooling.**

Demonstration of site-cooling.

Cryocooler connected to magnet on site.



- Remotely monitored process using internet connection.
- Magnet cooldown successful.

Custom-built Peli-case packaging protects cooler for multiple shipments and easy handling.



Summary

- Warm-shipping MRI magnets and utilising hub- or site-cooling can reduce helium losses and shipping costs.
- A mobile, compact cryocooler for MRI magnets has been designed and tested.
- Hub-cooling in Brazil has been fully implemented.
- Site-cooling has been demonstrated.
- The cryocooler works for complete portfolio of Siemens MRI magnets.

Acknowledgements

Sumitomo Cryogenics of America

N. L. Fasnacht Jr.

B. Sloan

R. Longsworth

Siemens Magnet Technology

A. Johnstone

D. Gubbins

I. Wilkinson

J. Lyness

P. Walton