

Hardware integration and performance analysis of a 10 kW HTS wind power generator

CAPTA

MT25

25th International Conference
on Magnet Technology

Presenter: Hae-Jin Sung*

Byeong-Soo Go*, Gi-Dong Nam*,
Heuijoo Park**, Minwon Park*,
and In-Keun Yu*

*Changwon National University


**DOOSAN Heavy Industries &
Construction Co., Ltd.



Changwon National University

CAPTA

Center for Advanced Power Technology Applications



Contents

MT25CAPTA
Centre for Advanced Power Technology Applications

CAPTA



I. Study background & Motivation

- 1.1) Wind power generation system
- 1.2) Reason why we use a superconducting generator

II. Design of a 10 kW HTS generator for the wind turbine

- 2.1) Specifications of the 10 kW class HTS generator
- 2.2) FEM results of the generator

III. 10 kW HTS generator system for hardware implementation

IV. Performance results of the generator

V. Conclusions

Contents

MT25CAPTA
Center for Advanced Power Technology Applications

CAPTA



I. Study background & Motivation

1.1) Wind power generation system

1.2) Reason why we use a superconducting generator

II. Design of a 10 kW HTS generator for the wind turbine

2.1) Specifications of the 10 kW class HTS generator

2.2) FEM results of the generator

III. 10 kW HTS generator system for hardware implementation


IV. Performance results of the generator

V. Conclusions

But, problem is the top head weight.

MT25

The heavy top head causes the high mechanical stress and high cost of foundation and tower.



The large-scale wind turbine using HTS

MT25

CAPTA
Center for Advanced Power Technology Applications

CAPTA

Scale-up properties of WT

A scale factor, α , is defined as the ratio of the scaled blade length (L_1) to the nominal blade length (L_2):

$$\alpha = \frac{\text{Scaled length}}{\text{Nominal length}} = \frac{L_1}{L_2}$$

The total blade mass follows this relationship:

$$m_{up} = \alpha^3 m_{blade}$$

The rotor power:


$$P_{up} = \alpha^2 P$$

<Conventional WT> Ref. SANDIA REPORT, June 2011 (Criterion: 5MW)

Capacity	Scale ratio (α)	Rotor diameter (m)	Blade length (m)	Blade mass (tons)
5 MW	1	126	61.5	18
10 MW	1.414	178.2	87.0	50
12 MW	1.549	195.2	95.3	66
13.2 MW	1.625	204.7	99.9	76
15 MW	1.732	218.2	106.5	92

Capacity	Scale ratio (α)	Top tower mass (tons)	Nacelle mass (tons)	Hub mass (tons)
5 MW	1	350	240	56.8
10 MW	1.414	990	679	161
12 MW	1.549	1,301	892	211
13.2 MW	1.625	1,501	1030	244
15 MW	1.732	1,819	1250	295

Cap.	Conventional scaling	HTS generator scaling			
	Top tower (tons)	Nacelle (tons)	Hub (tons)	Blade-CFRP (tons)	Top tower (tons)
12 MW	1,301	400	169	42.7	697



Ref. UOU, Development of 12MW FOWT core technology for commercialization


Project about 12 MW Floating Offshore Wind Turbine

MT25

CAPTA
Center for Advanced Power Technology Applications



➤ 12MW Superconducting generator



Year	Appraisal
1 st yr. Design of a 12 MW wind turbine	Confirm 12 MW wind turbine output power with the HTS generator
2 nd yr. An HTS pole manufacturing for the HTS generator	HTS one pole coil test in liquid nitrogen based on design results of the 12 MW HTS generator (<10% error of simulation result)
3 rd yr. Detail design of a 12 MW wind turbine with cooling system	Validity and review of the 12 MW wind turbine detail design using 3D CATIA program from related experts

Contents

MT25CAPTA
Center for Advanced Power Technology Association

CAPTA



I. Study background & Motivation

- 1.1) Wind power generation system
- 1.2) Reason why we use a superconducting generator

II. Design of a 10 kW HTS generator for the wind turbine

- 2.1) Specifications of the 10 kW class HTS generator
- 2.2) FEM results of the generator

III. 10 kW HTS generator system for hardware implementation


IV. Performance results of the generator

V. Conclusions

Fundamental design of the 10 kW HTS generator

➤ Fundamental specifications of the SCSG

Items	Value
Rated power	10.3 kW
Rated L-L voltage	380 V
Rated armature current	15.65 A
Rated rotating speed	400 RPM
Rated torque	246 N·m
The length of air gap	20 mm
Thickness of vacuum vessel	7 mm
Current density of copper wire	3 A/mm ²
Safety margin of operating current	40%
Width of the SC wire	4 mm
Thickness of the SC wire	0.16 mm




< Configuration of the superconducting generator >

Fundamental design of the 10 kW HTS generator

➤ Properties of the superconducting wire

Property	Ref.
Type	(Gd/Y)BCO
Thickness	0.16 mm
Width	4 mm
Min. RT bend diameter	11 mm
Max. RT rated tensile stress	550 Mpa
Critical current (self field, 77 K)	200 A
Operating temperature	30 K



Specifications of 10 kW HTS generator

MT25

 CAPTA
 Center for Advanced Power Technology Applications

CAPTA

Parts		Value
HTS coil	Rotational speed	400 rpm
	Temperature	30 K
	Insulation thickness of coil layers	1 mm
	Width of coil bobbin	28 mm
	Total width of HTS coil	98.5 mm
	Effective length of HTS coil	174 mm
	Turns of HTS coil/layer/pole	225
	Operating current	90 A
	Margin of field current	40%
	Num. of poles	6
	No. of HTS coil layers/pole	4
	Total length of HTS wire	3.1 km
Results	Inductance	0.88 H
	Total diameter	476 mm
	Frequency	15 Hz
	Maximum magnetic field	2.6 T
	Perpendicular magnetic field	1.1 T


◀ Detail specifications of the generator

▼ Materials of the generator


Parts		Value
Rotor part	Bobbin of HTS field coil	Aluminum
	Rotor body	Aluminum
	Cryostat	Stainless steel
Stator part	Stator coil	Copper
	Bobbin stator coil	GFRP
	Magnetic shield	M-27 24 Ga

Thermal analysis results

Thermal distribution result of the rotor part



Total heat load is 41.41 W




Mechanical analysis results

MT25

 CAPTA
 Center for Advanced Power Technology Applications

CAPTA

➤ Torque tube and torque sticks




❖ Thermal insulation and Torque transmission

- Shaft generates a very large thermal gradient.
- GFRP torque tube and sticks are required to transfer torque to the shaft at room temperature.

➔ When designing the torque tube or sticks there is always a trade off between structural and thermal.

Mechanical analysis results



CAPTA


➤ Simulation model

Thermal contraction

Heat transfer in solids

Torque of the generator

Structural Mechanics



❖ Heat transfer in solids

❖ Structural Mechanics

- Temperature conditions
: The superconducting part is 30 K.
Two ends of the rotor is room temperature.
- Temperature gradient
: *GFRP & Al*

- Thermal stress
: Induced by thermal expansion of structures
- Torque
: Induced by the applied torque (shear stress)


Mechanical analysis results – Thermal contraction

CAPTA


➤ Simulation model-A/ rotor body

✓ Displacement (mm)

Max. displacement=2 mm



✓ Von mass stress (MPa)



The effective displacement of the rotor body to the torque tube and stick is 2 mm.

Mechanical analysis results - Thermal contraction & Torque

MT25

 CAPTA
 Center for Advanced Power Technology Applications

CAPTA

➤ Simulation model- Torque tube

$$\text{Force} = \text{Torque} / \text{Tube length} = 246 \text{ Nm} / 0.09 \text{ m} = 2,733 \text{ N}$$

✓ Displacement (mm)



✓ Von mises stress (MPa)

Max. displacement=1.16 mm

▲ 0.36

Max. stress=65.3 MPa

▲ 65.3



In this case, the thermal stress is larger than mechanical stress (torque).

*Scale factor: 50

▼ 0

▼ 0.06

Mechanical analysis results - Thermal contraction & Torque

MT25

CAPTA
Center for Advanced Power Technology Applications

CAPTA

➤ Simulation model- Torque stick


$$\text{Force} = \text{Torque} / \text{Tube length} = 246 \text{ Nm} / 0.07 \text{ m} = 3,514 \text{ N}$$

✓ Displacement (mm)

✓ Von mises stress (MPa)

Max. displacement=0.35 mm

Max. stress=66.9 MPa



*Scale factor: 50

Mechanical analysis results - Thermal contraction & Torque

MT25



Ref. Case Studies in Superconducting Magnets, Yukikazu Iwasa

Material	T [K]	σ_U [MPa]	
		295	77
Aluminum 6061 (T6)		315	415
Copper (annealed)		160	310
Copper (1/4 hard)		250	350
Copper (1/2 hard)		300	
Nickel		345→2000	
Silver		190	295
Stainless steel 304		550→ 1030	1450→ 1860
Stainless steel 316LN		1290	1790
Epoxy		40	100
G-10 (warp/normal)		280/240	—
Mylar		145	215
Teflon		14	105

➤ The sum of the thermal stress and mechanical stress

- Torque tube: 65.3 MPa
- Torque sticks: 66.9 MPa

Therefore, the stresses of the torque tube and sticks are within acceptable value (72 MPa @ 70% margin).

Contents

MT25CAPTA
Centre for Advanced Power Technology Applications

CAPTA



I. Study background & Motivation

- 1.1) Wind power generation system
- 1.2) Reason why we use a superconducting generator

II. Design of a 10 kW HTS generator for the wind turbine

- 2.1) Specifications of the 10 kW class HTS generator
- 2.2) FEM results of the generator

III. 10 kW HTS generator system for hardware implementation

IV. Performance results of the generator

V. Conclusions

Winding of HTS field coil (QPC)

CAPTA

➤ Assembly of the DPC




➤ Assembly of the QPC



Measured results of QPC (I_c & B)


➤ I_c @77 K test results



- Num. of QPC turns: 450 turns
- Total HTS length: 500 m
- Inductance: 125 mH

Conduction cooling test set-up


Configuration of test chamber



Tem. sensor

Conduction cooling test set-up

- ✓ Two coils are one set for the conduction cooling test




● Hall sensor ● Tem. sensor → Current direction


Conduction cooling test – Current & Temperature

MT25

CAPTA
Center for Advanced Power Technology Applications



Conduction cooling test – Current & Voltage & Magnetic field



Conduction cooling test – Measurement results of QPCs




CAPTA


Fabrication of the HTS field coils for 10 kW SCSG (Target = QPC 6 ea)

Coil	Winding	Impregnation	Inductance (mH)	Operating current (A)	Magnetic field (T)	Test
QPC1	Done	Done	127 mH	95 A	0.85 T	Success
QPC2	Done	Done	127 mH	95 A	0.86 T	Success
QPC3	Done	Done	130 mH	95 A	0.85 T	Success
QPC4	Done	Done	130 mH	95 A	0.86 T	Success
QPC5	Done	Done	130 mH	95 A	0.87 T	Success
QPC6	Done	Done	127 mH	95 A	0.85 T	Success

Configuration of the 10 kW HTS generator system

CAPTA



Wire type	2G GdBCO wire (SuNAM Corp.)	Refrigerant	Liquid Neon
Target I_{op}	95 A	Number of pole	6 pole
Target temp.	<30 K	Rotating speed	400 rpm
Cooling method	Thermosyphon + Conduction cooling	Target capacity	10 kW



10 kW HTS generator system

MT25

CAPTA
Center for Advanced Power Technology Applications





Video of the 10 kW HTS generator





Cooling test of the generator

Temp. sensor positions



Chamber-2

Coil-2


Coil-1

Chamber-1

Contents

MT25CAPTA
Centre for Advanced Power Technology Applications

CAPTA



I. Study background & Motivation

- 1.1) Wind power generation system
- 1.2) Reason why we use a superconducting generator

II. Design of a 10 kW HTS generator for the wind turbine

- 2.1) Specifications of the 10 kW class HTS generator
- 2.2) FEM results of the generator


III. 10 kW HTS generator system for hardware implementation

IV. Performance results of the generator

V. Conclusions


Performance results

CAPTA



Performance results


➤ QPC voltage & Current



Performance results

➤ Temperature & Current


- From 29 K to 31 K



Performance results

➤ Magnetic field of air-gap (or stator)


- At 400 rpm



Performance results

➤ EMF at load test

- At 400 rpm
- Full output power= 11 kW



Measure	P1:rms(C1)	P2:rms(C2)	P3:rms(C3)	P4:freq(C2)	P5:pkpk(C2)	P6:max(C3)
value	411 V	414 V	397 V	18.695 Hz	1.18 kV	591 V
status	✓	✓	✓	✓	✓	✓

C1	C2	C3
200 V/div	190 V/div	200 V/div
-10 V offset	0 V offset	20 V offset
----- 222 V	----- 201 V	----- 192 V
----- 96 V	----- 82 V	----- 66 V
Δy -126 V	Δy -120 V	Δy -126 V

Tbase	-86.6768 s	Trigger	C1 DC
	20.0 ms/div	Stop	-10 V
200 kS	1.0 MS/s	Edge	Positive

Conclusions

- A high temperature superconducting (HTS) generator for a large-scale wind power generation system draws much attention as a contemporary research item.
- This presentation deals with the **hardware integration and performance analysis of a 10 kW HTS wind power generator**.
- The HTS generator, which consists of 6 pole racetrack type HTS coils for rotor and 36 slots copper windings for stator, was designed.
- The generator was designed by **considering electromagnetic, thermal, and mechanical analyses**.
- Conduction cooling test for HTS field coils wound by 2G GdBCO wire was performed in a cryogenic test chamber using two GM cryocoolers at 30 K, and then the whole generator system was fabricated and assembled.
- The generator was cooled down by **thermosyphon cooling method** with a GM cryocooler using liquid neon, and **achieved at 30 K**.
- As a result, full output power of the generator was **11 kW**. Therefore, rated output power of 10 kW was achieved.
- The results will be applied to comparative analysis with the generator having the HTS brushless exciter and the development of the large-scale wind power generator core technology.

Thank you for your attention

Acknowledgement

This work was supported by the Human Resource Training Program for Regional Innovation and Creativity through the Ministry of Education and National Research Foundation of Korea (2014H1C1A1066941)

in Changwon national university