

# 043

## Construction and test of the NHMFL 32 T superconducting magnet



Huub Weijers, Denis Markiewicz, Adam Voran, Scott Gundlach, Yuri Viouchkov, Andy Gavrilin, Patrick Noyes, Eric Stiers, Tom Painter, Brent Jarvis, Bill Sheppard, Greg Sheppard, David Hilton, Dima Abramov, and Tim Murphy, all NHMFL

### Background

The 32 T project aims to combine a 15 T LTS magnet with two REBCO double pancake coils generating 17 T to create a 32 T / 34 mm cold bore user magnet for the MilliKelvin facility at the NHMFL. Both coil sets operate at 4.2 K using two separate power supplies. Oxford Instruments provided the NbTi & Nb<sub>3</sub>Sn LTS magnet, which features both passive and active quench protection. The HTS coil technology was developed at the NHMFL, based on SuperPower coated conductor. A key feature is the active quench protection system that relies on powerful quench heaters to protect the HTS coils, in case of a quench in either the HTS or LTS coils, from excessive hoop stress, peak hot-spot temperatures and voltage-to-ground.

### Relevance

- The first all superconducting user magnet that aims to substantially exceed the limits of Nb-based LTS superconductors is constructed
- Quench detection, Quench protection and long lifetime (fatigue) are an integral part of the magnet technology development
- NI promises higher current density & more compact magnets but has unresolved issues requiring development before practical & reliable high field user magnets, especially those with ramp rate requirements, can be expected.

### Summary

- The 32 T superconducting magnet is in the 4.2 K test phase
- All supporting electronic systems are qualified
  - After extensive stand-alone and in-system testing
  - Two redesigns of the battery bank switch system
- Site for user operations has been built and is being fitted out.
- The 32 T magnet has been tested to 5 T in HTS-only mode
  - Quench detection needs adjustment
- Deliberate quenches at moderate field/coil energy levels are next
  - 12 T HTS-alone and 16 T HTS + LTS
- Design of HTS magnets with insulated anisotropic conductor requires careful design of the  $I_c$  / temperature margin: both minimum and maximum
  - To limit quench heater power and voltage to ground during quench
  - Conductor grading highly desirable



32 T at test site (Cell 4) 1) Site of future User Operations (Millikelvin Building Expansion Magnet pit (with cover) 2) Room for pumps, battery racks

### Target

- 32 T, 34 mm cold bore,  $5 \times 10^{-4}$  uniformity/1cm DSV
- 1 hour to full field
- 20 year life time

### Choices

- 4 mm wide REBCO Coated Conductor tapes
- Double pancake construction
- Insulated stainless steel co-wind
- Wax impregnation
- Quench heaters between double pancakes
- 15 T / 250 mm bore 7 MJ LTS magnet

### Design Constraints

- Operating current  $\leq 70\%$  of  $I_c$
- $J_{copper} \leq 450$  A/mm<sup>2</sup>
- Max stress/strain : 400 MPa / 0.4 % ( $\leq 70\% \alpha_{critical}$ )
- Target  $T_{hot spot} \leq 200$  K
- Voltage to ground  $\leq 1.0$  kV

### Consequences


- 8.3 MJ, 2.6 ton system
- 50,000 lifetime cycles
- Integrated HTS & LTS magnet design & quench management
- New technology requires testing and prototypes
- Screening currents in HTS

	Coil 1	Coil 2
IR, OR, height [mm]	20, 70, 178	82, 116, 318
Double pancakes	20	36
$I_{operation}$ [A]	174	174
$J_{average}$ [A/mm <sup>2</sup> ]	200	170
Conductor length [km]	2.9	6.8
Inductance [H]	2.6	9.9
Field contribution [T]	10.7	6.3
Co-wind thickness [ $\mu$ m]	25	50

### Construction



### Supporting Systems




### As-built




- 330 A / 20 V capable LTS Magnet Power Supply
- 200 A / 8 V capable HTS Magnet Power Supply
- 31 Lead-acid batteries in two racks  
390 V open circuit, ~300 V at 500° A
- 3 × Quench detection, High-voltage Isolation, Interlock and instrumentation
- Quench heater switch boxes

### Results


#### Conductor as-received



#### Margins as-built and consequences



#### Quench simulations



#### First 4.2 K data

