

The CLIC re-baselining document

Eva Sicking (CERN / LAPP Annecy)
on behalf of the CLIC re-baselining editor team

CLIC workshop
January 22, 2016

The CLIC re-baselining document



CLIC-Note-201X-XXX
21 January 2016

Updated baseline for a staged Compact Linear Collider

The CLIC and CLICdp collaborations (list incomplete)

P.J. Giansiracusa, T.G. Lucas, R.P. Rassool
The University of Melbourne, Australia

C. Balazs, T.K. Charles
Monash University, Australia

M. Boland, U. Felzmann
Australian Synchrotron, Australia

K. Afanaciev, I. Emeliantchik, A. Ignatenko, V. Makarenko, N. Shumeiko
Research Institute for Nuclear Problems of Belarusian State University (INP BSU), Minsk, Belarus

A.C. Abusleme Hoffman, M.A. Diaz Gutierrez, M. Vogel Gonzalez
Pontificia Universidad Católica de Chile, Santiago, Chile

T. Laštovička
Institute of Physics, Academy of Sciences of the Czech Republic, Prague, Czech Republic

U. Uggerhøj, T.N. Wistisen
Department of Physics and Astronomy, Aarhus University, Denmark

J.-J. Blaising, M. Chefdeville, Y. Karyotakis
Laboratoire d'Annecy-le-Vieux de Physiques des Particules, Annecy, France

I. Peric
Karlsruhe Institute for Technology (KIT), Germany

M. Gabriel, F. Simon, M. Szalay, N. van der Kolk
Max-Planck-Institut für Physik, Föhringer Ring 6, D-80805 Munich, Germany

H. Abramowicz, Y. Benhammou, O. Borysov, S. Kananov, A. Levy, I. Levy, O. Rosenblat
Raymond & Beverly Sackler School of Physics & Astronomy, Tel Aviv University, Tel Aviv, Israel

G. Eigen, J. Zalieckas
Department of Physics and Technology, University of Bergen, Bergen, Norway

S. Bugiel, R. Dasgupta, M. Firlej, T.A. Futowski, M. Idzik, M. Kuczyńska, J. Moron,
K.P. Swientek

*Faculty of Physics and Applied Computer Science, AGH University of Science and Technology,
Al. Mickiewicza 30, Kraków, Poland*

● Authors:

The CLIC and CLICdp collaborations

→ Please check if your institute is already represented correctly in the author list and in the acknowledgements

● Editors:

Philip Burrows, Philippe Lebrun,
Lucie Linssen, Daniel Schulte, ES,
Steinar Stapnes, Mark Thomson

● Update of CLIC staging baseline

● Focus on initial energy stage

● Updated official CLIC figures

● Latest version always at this website

► <http://esicking.web.cern.ch/esicking/ClcStagingBaseline/>

Content of re-baselining document

Contents

Contents	
1 Introduction	5
2 CLIC physics at various centre-of-mass energies	6
2.1 CLIC detector and experimental conditions	6
2.2 CLIC energy stages and their impact on the physics potential	7
2.3 Higgs physics	8
2.3.1 Combined Higgs fits	12
2.4 Top physics	15
2.4.1 Top quark mass	15
2.4.2 Top quark as probe for BSM physics	17
2.5 Physics beyond the Standard Model	19
2.5.1 Direct searches for BSM physics	20
2.5.2 Sensitivity of precision measurements to BSM physics	20
2.6 Summary of physics requirements for the CLIC energy stages	20
3 CLIC post-CDR accelerator optimisation	22
3.1 Overview	22
3.2 State of understanding	23
3.2.1 Beam Parameters	23
3.2.2 RF structure design	24
3.2.3 Cost and power estimates	24
3.3 Optimisation procedure and results	25
3.3.1 Optimum at 3 TeV	25
3.3.2 Optimum at 380 GeV	27
3.3.3 Staging strategy	27
4 CLIC staging baseline	28
4.1 Description and performance parameters	29
4.2 Operation scenario	29
4.3 Power and energy consumption	29
4.4 Cost estimate	34
5 Alternative klystron-based scenario for the first CLIC stage	35
6 Summary and outlook	38


→ Physics considerations

→ Accelerator optimisation methodology

→ New staging baseline

Physics motivation of re-baselining

- CLIC is foreseen as staged machine with \sqrt{s} from few-hundred GeV to 3 TeV



1st stage

- Guaranteed physics: **Higgs couplings + width** and **top**
- Higgs discovered after CDR
- $m_H = 125$ GeV


Subsequent (2nd and 3rd) stages

- Motivated by Higgs physics and new physics
- Potential discoveries at the LHC at 14 TeV
- Direct and indirect searches for beyond standard model physics


- Optimal \sqrt{s} for 1st stage is **not** at peak of HX and $t\bar{t}$ cross sections
 - luminosity and backgrounds can scale with centre-of-mass energy
 - theory uncertainties for $t\bar{t}$ can be larger close to on-set of $t\bar{t}$ production

Higgs recoil mass at $\sqrt{s} = 250/350/420$ GeV

- Accuracies of Higgs results governed by accuracy of **HZ coupling**
- HZ coupling in Z recoil mass measurement in first energy stage
- Hadronic channel ($\text{BR}_{Z \rightarrow q\bar{q}} \approx 70\%$) has largest impact
- Test three energies:



$$m_{\text{recoil}}^2 = s + m_Z^2 - 2E_Z\sqrt{s}$$



\sqrt{s}	$\sigma(\text{HZ})$	$\Delta\sigma(\text{HZ})$
250 GeV	136 fb	$\pm 3.65\%$
350 GeV	93 fb	$\pm 1.80\%$
420 GeV	68 fb	$\pm 2.63\%$


→ [arXiv:1509.02853\[hep-ex\]](https://arxiv.org/abs/1509.02853)

- Find optimal energy for first CLIC stage
 - Cross section decreases with \sqrt{s}
 - Absolute detector resolution degrades with \sqrt{s}
 - Background rejection improves with increasing \sqrt{s}

→ **Optimum close to 350 GeV**

Access to Higgsstrahlung and WW fusion


- For a comprehensive Higgs study in the first energy stage only, access to several Higgs production processes is advantageous




- Below $\sqrt{s} \sim 300 \text{ GeV}$
Higgsstrahlung dominates
- Above $\sqrt{s} \sim 500 \text{ GeV}$,
WW-fusion dominates

→ At $\sqrt{s} = 350\text{--}450 \text{ GeV}$ both processes contribute

Top physics



- At $\sqrt{s} > 350$ GeV, top pair production sets on
- Maximum at $\sqrt{s} > 420$ GeV, then cross section falls steeply (s-channel)





- High precision measurement of top mass from threshold scan with modest luminosity ($10 \text{ fb}^{-1}/\text{point}$) in addition to first energy stage
- $\delta m_t = 33 \text{ MeV}$ statistical uncertainty

→ Eur. Phys. J. C73 (2013) 2530

Top form factor measurement

→ Talk by Ignacio Garcia on Thursday

- Probe top vertex through **cross section** and **forward-backward asymmetry** (A_{FB})
 - Derive top form factors (F)
 - Expect deviations from SM expectations in form factors for BSM models
- Form factor uncertainty vs. \sqrt{s} (500 fb⁻¹ each)



- Reconstruction capability and impact of BSM on form factor increases with \sqrt{s}
 - Theoretical uncertainty decrease with \sqrt{s}
- Optimum close to 500 GeV (for fixed luminosity per \sqrt{s})

Conclusion on CLIC first energy stage

Find compromise for comprehensive physics programme of initial stage

- Higgs recoil mass measurement
→ $250 \text{ GeV} < \sqrt{s} < 420 \text{ GeV}$
- Higgs production via Higgsstrahlung and WW-fusion
→ $250 \text{ GeV} < \sqrt{s} < 450 \text{ GeV}$
- Top pair production
→ $\sqrt{s} > 350 \text{ GeV}$, maximum at $\sqrt{s} \approx 420 \text{ GeV}$
- Top as probe for BSM
→ $\sqrt{s} > 360 \text{ GeV}$
- Top not too close to threshold (theory uncertainties, boost)
→ $\sqrt{s} \gg 350 \text{ GeV}$

$$\rightarrow \sqrt{s} = 380 \text{ GeV}$$

Proposed CLIC staging baseline

- CLIC energy stages defined by physics

- Proposed scenario

1) $\sqrt{s} = 380 \text{ GeV}$


- SM Higgs physics including total width measurement
- Top precision measurements
- New physics

2) $\sqrt{s} = 1.5 \text{ TeV}$

- New physics
- $t\bar{t}H$, Higgs self coupling
- Rare Higgs decays

3) $\sqrt{s} = 3 \text{ TeV}$


- New physics
- Higgs self coupling
- Rare Higgs decays



Stage	\sqrt{s} (GeV)	\mathcal{L}_{int} (fb $^{-1}$)
1	380	500
	350	100
2	1500	1500
3	3000	3000

CLIC Accelerator Optimisation for $\sqrt{s} = 380$ GeV

- Accelerator structure design fixed by few parameters ($L_{\text{structure}}, \Phi, \dots$)
- Find optimal parameter set for 380 GeV CLIC accelerator in parameter scan
- Evaluation tool exists, developed after CDR, based on methods already used in CDR
- Tested ~ 2 billion possible structures and resulting accelerator complexes based on these parameters




- All structures are checked for consistency with beam and RF constraints
- Gauging cost, power and luminosity (not including beam induced backgrounds)


Example: Cost and power for 380 GeV

- Compared cost and power consumption for all resulting structures
 - Choice: fixed pulse length of 244 ns for all stages
 - Note: some accelerator components not included in cost and power, e.g. BDS, main beam injector

Safety margin S for gradient




Luminosity target L



- Choice of safety margin 10% ($S=1.1$): only small impact on cost and power
- Cost and power increase with luminosity target
(choice $L=1.5 \cdot 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$: can reach $\mathcal{L}_{\text{int}} = 600 \text{ fb}^{-1}$ in 7 years)


→ Most efficient structure: $G = 72 \text{ MV/m}$, similar to “CLIC_G”

Potential staging concept



- For the structures optimised for 380 GeV, staging scenario towards higher energy stages is available


Updated CLIC footprint



Updated CLIC parameter table: Stage 1–3


Parameter	Symbol	Unit	Stage 1	Stage 2	Stage 3
Centre-of-mass energy	\sqrt{s}	GeV	380	1500	3000
Repetition frequency	f_{rep}	Hz	50	50	50
Number of bunches per train	n_b		352	312	312
Bunch separation	Δt	ns	0.5	0.5	0.5
Pulse length	τ_{pulse}	ns	244	244	244
Accelerating gradient	G	MV/m	72	72/100	72/100
Total luminosity	\mathcal{L}	$10^{34} \text{ cm}^{-2} \text{ s}^{-1}$	1.5	3.7	5.9
Luminosity above 99% of \sqrt{s}	$\mathcal{L}_{0.01}$	$10^{34} \text{ cm}^{-2} \text{ s}^{-1}$	0.9	1.4	2
Main tunnel length		km	11.4	29.0	50.1
Charge per bunch	N	10^9	5.2	3.7	3.7
Bunch length	σ_z	μm	70	44	44
IP beam size	σ_x/σ_y	nm	149/2.9	$\sim 60/1.5$	$\sim 40/1$
Normalised emittance (end of linac)	ϵ_x/ϵ_y	nm	—	660/20	660/20
Normalised emittance	ϵ_x/ϵ_y	nm	950/30	—	—
Estimated power consumption	P_{wall}	MW	252	364	589

New CLIC layout at 380 GeV





- Removed 1 e⁻-damping ring
- 11 km length (instead of 13 km at 500 GeV)
- 4 sectors (instead of 5 sectors at 500 GeV), ...

New CLIC layout at 3 TeV



- Removed 1 e^- -damping ring
- 50 km length instead of 48 km
- 25 sectors instead of 24 sectors, ...


Updated luminosity development



- CLIC programme of 22 years:
7 years (380 GeV), 5 years (1.5 TeV), 6 years (3 TeV)
interleaved by 2-years upgrade periods
- Luminosity ramp up of 4 years / 2 years
(5%, 10%,) 25%, 50%, 100%


Updated power consumption at 380 GeV

per domain of the CLIC accelerator



- DB linac
- DB frequency multiplication & transport
- MB production
- MB damping rings
- MB booster linac & transport
- Main linacs
- BDS & experiment
- Instrumentation & Control

per technical system



- Radio-frequency
- Magnets
- Cooling
- Ventilation
- Instrumentation & Controls
- Interaction area & experiments

- CLIC power consumption at 380 GeV: $\sim 252 \text{ MW}_{\text{preliminary}}$
including all accelerator systems, services, experimental area and detector

(Note → Numbers scaled from CDR design at 500 GeV
→ To be repeated with detailed tech. description of 380 GeV CLIC)

Updated power consumption at all stages

- Current estimates of power consumption¹


\sqrt{s} [TeV]	P_{nominal} [MW]	$P_{\text{waiting for beam}}$ [MW]	P_{stop} [MW]
0.38	252	168	30
1.5	364	190	42
3.0	589	268	58

- Potential power savings ([not yet included here](#)):
 - Re-design, possibly trading operation expenditure against investment costs
 - Lower current density in normal conducting magnets and cables
 - Use of permanent magnets → [Talk by Jim Clarke on Wednesday](#)
 - Reduction of heat loads to ventilation system (enhancement of water cooling)
 - Replacing normal-conducting by “super-ferric” magnets
 - Improving network-to-RF power conversion

→ estimated to be [up to 30 MW at 380 GeV](#)


¹Note: 380 GeV numbers scaled from CDR, 1.5 TeV and 3 TeV numbers from CDR

Yearly energy consumption



- Including reduced operation in the first years at each energy
 - At 380 GeV, a single positron target is used for the first three years (-10 MW with respect to nominal)
- (Note → 380 GeV numbers scaled from CDR design at 500 GeV
→ To be repeated with detailed tech. description of 380 GeV CLIC)

Yearly energy consumption




- Including reduced operation in the first years at each energy
 - At 380 GeV, a single positron target is used for the first three years (-10 MW with respect to nominal)
- (Note → 380 GeV numbers scaled from CDR design at 500 GeV
→ To be repeated with detailed tech. description of 380 GeV CLIC)

Cost estimate for 380 GeV

- Full CLIC cost estimation including all contributions
- Use 2010 CHF for direct comparison to CDR estimates

	Value [MCHF (2010)]
Main beam production	1245
Drive beam production	974
Two-beam accelerators	2038
Interaction region	132
Civil engineering & services	2112
Machine control & operational infrastructure	216
Total	6690

Comparison to CDR values



- Full 380 GeV CLIC machine: $\sim 6.7 \text{ BCHF (2010)}$ preliminary (+ 4 MCHF/GeV up to 1.5 TeV)

(Note → Numbers scaled from CDR design at 500 GeV

→ To be repeated with detailed tech. description of 380 GeV CLIC)

Summary


- CLIC re-baselining document close to final
 - Focus on initial energy stage at 380 GeV
 - 380 GeV cost: 6.7 BCHF(2010), power: 252 MW
 - Optimal accelerator structures close to CDR design “CLIC_G”
 - Update of official CLIC figures and tables
- Latest document version can be found at this website
 - ▶ <http://esicking.web.cern.ch/esicking/ClicStagingBaseline/>
- Please check if you and your institute are already represented correctly in the author list and the acknowledgements
- Collaboration review will start soon



Backup

CLIC Higgs results for example staging scenario

- Studied Higgs physics potential of CLIC in staging scenario including 350 GeV (500 fb^{-1}), 1.4 TeV (1500 fb^{-1}) and 3 TeV (2000 fb^{-1})
- Combine results of studied Higgs production and decay channels in global fit
→ extract couplings and Higgs width




Based on results from full Geant4 detector simulations including backgrounds →

Assuming 80 % e^- beam polarisation at 1.4 TeV and 3 TeV


- Accuracies **governed by H-Z coupling** from H recoil mass measurement

Cost of initial stage



- Structures **optimised for 380 GeV** are similar in cost to those **optimised for matching 3 TeV** needs (+3% at $L = 1.5 \cdot 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$)

Assumed operational scenario in “normal” years




- Annual shutdown
- Scheduled short stops
- Fault-induced stops (normal year)
- Operation (MD, beam commissioning)
- Operation (data taking)

- 90-day annual shut-down
- 50 days of scheduled maintenance stops (1 day per week and 2 weeks every 2 months)
- Remaining 225 days
 - 45 days (20%) fault-induced stops
 - 180 days (80%) for operation
 - 55 days machine development and tuning runs
 - 125 days for physics data taking

Alternative klystron-based scenario

- At 3 TeV, drive-beam acceleration is more efficient and cost effective than klystrons
- At 380 GeV, X-band klystrons however interesting alternative



- Klystron-based CLIC concept for 380 GeV designed including
 - X-band klystrons
 - Pulse compressor
 - RF distribution system
 - Accelerating structures