

Optimisation of SLED Cavities and Waveguide Network to Drive the Linac at the Australian Synchrotron

Thomas Lucas, Karl Zingre, Mark Boland, Roger Rassool


University of Melbourne and Australian Synchrotron

June 24, 2016

Outline

- 1 Motivation
- 2 Project Outline
- 3 Background
- 4 Modelling
- 5 Future Work

Australian Synchrotron




Australian Synchrotron



Australian Synchrotron



Australian Synchrotron



Australian Synchrotron


- 3 GeV Synchrotron Light Source.
- 100 MeV linac to 3 GeV Booster Synchrotron.
- Deliver $> 99\%$ of scheduled beam.
- Storage Ring contains 200 mA for user beam.

Motivation


Operations: Ageing equipment is prone to faults. A SLED system will allow the linac to run with a single klystron.

Research: Generation of electrons over a range of energies. Aims for an extraction line.

SLED Upgrade to Linac



SLED Upgrade to Linac





SLED Upgrade to Linac

- An extra variable power splitter VPS I, suitable for vacuum compared to SF6 and a higher peak power level, was added while reusing existing VPS IV as a switch to select either klystron I, II or both.
- The LINAC vacuum section was extended into the waveguide and an extra RF window placed downstream VPS I to reduce the power level and risk of failure.
- The new design will allow to select remotely two operation modes:
 - 1 with the SLED and klystron I or II; or
 - 2 operation with two klystrons and a detuned SLED.

SLED Cavities

$$E_O = E_C - E_K \quad (1)$$



SLED Equations

The electric fields in the cavities are governed by the following formula:

$$T_c \frac{dE_c}{dt} + E_c = \alpha E_K \quad (2)$$

$$\text{where } \alpha = \frac{2\beta}{\beta + 1}$$

$$\text{and } T_c = \frac{2Q_0}{\omega(1 + \beta)}.$$


Calculations of the accelerating gradient from the electric fields is done by integrating over the structure length L .

$$\Delta W = q \cos \phi \int_0^L E_a(z, t) dz \quad (3)$$


Ideal SLED model (Farkas et al. 1974)

$E_K =$

$$\begin{cases} 1 & t \leq t_{flip} \\ -1 & t_{flip} < t \leq t_{pulse} \\ 0 & t_{pulse} < t \end{cases}$$







LLRF Testing




LLRF Testing

- Klystron Rise time ≈ 300 ns
- Flip time $\approx 50 - 100$ ns





Realistic SLED model

$$E_K = \begin{cases} \frac{t}{t_{rise}} & t \leq t_{rise} \\ 1 & t_{rise} < t \leq t_{stop} \\ 0 & t_{stop} < t \leq t_{f1} \\ \frac{1}{t_f}(t_{f1} - t) & t_{f1} < t \leq t_{f2} \\ -1 & t_{f2} < t \leq t_{pulse} \\ 0 & t_{pulse} < t \end{cases}$$




Power Output




Beta Coupling Optimisation

- 100 MW limit on RF window for VPS I
- Charge time of $3\mu\text{s}$ would be used for general user beam.




Beta Coupling Optimisation

- Lower beta reduces energy spread




Energy Spread

- Low energy spread vital for booster ring.
- Trade off between high gradient and energy spread.





Beam Energy

- Two Configurations:
 - 1 Single klystron + SLED
→ All Structures.
 - 2 Klystron 1 at 17 MW →
PBU, FBU and ACC1
Klystron 2 + SLED →
ACC2




Phase Ramp

- Phase ramp allows for pulse flattening
- Phase slip over long structures.



Extraction Lines



Next Steps

- Installation in September
- Need to compare beam properties with and without the SLED. Optimising the energy spread and maximising the bunch train length.
- μ TCA upgrade to the LLRF \rightarrow RF monitoring and phase modulation.

Summary

- Using a realistic input the modelling has shown an optimal beta coupling of 5.
- Manufacturing the ports with smaller beta allows for less energy spread but can be increased later.
- A beam energy of 50-165 MeV electrons possible without changes to hardware.
- Bunch train length of 75 ns possible for MBM to be used for injection. Injection frequency doubles.

Thanks to...

Rohan Dowd, Peter Corlett, Paul Giansiracusa, David Peake and the Australian Synchrotron's operations staff.

Questions?