#### **MICE Analysis Status and Plans**



C. Rogers, ASTeC Intense Beams Group Rutherford Appleton Laboratory



#### Status

- Analysis of data since CM43
  - Diagnostics
  - Magnets and physics
- Plans
  - Step IV lattice
  - Demonstration of Ionisation Cooling issues



## **Outline Data Plan**

WICE

- Commission hardware
- Beam-based alignment of detectors with field off
- Beam-based alignment of magnets with field on
- Understand diagnostics
- Check beam quality through the lattice
- Optics and momentum scans with/without absorber

- First pass analysis should follow data ASAP
- At least two analyses for every (major) measurement

### Data taking update



	September 21 <sup>st</sup> – 22 <sup>nd</sup>	SSU at 1.5 T
	September 25 <sup>th</sup> – 29 <sup>th</sup>	Ckov momentum scan
		Magnetic field remnant study
		Beam polarisation measurement
	October 7 <sup>th</sup>	4 T in SSU
CM	October 14 <sup>th</sup>	TOF0 alignment
43	December 3 <sup>rd</sup> - 7 <sup>th</sup>	FC alignment study
	December 13 <sup>th</sup> - 16 <sup>th</sup>	Scattering in Xenon and empty
	February 23rd – March 24 <sup>th</sup>	Alignment studies
		Empty absorber data
		Scattering in LiH
		Pionic beamline studies



Measurement	Coordinator	Principle of Measurement	Laptop Studies	Batch MC & Analysis	Final Run Settings	Data Taking	First Analysis & Data Checks	Final Analysis	Write up
				Step I	V				
Magnet Mapping - Axes	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Not started
Magnet Mapping - Coil Geometries	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	In progress	Not started
Tracker Alignment – least squares	J. Nugent	Complete	Complete	In progress	Complete	Complete	Complete	In progress	Scattering Paper
Tracker Alignment – residuals	F. Drielsma	Complete	Complete	In progress	Complete	Complete	Complete	In progress	MICE Note
PID Detector Alignment	F. Drielsma	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Beamline Commissioning – u/s	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	MICE Note 476
Beamline Commissioning – d/s	P. Franchini	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Upstream detector resolution	V. Blackmore	Complete	Complete	Complete	Complete	Complete	Complete	In progress	Emittance Paper
Downstream/global detector resolution	n M. Uchida M. Uchida/F.	Complete	Complete	In progress	Complete	In progress	In progress	Not started	Not started
Detector efficiencies	Drielsma T. Mohayai/S.	Complete	In progress	In progress	In progress	In progress	In progress	Not started	Not started
PID measurement – cut based	Wilbur	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
PID measurement – log likelihood	C. Pidcott	Complete	Complete	In progress	In progress	In progress	In progress	Not started	Not started
Magnet alignment – transfer matrix	S. Middleton	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Magnet alignment – minimise	C. Rogers/S.								
residuals	Middleton	Complete	In progress	In progress	In progress	In progress	In progress	In progress	Not started
Magnet alignment – cycloid fit	C. Rogers	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Beam quality	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
First emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Full emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Non-linear optics	R. Ryne	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
MCS - field off	J. Nugent	Complete	In progress	In progress	Complete	Not started	Not started	Not started	Not started
MCS - field on	C. Pidcott	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – measurement based	R. Gardner	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – minimise residuals	D. Maletic	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Beam polarisation	S. Middleton	Complete	Complete	In progress	Complete	Complete	Complete	In progress	In progress
				Step ]	[				
EMR	F. Drielsma	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete
Pion contamination	J. Nugent	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete



Management	Coordinator	Principle of	Laptop	Batch MC &	Final Run	Data Taking	First Analysis & Data	Final Analysis	Marita un
Measurement	Coordinator	wiedsureinent	Studies	Step I	V	Data laking	CHECKS	Fillal Allalysis	write up
Magnet Mapping - Axes	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Not started
Magnet Mapping - Coil Geometries	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	In progress	Not started
Iracker Alignment – least squares	J. Nugent	Complete	Complete	In progress	Complete	Complete	Complete	In progress	Scattering Paper
Tracker Alignment – residuals	F. Drielsma	Complete	Complete	In progress	Complete	Complete	Complete	In progress	MICE Note
PID Detector Alignment	F. Drielsma	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Beamline Commissioning – u/s	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	MICE Note 476
Beamline Commissioning – d/s	P. Franchini	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Upstream detector resolution	V. Blackmore	Complete	Complete	Complete	Complete	Complete	Complete	In progress	Emittance Paper
Downstream/global detector resolution	<b>n</b> M. Uchida	Complete	Complete	In progress	Complete	In progress	In progress	Not started	Not started
	M. Uchida/F.	<b>a</b> 1	-		-	-	-		
Detector efficiencies	Drielsma	Complete	In progress	Not started	Not started				
	T. Mohayai/S.	Complete	Complete	T.,	Complete	T	T	T	NT- t - t - t - d
PID measurement – cut based	wildur	Complete	Complete	in progress	Complete	In progress	In progress	in progress	Not started
PID measurement – log likelinood	C. Placott	Complete	Complete	in progress	in progress	In progress	In progress	Not started	Not started
Magnet alignment – transfer matrix	S. Middleton	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Magnet alignment – minimise	C. Rogers/S.	<b>C</b> 1.	<b>T</b> .	<b>T</b> .	NT / / / I				
	Middleton	Complete	In progress	In progress	Not started				
Magnet alignment – cycloid fit	C. Rogers	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Beam quality	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
First emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Full emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Non-linear optics	R. Ryne	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
MCS - field off	J. Nugent	Complete	In progress	In progress	Complete	Not started	Not started	Not started	Not started
MCS - field on	C. Pidcott	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – measurement based	R. Gardner	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – minimise residuals	D. Maletic	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Beam polarisation	S. Middleton	Complete	Complete	In progress	Complete	Complete	Complete	In progress	In progress
				Step I	[				
EMR	F. Drielsma	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete
Pion contamination	J. Nugent	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete



		<b>D</b> · · I (	<b>T</b> .				First Analysis		
Measurement	Coordinator	Principle of Measurement	Laptop Studies	Analysis	Final Run Settings	Data Taking	& Data Checks	Final Analysis	Write un
	000100000		States	Step I	V	Dum Inning	cheens		, in the up
Magnet Mapping - Axes	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Not started
Magnet Mapping - Coil Geometries	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	In progress	Not started
Tracker Alignment – least squares	J. Nugent	Complete	Complete	In progress	Complete	Complete	Complete	In progress	Scattering Paper
Tracker Alignment – residuals	F. Drielsma	Complete	Complete	In progress	Complete	Complete	Complete	In progress	MICE Note
PID Detector Alignment	F. Drielsma	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Beamline Commissioning – u/s	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	MICE Note 476
Beamline Commissioning – d/s	P. Franchini	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Upstream detector resolution	V. Blackmore	Complete	Complete	Complete	Complete	Complete	Complete	In progress	Emittance Paper
-									
Downstream/global detector resolution	<b>1</b> M. Uchida	Complete	Complete	In progress	Complete	In progress	In progress	Not started	Not started
	M. Uchida/F.								
Detector efficiencies	Drielsma	Complete	In progress	In progress	In progress	In progress	In progress	Not started	Not started
	T. Mohayai/S.								
PID measurement – cut based	Wilbur	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
PID measurement – log likelihood	C. Pidcott	Complete	Complete	In progress	In progress	In progress	In progress	Not started	Not started
Magnet alignment – transfer matrix	S. Middleton	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Magnet alignment – minimise	C. Rogers/S.								
residuals	Middleton	Complete	In progress	In progress	In progress	In progress	In progress	In progress	Not started
Magnet alignment – cycloid fit	C. Rogers	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Beam quality	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
First emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Full emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Non-linear optics	R. Ryne	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
MCS - field off	J. Nugent	Complete	In progress	In progress	Complete	Not started	Not started	Not started	Not started
MCS - field on	C. Pidcott	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – measurement based	R. Gardner	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – minimise residuals	D. Maletic	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Beam polarisation	S. Middleton	Complete	Complete	In progress	Complete	Complete	Complete	In progress	In progress
				Step 1	[				
EMR	F. Drielsma	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete
Pion contamination	J. Nugent	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete



Measurement	Coordinator	Principle of Measurement	Laptop Studies	Batch MC & Analysis	Final Run Settings	Data Taking	First Analysis & Data Checks	Final Analysis	Write up
				Step I	v	0		ÿ	•
Magnet Mapping - Axes	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Not started
<b>Magnet Mapping - Coil Geometries</b>	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	In progress	Not started
Tracker Alignment – least squares	J. Nugent	Complete	Complete	In progress	Complete	Complete	Complete	In progress	Scattering Paper
Tracker Alignment – residuals	F. Drielsma	Complete	Complete	In progress	Complete	Complete	Complete	In progress	MICE Note
PID Detector Alignment	F. Drielsma	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Beamline Commissioning – u/s	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	MICE Note 476
Beamline Commissioning – d/s	P. Franchini	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Upstream detector resolution	V. Blackmore	Complete	Complete	Complete	Complete	Complete	Complete	In progress	Emittance Paper
Downstream/global detector resolution	n M. Uchida M. Uchida/E	Complete	Complete	In progress	Complete	In progress	In progress	Not started	Not started
Detector efficiencies	Drielsma T. Mohayai/S.	Complete	In progress	In progress	In progress	In progress	In progress	Not started	Not started
PID measurement – cut based	Wilbur	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
PID measurement – log likelihood	C. Pidcott	Complete	Complete	In progress	In progress	In progress	In progress	Not started	Not started
Magnet alignment – transfer matrix	S. Middleton	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Magnet alignment – minimise	C. Rogers/S.								
residuals	Middleton	Complete	In progress	In progress	In progress	In progress	In progress	In progress	Not started
Magnet alignment – cycloid fit	C. Rogers	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Beam quality	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
First emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Full emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Non-linear optics	R. Ryne	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
MCS - field off	J. Nugent	Complete	In progress	In progress	Complete	Not started	Not started	Not started	Not started
MCS - field on	C. Pidcott	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – measurement based	R. Gardner	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – minimise residuals	D. Maletic	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Beam polarisation	S. Middleton	Complete	Complete	In progress	Complete	Complete	Complete	In progress	In progress
				Step 1	[				
EMR	F. Drielsma	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete
Pion contamination	J. Nugent	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete



		<b>Drinciple of</b>	Lanton	Batch MC &	Final Dun		First Analysis		
Measurement	Coordinator	Measurement	Studies	Analysis	Settings	Data Taking	Checks	<b>Final Analysis</b>	Write up
				Step I	V	0		5	
Magnet Mapping - Axes	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Not started
<b>Magnet Mapping - Coil Geometries</b>	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	In progress	Not started
Tracker Alignment – least squares	J. Nugent	Complete	Complete	In progress	Complete	Complete	Complete	In progress	Scattering Paper
Tracker Alignment – residuals	F. Drielsma	Complete	Complete	In progress	Complete	Complete	Complete	In progress	MICE Note
PID Detector Alignment	F. Drielsma	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Beamline Commissioning – u/s	V. Blackmore	Complete	Complete	N/A	Complete	Complete	Complete	Complete	MICE Note 476
Beamline Commissioning – d/s	P. Franchini	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Upstream detector resolution	V. Blackmore	Complete	Complete	Complete	Complete	Complete	Complete	In progress	Emittance Paper
Downstream/global detector resolution	n M. Uchida	Complete	Complete	In progress	Complete	In progress	In progress	Not started	Not started
	M. Uchida/F.		_	_	_	_	_		
Detector efficiencies	Drielsma	Complete	In progress	Not started	Not started				
	T. Mohayai/S.	Commiliate	Commiliate	T	Complete	T	T	T	NT- 4 - 4 - 4 - J
PID measurement – cut based	wildur	Complete	Complete	in progress	Complete	In progress	in progress	In progress	Not started
PID measurement – log likelihood	C. Pidcott	Complete	Complete	In progress	In progress	In progress	In progress	Not started	Not started
Magnet alignment – transfer matrix	S. Middleton	Complete	Complete	In progress	Complete	In progress	In progress	In progress	MICE Note
Magnet alignment – minimise	C. Rogers/S.		<b>T</b> .	<b>T</b> .	NT I				
residuals	Middleton	Complete	In progress	In progress	Not started				
Magnet alignment – cycloid fit	C. Rogers	Complete	Complete	In progress	Complete	In progress	In progress	In progress	Not started
Beam quality	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
First emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Full emittance reduction	C. Rogers	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Non-linear optics	R. Ryne	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
MCS - field off	J. Nugent	Complete	In progress	In progress	Complete	Not started	Not started	Not started	Not started
MCS - field on	C. Pidcott	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – measurement based	R. Gardner	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Energy loss – minimise residuals	D. Maletic	Complete	In progress	In progress	In progress	Not started	Not started	Not started	Not started
Beam polarisation	S. Middleton	Complete	Complete	In progress	Complete	Complete	Complete	In progress	In progress
				Step 1	[				
EMR	F. Drielsma	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete
Pion contamination	J. Nugent	Complete	Complete	N/A	Complete	Complete	Complete	Complete	Paper Complete

### Diagnostics (from physics p.o.v.)



C. Rogers, ASTeC Intense Beams Group Rutherford Appleton Laboratory



#### **TOF Performance**



TOF0 SlabHit Efficiency





#### **TOF Performance**





#### TOF2 Spacepoint Efficiency



#### **Tracker Performance**





#### Tracker Performance



Also: Need to finish efficiency analysis



Ckov Avrg\_#\_of\_CkovB\_pes\_v.s.\_momentum\_PID=-13 Avrg\_#\_of\_CkovA\_pes\_v.s.\_momentum\_PID=-13 10E 9F ЗF 0<sup>E</sup> 

- Resolved issue with turn on point in CkovA and B
- Light yield has gone up in CkovA

### Cut based PID – (Run 7469)







- EMR mass cut
- Tracker mass cut
- Not clear that the two cuts are consistent
  - Can we be quantitative about this?
- Need to prove, conclusively, source of low mass "shouldes"

#### Track extrapolation/consistency





#### 17

#### Magnets and Physics Data Analysis



C. Rogers, ASTeC Intense Beams Group Rutherford Appleton Laboratory



# Field mapping analysis



3.247

E2

3.257



- Optimised coil positions
  - Now looking at adjusting coil aspect ratio



## Magnet alignment (Residuals)







- Developed algorithm to extrapolate tracks, and errors between detectors
- Fitting using Minuit implemented
  - But slow
- Fitting using Kalman fits in development
- Aim is to wiggle the magnets and attempt to improve combined fit

## **Pionic Beamline**





- Use of a pion beamline gives very good rate
- MC studies indicate very good purity from simple TOF cut
- Looks very promising
- Need to reoptimise beamline optics

## **TOF-based Energy Loss**





- Compare TOF01 to TOF12
- Infer an energy loss
- Need to determine details of analysis technique and unfolding algorithm

#### **Future Plans**



C. Rogers, ASTeC Intense Beams Group Rutherford Appleton Laboratory



#### Step IV Lattice – no M1D



variable	flip, 140	flip, 200	flip, 200 ( $x_4 \le 185$ )	flip, 240	sol, 140	sol, 200	sol, 240
$x_1$	0.83	0.72	0.72	0.80	0.80	0.77	0.89
$x_2$	142.56	168.13	233.49	251.62	132.76	249.89	222.69
$x_3$	125.55	261.81	262.59	150.98	205.79	276.14	146.06
$x_4$	180.83	221.55	184.91	126.80	65.21	86.61	64.09
$x_5$	-191.34	-233.37	-237.68	-244.00	223.01	208.29	161.48
$x_6$	-0.73	-0.74	-0.74	-0.70	0.73	0.74	0.70
$\Delta \epsilon / \epsilon_i$	-7.4%	-4.0%	-3.5%	-2.2%	-4.6%	-3.5%	-2.3%
T	92%	92%	93%	90%	91%	92%	90%

## Step IV Lattice – no M1D or M2D



variable	flip, 140 (low T)	flip, 140 (high T)	flip, 200 (low T)	flip, 200 (high T, low $x_4$ )	sol, 140 (low T, no high T)	sol, 200 (high T)	sol, 240 (high T)
$x_1$	0.71	0.77	0.89	0.70	0.65	0.76	0.65
$x_2$	80.00	169.49	153.19	125.73	172.39	236.83	158.43
$x_3$	158.14	208.96	251.15	133.93	242.20	135.21	132.32
$x_4$	172.05	118.23	224.99	88.85	56.15	55.98	64.11
$x_5$	0	0	0	0	0	0	0
$x_6$	-0.56	-0.53	-0.5	-0.51	0.57	0.54	0.57
$\Delta \epsilon / \epsilon_i$	12.8%	6.8%	6.3%	1%	8.2%	2.6%	2.7%
T	72%	80%	74%	85%	73%	82%	80%

#### Step IV Lattice – no M2D



variable	flip, 140 (low T)	flip, 140 (high T)	flip, 200 (low T)	flip, 200 (high T, low $x_4$ )	sol, 140 (low T, no high T)	sol, 200 (high T)	sol, 240 (high T)
$x_1$	0.71	0.77	0.89	0.70	0.65	0.76	0.65
$x_2$	80.00	169.49	153.19	125.73	172.39	236.83	158.43
$x_3$	158.14	208.96	251.15	133.93	242.20	135.21	132.32
$x_4$	172.05	118.23	224.99	88.85	56.15	55.98	64.11
$x_5$	0	0	0	0	0	0	0
$x_6$	-0.56	-0.53	-0.5	-0.51	0.57	0.54	0.57
$\Delta \epsilon / \epsilon_i$	12.8%	6.8%	6.3%	1%	8.2%	2.6%	2.7%
T	72%	80%	74%	85%	73%	82%	80%

#### Non-linear beam optics











#### Wedge Absorber

Z(cm)	P <sub>z</sub> MeV/c	<b>E</b> <sub>x</sub> (mm)	ε <sub>y</sub>	ε <sub>L</sub> (mm)	σ <sub>E</sub> MeV	6-D ε increase
0	200	3.04	2.99	2.90	1.82	1.0
6	193	1.44	3.02	6.82	3.86	1.13
12	182	0.76	3.00	14.27	8.63	1.23





# Demo Alignment and Tolerances



- Trying to get the sample selection right
- Philosophical questions about what constitutes an "error"

#### **Demo Descope Options**



- US funding for SSD repair is looking uncertain
- UK STFC has asked us to present options for descope (last week)
- I have a list but no assessment of feasibility

#### **Demo Descope Options**



- 1) Only use 1 RF power supply
- 2) Use existing SSD; probably install a tracker station upstream of M1 which we use as reconstruction plane
  - Consider acquiring backup magnet system in case of SSD failure (e.g. quad triplet)
- 3) Use plastic *secondary* absorbers
  - Not much cost saving
- 4) Stop at Step IV
- 5) Seek a lattice for SSU, FC, RF, SSD
- 6) Consider "quarter lattice" stop demo at FCD
  - Install tracker around FCD
  - Apertures?
  - Resolutions?

#### Analysis Workshop

- RAL, CR10 in Atlas building
- Thursday April 28<sup>th</sup>



# Coming up...



- In this session:
  - "Emittance paper" Victoria Blackmore
  - "(Xenon) scattering paper" John Nugent
  - "Demonstration of Ionisation Cooling Paper" JB Lagrange
  - "Detector alignment" F Drielsma
- Over to Victoria...