



Improvements of the ALICE HLT data transport framework for LHC Run 2



David Rohr
Frankfurt Institute for Advanced Studies
CHEP 2016, San Francisco
10.10.2016


SPONSORED BY THE





Highlights

- **The ALICE HLT framework was improved to cope with high rates expected in run 2.**
- **All trigger scenarios and maximum run 2 readout speed of detectors has been simulated with event replay and can be handled.**
- **CPU requirements of data transport framework reduced significantly to provide more compute power for reconstruction processing tasks.**





Summary

- **HLT framework throughput improved:**
 - Can cope with any data and event rate expected for run 2.
 - Can process TPC data at maximum link speed of 50 GB/s.
 - Event mergers with highest load of 12 links operate at up to 6 kHz.
 - Framework load reduced significantly, leaving more resources for reconstruction tasks.
- **HLT Startup time improved → never delays the start of run.**
- **Main improvement step:**
 - Improve inter-process communication via shared memory.
 - Redesign processing graph for better load-balancing.
 - Speed up python configuration scripts, use multi-processing in python.
- **New feature added:**
 - Feedback loop and asynchronous processes enable online calibration.
 - ZeroMQ transport added for calibration and for online QA.
 - Asynchronous processes protected against fatal errors like segmentation violations.