



Contribution ID: 120

Type: Poster

Ultra-sensitive and highly selective H₂ sensors based on FSP-made Rh-substituted SnO₂ sensing films

In this research, SnO₂ nanoparticles doped with 0.1-2 wt% rhodium (Rh) were synthesized by flame spray pyrolysis (FSP) and systematically investigated for H₂-sensing applications. From X-ray and electron microscopic characterizations, SnO₂ nanostructures exhibited spheroidal morphology with polycrystalline tetragonal SnO₂ phase and Rh might form solid solution with SnO₂ lattice. The sensing films were prepared by spin coating technique and their gas sensing performances were studied at the operating temperatures ranging from 100-350°C in dry air. Gas-sensing measurements showed that SnO₂ sensing films with the optimal Rh doping level of 0.2 wt% exhibited an ultra-high response of ~22,170, which was more than three orders of magnitude higher than that of undoped one, and a short response time of 6 s towards 30,000 ppm H₂ at an optimum operating temperature of 300°C. In addition, the optimal Rh-doped SnO₂ sensor displayed high H₂ selectivity against NO₂, SO₂, C₂H₄, C₃H₆O, CH₄, H₂S and CO. Thus, Rh-doped SnO₂ nanoparticulate films are promising candidates for hydrogen-sensing applications.

Primary author: Prof. LIEWHIRAN, Chaikarn (Department of Physics and Materials Science, Faculty of Science, Chiang Mai University, Chiang Mai 50202, Thailand)

Presenter: Prof. LIEWHIRAN, Chaikarn (Department of Physics and Materials Science, Faculty of Science, Chiang Mai University, Chiang Mai 50202, Thailand)

Track Classification: Nanomaterials & nanostructures