



Contribution ID: 118

Type: Oral

## Effect of F incorporation on physical, electrical and optical properties of hydrothermally grown ZnO nanorods

*Sunday 27 November 2016 16:05 (15 minutes)*

F-doped ZnO nanorod were synthesized via hydrothermal process with variation of processing temperature and Fluorine doping contents (0-10%) starting from zinc oxide thin film as a seeding layer for nanorod growth. The zinc oxide seeding thin film was prepared by sol-gel spin coating at 2000 rpm on glass substrate using zinc acetate precursor with annealing at 500 °C in air for 2 h. Ammonium fluoride (NH<sub>4</sub>F) was used as F doping precursor. The properties of F-doped ZnO nanorods were characterized by field emission electron microscope (FESEM), X-ray diffraction (XRD), energy-dispersive X-ray spectroscopy (EDX), Four-point probe technique and UV-Visible spectrophotometer. Corresponding results indicated that growth of ZnO:F nanorod with good crystallinity and grown in (002) plane. The influence of F dopant incorporated into ZnO nanorods has been extensively investigated and discussed.

**Primary author:** Mr SINORNATE, Wuttichai (College of Nanotechnology, King Mongkut's Institute of Technology Ladkrabang, Thailand)

**Presenter:** Mr SINORNATE, Wuttichai (College of Nanotechnology, King Mongkut's Institute of Technology Ladkrabang, Thailand)

**Session Classification:** Falcon 1

**Track Classification:** Nanomaterials & nanostructures