


CERN alignment sensors

checks, calibrations and infrastructure

Andreas HERTY

April 02, 2009



sensors

checks and
calibrations

problems

future

summary

sensors

sensors

checks and
calibrations

problems

future

summary

field of application at CERN

- LHC low-beta magnet monitoring and alignment system
- **CLIC** studies



sensors

checks and
calibrations

problems

future

summary

field of application at CERN

- Monitoring of the **ATLAS** feet (**Bedplates HLS**)
- Monitoring of **CMS YB0-HLS** with direct link to low-beta magnets
- vibration measurements **CNGS neutrino horn**



monitoring sensors in the LHC

- 112 hydrostatic levelling sensor (HLS)
- 64 wire position sensor (WPS)
- 24 distance offset measurement sensor (DOMS)



HLS




WPS



DOMS

characteristics

- FOGALE nanotech
- capacitive sensors
- no stand alone
- different generations
- integrated / remote electronics
- range of up to 10 mm
- resolution of 0.1 micron
- signal output 0 - 10 V
- power input 15 VDC



sensors

checks and
calibrations

problems

future

summary


sensor choice for the LHC

- all sensors already **used at CERN before** (LEP, CTF2, calibration laboratory, vibration measurements)
- sensors already tested for **long-term** and **radiation** in accelerator environment
- only tested **off-the-shelf** sensors available

nevertheless

- development of remote electronics for HLS
- cable lengths of up to 30 m

off-the-shelf with major modifications



sensors

checks and calibrations


problems

future

summary

checks and calibrations

Nuclear Base Installation



sensors

checks and
calibrations

problems

future

summary

CERN is declared a Nuclear Base Installation

- Installation Nucléaire de Base (INB)
- convention with French government (1984 & 2000)


all material exposed to radiation has to be traced

makes it difficult to ship material back to manufacturer

- for check and calibration
- for repair

**calibration methods, knowledge and
infrastructure have to be created at CERN**

checks and calibrations



sensors

checks and calibrations

problems

future

summary

checks: at reception

- validate manufacturer's parameters before installation in the LHC
- same checks as manufacturer carries out during calibration
- **warm-up, stability and linearity**

additional checks: investigate sensor performance

- **radiation**: total ionisation dose (TID), dose rate dependence (DRD)
- **magnetic field**: influence to the exposure to magnetic fields
- on-site check with **capacitive references**

calibrations

- additional parameters for the low-beta monitoring system
- **interchangeability** and **absolute reference**
- **geodetic interface calibration**

sensors

checks and calibrations


problems

future

summary


warm-up times given by manufacturer

- WPS and DOMS after 5 min
- HLS after 48 hrs → electrode heated



example: WPS warm-up test

warm-up effect shown for WPS on both axes (blue curve)
no warm-up after short power cut of 10 min (red curve)




all sensors need 3 hrs to be within ± 2 micron of final value

maximum warm-up effect observed ± 6 micron

- sensors
- checks and calibrations
- problems
- future
- summary

measurements show

- all sensors are within manufacturer's drift limits (≤ 3 micron / month)
- DOMS prototypes with problems, method changed manufacturer



sensors

checks and calibrations

problems

future

summary

stability bench allows

- measurements at fixed distances
- reference measurements with respect to calibrated distances
- offset and interchangeability determination



concept also used for

- warm-up measurements
- zero and gain point determination of the sensor

sensors

checks and
calibrations


problems

future

summary


FOGALE nanotech provides calibration functions to better than

- ± 0.4 micron for HLS (3rd order polynomial)
- ± 0.8 micron for DOMS (4th order polynomial)
- ± 3.0 micron for WPS (6 x 6 matrix for each axis)



linearity check bench designed to validate calibration within 10 micron

linearity





sensors

checks and calibrations

problems

future


summary



results

- non conform sensors detected
- manufacturer's linearity calibration validated
 - within 10 micron for HLS and DOMS
 - WPS linearity check bench with concept problem

radiation tests



sensors


checks and calibrations


problems

future

summary

for TID and DRD tests a ^{60}Co source is used





sensors


checks and calibrations

problems

future

summary

Total Ionisation Dose: sensor



tested HLS and WPS withstand 160 kGy

Total Ionisation Dose: electronics

electronics withstand 500 Gy

this means for the LHC

- electronics are placed in protected areas
- long cables between sensor and electronics needed
- electronics can recover from radiation damage

sensors


checks and calibrations

problems

future

summary


Dose Rate Dependence on HLS sensors



influence

- quantified by an experimental formula
- can be deduced from measurements
- investigation for WPS and DOMS pending

magnetic field



sensors


checks and calibrations

problems

future

summary

electronics supposed to withstand 0.03 T (FOGALE nanotech)



sensors


checks and calibrations

problems

future

summary


DOMS sensor in field of up to 0.54 T



no influence on sensor

- neither cable, nor electronics tested
- HLS and WPS have to be tested

checks and calibrations



sensors

checks and calibrations


problems

future


summary

interfaces and references

- additional parameters for the low-beta monitoring system
- interchangeability, external reference



checks and calibrations



sensors

checks and calibrations

problems

future

summary

absolute reference


- external, absolute reference provided to ± 50 micron
- not sufficient for LHC . . . and particularly not for CLIC studies

solution

- investigate calibration methods
 - aim: absolute calibration to better than ± 5 micron
 - HLS concept, validated on manual and automated bench (absolute and geodetic interface)
 - DOMS concept, validation on linearity calibration bench pending
 - WPS concept, bench ready, validation pending (Thomas Touzé)

coordinate-measuring machine available since 2008

capacitive references



sensors

checks and calibrations

problems

future

summary


mobile on-site testing device for stability of electronics

- capacitive references
- suitable for zero and gain measurements
- allows check of sensor's stability



follow-up of sensors without dismounting

- short interruption in data acquisition
- no complicated radiation protection checks of equipment



sensors

checks and
calibrations


problems

future

summary

problems

problems



sensors

checks and
calibrations

problems

future

summary


sensors

- mechanically broken cables (HLS/DOMS)
- electronics components broken (WPS)
- dust problem (WPS)
- stability drifts (DOMS)
- sensor frequency drifts (WPS)
- noise and electro-magnetic interference with other equipment

concept

- sensors associated with cable and electronics
- absolute calibration

broken cables



sensors

checks and
calibrations

problems

future

summary




problem

- fragile wires in the cable
- several layers of shielding for primary, capacitive sensor signal


solution

- cable can be fixed in our workshop
- calibration will be checked

electronics components broken




- sensors
- checks and calibrations
- problems
- future
- summary



problem identified

- always same components brake
- can not be reproceded
- source of the problem to be found

WPS frequency drifts



sensors

checks and
calibrations

problems

future

summary

WPS has a frequency modulated on the wire for each sensor


- frequencies range from 3 kHz to 8 kHz
- sensors adjusted to 100 Hz gap
- frequency gaps have to be more than 20 Hz
- same frequencies on the same wire create an oscillating signal of one or both sensors involved

observations

- frequencies drifted with up to 980 Hz
- range of the drifts 1480 Hz

solution

- adjustment of frequencies
- increasing of the gap



sensors

checks and
calibrations

problems

future

summary

future

sensors

checks and
calibrations


problems


future

summary

automated linearity calibration

- HLS: in operation since 11/2008
- DOMS: bench validation phase
- WPS: concept and installation





sensors

checks and
calibrations

problems

future

summary

radiation tests

- Single Event-Upset (SEU) tests for sensors and DAQ rack
- Total Ionisation Dose (TID) tests for DAQ rack

absolute calibration


- validated for DOMS on automated linearity bench
- concept and design for WPS (Thomas Touzé)

long-term

- sensor long-term stability in LHC with radiation
- in TT1 test facility
- test benches in the laboratory

compare

- started for HLS with Fermilab, since beginning 2009



sensors

checks and
calibrations


problems

future

summary

summary

sensor results: ATLAS



sensors


checks and
calibrations

problems


future

summary

installation of the calorimeter



sensor results: ATLAS



sensors


checks and calibrations

problems

future

summary

deformation monitored during calorimeter displacement



sensors


checks and calibrations

problems

future

summary


pressure change in cryostat causes magnet displacement



observations

- same displacement monitored by HLS and WPS
- coherent results of both sensor types

summary



sensors

checks and
calibrations

problems

future

summary

sensors passed the LHC validation tests


- linearity and stability
- total ionisation dose
- interchangeability and external references
- additional calibration parameters introduced
- on site test methods designed

further investigation in

- long-term behaviour in the LHC
- radiation influence with TID, test for SEU influence
- absolute calibration of the sensors
- magnetic field influences

important for CERN

- to be able to check / repair sensors due to INB
- to have check and calibration methods to be confident in measurements



CERN alignment sensors

checks, calibrations and infrastructure

Andreas HERTY

April 02, 2009