

Development of Distributed Tin processed Nb₃Sn wire for FCC

Tuesday 30 May 2017 19:16 (2 minutes)

Kobe Steel Ltd. have been doing research of Nb₃Sn wire since 1980s', and Japan Superconductor Technology, Inc. (JASTEC), one of her affiliated company manufacturing superconducting wire and magnet, has high production capacity of Bronze (Cu-Sn alloy) routed Nb₃Sn wire. JASTEC was one of the main supplier of Nb₃Sn strand for ITER (International Thermal Experimental Reactor) project, and supplied amount of more than 100 tons of bronze routed Nb₃Sn wire in total for ITER project from 2008 to 2016. Jc requirement for Nb₃Sn in FCC project is much higher than ITER project. In the case of bronze routed Nb₃Sn wire, Jc could be increased by the enhancement of tin concentration in Cu-Sn alloy. But higher tin concentration (more than 16% tin) makes it difficult for drawing process. So, as one of alternative method to increase tin concentration, KSL is developing Distributed Tin wire (DT wire). With this method we can improve Jc at 16 Tesla twice than the conventional our bronze routed Nb₃Sn. In addition, DT compared with other high tin concentration methods such as Internal Tin, it can be manufactured stably, so it is suitable for mass production. In this presentation, we will introduce our research for increasing Jc using DT wire.

Primary author: KAWASHIMA, Shinya (Kobelco)

Presenter: KAWASHIMA, Shinya (Kobelco)

Session Classification: Poster session