







## Sessions Summary

<https://indico.cern.ch/e/arw17>

## PARTICIPANTS' HOME COUNTRIES








- At LHC Integrated luminosity is a function of...

1. time colliding physics beams
2. turnaround between successive physics beams
3. time to clear faults
4. physics performance during colliding beams



$$\frac{t_{rt} - t_{infault}}{t_{rt}} = \text{availability } 66.7\%$$

Availability : time when machine is ready to accept and accelerate beam, versus run time  
Units: scalar [%]

Fault Duration =  
Integrated time logged for fault

Machine Downtime =  
Corrects for parallelism Discounts dependencies


Root Cause Duration =  
Corrects for dependencies parent / child / shadow

The tracking of the faults is done by a combine metric & the cardiogram


## Many different metrics

Machine mode metrics	Duration [h]
Fault / Downtime	470.2
Stable Beams	308.9
Operations	224.9
Pre-Cycle	28.0

- New methods like System-Theoretic Process Analysis focus on system interaction and show that there is some evolution in the basic methodologies and processes
- Accelerators are complex, but don't have tight regulatory or prescriptive standards for a large part of the equipment – provide forum for evaluation and testing of methods.
- Renovation / extension is an opportunity to do things better
- Replacing or extending like-for-like should just be a basic starting point for any such project. Basic renovation / extension requests are opportunities to try new concepts, do things in a new way, and do a better job.
- The new Rabbit Line Send Station was a nice example of this.



- For better return on investment, address availability as earlier stages.
- Availability issues which get addressed later on in the cycle are costing significantly more to solve.
- Early investment in availability is obvious when initially budgeting a project BUT “Design it to work well” appears to face common fiscal obstacles.



- 3 talks and discussion:
- Critical Failure Modes
- CRITICAL means a potential unavailability of cryogenics for LHC for weeks or months: breakdown of a critical equipment without alternative scenario.
- MEDIUM & HIGH means that failure is likely to happen with a potential unavailability of cryogenics for LHC for hours or days.

		<b>SEVERITY</b>			
	Catastrophic	<b>Critical</b>	<b>Critical</b>	<b>Critical</b>	<b>Critical</b>
	Major	Low	Medium	High	High
	Moderate	Low	Low	Medium	High
	Minor	Low	Low	Low	Low
		Remote	Uncommon	Occasional	Frequent
		<b>PROBABILITY</b>			



- When completing upgrades to infrastructure, ensure proper materials are used-Inspection, work plan and spec.
- Good intentions, not properly communicated, can lead to unintended consequences.

\$5



\$500000



Ylique towes are ti to scall


lanigno htemosolqer Ylique towes gnhU  
rthi dteacelqer was foj leetw gteelstz  
prase foj ni order to increase conductiv  
This foj was ionud broken insel the  
power supq rack:  
L' 137 magnen: ni ni magne: 137




## Before start of operations:

Test all electrical lead connections between magnets and power supplies at the Laboratory (459 superconducting and room temperature magnets)

- **Visual Inspection**  
(you can see a lot by just looking)
- **Measurement of resistance with milli-Ohm meter**
- **Thermal imaging with infrared imaging system**  
(operate magnet at high current and inspect temperatures of electric connections)




- J-PARC infrastructure and earthquake affects



*Water pump vibration measurement*

Water Leakage from RCS Sub tunnel ceiling



Damage to high voltage cable

Enhance monitoring system



Time series visualization of operation parameter (Flow, Pressure, Temperature, etc.)



Mechanical vibration monitoring



Vibration measurement of rotating equipment (Pump, Fan, Motor, etc.)



Vibration data : displacement, velocity, acceleration  
-> FFT analysis

Water quality monitoring




Water conductivity -> Ion detection in water  
Dust trapping by Filter  
-> Micro particle detection

- The session had 4 talks
- The first talk described the advantages of using solid state RF amps and the role SOLIEL has played and will play in the further developments.

**2 types of failures : - Transistor breakdown ( )**

**- Damaged soldering due to thermal fatigue ( )**




- The second talk, from KEK, presented some of the issues associated with beam commissioning with a focus on power supplies

Failures in Large class PS	# of event	comment
AC input over current	3	AC distortion (RF system crowbar work)
AC input over current	6	AC distortion (VAR system <sup>#</sup> work in line facility)
AC input Stop, CB Fault	2	Earthquake

- Third talk, from TRIUMF, presented the role of operators in improving cryogenics availability
- The last talk of the session presented a High Level Application (HLA) written for the automation of magnet power supplies optimization

- “First responders” during a situation
- On-site “hands” for expert help
- Alarm handler for warnings




- New switch mode power supplies
  - Replaced during 2012/2013 shutdown periods
  - \$733 000 CAD
- Results
  - Maintained functionality
  - Reduced down time
  - Increased stability
  - Reduced power consumption
  - Reduced heat load
  - Reduced replacement hazards



- CERN's machine protection team's success maintaining legacy code and developing new software tools was presented.
- There is high confidence for both the software developers and end users, using Continuous Delivery Workflow at CERN.
- >50% test result analysis is automated and >1M lines of code!

- Automation vs manual/human

- Consistent
- Repetitive
- Fast



Time comparison of Commissioning Test Analysis

### Automated Analysis Results $\pm$ PCC.1

- PCC.1 Automated Analysis Results 2012-2013

**2012-2013 HWC campaign**

- 398 PCC.1 tests on 350 60A-circuits
- 10 consistency fails
- 1 was "successful" but "tuning to be done"?
- 8 cases due to "just" failing decay criteria
- 1 anomaly accepted manually???
- 97.5% of consistency!

*Should have failed!  
Circuit: RCBV19.L5B1*

S. Rowan - MPE-TM - 27/02/2013

- LIPAc Control Systems and Reliability Improvements were discussed. We heard about the successes and some of the difficulties involved in the upgrade reliability analysis of the prototype accelerator with an eye on setting reliability figures.

Event report system,  
As part of **quality system**

identification, after analysis, of the problem

Corrective actions

Proposal for design improvements

Impact in "operation" time (downtime)

IFMIF

1 Event report: ER040 - Surge Protection damaged in RF module

Discoverer: M. Weber Date: 06/10/17

Sub assembly Components: RF Pw. Module #3 PWS Number (pws\_number): 04 10 02 01 03 Phase D.A. B

Surge Protection damage

Component(s): description

3 Description (Describe as precisely as possible the event (include pictures, schematic views))

4 Authorisation for actions

5 QST F4E PT

6 Maintenance request date Maintenance completion date - Expected Maintenance completion date - Executed Machine down time (h) Elapsed time to complete the operation (h)

7 Event closed on: --/--/17 VISA (DMS approval)

- We heard how a good alarm system is very useful in “The Use of PANIC Alarm System at ALBA” presentation.
- Alerts users of problems and abnormal machine conditions, even taking automatic actions in response to problems, and above all it needs to be easily configurable by the user.

PyAlarm Device Configuration (on claudius)

bo/pc/alarms



	Attribute Name	Attribute Value
1	AlarmThreshold	3
2	AlertOnRecovery	false
3	AutoReset	600
4	CreateNewContexts	False
5	Enabled	120
6	EvalTimeout	500
7	FlagFile	/tmp/alarm_ds.nagios
8	FromAddress	oncall
9	HtmlFolder	htmlreports
10	IgnoreExceptions	True
11	LogFile	/dev/null
12	LogLevel	INFO
13	MaxMessagesPerAlarm	0
14	PollingPeriod	5
15	Reminder	0
16	RethrowAttribute	False
17	RethrowState	True
18	SMSCConfig	cells:cells:cells
19	StartupDelay	60
20	UseProcess	False
21	UseSnap	True
22	UseTaurus	False

Refresh

Create New




- Diagnostic data should be used to improve performance.
  - Harmonic analysis of vibration dampening shows good promise to providing a path to improved performance.
  - We don't always need to reinvent the wheel. If someone has done it already, why not utilize that expertise.
  - What are the obstacles to wider collaboration?
- 
- New diagnostic tools provide mechanisms to track down simple, but hard to find, problems
  - 16 Channel o-scope tool was a good example of improved diagnostics analyzing system reliability.
  - Identified issues in RF system and led to resolving a terminal block issue causing intermittent trips.



- Formal investigation tools provide a formal mechanism to conduct investigations and get to the root of a real problem.
- TapRoot example was presented as a means to capture systemic, cultural & organizational causal factors.
- Despite training and policy, human factors and (mis)communication can often lead to unpredictable situations.

13 SnapChart®



- Many facilities face maintenance crossroads.
- Do you maintain the status quo or embark on infrastructure renewal – Repair or Replace?
- Issues: Part availability, in house design, manpower and lead time
- The problem: management expects to see immediate improvement in performance after their investment.
- When is a plan not a plan?
- Things quickly fall apart when subject to schedule changes of projects, users, and other external forces.
- When 40 planned accelerator changes/upgrades are reduced to 8 due to program schedule changes, performance and reliability are going to suffer.
- Sharing of operators with technical staff adds complexity.
- Frequent meetings and schedule updates are necessary to track shutdown progress and to keep everyone informed. Fortunately experiment requirements were temporarily reduced to accommodate compromised machine operation.
- You may not be able to complete necessary work, but everyone will be aware of it.

- Paul reinforced the need for detailed planning and communication. Prioritizing, planning, sequencing work, testing/commissioning while shutdown, construction, upgrades, and maintenance must all be integrated.
- Everybody thinks their system is 1st priority
  - Subsystems want their work completed regardless of the availability or impact on other systems. (Well known in systems engineering as the “Sub-optimization Principle”)
- Meetings, planning and good communication are all key elements along with a good job entry, approval, and tracking system.

- Methods for achieving the very high reliability necessary for use in space was discussed by Jean Fontignie – PA/QA manager at CEA/IRFU

CEA/IRFU

Complex organization, mixing different cultures

Space Agencies impose a common reference to all “contractors”

European Coordination for Space Standards (doc tree : bonus slide / [www.ecss.nl](http://www.ecss.nl))

Dependability , Electronic components procurement & Rad hardness

Material & Mechanical parts & processes procurement , Software

Rule : Each lab in charge of a “flight deliverable” identifies a “PA/QA manager” in charge of those matters + Quality Assurance

Space mission duration

- 100% ON - availability without maintenance
- > 100.000 hours

Compare to well known object

- A car : 150.000km @50km.h<sup>-1</sup>
- 3000 hr with maintenance


Gold rule for space instrumentation : Schmitt axiom (lesson learnt)

- part I : What is not identified as a requirement is not verified
- part II : What is not verified, don't expect it to work properly
- Part III : Early verification will lower failure consequence

- Gilles LE CALVEZ–ITE VEDECOM Vehicle Program Director gave a nice overview of the state of automated car development

## DIFFERENT LEVELS OF DRIVING DELEGATION

9



## Specificities of the Particle Therapy machines:

- Short breakdowns admissible, long breakdowns very perturbative
- continuous process, very short shutdowns allowed
- High level of safety required, documentation for conformity

## Hikaru SOUDA (Gunma - Japan)

### To prevent failure:

- Share troubles with other facilities
- Machine time for trouble shooting
- Evaluation of criticality - FMEA

## Benno KRÖCH (Marburg - Germany)

### -The constraints related to E.U. Medical Directive

-The different steps of an upgrade of the control system (risks analysis, ..., roll back, tests, QA ...)

-The different stakeholders: eng., companies, med physics, ...

## Samuel MEYRONEINC (Curie-France)

- The case of a contract of shared maintenance with the supplier
- The different issues of the contract
- The lessons learned: interfacing, technical- temporality, monitoring


- **At Jefferson Lab, the director set up a lab reliability task force to administer a lab based reliability program.**
- Their mandate was to provide a graded approach to corrective actions and to provide a comprehensive planning schedule.
- This was in response to commissioning problems during the 6-12 GeV upgrade.
  
- **Available considerations for an Accelerator System Based on the LHC Power Converter Controls was discussed.**
- Previous power converters were not reliable. Radiation resistant and high reliability converters were to be designed, built and tested prior to being deployed.
- Results of the initial deployment brought to light new problems which were corrected. These improvements were used to deploy the second batch and future converters.



- **RHIC continues to face issues with long term reliability.**
- Quench detect diodes protect magnets from discharge from other magnets during a quench.
- Damaged diodes have proved to cause problems during ramp up and do not provide adequate protection to magnets during a quench.
- Temporary techniques and mechanical switches have been implemented to allow the accelerator to run.
- **Age related failure is affecting the K1200 Cyclotron Electrode**
- While ramping up the RF on the cyclotron a number of atypical drop outs were encountered.
- Not sparks - but an internal problem with the upper half of one of the accelerating electrodes was found to be damaged.
- Innovative thinking provided a method of repairing this electrode and plans to machine replacement electrodes are being made.

## Experience with the KEK/SuperKEKB Magnet Cooling Water System

- KEKB/SuperKEKB is one typical example of aging facility where it has become a challenge to maintain stable operation with the cooling system of the ~1700 water-cooled magnet.
- To reduce the beam trips at KEKB, a thorough analysis was performed
  - Relocation of purge valves for easy access and remove air bubble in the circuit
  - Add new and finer strainer meshes to avoid clogging
  - Lack of freedom for easy tuning the distribution of the cooling water,
  - Add of Temperature sensor to have alarm precursors before reaching a beam drop



### Teachings

- Avoid running pumping station **with little margin**
- **Communication** with workers and contractors and always double check. **Continuous education is a must.**
  - Use of wrong type of seal
  - Grease contamination, etc.

## Effort for the Reliable Operation in J-PARC Rapid Cycling Synchrotron

- Thyratrons have very low lifetime and spread
  - Malfunctioning treated
  - Manual retuning
  - Monitor jitter and rise time of the waveform → determine precursor indicator to change the thyatron before failure

- Fixed target catastrophes
  - Redesign and **simplify** the “hot” part of the target
  - Prevent major incident by a **the interlock system** (preventing an extraction of an unexpected beam)
  - Add monitoring on many systems** including radiation monitors
- **Teachings**
  - Always prepare yourself for the the worse case scenario
  - Do not underestimate** the number of diagnostics an monitoring/alarms
  - Monitors signal from non accelerator equipment (Radiation safety, etc.).

## A Gradient Team to operate CEBAF at larger gradient

**Teachings:** “We couldn’t score what we didn’t understand so”

- News analysis tools can help a lot such as **Analytic Hierarchy Process**
  - Help setting the right weight on difference tasks
  - Promote discussion, use for convincing management
  - Identify actions with highest added values
- **Interdivision collaboration is the key**
  - Make bridges between groups, avoid work in silo
  - Investing and solving issues together
- **Prioritization**

## Operational metrics at PSI proton accelerator facility



We measure operational efficiency by monitoring the following Key Performance Indicators:

- Beam availability
- Current integrals at meson targets, SINQ, UCN, IP2
- Trip rate (number of trips)

Find “Happy-User-Index”!

A. Lüdeke (PSI)

## Some steps to achieve higher availability at the complex high-Intensity proton accelerator facility of PSI

- Enough time for the setup after the shutdown (at least 1 week)
- Longer beam time periods (4 weeks between maintenances)
- Continuous updating and modernizing the operational tools (GUI, panels, programs)
- Lessons learned: Dismount of the electrostatic elements at the beginning of the shutdown. Storage of the electrostatic elements in a vacuum and under the high voltage. After RF-conditioning switching on the electrostatic elements and then slowly ramp up

We heard about Modelling of the S3 RIB nuclear facility of Spiral2.

Their discussion included how the facility functions and the objectives of their radioactive studies.

Noted a common theme we all face – accelerator environments are very hostile for electronic components.

We heard about the Machine protection at ESS.  
They use protection functions, which integrate into several subsystems to provide a full scope of system protection.

## Machine Protection – System of Systems

- Many systems are owned by other groups and they hook to them. Integrated system management and communication remains a central theme.

# More work is needed on this button!

