



Contribution ID: 460

Type: Oral

HIGH CURRENT, HIGH VOLTAGE SOLID-STATE SWITCH PROGRESS AT AFRL

Monday 19 June 2017 11:30 (30 minutes)

A 50 kV solid-state switch has been developed using Thinpak™ Current Controlled SolidTRON® (CCS) thyristors from Silicon Power Corporation. A switch comprises thirty-six, series-connected thyristors and an internally powered, optically initiated trigger circuit. The trigger circuit drives the common primary winding of sixteen trigger transformer; each transformer has two output windings coupled to a pair of thyristor gates. This triggering arrangement provides simultaneous switching of all 36 thyristors. Because the only control signal is optical, these modules can be series-connected to switch higher voltages or floated to provide switching for Marx generators. Single switch modules have been operated at pulse widths from 300 ns up to 7 μ s and pulsed currents from 250 A up to 2500 A with risetimes < 50 ns. The switching delay is approximately 100 ns with a pulse to pulse jitter of < 1.5 ns. This performance is achievable down to applied voltages as low as 2 kV. Testing at higher current is ongoing with a performance objective of 10 kA in a 300 ns pulse. A number of applications of these solid-state switch modules will be presented.

Primary author: HEIDGER, Susan (U.S. Air Force Research Laboratory)

Co-authors: Mr KOSTORA, Mark (Leidos, Inc.); Mr LERMA, Al (Leidos, Inc.); Mr LOREE, Ellis (Loree Engineering); Dr PARKER, Jerald (Leidos, Inc.)

Presenter: HEIDGER, Susan (U.S. Air Force Research Laboratory)

Session Classification: Oral session 1 - High-Energy Density Storage, Opening and Closing Switches
- Session Chair : Jiande Zhang

Track Classification: Pulsed Power Physics and Technology, Components and HV Insulation