



Contribution ID: 447

Type: **Poster**

## Fast Magnetization of Amorphous Metallic Cores

*Wednesday 21 June 2017 13:30 (1h 30m)*

Due to their high saturation flux density, amorphous metallic alloys play a key role in linear induction accelerators that require ferromagnetic cores with sufficient volt-seconds to support multiple pulses. As both the shape of the material hysteresis curve and the core losses depend on the magnetization rate,  $dB/dt$ , measurements at various rates are necessary in any system model involving these alloys. We present the characterization of two candidate materials, Metglas 2605CO and HB1M, at magnetization rates ranging from 1-7 T/ $\mu$ s. We also compare our results to published data [1].

[1] Smith, C. H., and L. Barberi. "Fast Magnetization Reversals in Tape-Wound, Square-Loop Amorphous Alloy Cores." In Proceedings of the Soft Magnetic Materials Conference, p. 329. 1985.

**Primary authors:** Dr MCCRADY, Rod (Los Alamos National Laboratory); Dr ROSE, Chris (Los Alamos National Laboratory); Dr TACCETTI, Martin (Los Alamos National Laboratory)

**Presenter:** Dr TACCETTI, Martin (Los Alamos National Laboratory)

**Session Classification:** Poster session III - Particle Beam and Accelerator Technologies

**Track Classification:** Particle Beam and Accelerator Technologies