Connecting The Dots / Intelligent Trackers 2017



Report of Contributions

Connecting The $\cdots \ /$ Report of Contributions

Dummy submission by david

Contribution ID: 1

Type: not specified

Dummy submission by david

this is a dummy submission

Author: ROUSSEAU, David (LAL-Orsay, FR)

Presenter: ROUSSEAU, David (LAL-Orsay, FR)

Track vertex reconstruction with …

Contribution ID: 2

Type: not specified

Track vertex reconstruction with neural networks at the first level trigger of Belle II

Thursday 9 March 2017 10:15 (30 minutes)

The track trigger is one of the main components of the Belle II first level trigger, taking input from the central drift chamber. It consists of several steps, first combining hits to track segments, followed by a 2D track finding in the transverse plane and finally a 3D track reconstruction. The results of the track trigger are the track multiplicity, the momentum vector of each track and the longitudinal displacement of the vertex of each track ("z-vertex"). The latter allows to reject background tracks from outside of the interaction region and thus to suppress a large fraction of the machine background. The contribution focuses on the track finding step using Hough transforms and on the z-vertex reconstruction with neural networks. We describe the algorithms and show performance studies on simulated events.

Author: NEUHAUS, Sara

Co-authors: KIESLING, Christian (Max-Planck-Institut fuer Physik (Werner-Heisenberg-Institut) (D); SKAMBRAKS, Sebastian (Technische Universität München)

Presenter: NEUHAUS, Sara

Track Classification: 11 : Using tracks

Young Scientist Forum : Online T ····

Contribution ID: 3

Type: not specified

Young Scientist Forum : Online Track and Vertex Reconstruction on GPUs for the Mu3e Experiment

Wednesday 8 March 2017 12:30 (15 minutes)

The Mu3e experiment searches for the lepton flavour violating decay $\mu^+ \rightarrow e^+e^-e^+$, aiming at a branching ratio sensitivity better than 10^{-16} . To reach this sensitivity, muon rates above $10^9 \mu/s$ are required. A high precision silicon tracking detector combined with excellent timing resolution from scintillating fibers and tiles will measure the momenta, vertices and timing of the decay products of muons stopped in the target to suppress background. During the first phase of the experiment, a muon rate of $10^8 \mu/s$ will be available, resulting in a rate of \sim 10 GB/s of zero-suppressed data. The trigger-less readout system consists of optical links and switching FPGAs sending the complete detector data for a time slice to one node of the filter farm. Since we can only store ~ 100 MB/s of data, a full online reconstruction is necessary for an event selection. This is the ideal situation to make use of the highly parallel structure of graphics processing units (GPUs). An FPGA inside the filter farm PC therefore transfers the event data to the main memory of the PC and then to GPU memory via PCIe direct memory access. The GPU finds and fits tracks using a non-iterative 3D tracking algorithm for multiple scattering dominated resolution. For three hits from subsequent detector planes, a helix is fitted by assuming that multiple scattering at the middle hit is the only source of uncertainty. In a second step, a three track vertex selection is performed by calculating the vertex position from the intersections of the tracks in the plane perpendicular to the beam axis and weighting them by the uncertainties from multiple scattering and pixel pitch. Together with kinematic cuts this allows for a reduction of the output data rate to below 100 MB/s by removing combinatorial background. The talk will focus on the implementation of the track fit and vertex selection on the GPU and performance studies will be presented.

Author: VOM BRUCH, Dorothea (Mainz University)

Presenter: VOM BRUCH, Dorothea (Mainz University)

Track Classification: 9 : Real Time Pattern Recognition

Track reconstruction for the Mu3e ····

Contribution ID: 4

Type: not specified

Track reconstruction for the Mu3e experiment based on a novel Multiple Scattering fit

Wednesday 8 March 2017 10:30 (30 minutes)

The Mu3e experiment is designed to search for the lepton flavour violating decay $\mu^+ \rightarrow e^+e^-e^+$. The aim of the experiment is to reach a branching ratio sensitivity of 10^{-16} . At first phase the experiment will be performed at existing beam line providing 10^8 muons per second at the Paul-Scherrer Institute (Switzerland) which will allow to reach sensitivity of 10^{-15} . The muons with a momentum of about 28 MeV/c are stopped and decay at rest on a target. The decay products (positrons and electrons) with energies below 53 MeV are measured by a tracking detector consisting of two double layers of 50 μ m thin silicon pixel sensors. The high granularity of pixel detector with a pixel size of $80 \times 80 \ \mu$ m

allows for a precise track reconstruction in the high occupancy environment of the Mu3e experiment reaching 100 tracks per reconstruction frame of 50 ns in the final phase of experiment.

The Mu3e track reconstruction uses a novel fit algorithm that in the simplest case takes into account only the multiple scattering, which allows fast online tracking on a GPU based filter farm.

The implementation of the 3-dimensional multiple scattering fit based on hit triplets is described.

The extension of the fit that takes into account energy losses and pixel size is used for offline track reconstruction.

The algorithm and performance of the offline track reconstruction based on a full Geant4 simulation of the Mu3e detector are presented.

Author: Dr KOZLINSKIY, Alexandr (Kernphysik Institut, JGU Mainz)

Co-authors: SCHOENING, Andre (Ruprecht-Karls-Universitaet Heidelberg (DE)); KIEHN, Moritz (Universite de Geneve (CH)); BERGER, Niklaus (Institute for High Energy Physics, Beijing)

Presenter: Dr KOZLINSKIY, Alexandr (Kernphysik Institut, JGU Mainz)

Track Classification: 0: Algorithms and theoretical analysis

Type: not specified

Combination of various data analysis techniques for efficient track reconstruction in very high multiplicity events

Wednesday 8 March 2017 15:30 (30 minutes)

Present data taking conditions and further upgrades of high energy particle colliders, as well as detector systems, call for new ideas. A novel combination of established data analysis techniques for charged-particle reconstruction is

proposed. It uses all information available in a collision event while keeping competing choices open as long as possible.

Suitable track candidates are selected by transforming measured hits to a binned, three- or four-dimensional, track parameter space. It is accomplished by the use of templates taking advantage of the translational and rotational symmetries of the detectors. Track candidates and their corresponding hits usually form a highly connected network, a bipartite graph, where we allow for multiple hit to track assignments. In order to get a manageable problem, the graph is cut into very many subgraphs by removing a few of its vulnerable components, edges and nodes (*k*-connectivity). Finally the hits of a subgraph are distributed among the track candidates by exploring a deterministic single-player game tree. A depth-limited search is performed with a sliding horizon maximizing the number of hits on tracks, and minimizing the sum of track-fit χ^2 .

Simplified but realistic models of LHC silicon trackers including the relevant physics processes are used to test and study the performance (efficiency, purity, timing, paralellisation) of the proposed method in the case of numerous simultaneous proton-proton collisions (high pileup), and for single ion-ion collisions at the highest available energies.

Author: SIKLÉR, Ferenc (Wigner RCP, Budapest (HU))

Presenter: SIKLÉR, Ferenc (Wigner RCP, Budapest (HU))

Track Classification: 1: Parallel and discrete pattern recognition

Type: not specified

Young Scientist Forum : Bivariate normal distribution for finding inliers in Hough space for a Time Projection Chamber

Wednesday 8 March 2017 16:00 (15 minutes)

A Time Projection Chamber (TPC) is foreseen as the main tracking detector for the International Large Detector (ILD) one of the two detectors for the next candidate collider named International Linear Collider (ILC).

GridPix, which is a combination of micro-pattern gaseous detector with a pixelised readout system, is one of the candidate readout systems for the TPC [1]. One of the challenges in the track reconstruction is the large numbers of individual hits along the track (around 100 per cm). Due to the small pixel size of 55 x 55 μm^2 , the hits are not consecutive. This leads to the challenge of assigning the individual hits to the correct track. Hits within a given distance from a reconstructed track are called inliers. Consequently, finding inliers within the many hits and noise is difficult for pattern recognition and this difficulty is increased by diffusion effects in the TPC.

One of the current algorithms which is utilized for track finding is the Hough transform. Using *bivariate normal distribution* based on the covariance matrix calculated from the diffusion defects improves collecting inliers in the Hough space directly [2].

References

[1] Michael Lupberger.*The Pixel-TPC:A feasibility study*.PhD thesis in PhysikBonn University, Germany, Bonn, August, 2015.

[2] Leandro A.F.Fernandes, Manuel M .Oliveira.

Real -time line detection through an improved Hough transform voting scheme.Universidade Federal do Rio Grande do Sul-UFRGS, Instituto de Informática-PPGC, CP 15064 CEP 91501-970 Porto Alegre, RS, Brazil, Germany, Received 2 September 2006; received in revised form 6 March 2007; accepted 13 April 2007.

Author: Mr NOORI SHIRAZI, Amir (Siegen University)

Co-author: FLECK, Ivor (Universitaet Siegen (DE))

Presenter: Mr NOORI SHIRAZI, Amir (Siegen University)

Track Classification: 0: Algorithms and theoretical analysis

New Track Seeding Techniques at ···

Contribution ID: 7

Type: not specified

New Track Seeding Techniques at the CMS Experiment

Wednesday 8 March 2017 14:30 (30 minutes)

Starting from 2019 the Large Hadron Collider will undergo upgrades in order to increase its luminosity.

Many of the algorithms executed during track reconstruction scale linearly with the pileup. Others, like seeding, due to the increasing combinatorics, will dominate the execution time, due to their factorial complexity with respect to the pileup.

We will show the results of the effort in reducing the effect of pile-up in CMS Tracking by

- · exploiting new information coming from an upgraded tracker detector: Vector Hits
- redesigning the seeding with novel algorithms which are intrinsically parallel
- executing these new algorithms on massively parallel architectures.

Authors: BRONDOLIN, Erica (Austrian Academy of Sciences (AT)); Mr PANTALEO, Felice (CERN - Universität Hamburg)

Co-authors: ROVERE, Marco (CERN); INNOCENTE, Vincenzo (CERN)

Presenter: Mr PANTALEO, Felice (CERN - Universität Hamburg)

Type: not specified

Young Scientist Forum : Comparison of pattern recognition methods for the SHiP Spectrometer Tracker

Wednesday 8 March 2017 12:45 (15 minutes)

SHiP is a new general purpose fixed target facility proposed at the CERN SPS accelerator to search for particles predicted by Hidden Portals. The SHiP detector consists of a spectrometer located downstream of a large decay volume. It contains a tracker whose purpose is to reconstruct charged particles from the decay of neutral New Physics objects with high efficiency, while rejecting background events. In this talk we will demonstrate how different track pattern recognition methods can be applied to the SHiP detector geometry. We will compare their reconstruction efficiency, ghost rate and accuracy of the track momentum reconstruction. Limitations of the methods based on the 2D projection of a track will be discussed and the approach of the pattern recognition directly in 3D will be presented. It will be shown how a track reconstruction efficiency above 99% can be achieved.

Authors: HUSHCHYN, Mikhail (Yandex School of Data Analysis (RU)); ALENKIN, Oleg (Yandex School of Data Analysis (RU))

Co-authors: USTYUZHANIN, Andrey (Yandex School of Data Analysis (RU)); VAN HERWIJNEN, Eric (CERN)

Presenter: HUSHCHYN, Mikhail (Yandex School of Data Analysis (RU))

Type: not specified

Wireless data transmission for high energy physics applications

Monday 6 March 2017 16:45 (30 minutes)

Over the last years, wireless data transmission technologies have seen tremendous progress to cope with the ever increasing demand on bandwidth, for instance in the mobile sector. Developments on short distance communication are pushing towards frequencies in the mm-band which allow the use of an even higher bandwidth and smaller form factors.

In high energy physics the demand on bandwidth is increasing rapidly with the development of more and more granular detectors. Especially tracking detectors require readout systems with thousands of links that can transfer several Gbit/s each. At the same time, stringent space, material and power constraints are set on these readout systems.

The WADAPT project (Wireless Allowing Data and Power Transmission) has been started to study the feasibility of wireless data and power transmission for future tracking detectors. The current focus is set on communication in the 60 GHz band, which offers a high bandwidth, a small form factor and an already mature technology. Tracking detectors can benefit a lot from wireless data transmission. For instance, the material budget of tracking detectors can potentially be minimized and installation can be simplified as the amount of cables and connectors can be reduced. Data transmission topologies that are impossible with wired data links can be realized using wireless communication, allowing for even faster on-detector data processing.

This talk presents current developments of 60 GHz transceiver chips for HEP applications. Studies of antennas and data transmission will be shown. Studies on crosstalk between wireless links in a reflecting environment have been conducted. Silicon strip and pixel sensors have been operated while being exposed to a 60 GHz data transmission and results of these studies will be presented.

Author: DITTMEIER, Sebastian (Ruprecht-Karls-Universitaet Heidelberg (DE))

Co-authors: SCHOENING, Andre (Ruprecht-Karls-Universitaet Heidelberg (DE)); ROHRICH, Dieter (Department of Physics & amp; Technology-University of Bergen); WIEDNER, Dirk (Ruprecht-Karls-Universitaet Heidelberg (DE)); KIM, Do-Won (Gangneung-Wonju National University (KR)); Dr DANCILA, Dragos (Uppsala University); LOCCI, Elizabeth (CEA/IRFU,Centre d'etude de Saclay Gif-sur-Yvette (FR)); DRAKE, Gary (Argonne National Laboratory (US)); SOLTVEIT, Hans Kristian (Ruprecht-Karls-Universitaet Heidelberg (DE)); ULLALAND, Kjetil (University of Bergen (NO)); BRENNER, Richard (Uppsala University (SE)); YANG, Shiming (University of Bergen (NO)); DJURCIC, Zelimir (Argonne National Laboratory); DEHOS, cedric (CEA)

Presenter: DITTMEIER, Sebastian (Ruprecht-Karls-Universitaet Heidelberg (DE))

Track Classification: 8 : High speed communication

Type: not specified

Young Scientist Forum : Online Track Reconstruction and Data Reduction for the Belle II Experiment using DATCON

Tuesday 7 March 2017 12:15 (15 minutes)

The new Belle II experiment at the asymmetric e^+e^- accelerator SuperKEKB at KEK in Japan is designed to deliver a highest instantaneous luminosity of 8×10^{35} cm⁻²s⁻¹. To perform highprecision track reconstruction, e.g. for measurements of time dependent CPV decays and secondary vertices, the Belle II detector is equipped with a DEPFET pixel detector (PXD) of high granularity, containing 8 million pixels in total. The high instantaneous luminosity and short bunch crossing times produce a large stream of online data in the PXD, which needs to be reduced significantly for offline storage. This is done using an FPGA-based Data Acquisition Tracking and Concentrator Online Node (DATCON), which uses information from the Belle II strip vertex detector (SVD) surrounding the PXD to carry out online track reconstruction, extrapolation back to the PXD, and to define Regions of Interest (ROI) on the PXD. This reduces the data stream approximately by a factor of ten with an ROI finding efficiency of >90% of PXD physics hits inside the ROI.

In this talk, I will present the current status of the FPGA-based implementation of the track reconstruction using the Hough transformation and the offline simulation.

Author: WESSEL, Christian (University of Bonn)

Co-authors: DESCHAMPS, Bruno (University of Bonn); MARINAS, Carlos (University of Bonn); BERN-LOCHNER, Florian Urs (University of Bonn (DE)); DINGFELDER, Jochen Christian (University of Bonn (DE))

Presenter: WESSEL, Christian (University of Bonn)

Track Classification: 9 : Real Time Pattern Recognition

Young Scientist Forum : Fast and …

Contribution ID: 12

Type: not specified

Young Scientist Forum : Fast and reliable Tracking for the High-Level-Trigger at Belle II

Tuesday 7 March 2017 12:00 (15 minutes)

The Belle II detector is currently being built in Tsukuba, Japan and will record e^+e^- collision events at a record-breaking instantaneous luminosity of $8 \cdot 10^{35}$ cm⁻²s⁻¹ which is delivered by the SuperKEKB collider. Such a large luminosity is required to significantly improve the precision on measurements of B, D and τ decays to probe for signs of physics beyond the standard model.

Luminosity- and beam-size dependent background processes make up a large part of the measured events and an early software-based trigger, which combines the measurements of the individual sub-detectors, is required to filter the data and only store events which are of interest to physics analyses.

Tracking, especially in the central drift chamber (CDC), plays a major role here, as it can provide variables needed for a correct event classification in a fast and reliable way. This talk will present the planned High-Level-Trigger scheme for Belle II and especially the chosen tracking concepts to reach the required speed and reliability as well as some results on the runtime and the efficiency of the algorithm.

Authors: BRAUN, Nils (KIT - Karlsruher Institute of Technology (DE)); HAUTH, Thomas (KIT - Karlsruhe Institute of Technology (DE))

Presenter: BRAUN, Nils (KIT - Karlsruher Institute of Technology (DE))

Track Classification: 9 : Real Time Pattern Recognition

Young Scientist Forum : Function ····

Contribution ID: 13

Type: not specified

Young Scientist Forum : Functional nonparametric regression for track reconstruction

Monday 6 March 2017 18:15 (15 minutes)

This paper describes the reconstruction of trajectories form charged particles (tracks) inside a generic tracker considering tracks as functional data and including particle properties. First the clusters are broadly grouped in regions of phase space to break down the pattern recognition problem into groups of tracks which point into similar directions. Curves are then interpolated from discrete cluster measurements, and each curve is expressed as a function of the particle trajectory within the detector, its cluster shape and charge. Functional data analysis modeling, in particular Functional Principal Components Analysis, is then applied with a functional predictor (representing the particle features) and functional responses (the tracks). Finally, two types of regressions are performed on the functional responses, using linear models and more complex Support Vector Regression for the track reconstruction. The reconstruction is tested in high pileup environment as predicted for the HL-LHC and FCC-hh scenarios.

Author: AMROUCHE, Cherifa Sabrina (Universite de Geneve (CH))

Co-authors: SALZBURGER, Andreas (CERN); Prof. PILZ, Jürgen (alpen adria university klagenfurt); GOLLING, Tobias (Universite de Geneve (CH))

Presenter: AMROUCHE, Cherifa Sabrina (Universite de Geneve (CH))

Track Classification: 2 : Machine learning approaches

Type: not specified

Young Scientist Forum : Weakly supervised classifiers in High Energy Physics

Thursday 9 March 2017 10:45 (15 minutes)

As machine learning algorithms become increasingly sophisticated to exploit subtle features of the data, they often become more dependent on simulations. This paper presents a new approach to classification called weak supervision in which class proportions are the only input into the machine learning algorithm. A simple and general regularization technique is used to solve this non-convex problem. Using one of the most important binary classification tasks in high energy physics - quark versus gluon tagging - we show that weak supervision can match the performance of fully supervised algorithms. Furthermore, by design, the new algorithm is insensitive to any mismodeling of discriminating features in the data by the simulation. Weak supervision is a general procedure that could be applied to a variety of learning problems and as such could add robustness to a wide range of learning problems.

Authors: SCHWARTZMAN, Ariel Gustavo (SLAC National Accelerator Laboratory (US)); NACH-MAN, Ben (Lawrence Berkeley National Lab. (US)); RUBBO, Francesco (SLAC National Accelerator Laboratory (US)); DERY, Lucio (Stanford University)

Presenter: RUBBO, Francesco (SLAC National Accelerator Laboratory (US))

Track Classification: 11 : Using tracks

Type: not specified

Fast and precise parametrization for extrapolation through a magnetic field

Wednesday 8 March 2017 15:00 (30 minutes)

Extrapolation of trajectories through a magnetic field is needed at various stages of pattern recognition or track fitting procedures, with more or less precision. The Runge-Kutta method implies many calls to a field function and it is generally time consuming. In practice the trajectories may be split in steps between a few predefined surfaces, with possible additional short segments to match the actual measurements. On the other hand, in a collider, the particles used for physics analysis have a small impact parameter with respect to the origin; so, when crossing a given surface, they cover a small part of the phase space describing the local state. As a result, the extrapolation to another surface may be expanded as a polynomial function of the initial parameters within convenient ranges; these ranges and the degrees of the expansion may be tuned to find the best compromise between the precision and the fraction of particles within the domain of validity. An example of precomputed tables of coefficients is given for a long range extrapolation in a detector covering the forward region of a collider, inspired by the LHCb configuration.

Author:BILLOIR, Pierre (Laboratoire de Physique Nucléaire et Hautes Energies (LPNHE))Presenter:BILLOIR, Pierre (Laboratoire de Physique Nucléaire et Hautes Energies (LPNHE))

Track Classification: 10 : Fitting tracks

Type: not specified

Tracking with the ultra fast pixelised Tipsy single photon detector

Monday 6 March 2017 15:45 (30 minutes)

Tipsy is an assembly of a pixel chip and a stack of transmission dynodes "tynodes", placed in the vacuum under a classical window+photocathode. A tynode is an array of thin membranes: an electron impinging the upper surface causes the emission of (now) 5.5 secondary electrons at the bottom side. A stack of 5 tynodes causes a cloud of $5.5^{**}5 = 5$ k electrons to enter the pixel input pad, sufficient to activate the pixel circuitry.

Due to the small geometry of the stack and the uniform straight electron paths between the tynodes, the time jitter of electrons entering the pixel is less than a ps.

A tynode with a transmission secondary electron yield of 5.5 has been realised. A prototype Tipsy is now under construction in the form of a modified Planacon (Photonis).

New concepts for TimePix chips are being proposed, with a TDC-per-pixel with time resolution better than 10 ps.

Future low-cost, mass produced Tipsy's may have the following specifications:

- Thin (4 mm), planar, light, square geometry
- 10 ps time resolution and 10 um 2D spatial resolution per single soft photon
- · amplification stack free of dark noise
- absence of ion feedback
- · operates in strong B-fields
- · hit-pixel data rates up to 5 Gb/s

Tipsy could be well-applied in PET scanners. Instead of a scintillator, a lead glass or saffire cube could be read-out at all six sides, recording (prompt) Cherenkov photons originating from the 511 keV gamma interaction point. By means of GPS algorithms, this point can be reconstructed in 4D with high precision.

The tracking of MIPs could be done by replacing the photo cathode by an 'e-brane': a foil having a high probability to emit at least one electron at the surface crossing point of the track of the MIP. Another method would be to create Cherenkov photons in thin transparent (mylar) foils. A future inner tracker of a collider experiment would then take the form of a vacuum tank around the interaction point in which foils are stretched in a cylinder geometry, at several radii. The detectors of Cherenkov photons could be placed at the inner side of the vacuum cylinder wall, meters away from the interaction point.

Author: VAN DER GRAAF, Harry (Nikhef National institute for subatomic physics (NL))

Presenter: VAN DER GRAAF, Harry (Nikhef National institute for subatomic physics (NL))

Track Classification: 4 : Intelligent tracking detectors

Type: not specified

L1 Tracking at CMS For the HL-LHC using the Tracklet approach

Tuesday 7 March 2017 10:30 (30 minutes)

The High Luminosity LHC (HL-LHC) is expected to deliver luminosities of 5×1034 cm2/s, with an average of about 140 overlapping proton-proton collisions per bunch crossing. These extreme pileup conditions place stringent requirements on the trigger system to be able to cope with the resulting event rates. A key component of the CMS upgrade for HL-LHC is a track trigger system which would identify tracks with transverse momentum above 2 GeV already at the first-level trigger. This talk presents a proposal for implementing the L1 tracking using tracklets for seeding.

Results from a recently completed demonstrator project will be presented, which shows good performance and ability to reconstruct tracks within $4\mu s$ of the collision, and projections for ultimate system performance.

Authors: RYD, Anders (Cornell University (US)); LEFELD, Anthony (Ohio State University (US)); WINER, Brian Lee (Ohio State University (US)); STROHMAN, Charles Ralph (Cornell University (US)); BARTZ, Edward Hugo (Rutgers, State Univ. of New Jersey (US)); HALKIADAKIS, Eva (Rutgers, State Univ. of New Jersey (US)); CHAVES, Jorge (Cornell University (US)); LANNON, Kevin Patrick (University of Notre Dame (US)); SKINNARI, Louise (Cornell University (US)); ZIENTEK, Margaret (Cornell University (US)); HILDRETH, Mike (University of Notre Dame (US)); WITTICH, Peter (Cornell University (US)); KYRIACOU, Savvas (Rutgers, State Univ. of New Jersey (US)); GERSHTEIN, Yuri (Rutgers, State Univ. of New Jersey (US)); TAO, Zhengcheng (Cornell University (US))

Presenter: ZIENTEK, Margaret (Cornell University (US))

Track Classification: 9 : Real Time Pattern Recognition

Type: not specified

Parameterization-based tracking for the P2 experiment.

Wednesday 8 March 2017 11:30 (30 minutes)

The P2 experiment in Mainz (Germany) aims to determine the weak mixing angle at low momentum transfer with an unprecedented precision. The approach of P2 is to measure the parity-violating asymmetry of elastic electron-proton scattering, from which the weak charge of the proton, and so the weak mixing angle can be evaluated.

In P2, an electron beam (150 μ A, 155 MeV/c²) of alternating polarization will be scattered on a 60 cm long liquid H₂ target, and the total current of the elastically scattered electrons will be measured with a fused silica Cherenkov detector. A tracking system is necessary to measure the momentum transfer distribution of the elastically scattered electrons, to validate the simulated acceptance of the Cherenkov detector, and to get a control over other systematic uncertainties. Although the tracking system is not required to work at the full beam rate, every attempt is made to achieve the highest possible rate capability.

The tracking system will consist of 4 layers of high-voltage monolithic active pixel sensors (HV-MAPS), with 80 x 80 μ m² pixel size, time resolution about 10 ns, and rate capability about 30 MHz/cm² (DAQ-limited).

At the full beam rate every reconstruction frame (45 ns long) will contain around 800 signal tracks, and 16 000 background hits from Bremsstrahlung photons. In order to cope with the extreme combinatorial background on-line, a parameterization-based tracking is developed.

Performance evaluations on simulated data show that the parameterization-based tracking requires to fit not more than 2 track candidates per one signal track at the full beam rate (whereas a simple implementation of track following requires to fit more than 100 candidates per signal track already at 2% of the full beam intensity). Moreover, the parameterization-based approach enables to replace the computation-heavy rigorous fit in the inhomogeneous field by an evaluation of a 3-rd order polynomial in a 3-dimensional space, with a negligible loss in accuracy.

The implementation, as well as the performance evaluations of the parameterization-based tracking will be presented.

Author: Dr SOROKIN, Iurii (PRISMA Cluster of Excellence and Institute of Nuclear Physics, Johannes Gutenberg University, Mainz, Germany)

Presenter: Dr SOROKIN, Iurii (PRISMA Cluster of Excellence and Institute of Nuclear Physics, Johannes Gutenberg University, Mainz, Germany)

Type: not specified

An FPGA based track finder at Level 1 for CMS at the High Luminosity LHC

Tuesday 7 March 2017 09:30 (30 minutes)

"A new tracking detector is under development for the Compact Muon Solenoid (CMS) experiment at the High-Luminosity LHC (HL-LHC). It includes an outer tracker that will construct stubs, built from clusters reconstructed in two closely-spaced layers, for the rejection of hits from low transverse momentum tracks and transmit them off-detector at 40MHz. If tracker data is to contribute to keeping the Level-1 trigger rate at around 750 kHz under increased luminosity, a crucial component of the upgrade will be the ability to identify tracks with transverse momentum above 3 GeV/c by building tracks out of stubs. A concept for an FPGA-based track finder using a fully time-multiplexed architecture is presented, where track candidates are identified using a projective binning algorithm based on the Hough Transform. A complete hardware demonstrator based on the MP7 processing board has been assembled to prove the entire system from the input to the tracker readout boards to producing tracks with fitted helix parameters. This has been achieved within the latency constraints with existing technology in 1/8th of the tracker solid angle at up to 200 proton-proton interactions per event. The track reconstruction system demonstrated, the architecture chosen, the achievements to date and future options for such a system will be discussed."

Author: MORTON, Alexander (Brunel University (GB))

Co-authors: TAPPER, Alex (Imperial College (GB)); ROSE, Andrew William (Imperial College (GB)); SHTIPLIYSKI, Antoni (Imperial College (GB)); AMSTUTZ, Christian (KIT - Karlsruhe Institute of Technology (DE)); SHEPHERD-THEMISTOCLEOUS, Claire (STFC - Rutherford Appleton Lab. (GB)); Prof. NEWBOLD, Dave (University of Bristol (GB) / Rutherford Appleton Laboratory (GB)); CIERI, Davide (STFC - Rutherford Appleton Lab. (GB)); CLEMENT, Emyr (University of Bristol (GB)); BALL, Fionn Amhairghen (University of Bristol (GB)); HALL, Geoff (Imperial College (GB)); ILES, Gregory Michiel (Imperial College (GB)); TOMALIN, Ian (STFC - Rutherford Appleton Lab. (GB)); Dr REID, Ivan (Brunel University London (GB)); BROOKE, Jim (University of Bristol (GB)); UCHIDA, Kirika (Imperial College (GB)); MANOLOPOULOS, Konstantinos (STFC - Rutherford Appleton Lab. (GB)); HARDER, Kristian (STFC - Rutherford Appleton Lab. (GB)); CALLIGARIS, Luigi (STFC - Rutherford Appleton Lab. (GB)); WEBER, Marc (KIT - Karlsruhe Institute of Technology (DE)); PESARESI, Mark (Imperial College (GB)); BALZER, Matthias Norbert (KIT - Karlsruhe Institute of Technology (DE)); SANDER, Oliver (KIT - Karlsruhe Institute of Technology (DE)); VICHOUDIS, Paschalis (CERN); HOBSON, Peter (Brunel University (GB)); SUMMERS, Sioni Paris (Imperial College (GB)); PARAMESVARAN, Sudarshan (University of Bristol (GB)); MATSUSHITA, Takashi (Austrian Academy of Sciences (AT)); HARBAUM, Tanja Renate (KIT - Karlsruhe Institute of Technology (DE)); JAMES, Thomas Owen (Imperial College (GB)); SCHUH, Thomas (KIT - Karlsruhe Institute of Technology (DE))

Presenter: MORTON, Alexander (Brunel University (GB))

Track Classification: 9 : Real Time Pattern Recognition

Type: not specified

Young Scientist Forum : High precision timing with HVCMOS MAPS Censors

Monday 6 March 2017 17:45 (15 minutes)

There is an increasing demand for precision time measurement in particle physics experiments, to reject pile-up as efficiently as possible. This translates into projects of precision timing tracker/preshower detectors at LHC experiments, in the frame of high luminosity upgrades (Phase 2 HL-LHC). There is little doubt that these techniques, if they can be used successfully at HL-LHC, will enter the arsenal of standard instrumentation for high occupancy environments like the one expected at FCC-hh.

Operating the LHC with more than 200 collisions per crossing of protons bunches, as it is foreseen from 2025 onward (HL-LHC phase), will greatly complicate the analysis, particularly in the forward regions, where it will be very difficult to link the tracks with the primary vertex (associated with the only interesting collision) and thus to prevent the formation of fake jets created by the random stacking (or pile-up) of tracks from several secondary vertices. A solution proposed to fight against this pile-up effect in the forward regions (pseudo-rapidity greater than 2.4) is to measure very accurately the time of arrival of the particles just before they enter the endcap calorimeter. This allows to reject by the time of flight technique the tracks associated with secondary vertices spread longitudinally over a distance of about 20 cm at the centre of the detector. A time resolution of a few tens of ps with a spatial granularity better than a few mm will be needed to obtain a fake jet rejection rate that is acceptable for physics analyses. Such performances should be obtained with a detector capable of withstanding the very important radiation levels (similar to the levels the outermost layers of the tracker will have to survive) expected in this part of the detector.

The main characteristic of the HV-HR CMOS monolithic technology is that it enables the integration in a single IC of the detection part (polarized diode) together with the needed stages of the front-end electronics for signal treatment and data sparsification. HVCMOS silicon sensors allow the application of a very strong electrical field in the depleted zone of the charge collection diode. This has several advantages. It opens the possibility to have a very large depleted region, which enables to reach a detection efficiency very close to 100% for a single particle, with good signal to noise ratio, enabling good time measurements without in-situ amplification of the deposited charge. Another advantage of HVCMOS technologies is its low cost, since these technologies are widely used in the automotive industry, where the cost has been pushed down by the high production volumes. This also implies that going from a small demonstrator to a full scale detector should in principle be easy, once the demonstrator performance is validated.

Simulation studies based on the HV-HR CMOS LFOUNDRY 150 nm technology design kit have shown that a resolution of the order of 50 to 80 ps per MIP impact point can in principle be reached for MAPS pixels sensor of 1 mm pitch. We will present here the simulation results of the performance, and the architecture of a demonstrator chip, featuring a few rows and columns of individual pixels. Each pixel is equipped with a fast preamplifier, discriminator, and ancillary electronics to identify the position of the pixel hit, DACs to configure the discriminator, plus an injection chain to calibrate in-situ the performance of the readout electronics. At the time of the workshop, the chip will hopefully be in final submission stages.

Authors: OURAOU, Ahmimed (CEA/IRFU, Centre d'etude de Saclay Gif-sur-Yvette (FR)); GUYOT,

Claude (Saclay CEA/IRFU); BALLI, Fabrice (CEA/IRFU,Centre d'etude de Saclay Gif-sur-Yvette (FR)); MEYER, Jean-Pierre (CEA/IRFU,Centre d'etude de Saclay Gif-sur-Yvette (FR)); Mr LACHKAR, Mohamed (CEA-Irfu, Saclay); SCHWEMLING, Philippe (CEA/IRFU,Centre d'etude de Saclay Gif-sur-Yvette (FR)); DEGERLI, Yavuz (CEA - Centre d'Etudes de Saclay (FR))

Presenter: Mr LACHKAR, Mohamed (CEA-Irfu, Saclay)

Track Classification: 6 : Timing measurement

Type: not specified

L1 track trigger for the CMS HL-LHC upgrade using AM chips + FPGA

Tuesday 7 March 2017 10:00 (30 minutes)

The increase of luminosity at HL-LHC will require the introduction of tracker information at Level-1 trigger system in CMS to maintain an acceptable trigger rate to select interesting events despite the one order of magnitude increase in the minimum bias interactions. To extract in the required latency the track information a dedicated hardware has to be used. We present the tests of a prototype system (Pattern Recognition Mezzanine) as core of pattern recognition and track fitting for the CMS experiment, combining the power of both Associative Memory custom ASIC and modern Field Programmable Gate Array (FPGA) devices. The mezzanine uses the latest available associative memory devices (AM06) and the most modern Xilinx Ultrascale FPGA. The results of the test for a complete tower comprising about 0.5 Million patterns will be presented using as input simulated events in the upgraded CMS detector. We will show the performances of the pattern matching, track finding and track fitting, along with the latency and processing time needed.

Authors: MODAK, Atanu (Saha Institute of Nuclear Physics (IN)); CHECCUCCI, Bruno (Universita e INFN, Perugia (IT)); GENTSOS, Christos (Aristotle University of Thessaloníki (GR)); MAGALOTTI, Daniel (Universita e INFN, Perugia (IT)); Mr TCHERNIAKHOVSKI, Denis (KIT - Karlsruhe Institute of Technology (DE)); PALLA, Fabrizio (Universita di Pisa & INFN (IT)); GALBIT, Geoffrey Christian (Universite Claude Bernard-Lyon I (FR)); FEDI, Giacomo (Universita di Pisa & INFN (IT)); MAGA-ZZU, Guido (Universita di Pisa & INFN (IT)); BAULIEU, Guillaume (Universite Claude Bernard-Lyon I (FR)); STORCHI, Loriano (Universita e INFN, Perugia (IT)); BALZER, Matthias Norbert (KIT - Karlsruhe Institute of Technology (DE)); SANDER, Oliver (KIT - Karlsruhe Institute of Technology (DE)); VIRET, Sebastien (Universite Claude Bernard-Lyon I (FR)); ROY CHOWDHURY, Suvankar (Saha Institute of Nuclear Physics (IN))

Presenter: FEDI, Giacomo (Universita di Pisa & INFN (IT))

Track Classification: 9 : Real Time Pattern Recognition

Young Scientist Forum : Lossless ····

Contribution ID: 23

Type: not specified

Young Scientist Forum : Lossless data compression for the HL-LHC silicon pixel detector readout

Monday 6 March 2017 18:00 (15 minutes)

The readout rates required for the next generation pixel detectors to be used in the ATLAS and CMS experiments at the High-Luminosity LHC (HL-LHC) will be about 3 Gb/s/cm2. The very high radiation levels and small space available makes it impossible to envisage optical conversion on chip, which should be done using electrical links, implying that a significant material contribution will be associated with data transport out of the detector volume. In this contribution we will present the results of an implementation of a lossless arithmetic data compression that achieves an efficient bandwidth reduction. We will discuss the performances of the algorithm and its integration in the data output.

Authors: PALLA, Fabrizio (Universita di Pisa & INFN (IT)); MAGAZZU, Guido (Universita di Pisa & INFN (IT)); ANDROSOV, Konstantin (INFN Pisa (IT)); BECCHERLE, Roberto (INFN, Pisa (IT)); POULIOS, Stamatios (Universita di Pisa & INFN (IT))

Presenter: POULIOS, Stamatios (Universita di Pisa & INFN (IT))

Track Classification: 4 : Intelligent tracking detectors

Type: not specified

TBC Young Scientist Forum : Expected performance of the upgraded phase 1 pixel detector of CMS

The current silicon pixel detector is the innermost component of the CMS tracking system. Based on the precise measurement of up to three unambiguous space points, it allows an effective pattern recognition even in the multiple track environment near the interaction point. With the upgrade of the LHC accelerators, the luminosity and pile-up will surpass the original design goal of 1×10^{34} cm-2s -1 by at least a factor of 2. The current pixel detector in CMS was not designed to perform effectively in such collision conditions and the tracking performance and the physics program of CMS would suffer as a result. The current pixel tracker will be replaced with a new high efficiency and low mass detector during the end of year technical stop which lasts from December in 2016 to May in 2017. The new detector is composed of four barrel layer s and three forward/backward disks to provide four-hit pixel coverage out to pseudorapidities of ±2.5. In this talk I will describe the design and system testing of the upgraded pixel detector. I will also discuss the expected improvements in performance.

Author: Ms LIU, Miaoyuan (Fermi National Accelerator Laboratory in Batavia, IL, United States.)

Optimal use of charge informatio ...

Contribution ID: 25

Type: not specified

Optimal use of charge information for HL-LHC pixel readout

Tuesday 7 March 2017 12:45 (30 minutes)

Due to an enormous collision rate, charge information from particles traversing the innermost layers of the upgraded ATLAS and CMS detectors will be discretized using the time over threshold (ToT) method. Clever data manipulation, compression, or augmentation schemes can make a significant impact on downstream pattern recognition algorithms. In the context of the high-luminosity LHC (HL-LHC) pixel readout chip design, we systematically study the impact of various schemes on single and multi-particle cluster resolution, efficiency, classification, and particle identification. We show that with limited charge information, one can provide nearly optimal input to the pattern recognition for each of these tasks. This work provides an important input to the design of the next generation pixel chips that must cope with extreme rates (GHz/cm²), data volumes (1 Gbps/cm²), and radiation damage (1 GRad) at the HL-LHC.

Authors: NACHMAN, Ben (Lawrence Berkeley National Lab. (US)); WANG, Fuyue (Lawrence Berkeley National Lab. (US)); GARCIA-SCIVERES, Mauricio (Lawrence Berkeley National Lab. (US))

Presenter: NACHMAN, Ben (Lawrence Berkeley National Lab. (US))

Track Classification: 9 : Real Time Pattern Recognition

Type: not specified

Performance of the ATLAS Tracking and Vertexing in the LHC Run-2 and Beyond

Wednesday 8 March 2017 09:00 (30 minutes)

Run-2 of the LHC has provided new challenges to track and vertex reconstruction with higher centre-of-mass energies and luminosity leading to increasingly high-multiplicity environments, boosted, and highly-collimated physics objects. In addition, the Insertable B-layer (IBL) is a fourth pixel layer, which has been inserted at the centre of ATLAS during the shutdown of the LHC. We will present results showing the performance of the track and vertex reconstruction algorithms using Run-2 data at the LHC and highlight recent improvements. These include a factor of three reduction in the reconstruction time, optimisation for the expected conditions, novel techniques to enhance the performance in dense jet cores, time-dependent alignment of sub-detectors and special reconstruction of charged particle produced at large distance from interaction points. Moreover, data-driven methods to evaluate vertex resolution, fake rates, track reconstruction inefficiencies in dense environments, and track parameter resolution and biases will be shown. Luminosity increases in 2017 and beyond will also provide challenges for the detector systems and offline reconstruction, and strategies for mitigating the effects of increasing occupancy will be discussed.

Author: HSU, Shih-Chieh (University of Washington Seattle (US))Presenter: ALONSO DIAZ, Alejandro (University of Copenhagen (DK))

Type: not specified

Expected Performance of the ATLAS Inner Tracker at the High-Luminosity LHC

Wednesday 8 March 2017 09:30 (30 minutes)

The large data samples at the High-Luminosity LHC will enable precise measurements of the Higgs boson and other Standard Model particles, as well as searches for new phenomena such as super-symmetry and extra dimensions. To cope with the experimental challenges presented by the HL-LHC such as large radiation doses and high pileup, the current Inner Detector will be replaced with a new all-silicon Inner Tracker for the Phase II upgrade of the ATLAS detector. The current tracking performance of two candidate Inner Tracker layouts with an increased tracking acceptance (compared to the current Inner Detector) of $|\eta| < 4.0$, employing either an 'Extended'or 'Inclined' Pixel barrel, is evaluated. New pattern recognition approaches facilitated by the detector designs are discussed, and ongoing work in optimising the track reconstruction for the new layouts and experimental conditions are outlined. Finally, future approaches that may improve the physics and/or technical performance of the ATLAS track reconstruction for HL-LHC are considered.

Author: STYLES, Nicholas (Deutsches Elektronen-Synchrotron (DE))

Presenter: PETTERSSON, Nora Emilia (University of Massachusetts (US))

Status of study on tracker and tra ...

Contribution ID: 32

Type: not specified

Status of study on tracker and tracking at CEPC

Wednesday 8 March 2017 12:00 (30 minutes)

The Conceptual Design Report study on a high energy Circular Electron Positron Collider as a Higgs and/or Z factory is in progress and the tracker research is one of important parts. Based on the design from the ILD using TPC, the study group study the performances on the flavor tag varied with the parameters of the tracker to optimize the tracker design. As parallel, a preliminary design of full-silicon-based tracker is also considered at CEPC. And the study on the tracking algorithms and their performances under a digitization with multi-hits are in progress to improve the tracking performance.

Authors: Dr FU, Chengdong (CEPC); Dr LI, Gang (CEPC); Dr RUAN, Manqi (CEPC); Dr ZHANG, Yao (CEPC)

Presenter: Dr FU, Chengdong (CEPC)

"4D"Tracking with a Timepix3 d

Contribution ID: 33

Type: not specified

^{"4D"}Tracking with a Timepix3 detector

Monday 6 March 2017 15:15 (30 minutes)

Timepix3 detectors are the latest generetion of hybrid active pixel detectors of the Medipix family. Such detectors consist of an active sensor layer wich is flip-chip bump-bonded the readout ASIC, segmenting the detector into a square matrix of 256 x 256 pixels (pixel pitch 55 μ m). Ionizing radiation interacting in the active sensor material creates charge carriers, which drift towards the pixelated electrode, where they are collected. In each pixel, the time of the interaction (time resulution 1.56 ns) and the energy deposition are measured.

We demonstrate with measured data (120 GeV pions, cosmic muons) how the time information can be used for "4D" particle tracking, with the three spatial dimensions and the energy losses along the particle trajectory (dE/dx). Since the coordinates in the detector plane are given by pixelation (x,y), the x- and y-resolution is determined by the pixel pitch. The z-coordinate is reconstructed by evaluating the charge carrier drift times (z) with a resolution, experimentally proven to be better than 40 μ m for a Timepix3 equipped with a 500 μ m thick silicon sensor. Due to the data-driven readout scheme, the track information can be obtained in real-time.

Authors: BERGMANN, Benedikt Ludwig (Czech Technical University (CZ)); POSPISIL, Stanislav (Institute of Experimental and Applied Physics, Czech Technical University in Prague); BURIAN, Petr (Czech Technical University (CZ)); VYCPALEK, Jiri (Institute of Experimental and Applied Physics, Czech Technical University in Prague); BROULIM, Pavel (Faculty of Electrical Engineering, University of West Bohemia Pilsen)

Presenter: BERGMANN, Benedikt Ludwig (Czech Technical University (CZ))

Track Classification: 4 : Intelligent tracking detectors

Type: not specified

Parallelized Kalman-Filter-Based Reconstruction of Particle Tracks on Many-Core Processors and GPUs

Wednesday 8 March 2017 17:15 (30 minutes)

For over a decade now, physical and energy constraints have limited clock speed improvements in commodity microprocessors. Instead, chipmakers have been pushed into producing lower-power, multi-core processors such as GPGPU, ARM and Intel MIC. Broad-based efforts from manufacturers and developers have been devoted to making these processors user-friendly enough to perform general computations. However, extracting performance from a larger number of cores, as well as specialized vector or SIMD units, requires special care in algorithm design and code optimization. One of the most computationally challenging problems in high-energy particle experiments is finding and fitting the charged-particle tracks during event reconstruction. This is expected to become by far the dominant problem in the High-Luminosity Large Hadron Collider (HL-LHC), for example. Today the most common track finding methods are those based on the Kalman filter. Experience with Kalman techniques on real tracking detector systems has shown that they are robust and provide high physics performance. This is why they are currently in use at the LHC, both in the trigger and offline.

Previously we reported on the significant parallel speedups that resulted from our investigations to adapt Kalman filters to track fitting and track building on Intel Xeon and Xeon Phi. We continue to make progress toward the understanding of these processors while progressively introducing more realistic physics. These processors, in particular Xeon Phi, provided a good foundation for porting these algorithms to NVIDIA GPUs, for which parallelization and vectorization is of utmost importance. The challenge lies mostly in the ability to feed these graphical devices with enough data to keep them busy. We also discuss strategies for minimizing code duplication while still being able to keep the previously cited algorithms as close to the hardware as possible.

Authors: Dr CERATI, Giuseppe (Fermilab (US)); Dr ELMER, Peter (Princeton University (US)); Dr KRUTELYOV, Slava (Univ. of California San Diego (US)); Dr LANTZ, Steven R (Cornell University (US)); LEFEBVRE, Matthieu (Princeton University (US)); Mr MCDERMOTT, Kevin (Cornell University (US)); Dr RILEY, Daniel Sherman (Cornell University (US)); Dr TADEL, Matevz (Univ. of California San Diego (US)); Prof. WITTICH, Peter (Cornell University (US)); Prof. WURTHWEIN, Frank (Univ. of California San Diego (US)); Prof. YAGIL, Avi (Univ. of California San Diego (US))

Presenter: LEFEBVRE, Matthieu (Princeton University (US))

Track Classification: 1: Parallel and discrete pattern recognition

Young Scientist Forum : Online t ····

Contribution ID: 35

Type: not specified

Young Scientist Forum : Online track reconstruction using Kalman Filters on FPGAs

Tuesday 7 March 2017 12:30 (15 minutes)

The significant instantaneous luminosity planned at the High-Luminosity LHC will present a challenging environment for online track reconstruction.

Hardware acceleration of tracking algorithms on parallel architectures is an attractive solution to meeting latency restrictions in online systems.

Here we present an FPGA implementation of the Kalman Filter for fitting and cleaning tracks. The implementation has been developed targeting a Xilinx Virtex 7 FPGA.

A High Level Synthesis language, MaxJ, was used to simplify the implementation of the algorithm compared to conventional FPGA programming techniques.

A single iteration latency of 210 ns is achieved at a clock frequency of 240 MHz.

Due to the small resource usage of the matrix maths, 36 independent Kalman Filter nodes operate in the chip.

Operation pipelining enables the processing of multiple data simultaneously within a node.

The implementation has a theoretical upper limit of 1 billion track fits per second for a 6 layer tracker.

At the data rate observed in high pile-up Monte Carlo data, with a preceding track finding stage, we fit 23 million tracks per second, with spare capacity.

Here we present the algorithm, its performance and applications, including at different levels of online reconstruction.

Author: SUMMERS, Sioni Paris (Imperial College (GB))

Presenter: SUMMERS, Sioni Paris (Imperial College (GB))

Track Classification: 9 : Real Time Pattern Recognition

Type: not specified

The track finding algorithm of the Belle II vertex detectors

Wednesday 8 March 2017 16:45 (30 minutes)

Belle II is a multipurpose detector which will be operated at the asymmetric B-Factory SuperKEKB (Japan). The unprecedented instantaneous luminosity of up to 8×10^{35} cm⁻²s⁻¹ provided by the accelerator together with the level 1 trigger rate in the range of 30kHz will pose extreme requirements on the sub-detectors of Belle II and the track finding algorithms. Track position information close to the interaction point is provided by the vertex detector (VXD) which consists of 2 layers of pixel detectors (PXD) and 4 layers of double sided silicon strip vertex detectors (SVD).

The track finding code for the VXD of Belle II implements in an efficient way the Sector Map concept originally proposed by Rudolf Frühwirth. The typical event recorded by the VXD will be dominated by random hits produced by beam background (order of 500 pixels hit per event per sensor on the inner layer of the PXD, 20 GByte/s required to readout the whole PXD.) In this harsh environment the pattern recognition algorithm for the VXD has to be capable to efficiently and quickly recognize the 11 tracks of a typical Y4S event.

The track finding algorithm I will present will be used both for the final reconstruction of the event and at the High Level Trigger stage for the definition of the Regions Of Interest on the PXD sensors used to reduce the PXD data stream to a manageable level. This latter task put further constraints on the reliability and time consumption of the track finding algorithm. I will present the main concepts of the algorithm, some details of its implementation together with its current performances.

Authors: PAOLONI, Eugenio (INFN Pisa); Mr METZNER, Felix (Karlsruhe Institue of Technology); WAGNER, Jonas Ferdinand (KIT - Karlsruhe Institute of Technology (DE)); LUECK, THOMAS (University of Pisa)

Co-author: HECK, Martin (KIT)

Presenter: LUECK, THOMAS (University of Pisa)

Track Classification: 1: Parallel and discrete pattern recognition

Type: not specified

A Multi-Purpose Particle Detector for Space Missions

Monday 6 March 2017 14:15 (30 minutes)

Precisely characterizing a radiation environment is essential for space exploration-manned and unmanned missions to, for example, the Moon or Mars-and astroparticle-physics experimentsfor example, solar observations and cosmic-ray measurements. Particle detectors used for such endeavors must be compact, use as little power as possible, and withstand the harsh space environment. We are developing the Multi-purpose Active-Target Particle Telescope (MAPT), a detector capable of omnidirectionally measuring particle fluxes with a large geometric acceptance. The detector fits into a cube with an edge length of 10 cm and weighs less than 3 kg. It is essentially a tracking calorimeter with a segmented active core made of scintillating plastic fibers. Besides tracking charged particles and ions, MAPT can also identify them by analyzing their energy-loss profiles using extended Bragg-curve spectroscopy methods. Anti-ions can be distinguished by the secondary particles created by their annihilation inside the detector. We simultaneously analyze track parameters and particle characteristics using Bayesian inference techniques to minimize the expected uncertainties of particle flux measurements. We tested basic implementations of a particle filter and a maximum-likelihood method and obtained an angular resolution of about 3 degrees and an energy resolution of better than 2.5% for 50 MeV protons. We present the expected capabilities of the detector, use cases, and first results from beam experiments and discuss the requirements and challenges of on- and off-line data analysis methods.

Author: Mr PÖSCHL, Thomas (Technical University Munich)

Co-authors: Mr LOSEKAMM, Martin J. (Technical University Munich); Dr GREENWALD, Daniel (Technical University Munich); Prof. PAUL, Stephan (Technical University Munich)

Presenter: Mr PÖSCHL, Thomas (Technical University Munich)

Track Classification: 4 : Intelligent tracking detectors

Type: not specified

Improved AM chip pattern recognition with optimized ternary bit usage

Tuesday 7 March 2017 11:30 (30 minutes)

For the ATLAS Fast TracKer (FTK) hardware-based track reconstruction system, the AM chip is used in the pattern recognition step. The version of the AM chip used in the FTK is based on eight associative memory cells per pattern, corresponding to eight detector planes. Patterns are identified for addresses where seven out of the eight memory cells indicate a matching hit. The associative memories each accept 15-bit hit addresses for the look-up. Three of these bits are ternary, such that the associative memory can be programmed at each address to either match the bit exactly (B=0 or B=1) or to always match (B=X). The use of ternary bits gives the possibility to tune the resolution of the pattern match for each layer of each pattern independetly, thus achieving better signal to noise in the pattern match. In this talk, a fast and efficient method to optimize the use of ternary bits is presented. It is based on limiting the number of bits which have state X while the desired patterns are imported to the AM chip. With respect to previously used methods improved data flow is achieved at constant efficiency.

Author: PANDURO VAZQUEZ, William (Royal Holloway, University of London) Presenter: SCHMITT, Stefan (Deutsches Elektronen-Synchrotron (DE))

Track Classification: 9 : Real Time Pattern Recognition

Hough transform based curling t ...

Contribution ID: 40

Type: not specified

Hough transform based curling track finding for BESIII and COMET multi turn track fitting

Thursday 9 March 2017 09:15 (30 minutes)

In order to overcome the difficulty brought by the curling charged tracks in the BESIII drift chamber,

we introduce the Hough transform based tracking method. This method is used as the supplementary to find

low transverse momentum tracks. This tracking algorithm is realized in C++ in BOSS (BESIII offline software system) and the performance has been checked by both Monte Carlo data and real data. We show that this tracking method could enhance the reconstruction efficiency in the low transverse momentum region.

Track reconstruction in the COMET Phase-I drift chamber is characterized by large amount of multi-turn curling tracks. We present the method based on the Deterministic Annealing Filter (DAF) and implements a global competition. The method assigns the detector measurements to the track assumption on different turns. This method is studied on the simulated tracks in the COMET drift chamber. We show that it can be a candidate to the assign hits on different track turns.

Authors: ZHANG, Yao (China); Prof. YUAN, Ye (IHEP, CAS, China); Mr ZHANG, Jin (IHEP, CAS, China); Dr ZHANG, Yao (IHEP,CAS,China)

Presenter: Prof. YUAN, Ye (IHEP, CAS, China)

Track Classification: 1: Parallel and discrete pattern recognition

Type: not specified

Young Scientist Forum : Identification of Jets Containing b-Hadrons with Recurrent Neural Networks at the ATLAS Experiment

Thursday 9 March 2017 14:15 (15 minutes)

A novel b-jet identification algorithm is constructed with a Recurrent Neural Network (RNN) at the ATLAS Experiment. This talk presents the expected performance of the RNN based b-tagging in simulated $t\bar{t}$ and high $p_T Z' \rightarrow b\bar{b}$ events. The RNN based b-tagging processes properties of tracks associated to jets which are represented in sequences. In contrast to traditional impactparameter-based b-tagging algorithms which assume the tracks of jets are independent from each other, RNN based b-tagging can exploit the spatial and kinematic correlations of tracks which are initiated from the same b-hadrons. The neural network nature of the tagging algorithm also allows the flexibility of extending input features to include more track properties than can be effectively used in traditional algorithms.

Author: JIANG, Zihao (Stanford University (US))

Presenter: JIANG, Zihao (Stanford University (US))

Track Classification: 11 : Using tracks

Type: not specified

The design and simulated performance of a fast Level 1 track trigger for the ATLAS High Luminosity Upgrade

Tuesday 7 March 2017 09:00 (30 minutes)

The ATLAS experiment at the high-luminosity LHC will face a five-fold increase in the number of interactions per collision relative to the ongoing Run 2. This will require a proportional improvement in rejection power at the earliest levels of the detector trigger system, while preserving good signal efficiency. One critical aspect of this improvement will be the implementation of precise track reconstruction, through which sharper trigger turn-on curves can be achieved, and b-tagging and tau-tagging techniques can in principle be implemented. The challenge of such a project comes in the development of a fast, custom electronic device integrated in the hardware-based first trigger level of the experiment, with repercussions propagating as far as the detector read-out philosophy. This talk will discuss the requirements, architecture and projected performance of the system in terms of tracking, timing and physics, based on detailed simulations. Studies are carried out comparing two detector geometries and using data from the strip subsystem only or both strip and pixel subsystems.

Authors: BRENNER, Richard (Uppsala University (SE)); KONSTANTINIDIS, Nikos (University College London (UK)); GRADIN, Per Olov Joakim (Uppsala University (SE)); ALLBROOKE, Benedict (University of Sussex (GB))

Presenter: MARTENSSON, Mikael (Uppsala University (SE))

Track Classification: 9 : Real Time Pattern Recognition

Expected Performance of tracking ···

Contribution ID: 43

Type: not specified

Expected Performance of tracking at HL-LHC CMS

Wednesday 8 March 2017 10:00 (30 minutes)

After 2020, CERN is planning an upgrade program of the LHC collider (HL-LHC) which will bring the luminosity up to 5x10^{{34}} cm^{{-2}s^{{-1}}</sup>, almost five times the one foreseen for 2017, meaning a mean of more than 140 inelastic collisions superimposed on the event of interest. In this high-occupancy environment, reconstructing the particle momentum with high precision is one of the biggest challenges. In order to face this new scenario (called Phase 2), the Compact Muon Solenoid (CMS) experiment will build a completely new silicon-tracker detector and will need to implement new approaches to track finding to exploit the capabilities of the new tracker in addition to the algorithms already in use. In this talk the expected performance of CMS tracking at HL-LHC will be presented.

Author: BRONDOLIN, Erica (Austrian Academy of Sciences (AT))

Presenter: BRONDOLIN, Erica (Austrian Academy of Sciences (AT))

Connecting The $\cdots \ /$ Report of Contributions

Welcome

Contribution ID: 45

Type: not specified

Welcome

Monday 6 March 2017 14:00 (15 minutes)

Connecting The $\cdots \ /$ Report of Contributions

Keynote talk

Contribution ID: 46

Type: not specified

Keynote talk

TBA

4D trackers (space + time inform ...

Contribution ID: 47

Type: not specified

4D trackers (space + time information)

Monday 6 March 2017 14:45 (30 minutes)

As particle physics strives for increased precision and sensitivity in its measurements, the beam energy, power, and per-bunch luminosity of colliders increase and produce significantly more complex events primarily by way of overlapping collisions (pileup) that test the performance and robustness of our algorithms and analysis.

One avenue towards mitigating the effects of pileup in tracking detectors is to create sensors with finer and finer segmentation to accurately identify individual particles, and this has seen great success within the field. Next generation colliders, like the HL-LHC (200 pileup) and FCC (1000 pileup with 25ns bunches) where pileup events can occur multiple times per millimeter pose a significant challenge using spatial information alone, since events can overlap in space, and track distributions from near-by vertices can become confused. This leads to degradations in reconstruction performance and physics analysis. A clear way to mitigate these degradations is to use the time-at-closest-approach of tracks to more precisely connect tracks to their true vertex of origin, increasing the quality and amount of information in the event.

Recent advancements in silicon precision timing detectors indicate that finely pixellated, lightweight planar timing detectors with MIP sensitivity are coming within reach. I will discuss these devices, and demonstrate their uses in terms of mitigation of pileup in "timing layer" configurations, where there is one layer providing the time stamp. This initial discussion will be extended to true 4-dimensional trackers where each coordinate measurement is a point in spacetime, focusing on the algorithmic implications and next steps needed to achieve these devices.

Presenter: GRAY, Lindsey (Fermi National Accelerator Lab. (US))

Track Classification: 4 : Intelligent tracking detectors

Type: not specified

Potential of Monolithic CMOS pixel detectors for future track triggers

Monday 6 March 2017 17:15 (30 minutes)

Monolithic pixel sensors based on commercial CMOS processes offer many features which are important for track trigger applications. Most relevant are the smaller pixel sizes at reduced material and the lower production costs. Industrially produced monolithic pixel sensors are significantly cheaper than standard semiconductor trackers, thus allowing to instrument large areas of tracking detectors with highly granular pixel sensors.

I will discuss the main requirements for track triggers at (future) hadron colliders and explain how these requirements are fulfilled by monolithic pixel sensors. An overview over

current hardware activities is given. First simulation results using a design based on large area pixel sensors are presented.

Presenter: SCHOENING, Andre (Ruprecht-Karls-Universitaet Heidelberg (DE))

Track Classification: 7 : Electronic circuits

Abstraction in scientific data visu

Contribution ID: 49

Type: not specified

Abstraction in scientific data visualization: application to brain connectivity and structural biology

Tuesday 7 March 2017 14:30 (30 minutes)

Scientific simulations or data acquisition processes often result in large amounts of data samples that need to be "connected" to allow people to understand the information/meaning hidden within. However, if we simply connect all related data points we may end up with an even larger dataset that is more difficult to understand. I will thus talk about illustrative forms of visualization that are inspired by a long tradition of hand-made illustration. In particular, I will talk about the concept of abstraction, using examples from brain connectivity visualization and from structural biology. I will talk about different forms of abstraction, photometric and geometric abstraction, and show how they can be used to create meaningful illustrative visualizations of scientific datasets.

Presenter: Dr ISENBERG, Tobias (INRIA-Saclay)

Type: not specified

Status of Track Machine Learning challenge and introduction to the TrackMLRamp hackathon

Tuesday 7 March 2017 15:30 (30 minutes)

Tracking at the HL-LHC in ATLAS and CMS will be very challenging. In particular, the pattern recognition will be very resource hungry, as extrapolated from current conditions. There is a huge on-going effort to optimise the current software. In parallel, completely different approaches should be explored.

To reach out to Computer Science specialists, a Tracking Machine Learning challenge (trackML) is being set up, building on the experience of the successful Higgs Machine Learning challenge in 2014 (which associated ATLAS and CMS physicists with Computer Scientists). A few relevant points:

• A dataset consisting of a simulation of a typical full Silicon LHC experiments has been created, listing for each event the measured 3D points, and the list of 3D points associated to a true track. The data set is large to allow the training of data hungry Machine Learning methods : the orders of magnitude are : one million event, 10 billion tracks, 1 terabyte. Typical CPU time spent by traditional algorithms is 100s per event. ⊠

• The participants to the challenge should find the tracks in an additional test dataset, meaning building the list of 3D points belonging to each track (deriving the track parameters is not the topic of the challenge) \boxtimes

• A figure of merit should be defined which combines the CPU time, the efficiency and the fake rate (with an emphasis on CPU time) \boxtimes

- The challenge platforms should allow measuring the figure of merit and to rate the different algorithms submitted. \boxtimes

The emphasis is to expose innovative approaches, rather than hyper-optimising known approaches. Machine Learning specialists have showed a deep interest to participate to the challenge, with new approaches like Convolutional Neural Network, Deep Neural Net, Monte Carlo Tree Search and others. ⊠

A slimmed down 2D version of the challenge will be proposed right after this talk, and will be introduced here.

Presenter: ROUSSEAU, David (LAL-Orsay, FR)

TrackMLRamp hackathon : a 2D ···

Contribution ID: 51

Type: not specified

TrackMLRamp hackathon : a 2D tracking challenge

Tuesday 7 March 2017 16:30 (3h 30m)

To participate to this hackathon, it is necessary to register using the "hackathon registration" button on the left hand side menu.

See the motivation for an HL-LHC tracking challenge in the previous talk abstract. A RAMP (Rapid Analysis and Model Prototyping) on the Paris-Saclay platform is a mini-challenge/hackathon. Simulated LHC like events in 2D will be proposed, simplified but not too simple: circular detectors with Si-like resolution, uniform magnetic field, multiple scattering. the name of the game will be to propose new approaches to associate hits into tracks. Code submission (in python only) will be evaluated online and be ranked on a leaderboard, based on the best efficiency with limited fake rate. Participants will be able to download the best contributions and improve on them. Set up instructions are provided.

Winners as determined by the leaderboard Thursday 9AM have been congratulated at 11AM Thursday (see agenda).

However the hackathon site remains open for the foreseeable future.

Presenters: KÉGL, Balázs (Linear Accelerator Laboratory); ROUSSEAU, David (LAL-Orsay, FR); GUYON, Isabelle; HUSHCHYN, Mikhail (Yandex School of Data Analysis (RU)); YILMAZ, Yetkin (Laboratoire Leprince-Ringuet, France)

Type: not specified

Fast, Parallel and Parametrized Kalman Filters for LHCb upgrade

Wednesday 8 March 2017 17:45 (30 minutes)

By 2020 the LHCb experiment will be upgraded to run at an, by a factor of 5, increased instantaneous luminosity of $2x10^33$ cm⁻² s⁻¹. The hardware trigger will be removed and replaced by a fully software based stage. This will dramatically increase the rate of collisions the software trigger system has to process. Additionally, the increased luminosity will lead to a higher number of tracks that need to be reconstructed per collision.

The Kalman filter, which is employed to extract the track parameters, currently consumes a major part of the reconstruction time in the trigger software and, therefore, needs further optimization. We investigate two, noncompeting, strategies to speed up the current version of the filter. The first one is an algorithm that makes use of several different levels of SIMD instructions on different processor architectures to fit multiple tracks in parallel.

The second one is to replace the computational costly use of magnetic field and material look up tables, including a Runge-Kutta method for calculating the extrapolation, by simple parametrizations of every extrapolation step.

For both strategies details and performance studies are presented.

Presenter: STEMMLE, Simon Benedikt (Ruprecht-Karls-Universitaet Heidelberg (DE))

Track Classification: 10 : Fitting tracks

Connecting The $\cdots \ /$ Report of Contributions

Dinner at Atelier de Maitre Alber

Contribution ID: 54

Type: not specified

Dinner at Atelier de Maitre Albert, Paris

Wednesday 8 March 2017 20:00 (3 hours)

http://www.ateliermaitrealbert.com

Type: not specified

Flavour Tagging using Deep Neural Networks in Belle II

Thursday 9 March 2017 09:45 (30 minutes)

Machine learning techniques have been successfully utilized in data processing and analysis for decades.

Hand in hand with the "deep learning revolution", the importance of Neural Networks in this area is still growing.

One advantage of employing a Neural Network is that certain features do not have to be engineered manually but are constructed by representations of the network.

This can enable a higher exploitation of correlations between input variables and also allow an increased variable space compared to other techniques. Modern machine learning frameworks make construction and usage of these techniques even more accessible and utilizable.

This presentation covers the successful deployment of a Deep Neural Network for the discrimination of neutral B and \overline{B} mesons at the Belle II experiment, the so-called flavour tagging. Implementation and results of this approach will be presented.

Presenter: GEMMLER, Jochen (KIT/IEKP)

Track Classification: 11 : Using tracks

Type: not specified

HEP.TrkX project: DNNs for HL-LHC online and offline tracking

Thursday 9 March 2017 12:00 (30 minutes)

Particle track reconstruction in dense environments such as the detectors of the HL-LHC is a challenging pattern recognition problem. Traditional tracking algorithms such as the combinatorial Kalman Filter have been used with great success in LHC experiments for years. However, these state-of-the-art techniques are inherently sequential and scale poorly with the expected increases in detector occupancy in the HL-LHC conditions.

The HEP.TrkX project is a pilot project with the aim to identify and develop cross-experiment solutions based on machine learning algorithms for track reconstruction. Machine learning algorithms bring a lot of potential to this problem thanks to their capability to model complex non-linear data dependencies, to learn effective representations of high-dimensional data through training, and to parallelize easily on high-throughput architectures such as GPUs.

This contribution will describe our initial explorations into this relatively unexplored idea space. We will discuss the use of recurrent (LSTM) and convolutional neural networks to find and fit tracks in toy data and LHC-like data generated with ACTS.

Presenter: FARRELL, Steven Andrew (Lawrence Berkeley National Lab. (US))

Track Classification: 0 : Algorithms and theoretical analysis

Type: not specified

Status of the ACTS (A Common Tracking Software) project

Thursday 9 March 2017 11:30 (30 minutes)

A Common Tracking Software (ACTS) is a project that attempts to preserve the highly performant track reconstruction code from the first LHC era and prepares the code and concept for long term maintainability and adaption to future architecture. It is based primarily on the ATLAS Common Tracking Software, but has been decoupled to be detector and framework agnostic. ACTS supports several detector geometry backends and a plug-in mechanism for track parameterisation, Identification schema and measurement definitions. It attempts to provide a toolbox for track reconstruction including track propagation, track fitting, pattern recognition, such as a fast simulation module. Dedicated care is taken that the code runs in concurrent environment and complies with the C++14 standard. We present first test suites for different detector geometries, and results testing multithreaded test applications.

Presenter: SALZBURGER, Andreas (CERN)

Type: not specified

Kalman Filter on IBM's TrueNorth

Thursday 9 March 2017 12:30 (30 minutes)

As High Energy Physics (HEP) experiments extend the range of attainable luminosities to produce more particle tracks per bunch crossing than ever before, reconstructing the tracks produced in detectors from such interactions becomes more challenging and new methods of computation and data-handling are being explored.

Additionally, understanding portability of HEP algorithms to future commodity computing architectures is necessary to project future computing costs. A key algorithm in track reconstruction in multiple HEP experiments over the past 50 years is the Kalman filter. Implementing this algorithm in a neuromorphic architecture represents a first step in understanding the benefits and limitation of introducing such a device into the computational resources available to HEP experiments.

This talk will outline the first instance of a Kalman filter implementation in IBM's neuromorphic architecture, TrueNorth, for both parallel and serial spike trains. The implementation is tested on multiple simulated systems and its performance is evaluated with respect to an equivalent non-spiking Kalman filter. The limitations of implementing algorithms in neuromorphic neural networks are explored with respect to data encoding, weight representation, latency, and throughput.

Presenter: CARNEY, Rebecca (Stockholm University (SE))

Track Classification: 0 : Algorithms and theoretical analysis

Machine Learning approach to n …

Contribution ID: 59

Type: not specified

Machine Learning approach to neutrino experiment track reconstruction : DUNE/ uBooNE/ NOvA

Thursday 9 March 2017 15:00 (45 minutes)

Neutrino experiments discussed in this talk represent a category of event reconstruction problems very distinct from the collider experiments. The two main differences are: i) the representation of data, in form of 2D, high resolution, image-like projections, and ii) the nature of neutrino interactions observed in the detectors, with their high diversity of topologies and undefined location of the interaction point. In such conditions, two basic features of events have to be reconstructed: flavor and energy of incident neutrino.

DUNE and MicroBooNE are Liquid Argon Time Projection Chamber (LArTPC) based experiments, while NOvA's detector is made of liquid scintillator filled cells. The technology choice in these experiments results in the different resolution of recorded "images", however the basic concepts in the reconstruction and application of the machine learning techniques, are similar. I will discuss those, focusing on the expected DUNE detector conditions and reconstruction approaches currently being developed.

Presenter: SULEJ, Robert (FNAL / NCBJ)

Track Classification: 0 : Algorithms and theoretical analysis

Deep Neural Nets and Bonsai BD ...

Contribution ID: 60

Type: not specified

Deep Neural Nets and Bonsai BDTs in the LHCb pattern recognition

Thursday 9 March 2017 14:30 (30 minutes)

Presenter: DENDEK, Adam Mateusz (AGH University of Science and Technology (PL))

Track Classification: 0: Algorithms and theoretical analysis

Connecting The $\cdots \ /$ Report of Contributions

Final words

Contribution ID: 61

Type: not specified

Final words

Thursday 9 March 2017 15:45 (15 minutes)

Connecting The · · · / Report of Contributions

Discussion on common tracking

Contribution ID: 62

Type: not specified

Discussion on common tracking

Thursday 9 March 2017 16:00 (1 hour)

satellite meeting in room 101 : C ····

Contribution ID: 63

Type: not specified

satellite meeting in room 101 : CWP Working Group meeting on Software Triggers and Event Reconstruction

Thursday 9 March 2017 17:00 (3 hours)

Type: not specified

Robust classification of particle tracks for characterization of diffusion and dynamics in fluorescence microscopy

Tuesday 7 March 2017 15:00 (30 minutes)

The characterization of molecule dynamics in living cells is of paramount interest in quantitative microscopy. This challenge is usually addressed in fluorescent video-microscopy from particle trajectories computed by tracking algorithms. However, classifying individual trajectories into three diffusion groups –subdiffusion, free diffusion (or Brownian motion) and superdiffusion – is a difficult task. To overcome this problem, we have developed a two stage approach based on statistical measure of diffusion and requiring the setting of only one parameter corresponding to a p-value. In the first stage, the procedure is related to a statistical test with the Brownian motion as the null hypothesis and the subdiffusion and super diffusion as the alternative hypothesis. The testing procedure is well grounded in statistics, robust to different lengths of trajectories and low signal-to-noise ratios. However, it is known that applying multiple times a test without care leads to a high number of false positives.

Accordingly, in the second stage, we modified the results of the first stage to address this problem. We considered the multiple testing framework to reduce the number of trajectories wrongly classified as superdiffusion or sub diffusion. This approach has been especially developed to process individual trajectories provided by particle tracking algorithms and 2D+t and 3D+t images acquired with standard microscopy methods such as wide-field or confocal microscopy or with super-resolution microscopy such as (Single Particle Tracking) SPT-PALM. We demonstrate that the proposed approach is more robust than previous techniques, including the Mean Square Displacement (MSD) method.

Presenter: Dr KERVRANN, Charles (INRIA, Centre Rennes - Bretagne Atlantique)

Track Classification: 11 : Using tracks

Connecting The $\cdots \ /$ Report of Contributions

Announcement

Contribution ID: 65

Type: not specified

Announcement

Wednesday 8 March 2017 11:00 (5 minutes)

Presenter: ROUSSEAU, David (LAL-Orsay, FR)

Connecting The $\cdots \ /$ Report of Contributions

TrackMLRamp hackathon winner \cdots

Contribution ID: 66

Type: not specified

TrackMLRamp hackathon winner announcement

Thursday 9 March 2017 11:00 (5 minutes)