

HL-LHC Crab Cavities and SPS Tests

R. Calaga on behalf HL-LHC WP4 CERN




12 July 2019, EPS-HEP 2019, Ghent

HL-LHC Crab Cavity System

Use 8+8 Superconducting compact RF crab cavities (ATLAS + CMS) to compensate the geometric angle of ~500 μ rad

Recover ~70% of the Peak Luminosity – use levelling with β^*





Dressed Cavity Geometries

Double Quarter Wave


RF Dipole

3






Super Proton Synchrotron, SPS



CERN

IL-LHC PROJ

Circumference	7 km		
Injection-Extraction energy	26-450 GeV		
Main RF Frequency	200 MHz, TW		
CC Frequency swing	400.528 – 400.788 MHz		
CC bandwidth	800 Hz		



SPS-LSS6 – Crab Cavity Module






CERN


SPS-Crab Installation

 Massive installation of a new RF & Cryo plant in SPS machine during 2017/18









Expected SPS Test Sequence


- 4 main phases foreseen 10 machine development sessions (MDs) requested
- 2 slots were for table and RF setup in-beam
- 7 MDs of 10 hrs each were performed

	What	When	MD slots
0	RF commissioning (no-beam)	Mar-Apr	~ 4 weeks
1	RF-beam synchronization	Apr-May	2-4 x 10h
2	Transparency to beam	Jun-Jul	2-4 x 10h
3	Performance & Stability	Aug-Sep	4 x 10h
4	High intensity RF operation	October	2 x 10h



Cryo Availability

- Issues with LN₂ meant operation at 4.5K before the Summer
- 4.5K not ideal due to large pressure modulation, higher than 1 MV caused vacuum-thermal runaway




MD Overview

* Operating temperature is 2K

MD#		Cav1	Cav2 [MV]	Temp [K]	Energy [GeV]
1	First crabbing, phase and voltage scan	0.5	0	4.5	26
2	270 GeV ramp with single bunch	1-2	0	4.5	26, 270
3	Intensity ramp up	1	~0.3	4.5	26
4	270 GeV coast setup	1.0	0.5	2.0	270
5	Emittance growth at 270 GeV with induced noise	0	1.0	2.0	270
6	Intensity ramp up to 4-batches	-	1.0-1.5	2.0	26
7	Intensity/Energy ramp up	-	1.0	2.0	26, 270, 400




Protons meet Crabs



First injection – 12:55, May 23 Cavity 1 only

Single bunch $0.2 - 0.8 \times 10^{11}$ p/b




Head-tail monitor as main beam diagnostic

Beam measurements showed 10-20% larger voltage than RF measurements


How to synchronize Crab-RF?

Crab cavity is at fixed frequency

- Freq (400.53 400.78 MHz): 26 450 GeV
- SPS RF ~200 MHz is rephased to crab Freq




Reconstruction of Crabbing using HT




of turns for ref position along the bunch ~ 2k turns RF re-synchronization ~ 1s after injection



Phase Scans & "Transparency"



Transparency: V=1MV in both cavities




Energy Ramp to 270 GeV

- Due to large frequency swing during energy ramp, with cavities powered at fixed frequency, the beam is rapidly lost due to resonant excitation while crossing one of the betratron sidebands.
- With <u>cavities off</u> during the ramp the beam makes it through without losses. New operational scenario for HL-LHC

SPS-PAGE1 Current user: SFTPRO2 0.00E+00 30-05-18 17:29:31 SC 58 (39BP, 46.8s) Last update: 0 seconds ago Beam Dumped due to voltage ramp set at start injection I/E11 MUL %SYM Target Experiment Τ2 0.0 0 0 H2/H4 Τ4 0.0 0 0 H6/H8 Τ6 0.0 0 0 COMPASS T10 0.0 0 0 NA62 Phone: 77500 or 70475 Comments (30-May-2018 07:29:46) LHC3 307 E8 -9.4 E8 MD from 8h-18h. No beam for north area


Cav1 ~1MV (400.787 MHZ), Cav2 off (400.528 MHz)






Cavity Alignment


- Tight intra-cavity alignment tolerances transversely (±500 μm at 2K) for HL-LHC
- Alignment reached w/o compensation is within a radius of <u>130 µm.</u> FSI system validated and allows for continuous monitoring of cavity positions





Beam Loading & Electrical Center


 Beam induced voltage with cavities off performed to determine the magnitude & electrical center



E. Yamakawa et al.


Emittance Growth

- SPS natural emittance growth at 270 GeV, \leq 0.5 μ m/h. HL-LHC needs to be below 0.05 μ m/h
- CC expected growth with existing electronics (noisy!).
 Scaling with additional induced noise is qualitatively reproduced but more pessimistic than measured growth



RF Multipoles


 Very promising results to measure for the first time RF multipoles with beam. But extracting the cavity multipoles from other machine elements still remains challenging





Higher Order Modes

- Integrated max HOM power measured < 3 W. More than 75% from \sim 960 MHz.
- Overall HOM power & scaling to the HL-LHC looks reasonable, some deviations from expectations



High Intensity

- MD6: 72 bunches at 2×10^{10} p/b increased to 4×36 at 1×10^{11} p/b (1/2 the max intensity)
 - Limited by crab by-pass pressure rise 10⁻⁶mb
 - With moderate voltage (1 MV), no beam induced failures or fast transients seen except for pressure rise
- MD7: 2×60 bunches at 1×10^{11} p/b
 - Also limited by vacuum pressure rise in by-pass
 - Cavities on/off at 1MV didn't make any difference on pressure dynamics
 - Ramp the multi-bunches to 270-400 GeV to reach closer to LHC like bunch lengths – longitudinally unstable beyond 12-bunches, required more setup time




Few Challenges Encountered

- Cavity voltage reach (3.4 MV nominal)
- RF linearity at low power and optimization of RF chain including interlocks
- Direct beam coupling with field probe for field regulation
- Electro-acoustic instabilities above 1MV, recall LFD $\sim 300 800 \text{ Hz}/\text{MV}^2$
- Microphonics measured but not an issue
- Vacuum pressure rise in the bypass




Average Voltage Evolution (2K)

Long RF conditioning period to get beyond 1 MV stable operation




Oct 13, Stable Voltage CAV1/2 – 1.0 MV

- Many hours of stable operation with good correlation between RF and cryogenics. For most MDs 1.0 MV was used as safe operation
- Few occasions with stable operation over many hours with sudden increase in cryo load and loss of RF conditions – not fully understood




Crab Cavity Max Performance, Nov/Dec

Cavity 1 Voltage & RF Power (red)



Cavity 2 Voltage & RF Power (blue)





Note: After many hours of stable operation, we observed big thermal load and lost RF conditions, the trigger of such events is not fully understood

High Power RF

- Two 80 kW IOTs operational in SPS
 - <u>Issues of linearity</u> at very low power (< 5 kW) being addressed jointly with LLRF team
 - For series, SSPA spec with the required linearity
- RF chain validated during operation in SPS
 - Use of LHC-type circulators & loads are way oversized for crab needs, will be adapted for HL-LHC




CERN

Surface-BA6




Direct Beam Coupling


 Due to the hybrid field ANT & HOM coupler design, we saw strong coupling to the beam passage on top of measuring cavity field variation













Direct Beam Coupling & Mitigation


 Design change for field antenna adopted to minimize this effect by x10 for HL-LHC




SPS Field ANT




HL-LHC Field ANT





Electro-acoustic Instabilities > 1MV

- At 1MV, the LFD is ~400 Hz (1/2 the cavity BW)
- Self excited loop not implemented in early 2018, tested later in Nov.
- Cured by with tuning loop or with feedback. following the cavity tune with slow voltage ramp & tuning loop on.



Modal Analysis of Bare Cavity

 Measurements on bare cavities with 5 tri-axial accelerometers & modal hammer



112, 132, 151 Hz 210 Hz 298 Hz 200 Hz




Courtesy: L. Lacny, M. Guinchard, T. Jones, EDMS 1771639

Measured Transfer Functions

Microphonics


RF-FDBK is ON (Vcrab1:1.1 MV)






RF Dipole Development

- The horizontal version (RFD) cavity fabrication in full swing at CERN for its installation in 2021-22
- The HL-LHC series production is launched with Canada/US/UK and industrial partners to produce a total of 10 modules by 2024-25





RFD Cryomodule (CERN+UK)



CERN

I-IHC PROJE

Cryostating in the UK

Final Comments

- SPS tests with Crab Cavities
 - SPS-DQW experience was invaluable for both hardware and beam validation "almost" LHC like environment
 - Several operational aspects will be fine-tuned during 2021-23. Scrubbing will be needed before MDs
 - The next prototype module (RFD) fabrication progressing well. Series for HL-LHC is now launched
- The SCRF infrastructure in SPS-LSS6 is unique can could serve for future studies (for ex: PBC)
- Special thanks to our collaborations (UK & US) who played a critical part in the SPS success



Thank You !







https://videos.cern.ch/record/ (2631455, 2631454, 2630818)

Backup




Vertical Cavity Tests (6 Cavities)

Nominal Spec $V_{kick} = 3.4 \text{ MV}$

		DQW #1 (CERN)	DQW #2 (CERN)	DQW #1 (USLARP)	DQW #2 (USLARP)	RFD #1 (USLARP)	RFD #2 (USLARP)
Max Volt	[MV]	5.04	4.8	5.8	5.3	5.0	5.75
E_p, B_p [MV/m, mT]		56, 109	54, 103	65, 125	59, 114	42, 73	56, 96
R_s min	[nΩ]	10	10	9	9.5	11	7.6
<i>R_s</i> , 3.4MV	[nΩ]	15	18	15	17	13	8.2
Max Volt with HOM	[MV]	3.3*	-	-	4.7	-	5.5

* Voltage limit for SPS-DQW with HOMs due to inadequate BCP of HOMs





USLARP DQW & RFD



38

Summary of SPS-test Experience

- Bare cavity performance is +50% of the nominal voltage
 - In SM18 dressed cavities exhibited limit ~3MV, now understood
 - Performance of the SPS-test module limited to 1MV for machine developments, 2MV stable
- First crabbing of protons demonstrated. Main aspects such as transparency, beam loading, emittance growth, crab dispersion and other aspects studied – no show stopper
- Several hardware limitations: direct beam coupling, pondermotive instabilities, RF non-linearity at low power, RF/Cryo/Vacuum stability beyond 2MV..
- Consolidation of SPS test stand underway during LS2 with 2021 operation of DQW and 2022 RFD



Ramp to 270 GeV


Vertical tune: $Q_{\gamma} = 0.18$

RF Freq: Cavity 1: 400.787 MHz (~1 MV) Cavity 2: 400.528 MHz (almost zero)

Resonant excitation observed as we cross the vertical tune (black dotted lines).


Kicking the beam at 270 GeV equivalent frequency , while sweeping the beam frequency from 26-270 GeV

After setting the correct cycle start voltage to 270 GeV equivalent, beam circulated w/o any issue





Transparency Tests



HILUMI CERN