CEC-ICMC 2017 - Abstracts, Timetable and Presentations



Contribution ID: 580

Type: Contributed Oral Presentation

Development of NbTiN based multi-layered structures for SRF applications

Monday 10 July 2017 12:30 (15 minutes)

Theoretical interest has stimulated efforts to grow and characterize thin multi-layer superconductor/insulator/superconductor (SIS) structures for their potential capability of supporting otherwise inaccessible surface magnetic fields in SRF cavities. The technological challenges include realization of high quality superconductors with sharp, clean, transition to high quality dielectric materials and back to superconductor, with careful thickness control of each layer. Choosing NbTiN as the first candidate material, we have developed the tools and techniques that produce such SIS film structures and have begun their characterization. Using DC magnetron sputtering and HiPIMS (high power impulse magnetron sputtering), NbTiN and AlN can be deposited with nominal superconducting and dielectric parameters. Hc1 flux penetration field enhancement is observed for NbTiN layers with a Tc of 16.9 K for a thickness less than 150 nm. The optimization of the thickness of each type of layers to reach optimum SRF performance is underway. This talk describes this work and the rf performance characteristics observed to date.

Authors: VALENTE-FELICIANO, Anne-Marie (Jefferson Lab); EREMEEV, Grigory (Jefferson Lab); Prof. LUKASZEW, Rosa; Dr REECE, Charles (JLab); BEEBE, Melissa

Presenter: VALENTE-FELICIANO, Anne-Marie (Jefferson Lab)

Session Classification: M1OrD - Focused Session: Superconducting Thin Films for SRF and Magnets Applications