



Managed by Fermi Research Alliance, LLC for the U.S. Department of Energy Office of Science

Design of the cryogenic systems for the Near and Far LAr-TPC detectors of the Short-Baseline Neutrino program (SBN) at Fermilab

Michael Geynisman for Fermilab and CERN SBN Collaboration

CEC / ICMC 2017

12 July 2017



CEC / ICMC 2017




Outline:




- Introduction
- Design requirements for SBND and SBN-FD cryogenic systems
- Description of cryogenics and design solutions for SBND and SBN-FD
- Present state and conclusion



The Short-Baseline Neutrino (SBN) physics program at Fermilab and Neutrino Platform (NP) at CERN are parts of the international Neutrino Program leading to the development of Long-Baseline Neutrino Facility/Deep Underground Neutrino Experiment (LBNF/DUNE) science project. When operated, neutrinos created by the Fermilab beamline will pass the DUNE Near detector at Fermilab and then travel 1300 km to intercept DUNE's TPC based far detector at the Sanford Lab. The detector will be installed in caverns at about 1.5 km below the surface.










SBN: Three LAr-TPC detectors positioned along BNB at Fermilab



Highlights:

- Different design of cryostats => specific requirements for the SBN building facilities and SBN cryogenic systems
- Collaboration CERN <--> INFN <--> Fermilab while using different approaches for deliverables

			Fermilab-CERN- SBN Far	CERN Proto Dune SP	CERN 6 x 6 x 6
		Fermilab-CERN SBN Near			
	Fermilab 35 T		760 T 2018	676 T 2018	676 T 2018
CERN 1 x 1 x 3		270 T 2019			DUNE
	35 T operational				
26 T Cool down					4 x 17100 T First cryostat 2024

The main design requirement -> electron lifetimes in argon in excess of 3 milliseconds:

$$\tau [ms] \approx \frac{300 [ms \cdot ppt \text{ Oxygen Equivalent}]}{\rho [ppt \text{ Oxygen Equivalent}]} > 3 \text{ ms} \Rightarrow \rho < 100 \text{ ppt (10-10 parts)}$$

Problem: Commercial argon ~ 1 ppm, plus outgassing and back-diffusion

Solution: Filtration of O₂ and H₂O while transfer of LAr from storage to cryostat, plus continuous recirculation of LAr volume of cryostat with cryostat volume change every 5-8 days

Additional main requirements:

- Argon losses to atmosphere should be minimized to reduce re-filling
- Temperature difference over the detection volume shall be limited to have a uniform reaction over the sensitive volume
- Operating pressure should be tightly controlled

Design requirements for SBN cryogenic systems

Requirements and Specification: SBND	Value
Cryostat type and size	Membrane (GTT) with self-supported steel structure 5.202 m x 5.423 m x 7.027 m, ~270 tons (~2% ullage) Gas purge for insulation space
Verifiable contamination for LAr delivery	$O_2 < 1$ ppm, $H_2O < 1$ ppm, $N_2 < 2$ ppm
LAr purity in cryostat	> 3 ms electron lifetime (< 100 ppt O_2 equivalent)
Nitrogen contamination	< 2 ppm
Design Pressure	Internal 345 mbarg (~5 psig), external 50 mbar
Operating gas pressure	70 mbar (~1 psig) with +/- 5%
Initial purification technique	GAr Piston purge with rate of rise 1.2 m/hr
Cooldown technique	LAr spray with GAr and GAr momentum (< 10 -15 K/hr)
TPCs cool-down rate restriction	< 40 K/hr, < 10 K/m (vertically)
LAr recirculation rate	2.5 – 8.0 m ³ /hr (10 – 35 gpm)
Number of side/bottom penetrations	1 (use of Protego© internal valve or external safety valves)
Included subsystems	LAr and LN2 storage and transport, O_2 - N_2 - H_2O contamination monitoring, LAr and GAr recirculation and filtration, GAr condensing and recovery, safety and controls
Grounding and noise requirement or external equipment	Electrical isolation of noise from cryostat and its electronics

Design requirements for SBN cryogenic systems


Requirements and Specification: SBN-FD	Value
Cryostat type and size	Dual aluminum vessels with common LN ₂ shields within a warm self-standing steel structure with GTT-style insulation 3.600 m x 19.600 m x 3.900 m, ~380 tons each (~2% ullage) Gas purge for insulation space
Verifiable contamination for LAr delivery	O ₂ < 1 ppm, H ₂ O < 1 ppm, N ₂ < 2 ppm
LAr purity in cryostat	> 3 ms electron lifetime (<100 ppt O ₂ equivalent)
Nitrogen contamination	< 2 ppm
Design Pressure	Internal 345 mbarg (~5 psig), external up to 1 barg
Operating gas pressure	150 mbar (~2 psig) with +/- 5%
Initial purification technique	Pump down to full vacuum
Cooldown technique	Initial with LN ₂ shield, final with LAr fill at 2 K/hr
TPCs cool-down rate restriction	< 70 K/hr, < 50 K/m (vertically)
LAr recirculation rate	2.5 – 8.0 m ³ /hr (10 – 35 gpm)
Number of side/bottom penetrations	1 side and 1 bottom (per cryostat) (use of external safety valves)
Included subsystems	LAr and LN ₂ storage and transport, O ₂ -N ₂ -H ₂ O contamination monitoring, LAr and GAr recirculation and filtration, GAr condensing and recovery, safety and controls
Grounding and noise requirement or external equipment	Electrical isolation of noise from cryostat and its electronics


As Fermilab and CERN engage in SBN partnership, an agreement has been established for naming cryogenic sub-systems, some of which are deliverables of Fermilab and some are deliverables of CERN.


Deliverables Institutions	SBND				SBN-FD			
	Internal Cryo	Proximity Cryo	External Cryo	Cryogenic Controls	Internal Cryo	Proximity Cryo	External Cryo	Cryogenic Controls
CERN		X				X		
Fermilab	X		X	X			X	X
INFN					X			

To satisfy design requirements, the following modes of operations are implemented:


Mode of Operation	SBND (membrane cryostat)	SBN-FD (aluminum vessels)
Initial cleanup	Piston purge with gaseous argon to remove the initially present air	Pump down to full vacuum for up to 90 days
Final cleanup	Internal circulation via a membrane pump through a commercial room temperature purification system	None
Cooldown	Spray with commercial grade argon through spray nozzles with GAr and GAr momentum (< 10-15 K/hr)	Initial with LN2 shield, final with LAr fill at 2 K/hr
Fill	From LAr storage dewar with commercial grade argon and re-condensing with LN ₂	From LAr storage dewar with commercial grade argon and re-condensing with LN ₂
Purification	Circulation by LAr pumps through specially developed externally located purifiers consisting of volumes filled with molecular sieve, which will adsorb the eventual water traces present in the argon flow, and active copper pellets which will chemically react with the diminish the oxygen equivalent contamination from the low parts per million to the parts per trillion level.	Circulation by LAr pumps through specially developed inline purifiers consisting of removable cartridges filled with molecular sieve, which will adsorb the eventual water traces present in the argon flow, and active copper pellets which will chemically react with the diminish the oxygen equivalent contamination from the low parts per million to the parts per trillion level.
Normal operation	<ul style="list-style-type: none"> • Maintaining level by adding condensed GAr • Maintaining pressure by rate of condensing GAr boiloff • Maintaining purity by recirculating and filtering LAr 	<ul style="list-style-type: none"> • Maintaining level by adding condensed GAr • Maintaining pressure by rate of condensing GAr boiloff • Maintaining purity by recirculating and filtering LAr
Regeneration of filters	Regeneration filters in place with heated GAr / 2.5% H ₂ mix	Regeneration removed cartridges with heated GAr / 2.5% H ₂ mix









Typical P&ID Proximity, External




Typical P&ID Proximity, External




Typical Design: Condenser-Filter



Typical Design: LAr pump, External filter




 **DEMACO**
Courtesy of Demaco




 **DEMACO**
Courtesy of Demaco

Side penetration: Protego®




Internal cryogenic system for SBND


- Connecting interfaces
- Support of internal piping
- Design based on modeling
- SBN Cooldown - CFD Simulation



Frame Temperature @ 106 minutes




Integration: SBND



Integration via:

- Physical interfaces
- Management of space
- Installation
- Validation for safe operations

Integration: SBN-FD



Integration via:

- Physical interfaces
- Management of space
- Installation
- Validation for safe operations



Conclusions:

- Fermilab has already added two new neutrino detector buildings to the Neutrino Campus at Fermilab.
- Equipment for External cryogenics is beginning to populate SBND and SBNFD (in-house designed and constructed)
- The Proximity cryogenics are being designed and constructed in Europe.
- The commissioning of the cryogenic systems is scheduled for 2018 (SBN-FD) with SBND following.
- Many of the design solutions will be tested for SBN cryogenics to validate design of the cryogenic system for the LBNF/DUNE project.