



- Initial Layout
 - Initial Concept Based On
 - SSU, RF, FC, Primary Absorber, FC, RF, Secondary Absorber, 4 Station Tracker
 - Use current PRY (slight modifications)




- Initial Layout
 - PRY Changes
 - Move downstream endplate 55 mm
 - Slot middle & add removable close-out for RF coupler clearance & RF device removal






- Initial Layout
 - SS mount frame
 - Rail & carriage system for devices






- Initial Layout
 - New builds
 - 4 station tracker (G.Barber)
 - Primary absorber
 - Secondary absorber mount











WICE VALUE OF THE PARTY OF THE

Tracker Position







Tracker Position






- Possible Changes
 - Thin the secondary absorber assembly (countersunk screws)
 - Optimise the secondary absorber mount vessel & absorber position
 - Thin the connector between the FC & the RF
 - Move tracker in











- Possible Changes
 - Result of ~ small changes





Possible Changes - Limitation




This would need a small amount extra taken from the cut & the infill piece extended

*Current cut to be approved (S Plate)



TICE TO SERVICE TO SER

- Possible Changes Limitation
 - Extend cut



Putting back in 30 mm clearance the RF device could be moved a further ~ 80 mm

*Subject to engineering approval (S Plate)





Possible Changes – Moving FC

