

The Development of the Global Feature eXtractor (gFEX) for ATLAS Level 1 Calorimeter Trigger at the LHC

Shaochun Tang

On behalf of the ATLAS collaboration

Brookhaven National Laboratory, Upton, NY, 11973, USA



BROOKHAVEN
NATIONAL LABORATORY



Abstract

As part of ATLAS Phase-I Upgrade, the gFEX is designed to help maintain the ATLAS Level-1 trigger acceptance rate with the increasing LHC luminosity. The gFEX identifies patterns of energy associated with the hadronic decays of high momentum Higgs, W, & Z bosons, top quarks, and exotic particles in real time at the 40MHz LHC bunch crossing rate. The prototype v1 and v2 were designed and fully tested in 2015 and 2016 respectively. A pre-production gFEX board has been manufactured, which is an ATCA module consisting of three UltraScale+ FPGAs and one ZYNQ UltraScale+, and 35 MiniPODs are implemented in an ATCA module. This board receives coarse-granularity (0.2x0.2) information from the entire ATLAS calorimeters on up to 300 optical fibers and 96 links to the L1Topo at the speed up to 12.8 Gb/s.



Motivation of gFEX



gFEX will be installed during the Phase-I upgrade (2019 – 2020), and will be used for triggering from 2021 onwards.



- ❑ High p_T bosons and fermions are a key component of ATLAS physics.
 - W, Z and H bosons, top quarks and exotic particles
 - Many analyses with boosted objects
- ❑ Analyses that addresses this physics use large R jets with $R > 1$
- ❑ Adding the gFEX, we can accept the boosted objects.

gFEX Prototype v2 Design




- ✓ Optical links interface with LAr LDPS and L1Topo are implemented
- ✓ MGT links and GPIOs for inter-FPGA communications
- ✓ 26-layer PCB with low loss material (Megtron-6) and back-drill for improved signal integrity

Evaluation Test at BNL



- ❑ All functions (JTAG, SD/QSPI boot, GbE, I2C, and Clock, etc.) are verified successfully
- ❑ MGTs speed test - All optical links are stable at 12.8Gb/s and all onboard electrical link are stable up to 25.6 Gb/s
- ❑ Nine groups of GPIOs are running at 1.12 Gb/s with good margin (>60%)

Link Speed Test at CERN



FOX: Fiber-Optic eXchange
FELIX: Front-End Link eXchange (Readout Link)
LDPB: LAr Digital Processing Blade
TTC: Timing, Trigger and Control


- 48 links between LDPB and gFEX are successfully tested simultaneously at following conditions.
 - a. Link speeds at 6.4/9.6/11.2 Gb/s
 - b. One or two stages of FOX
 - c. TTC clock from FELIX

gFEX Prototype v2 and FELIX Integration Test





The gFEX and FELIX integration test was carried out before the final design review.

- ❑ gFEX uses the recovered TTC clock from FELIX link as its system clock. Jitter cleaner (Si5345) is used to improve the clock quality.
- ❑ 4 links between gFEX ZYNQ FPGA and FELIX
RX Links: fixed low latency GBT mode (4.8Gb/s)
TX Links: FULL mode
- ❑ The links from FELIX to gFEX can work well in latency-fixed GBT mode. The latency is 87.3 ns for FEC mode, and 79 ns for Wide-Bus mode.
- ❑ The links from gFEX to FELIX can work well in FULL mode.
- ❑ With the recovered TTC clock, the GTH can work well at link speed of 12.8 Gbps, and the GTY work well at 25.6 Gbps.




gFEX Prototype v3 Design



- Comparing to the v2 board, the major changes are shown as below.
- ❑ ZYNQ → ZYNQ Ultrascale+;
 - ❑ 8 Gb DDR3 DRAM → 16GB DDR4 DIMM
 - ❑ XCVU160 → Vertex Ultrascale+ FPGA XCVU9P
 - ❑ Add 5 more TX MiniPODs and 2 RX MiniPODs
 - ❑ Only ZYNQ Ultrascale+ FPGA interface to FELIX, while all four FPGAs will interface to L1Topo
 - ❑ DC/DC converter from 400W → 500W version.
 - ❑ Stack up 26 layers → 30 Layers.

gFEX Prototype v3 function test at BNL



Evaluation test of gFEX prototype v3 has been carried out at BNL. For the first assembly, two FPGAs are installed for verification.

- ❑ Basic functionalities of 2 FPGAs have been verified successfully, such as ZYNQ Ultrascale+ interfaces, DDR4, GbE, UART and I2C monitoring.

- ❑ Link speed test for two FPGAs. All the optical links are stable at 12.8Gb/s and the onboard electrical GTY links are stable at 25.6 Gb/s.
- ❑ Parallel data buses are running up to 1.12Gb/s with good margin (>60%).

Summary and Conclusion

- ❑ The gFEX prototype v2 has been used to test all the challenging hardware technology successfully, such as 12.8 Gb/s optical links, 25.6 Gb/s on board electrical links, and 1.12Gb/s on board parallel data buses.
- ❑ The gFEX prototype v2 has been used in the link speed test, FELIX integration test, and gFEX firmware development.
- ❑ The partial assembled gFEX prototype v3 board has been tested successfully with all the functionalities and performance.
- ❑ Another fully assembled v3 board will be tested and used for the integration test at USA-15 at CERN in 2018.