PSD11: The 11th International Conference on Position Sensitive Detectors



Contribution ID: 71

Type: Poster

Modeling Radiation Damage to Pixel Sensors in the ATLAS Detector

Thursday, 7 September 2017 12:40 (1h 50m)

Silicon pixel detectors are at the core of the current and planned upgrade of the ATLAS detector at the Large Hadron Collider (LHC). As the closest detector component to the interaction point, these detectors will be subjected to a significant amount of radiation over their lifetime: prior to the High-Luminosity LHC (HL-LHC), the innermost layers will receive a fluence in excess of 1015 neq/cm2 and the HL-HLC detector upgrades must cope with an order of magnitude higher fluence integrated over their lifetimes. Simulating radiation damage is critical in order to make accurate predictions for current future detector performance that will enable searches for new particles and forces as well as precision measurements of Standard Model particles such as the Higgs boson. We present a digitization model that includes radiation damage effects to the ATLAS pixel sensors for the first time and considers both planar and 3D sensor designs. In addition to thoroughly describing the setup, we present first predictions for basic pixel cluster properties, alongside early studies with LHC proton-proton collision data.

Primary author: TRONCON, Clara (Milano Universita e INFN (IT))Presenter: TRONCON, Clara (Milano Universita e INFN (IT))Session Classification: Poster session