

# Injection and Top-Up experience at SOLEIL

A. Loulergue  
and Source & engineering division

Topical Workshop on Injection  
and Injection systems

HZB / BESSY II – Berlin  
27-30 August 2017



# Outline


- Top-Up overview at SOLEIL
- Residual bump corrections from pulsed elements
- Conclusion





# Different filling patterns



Top-Up operated since 2009




# Different filling patterns



Good flat shape linac pulse  
100 bunches / 300 ns

3 Hz booster power supplies  
ramped up and down over 10 s



# Top-Up operation survey

Before injection sequence checks :


Machine PSS

Machine interlock

Injector status

As well as the last injection  
Efficiencies



Manage the different ring filling  
patterns



# Top-Up operation survey


Uniform 500 mA

Hybrid 445 + 5 mA




Filling current control quarter to quarter  
Refill the lowest one

# Top-Up operation



Typically 2 mA every 3 mn  
Current stability below  $\pm 0.2 \%$

# Top-Up operation



Current stability below  $\pm 0.2\%$

Constant thermal load on beam-line optics

Mirror alignment, thermal optical bumps, ...

Constant thermal load on accelerator equipments.

Reduction of thermal drift on BPM electronics.

Only way to reach sub micron stability level


But Not suitable for all user needs (long integration time, image scanning, ...)



Very significant improvement for the data quality recorded at the SMIS IR-beamline. This results in an increase of the S/N of the spectra by a factor between 12 and 15!


# Users Top-Up operation over 6 days

450 mA hybrid mode




# Top-up efficiency and MTBF

When the stored current drops below 0.5 mA from the nominal value



# Ring injection layout

Inserted in free 12m long section




**Thin Septum :**  
Full sine wave  
120  $\mu$ s  
400 mT  
In vacuum Eddy  
current septum  
3 mm thick  
20 mm from axe

**Thick Septum :**  
Half sine wave  
3.3 ms  
1 T

**Kickers :**  
Half sine wave  
7  $\mu$ s (6 turns)  
120 mT

# Thin Septum H & V residual bump



**Initial** : Half sine wave, no shielding

**Step 1** : Change the pulse profil from an half sine to a full sine wave

*Gain = a factor of 2*

**Step 2** : Adapt a shield screen over the complet SR inner chamber including the pumping outlet



Magnetic alloy : SuperImphy of 0.5 mm thickness

*Gain=a factor of 100*

=> Residual stray field reduced from 400  $\mu\text{Tm}$  to  $\sim 2$   $\mu\text{Tm}$  (Mag. Meas.)

=> Residual orbits  $\sim$  cancelled

# Thick Septum H & V residual bump



2009 Bump reduced by means of  $\mu$ -metal and grounded upstream Eddy current.

A last pass in 2015 grounding downstream the Eddy current.

$\beta_x = 14 \text{ m @ BPM (long straight)}$

$\sigma_x = 320 \text{ } \mu\text{m @ 4 nm.rad}$


$20 \text{ } \mu\text{m} \Rightarrow \sim 6\% \text{ of } \sigma_x \Rightarrow \text{Below } 10 \%$

$\beta_z = 12 \text{ m @ BPM (long straight)}$

$\sigma_z = 20 \text{ } \mu\text{m @ K=1\%}$

$5 \text{ } \mu\text{m} \Rightarrow \sim 25\% \text{ of } \sigma_z \Rightarrow \text{Still larger than } 10\%$

# Kicker pulse profile investigation



## Beam Based turn by turn data analysis :

Get the differential ( $x, x', z, z'$ ) induced by the 4 kickers at each turn on a set of BPMs

Fit the differential kickers profiles in both planes


Repeat with different timing (circulating beam vs kicker) to sample the pulse profile measurements

# Kicker pulse profile investigation


Without any BPMs in between the kickers, it is not possible to distinguish the 4 kickers, there is only 2 unknowns per plane :

==> Fit the mean profile of K1 K2 and K3 K4

Exemple of different mis-matching kicker pulse :  
Voltage  
Timing  
duration



# Kicker pulse profile investigation



Exemple of kickers matching process by step


*Ring filled with 1 quarter  
Kicker pulse duration over 6 turns*

Voltage correction

Timing correction

Need duration correction  
==> Pulsers modification

# Kicker pulse profile investigation



Optimization based on :  
Saturating self  
Parallel capacitor


2007 optimization  
30  $\mu\text{rad}$  residual kicker deviation  
0.5% from max deviation



factor 2 to 3 gain


2009 optimization  
10  $\mu\text{rad}$  residual kicker deviation  
0.2% from max deviation

# Kicker pulse profile investigation



$\beta_x = 14 \text{ m}$  @ BPM (long straight)  
 $\sigma_x = 320 \mu\text{m}$  @ 3.7 nm


$70 \mu\text{m}$  rms  $\Rightarrow \sim 20\%$  of  $\sigma_x \Rightarrow$  Still larger than 10%



$\beta_z = 12 \text{ m}$  @ BPM (long straight)  
 $\sigma_z = 20 \mu\text{m}$  @ K=1%

$40 \mu\text{m}$  rms  $\Rightarrow \sim 200\%$  of  $\sigma_z$   
 $\Rightarrow$  Very large !

# Kicker pulse profile investigation



The perturbation times appears to be much larger than the kicker pulse....

# H & V residual bump

## *Summarized*

Bumps measured at BPM with  $\beta_x = 14$  m and  $\beta_x = 12$  m  
Target = 10 % beam size (with 1% coupling) !

Plane	H	V
<b>Target</b>	<b>~30 <math>\mu</math>m</b>	<b>~2 <math>\mu</math>m</b>
Thin septum	~0	~0
Thick septum	20 $\mu$ m	5 $\mu$ m
Kickers	100 $\mu$ m	50 $\mu$ m
		
To reduce it further :	Need a NLK	NLK ? Need feedforward /feedback ?

# Conclusion

## Top-Up operation :

- Fully operated since 2009 in all filling pattern modes
- Since 2011, the Top-Up efficiency is about 99.5 %
- Provides a good beam stability (constant thermal load)
- Pre-injection signal gating provided to the beamlines (long integration times)

## Residuals Orbits / Oscillations

- We have still about 20% in Hor. and 200% in Vert. plane beam size perturbations
- Beamlines presently don't complain from these perturbations
- A NLK (à la BESSY) is under construction in the frame of SOLEIL / MAXIV collaboration. Installation is planned in 2018.
- A feedforward (feedback?) will be necessary, at least in the vertical plane, to reduce these oscillations toward 10% beam size : under investigation

Thank you for your  
attention