

The AWAKE Electron Line Beam Position Monitors

Benjamin Moser BI-ML




Content

- What is AWAKE
- Experiment set up
- BPMs for electron beam
- BPM tests
- Electronics for BPM




AWAKE site






AWAKE site






The Advanced Proton Driven Plasma Wakefield Acceleration Experiment






AWAKE Ingredients

- Plasma
- LASER beam
- Proton beam
- Electron beam






Experiment set up









Proton beam	
Momentum	400 GeV/c
Protons/bunch	3 E11
Bunch length	σz=0.4 ns (12 cm)
Bunch size at focus	σ*x,y= 200 μm



Experiment set up








BPMs for electron beam

- Shorted stripline BPMs
- Designed and manufactured by TRIUMF for ARIEL their own LINAC
- Design modified to fit our requirements
- Electronic will also be supplied by TRIUMF
- Electronics modified to adapt to single bunch mode
- Two different Diameters for two different lines














Tests before installation




- Electrical offset and sensitivity measured at TRIUMF during production
- Vacuum leak tested at TRIUMF before shipping
- Vacuum acceptance test done at CERN
- Metrology measurements done at CERN








Collaboration with MSC-MNC






Corrector magnet

BPM



Test of prototype BPMs



 One prototype BPM Ø40mm was installed in CALIFES and tested with electrons Summer 2016

 One prototype BPM Ø60mm was installed and tested with protons December 2016



Electronics for BPM

- Working Frequency of 404MHz for electron line BPMs
- Working Frequency of 4-5GHz for last two BPMs on common line
- Protection against proton induced signal of ~100V is worked on by TRIUMF.






Electronics for BPM

 Rack will be installed in the Tunnel system

Input signal from BPM

404MHz Calibration

TRIUMF Cables




4.5GHz Local Oscillator and calibration

430MHz Local Oscillator




Electronics for BPM 404MHz





Electronics for BPM 404MHz





6/28/2017

-6000

180

200

220

240

260


Proton beam measured December 2016

Test of prototype BPM in CALIFES

Electronic noise found, understood to be 110V/220V AC power supply issue

Cavity BPM data: ~ 30-50µm noise/jitter

Stripline BPM: 200-300 µm noise






Test of prototype BPM in CALIFES

- Electron beam measurements at 404MHz
- 100pC bunch charge was used
- Horizontal resolution of 4.3µm

Vertical resolution of 7.8µm





Electronics for BPM 4-5GHz


Idea is measuring the position of the electrons with protons present

Different frequency spectrums related to bunch lengths allows to use frequency separation

Test at 2GHz gave inconclusive results

Expected electron beam spectrum


Bunch spectrum for AWAKE proton beam measured in SPS



Expected proton beam spectrum




Electronics for BPM 4-5GHz





Test of prototype BPM in AWAKE

- Proton measurements at 400MHz with a 40dB attenuator
- Measurements performed remotely from Vancouver.
- Beam trigger delay was found to be 84 us.
- Large X and Y position fluctuations correspond to missed extractions
- Y position p-p fluctuation is less than 50 um, while X is less than 200 um.





Current status

 All 5 BPMs on the Common line are installed

 BPMs on the electron line will be installed July 2017

 TRIUMF will install the electronics August 2017





Acknowledgments

- TRIUMF
- AWAKE
- Lars Søby
- Stefano Mazzoni



