



Impressions of the M2 beam line

Future of the M2 beam at CERN in the Physics Beyond Colliders Context


Johannes BERNHARD, Dipanwita BANNERJEE, Eva MONTBARBON, Lau GATIGNON
CERN EN-EA

19.03.2018



ENGINEERING
DEPARTMENT


IWHSS 2018
Bonn (Germany), 19 – 21 March 2018



Contact: Johannes.Bernhard@cern.ch

Agenda

- The “Physics Beyond Colliders” Initiative
- North Area Consolidation
- The M2 Beam and Future Options
- 2018 Test Beams in EHN2
- Summary and Outlook



<http://pbc.web.cern.ch/>

Physics Beyond Colliders – Introduction

- Extrapolatory study aiming at exploiting the full scientific potential of CERN's accelerator complex and its scientific infrastructure through projects complementary to the LHC, HL-LHC and other possible future colliders
- Projects targeting fundamental physics questions that are similar in spirit to those addressed by high-energy colliders, but that require different types of beams and experiments
- Initiated by CERN director-general and coordinated by J. Jaeckel, M. Lamont and C. Vallee (chair)
- Kick-off workshop (September 2016) identified a number of areas of interest, revisited at Annual Workshop (November 2017)
- Working groups in full-swing to pursue studies in these areas
- PBC study remains open to further ideas for new projects


Physics Beyond Colliders – Physics

Physics Groups


- **BSM subgroup:** SHIP; NA64++; NA62++; KLEVER; IAXO; LSW; EDM; REDTOP
- **QCD subgroup:** *COMPASS*++; μ -on-e; LHC FT (gas target + crystal extraction); DIRAC++; NA60++; NA61++

Deliverables:

- Evaluation of the physics case in the worldwide context
- Possible further detector optimization
- For new projects: investigation of the uniqueness of the CERN accelerator complex for their realization



Accelerator Working Group



Conventional Beams – Projects

Under consideration at present:

- NA62: Proposal to operate in beam-dump mode (HNL, axions)
- NA64⁺⁺: High intensity electron, muon and hadron beams for dark sector searches (A')
- K_L EVER: High intensity K_L beam (high flux, pencil beam, new target) for rare decays, in particular $K_L \rightarrow \pi \nu \nu$
- ***COMPASS⁺⁺: RF separated beams for hadron structure and spectroscopy; proton radius measurement with muon beam***
- μ -on-e: 150 GeV muon beams for high precision measurement of hadron vacuum polarisation for g-2 of the muon
- DIRAC⁺⁺: DIRAC@SPS for high statistics of mesonic atoms
- NA60⁺⁺: Heavy ion beams for di-muon physics and open-charm
- NA61⁺⁺: Higher intensity ion beam for open-charm studies

Conventional Beams – Structure

CONVENTIONAL BEAMS WORKING GROUP

Conveners: L.Gatignon, M.Brugger

Members: Experiments, H.Wilkens, G.Lanfranchi, T.Spadaro,
EA physicists, HSE, RP, EL, CV, RF, STI

CBWG-ECN₃

Convener: L. Gatignon

- K_LEVER
- NA62 Dump
- NA60
- DIRAC

CBWG-EHN₂

Convener: J. Bernhard

- COMPASS
(μ , RF-separated
and low energy
pbar beams)
- μ -on-e
- NA64- μ
- CEDAR project

CBWG-EHN₁

Convener: N. Charitonidis

- NA61
- NA64 hadrons

Main deliverable: Conceptual Design Report by end of 2018


EHN₂ Working Group



- Work Breakdown Structure (top level)
 - WP₁: Muon beams post 2020
 - WP₂: Hadron and Electron beams post 2020
 - WP₃: RF-separated beams
 - WP₄: Beam Particle Identification (dedicated meetings, WP leader S.Mathot/EN-MME)
- One project associate (full-time) and since March 2018 one fellow (part-time) for studies plus additional resources for WP₄
- User presentations for technical details and plans completed, user requirements document prepared
- Several studies launched
- Track progress by continuous reporting, about one WG meeting per month

EHN₂ Working Group – WP₄

- CEDAR thermal housing completed (main deliverable WP₄)
- Duct works being finalised and system being commissioned
- System ready for 2018 physics run




North Area Consolidation – Safety

EHN1

- Flammable gas detection (2018 & LS2)
- Fixed ODH & CO₂ detection (2018 & LS2)
- SUSI for underground galleries (LS2)
- ZORA for underground galleries(post-LS2)

ECN3

- Flammable gas detection (update tbc)
- Fixed ODH detection (update tbc)
- RP buffer zone (2018)



Overall NA buildings

(TDC₂, TCC₂, TCC₈, TT's, EHN1&2, ECN₃)

- Fire Detection Sectorisation Survey (YETS 2017/18)
- RP monitoring upgrade (LS2)
- Renovation of the Fire Detection & Evacuation Alarm (post –LS2)
- Renovation of the Beam Imminent Warning & Evacuation Alarm (post LS2)

EHN2

- SUSI to access building (YETS)
- Flammable gas and ODH detection (LS2)
- ZORA for underground galleries (post-LS2)
- RP buffer zone (2018)

Courtesy: Y. Kadi, F. Gautheron


North Area Consolidation

EHN₂

- SM₂ power converter upgrade (completed)
- Chilled water consolidation (pipework) => 2018, LS₂ + post-LS₂
- Roof renovation for water tightness => LS₂
- BA's sectional & personal doors => LS₂

Beam Instrumentation

- XBPF beam profile monitors (SciFis)



Further Works

- Gas Network renovation (2018 + LS₂)
- Cranes and lifts renovation (LS₂ + post-LS₂)
- Consolidation of TCC₂/TCC₈ target => YETS
- Thermal/FEM studies of primary target and TAX => 2018 & LS₂
- Cooling Tower 2 works (2018+YETS)

Courtesy: Y. Kadi, F. Gautheron

The M2 Beam

Three main operation modes:


- High-energy, high-intensity muon beam. Normally for muon momenta up to 200 GeV/c. Higher momenta up to 280 GeV/c are possible, but the flux drops very rapidly with beam momentum.
- High-intensity secondary hadron beam for momenta up to 280 GeV/c with radiation protection constraints.
- Low-energy, low-intensity (and low-quality) in-situ electron calibration beam.

| Beam Mode | Momentum (GeV/c) | Max. Flux (ppp / 4.8s) | Typical $\Delta p/p$ (%) | Typical RMS spot at target | Polarisation | Absorber (9.9 m Be) |
|-----------|--------------------------|---|--------------------------|----------------------------|--------------|---------------------|
| Muons | +208/190 +172/160 | $\sim 10^8$ $2.5 \cdot 10^8$ | 3% | 8 x 8 mm | 80% | IN |
| Hadrons | +190 -190 Max. 280 | 10^8 (RP) $4 \cdot 10^8$ (with dedicated dump) | - | 5 x 5 mm | - | OUT |
| Electrons | -10 to -40 | $< 2 \cdot 10^4$ | - | $> 10 \times 10$ mm | - | OUT |

The M2 Beam – Parameters and Principle


| Beam Parameters for COMPASS | Measured |
|---|---------------------|
| Beam momentum p_μ/p_π | 160 / 172 GeV/c |
| Proton flux on T6 per SPS cycle | $1.5 \cdot 10^{13}$ |
| Muon flux at COMPASS per SPS cycle | $2.5 \cdot 10^8$ |
| Beam polarisation | $-80\% \pm 4\%$ |
| Spot size at COMPASS target ($\sigma_x \times \sigma_y$) | 8mm x 8mm |
| Divergence at COMPASS target ($\sigma_{dx} \times \sigma_{dy}$) | 0.4mrad x 0.8mrad |
| Muon halo within 50mm from beam axis | 16% |
| Halo in experiment (6 x 4m ²) at $ x,y >150$ mm | 7% |

M2



RF-separated Beams

Reminder: Panofsky-Schnell-System with two cavities (CERN 68-29)



- Particle species have same momenta but different velocities
- Time-dependent transverse kick by RF cavities in dipole mode
- RF1 kick compensated or amplified by RF2
- Selection of particle species by selection of phase difference

$$\Delta\Phi = 2\pi (L f / c) (\beta_1^{-1} - \beta_2^{-1})$$
- For large momenta: $\beta_1^{-1} - \beta_2^{-1} = (m_1^2 - m_2^2) / 2p^2$

RF-separated Beams - Phases

For K^\pm beams: $\Delta\Phi_{\pi p} = 360^\circ$ and Φ_{RF2} such that both π and p go straight
i.e. dumped


$\Delta\Phi_{pK} = 94^\circ$, i.e. a good fraction of K outside the dump,
depending on phase at 1st cavity

For $p\bar{a}r$ beams: $\Delta\Phi_{\pi p} = 180^\circ$ and then $\Delta\Phi_{pe} = 184^\circ$, $\Delta\Phi_{pK} = 133^\circ$
with phase of $RF2$ such that pions go straight,
antiprotons get reasonable deflection, electrons are
dumped effectively and K reduced

RF-separated Beams

$$\Delta\Phi = 2\pi (L f / c) (\beta_1^{-1} - \beta_2^{-1})$$

$$\text{For large momenta: } \beta_1^{-1} - \beta_2^{-1} = (m_1^2 - m_2^2) / 2p^2$$




Example: input from CKM studies

- Kick: 15 MeV/c
- $f = 3.9$ GHz
- $dp/p = 2\%$
- $\Delta\phi_{\pi p} = \pi$ (pbar selection) / $\Delta\phi_{\pi p} = 2\pi$ (K selection)

CKM-based Example



$$\Delta\Phi = 2\pi (L f / c) (\beta_1^{-1} - \beta_2^{-1})$$

$$\text{For large momenta: } \beta_1^{-1} - \beta_2^{-1} = (m_1^2 - m_2^2) / 2p^2$$



Crab Cavities Example

Currently available technology at CERN: Crab Cavities for LIU SPS upgrade (400 MHz superconducting dipole cavities)



— $\Delta\phi = \pi$
 — $\Delta\phi = 2\pi$

Assume availability of $L=800\text{m}$:

| RF frequency | Limit p(K) | Limit p(pbar) |
|--------------|------------|---------------|
| 400 MHz | 20 GeV/c | 30 GeV/c |
| 1.3 GHz | 37 GeV/c | 55 GeV/c |


Conclusion: crab cavity design so far not compatible with user requirements, new developments necessary

RF-separated Beams – Hadron Section M2


Front-end

- Hadron section optimised for large acceptance
- About 100m necessary for front-end and momentum selection with goal to keep it for compatibility

HORIZONTAL:



VERTICAL:




RF-separated Beams – Absorber Region

Dispersion challenge


- To make use of the full length of the M2 tunnel, the beam needs to be adjusted vertically to the second slope with BENDS 4+5
- This introduces a new source of dispersion and thus needs to be compensated before the second cavity

HORIZONTAL PLANE :



Radiation Protection Considerations


- Intensity limitations: What can be gained with additional (roof) shielding for the beam line and/or a part of experimental set-up?
- To be studied (Summer Student project, new fellow)



Future Options for Experiments in EHN2


- Historically, EHN2 has already housed more than on muon beam experiment / set-up (e.g. NA2 + NA4, SMC + polarimeter)
- Most important WP₁ challenge: Will we be able to run μ -on-e or NA6₄ together with COMPASS?
- Main questions
 - Are the physics requirements compatible enough (e.g. beam momentum)?
 - Are the required intensities comparable?
 - Is there enough space?
- Need to study this from scratch

L. Gatignon, N. Doble et.al.,
NIMA 343 (1994) 351-362




Optics – Muon Section M2

- Focussing on targets non-trivial as the beam is not produced from a point-like source and has a relatively large $\Delta p/p$
- Important to know user requirements such as needed divergence and beam spot size to re-design the final focus




Future Options for μ -on-e in EHN2

- Entrance Area of EHN2
 - Pro: no interference with COMPASS spectrometer, enough space for full set-up
 - Con: needs many weeks change-over time, no installation of CEDARs possible, μ -on-e targets introduce multiple scattering
 - Compatibility with proton radius measurement depends on required beam quality and characteristics (energy, intensity, divergence)




Future Options for μ -on-e in EHN2

- Entrance Area of EHN2



Future Options for μ -on-e/NA64 in EHN2

- Downstream Area of EHN2
 - Pro: compatible with COMPASS running at the same time (able to use full COMPASS set-up)
 - Con: safety aspects (lock ABS in, no hadron beams), limited space, energy loss of muons in COMPASS could imply to re-measure momentum (i.e. another spectrometer magnet), re-/de-focusing of muons would imply 2-3 quadrupoles plus compensation of SM₁+SM₂ kick, thus an extension of the building




Future Options for NA64 in EHN2

- Installation inside SM2
 - Pro: compatible with COMPASS (able to use full COMPASS set-up)
 - Con: limited space, energy loss of muons within COMPASS, NA64 would need to invest in new non-magnetic calorimeter modules, change-over time




2018 Test Beams

- μ -on-e: Measure μ -e scattering on 2 target modules with Silicon instrumentation + 1 EM calorimeter. Total length 3m.
- Compass TPC: Measure μ -p scattering in high pressure TPC + Silicon telescope





2018 Test Beams

- Studies initialised due to parasitic nature of 2018 tests
- COMPASS has a physics program that uses the 190 GeV/c hadron beam mode with a dedicated hadron absorber
- Goal: Extrapolate muon beam through COMPASS set-up and assert widening of beam due to multiple scattering with HALO





2018 Test Beams

- Beam distribution at test location for muon beam configuration







- Beam momentum after passing hadron absorber




2018 Test Beams

- Beam divergence muon beam (after passing absorber)




2018 Test Beams

- Muon distribution at test location for 2018 190 GeV/c DY hadron beam



$$\sigma_x \times \sigma_y = 100 \text{ mm} \times 84 \text{ mm}$$





Momentum ~ 186 GeV/c

- Good news, still very useful for tests
- Flux for 10^{13} pot ~ 10^5 /spill (within 10cm x 10cm of beam axis)





2018 Test Beams

- Beam divergence of muons from DY hadron beam (after passing absorber)




2018 Test Beams

- A little extra output: Muon halo from for 2018 190 GeV/c DY hadron beam at the COMPASS target



Summary and Outlook

- The M2 beam at CERN continues to serve in its 40th year of operation
- Future options of RF-separated beams, other beam configurations (μ , h, e) plus compatibility of proposed experiments and integration of the full set-ups is currently being studied within the conventional beams working group / EHN2 WG of Physics Beyond Colliders
- More personnel available (project associate) for studies since 12/17, more from 03/18 (new fellow)
- North Area Consolidation Study established and first urgent consolidation works already completed
- Optics studies for 2018 tests finalised, proposal: Check RP limit for μ flux with tests this year
- Other news: Expect 10% increase of duty cycle in 2018 due to faster repetition of spills



<http://pbc.web.cern.ch/>






ENGINEERING
DEPARTMENT

Thank you!


Secondary Beams at CERN

High intensity secondary beams in a wide range of momenta with largely selectable particle species

- East Area / PS (24 GeV/c primary protons and ions for irradiation and 0.5 – 15 GeV/c secondary beams)
- North Area / SPS (400 GeV/c primary protons and up to 380 GeV/c secondary and ion beams)



Production Targets



| Position | Material | Length (mm) | Height (mm) | Width (mm) |
|----------|----------|-------------|-------------|------------|
| 0 | Air/OUT | - | - | - |
| 1 | Be | 500 | 2 | 160 |
| 2 | Be | 300 | 2 | 160 |
| 3 | Be | 180 | 2 | 160 |
| 4 | Be | 100 | 2 | 160 |
| 5 | Be | 40 | 2 | 160 |

5x plates, 40 mm inter-plate distance

Secondary Particle Production


Atherton parameterisation (CERN 80-07):

$$\frac{d^2N}{dpd\Omega} = A \left[\frac{B}{p_0} e^{-Bp/p_0} \right] \left[\frac{2Cp^2}{2\pi} e^{-C(p\theta)^2} \right]$$

$$\frac{d^2N}{dpd\Omega} = A \left[\frac{(B+1)}{p_0} \left(\frac{p}{p_0} \right)^B \right] \left[\frac{2Cp^2}{2\pi} e^{-C(p\theta)^2} \right]$$

with primary momentum p_0 and production angle θ


Flux per solid angle [steradian], per interacting proton, and per dp [GeV/c]



| | A | B | C |
|---|-----|------|-----|
| p | 0.8 | -0.6 | 3.5 |

| | A | B | C |
|-----------|------|------|-----|
| π^+ | 1.2 | 9.5 | 5.0 |
| π^- | 0.8 | 11.5 | 5.0 |
| K^+ | 0.16 | 8.5 | 3.0 |
| K^- | 0.10 | 13.0 | 3.5 |
| \bar{p} | 0.06 | 16.0 | 3.0 |

Secondary Particle Production



Nota bene: Flux given for a typical EHN1 beam line, e.g. H8