



# MC usage in ALICE

Redmer Alexander Bertens (UTK) on behalf of the ALICE collaboration

17th MCnet meeting

April 11, 2018, CERN, Switzerland

*what we will cover*

available generators and usage

MC productions and integration in the ALICE software  
framework

MC generators and RIVET

# Generators in the ALICE software framework

(red) indicates main use case, presented in no preferred order

- Pythia (pp)
  - Various versions (6.x, 8.x)
  - Various tunes (Perugia, Monash, etc)
- PHOJET / DPMJET (pp)
- EPOS LHC / EPOS 3 (pp, p-Pb, Pb-Pb)
- Herwig / Herwig++ (pp)
- Sherpa (pp)

# Generators in the ALICE software framework

- POWHEG (interfacing)
- STARLIGHT (ultra peripheral collisions)
- HIJING (Pb-Pb)
- AMPT (Pb-Pb)
- Therminator2 (Pb-Pb)
- JEWEL (Pb-Pb)


Analyzers **can** run generators **not** included in the software framework  
but for reasons of **validation** and efficiency this is **discouraged**

# usage of generators

hypothesis testing

corrections and modeling

# Usage: hypothesis testing



Generator relies on

- Ansatz / hypothesis
- (Tunable) parameters

Comparison between MC and data

- Confirm / refute hypothesis
- Constrain parameters

Experimental data should be corrected to particle level, or vice versa


Also important for **tuning and validation of MC generators**

# Usage: corrections and unfolding



Some measurements need to be **corrected** for 'unknown' signals

- MC generators necessary to quantify signals
- Prerequisite is **full confidence** in validity of generator output




ALI-PERF-115485

Measurement can be biased by

- **Detector** resolution
- Processes **uncorrelated** to the measurement

**Embedding** MC processes into real data (or even MC) allows to quantify these effects



ALI-PREL-125626

# MC productions and integration in the ALICE software framework

# ALICE main goal: heavy-ion physics

Heavy-ion MC generators generally resource hungry

- Multiple collision phases (**time consuming**)
  - Initial state
  - Medium evolution ( $x, y, z, t$ )
  - Rescattering and freeze-out (hadronization)


Large particle multiplicities (**large data volumes**)

Generator-only vs. generator+GEANT

- Simulation of detector effects often necessary but CPU intensive
- Per event GEANT CPU time order(s) of magnitude larger than generator-only CPU time

In practice

- **Large-scale** productions have to be **approved** by the collaboration
- Parallel production of events on **GRID**, mandatory validation
- Productions are **kept** on disk **until obsolete** (limited on-the-fly analysis)





# MC production on GRID

Output stored in standard ALICE AOD (Analysis Object Data) format

- User (data) analysis can run on production **without modifications**
- Full **MC info** is also still available (and accessible in user analysis)

name and description		status		events		resources			used software			
Production	Description	Status	Run range	Event Count	Requested	Comment	Known issues	Running time	Saving time	Output size	AliRoot version(s)	AliPhysics version(s)
LHC18b10b_caloc	p-p, 5.02 TeV - Pythia GJ events with gammas in DCal+PHOS anchored to 17p/q, caloc triggers, ALIROOT-7692	Quality check 10%	282146-282342	844,600		RAW OCDB		2y 298d	9d 19:47	407.2 GB	v5-09-20-1	v5-09-20-01-1
LHC18b10b_calofast	p-p, 5.02 TeV - Pythia GJ events with gammas in DCal+PHOS anchored to 17p/q, calofast triggers, ALIROOT-7692	Quality check 10%	282306-282342			B		4y 163d	15d 22:52	636.9 GB	v5-09-20-1	v5-09-20-01-1
LHC18b8_fast	p-p, 5.02 TeV - Pythia8+JetJet production anchored to LHC17p/q, fast, ALIROOT-7689	Running	282341-282343			B		49y 166d	76d 17:11	5.303 TB	v5-09-20-1	v5-09-20-01-1
LHC18b8_cent_woSDD	p-p, 5.02 TeV - Pythia8+JetJet production anchored to LHC17p/q, cent_woSDD, ALIROOT-7689	Running	282341-282343	8,183,200		RAW OCDB		27y 168d	40d 22:48	2.934 TB	v5-09-20-1	v5-09-20-01-1
LHC17h7a_extra	p-p, 13 TeV, Pythia6_Perugia2011 production anchored to LHC17j, extra statistics, ALIROOT-7432	Completed	274593-274595	54,628,400		RAW OCDB		160y 30d	235d 0:23	21.28 TB	v5-09-14-1	v5-09-14-01-1
LHC18b11c	Pb-Pb, 5.02 TeV - jet-jet Pythia events embedded in HI MC events anchored to LHC15o, cent 50-90 %, ALIROOT-7693	Completed	244918-246994	241,160		RAW OCDB						
LHC18b11b	Pb-Pb, 5.02 TeV - jet-jet Pythia events embedded in HI MC events anchored to LHC15o, cent 10-50 %, ALIROOT-7693	Completed	244918-246994	238,710		RAW OCDB						
				<b>6,113,138,864</b>				<b>28518y 249d</b>	<b>312y 223d</b>	<b>6.183 PB</b>		

'anchor'

total CPU time

disk usage

# 'On-the-fly' productions

MC generators can be selected as 'data sets' in the analysis framework

- User sets generator **configuration** and desired **number of events** via web interface
- **Generator** runs in **parallel** with analysis and sends output to a named pipe (fifo)
- Analysis framework converts fifo contents to AODs **on-the-fly**

Allows for efficient analysis of MC events with little IO

- Only suited for **fast** generators

Name	Owner	Dependencies	AMPT_v22...	DIPSY_v2...	DPMJE T	EPOS_3_d...	EOSL_HC_...	EOSL_HC_...	Herwi g	JEWEL	Pythi_a_6...	Pythi_a_8...	Pythi_a_8...	Therm ina...	Last test	Last run	
Group Default			Enable Disable	59	46												
FlowOnMC	rbertens		✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	46	46	✓ ✘ 📄
FlowOnMC_kaon	rbertens		✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	46	46	✓ ✘ 📄
FlowOnMC_pion	rbertens		✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	46	46	✓ ✘ 📄
FlowOnMC_proton	rbertens		✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	46	46	✓ ✘ 📄

MC generators

data analysis classes

# Integration with ALICE software

## Initial approach

- **Include** generator code as part of ALICE framework, load shared object at framework run-time
- Generation and AOD production handled by dedicated **wrapper class** for each generator

**Pro: full integration and control over generator**

**Con: not flexible (e.g. updating, RIVET use)**

```
class TAmpt : public TGenerator {  
public:  
  
...  
  
virtual void      GenerateEvent();  
virtual Int_t     ImportParticles(TClonesArray *particles, Option_t *option="");  
  
// common HIJJET1 access routines - read-only common:  
virtual Int_t     GetNPJ(Int_t key) const;  
virtual Int_t     GetKFPJ(Int_t key1, Int_t key2) const;  
virtual Float_t   GetPJPX(Int_t key1, Int_t key2) const;
```

example: AMPT wrapper class in AliROOT

includes e.g. functions to generate event and import particles to analysis format

functions in turn access fortran common blocks

# Integration with ALICE software

Approach for **new** generators / updates overseen by **dedicated new working group** (PWGMM)

- Distribute generators as **stand-alone** executables (on GRID via CernVM File System CVMFS)
  - Full integration of generators in ALICE build system
  - Requires that generators can be **properly built** (CMake, makefiles, etc)
- Run stand-alone generator as **background process** during production/analysis
- Generator writes to **fifo**, analysis framework reads from fifo

HepMC is **fully integrated** with the ALICE software framework

- Non-HepMC generator output is either **parsed** to HepMC or handled by a dedicated 'MC-to-AOD' parser

## Caveats of HepMC

- Mandatory **graph structure** incompatible with some HI generators
  - e.g. only producing particles at freeze-out (no **connection** to beam particles)



# MC generators and RIVET

# RIVET and ALICE



ALICE 'RIVETizes' only a fraction of analyses

- p-Pb and Pb-Pb analyses need some features that RIVET misses

Using MC generators as **stand-alone** executables (slide 14) well suited for (and aimed at) RIVET and MCPlots project

- **Same** generator suite can be used for **RIVET** analysis and **ALICE MC analysis**
- Ensures well-defined **generator configuration** for RIVET and ALICE MC analyses
- Ability to run generators with a **well-defined configuration**, be it **in** or **out** of the ALICE analysis framework, is generally **crucial**

Goal

- **Encourage** RIVETization of analyses
- **Actively** contribute to **tuning** of generators using RIVET plugins

~ *fin* ~

questions & discussion