




Status of the ALICE TPC upgrade

Markus Ball


Rheinische Friedrich-Wilhelms Universität Bonn
Helmholtz-Institut für Strahlen- und Kernphysik (HISKP)



- **Motivation for the GEM upgrade**
- Ion backflow, energy resolution and discharge probability
- **Full production**
 - GEM Production and QA
 - Framing
 - Chamber assembly
- **Summary**



Ion Backflow suppression of a GEM $\sim 10^{-1}$ for a single GEM
 $\sim 10^{-2}\text{-}10^{-3}$ for a GEM stack





Asymmetric field configuration
 can be repeated in a GEM stack


!

$$E_{\text{drift}} < E_{T1}, E_{T2} < E_{T3}$$

$$\Delta U_{G1} < \Delta U_{G2} < \Delta U_{G3} < \Delta U_{G4}$$





- ▶ Requirements could not be fulfilled with a triple GEM (S-S-S) setup
- ▶ New readout chambers employ standard pitch (S) and large pitch GEM foils in a S-LP-LP-S configuration
- ▶ HV configuration has to be optimal for ion back flow, energy resolution and low discharge probability at the same time



Foils rotated 1°

Foils rotated 90° to each other




Alignment of the GEM foils


- ▶ Alignment between the GEMs crucial → uniform IB
- ▶ Rotation makes the S, LP foils unique ($G1 \neq G4$, $G2 \neq G3$)
- ▶ To decrease the IB further than with the IB optimised electric field configuration → use GEM foils with different geometries (different optical transparencies)

Foils not rotated

Foils rotated 90° to each other



- Motivation for the GEM upgrade
- **Ion backflow, energy resolution and discharge probability**
- Full production
 - GEM Production
 - Framing
 - Chamber assembly
- Summary



CERN-LHCC-2013-020

Addendum:

CERN-LHCC-2015-002

Requirements for the upgrade GEM based TPC of ALICE

- ▶ Drift field: 0.4 kV/cm
- ▶ Detector gas: Ne-CO₂-N₂ (90-10-5)
- ▶ Effective gas gain: 2000
- ▶ S/N ratio ~ 20
- ▶ IB: < 1 %
- ▶ ϵ : < 20
- ▶ σ/E (5.9 keV): < 12 %
- ▶ Low discharge probability
- ▶ Operation at 50 kHz (Pb-Pb)



Ion Backflow

IB := Ratio of $I_{\text{Cath}} / I_{\text{Anode}}$

Number of back drifting ions / e^-_{prim}


$\epsilon := \text{IB} * \text{gain} - 1$

Baseline solution for IB and Energy-resolution (S-LP-LP-S)



Optimisation of two parameters at the same time is conflicting:

- ▶ Best Value IB $\sim 0.6\%$ at an energy resolution of $\sigma/E < 12\%$
- ▶ Upgrade goals have been reached with some margin for fine tuning (in case needed for the stability)
- ▶ Much larger phase space has been scanned no significant improvements (no order of magnitude) are expected




Stable operation under LHC conditions


- Discharge probability studies (TUM, CERN):
 - $< 10^{-10}$ (4GEM, measured with alpha particles)
 - $(6 \pm 4) \times 10^{-12}$ (hadron beam at the SPS)
- Discharge propagation studies
- HV system stability (CERN, IKF, TUM)
- Charge density studies
(see P. Gasik, A. Mathis, L. Fabbietti, J. Margutti NIM A870 (2017) 116)
- See presentation of P. Gasik

	S-S-S 'standard' HV G = 2000	S-S-S-S IB = 2.0% G = 2000	IB = 0.34% G = 1600	S-LP-LP-S		
			IB = 0.34% G = 3000	IB = 0.34% G = 5000	IB = 0.63% G = 2000	
²²⁰ Rn E _α = 6.4 MeV rate = 0.2 Hz	~10 ⁻¹⁰			< 2 × 10 ⁻⁶	< 7.6 × 10 ⁻⁷	
²⁴¹ Am E _α = 5.5 MeV rate = 11 kHz						< 1.5 × 10 ⁻¹⁰
²³⁹ Pu + ²⁴¹ Am + ²⁴⁴ Cm E _α = 5.2 + 5.5 + 5.8 MeV rate = 600 Hz		< 2.7 × 10 ⁻⁹	< 2.3 × 10 ⁻⁹	(3.1 ± 0.8) × 10 ⁻⁸		< 3.1 × 10 ⁻⁹
⁹⁰ Sr E _β < 2.3 MeV rate = 60 kHz					< 3 × 10 ⁻¹²	

- Motivation for the GEM upgrade
- Ion backflow, energy resolution and discharge probability
- **Full production**
 - GEM Production
 - Framing
 - Chamber assembly
- Summary




160 cm




Replace 72 Readout Chambers in total !

- Each IROC consists of 4 GEMs
- Each OROC consists of 3x4 GEMs
- 576 GEM foils
- (+ spare chambers, plus yield not 100 %, rather ~90 %)
- → The quality of at least 720 GEM foils has to be assured
- → 40 IROC and 40 OROC fully qualified chambers have to be delivered (640 GEM foils)

- R&D and Prototyping 2012-2015
 - LHCC approval June 2015
(TDR, TDR Addendum, TDR Addendum UCG)
 - Engineering design Review (EDR) November 2015
 - Training (School of ROCs, Visits at all institutes, etc.)
 - GEM and chamber final design review June 2016
 - Pre-production: finalized
 - Production Readiness Review (PRR) 10th March 2017
 - - full characterization of the final-design (aka PRR) chambers
- Mass production (40x IROCs + 40x OROCs) Q2.2017 – Q3.2018
 - ROC tests at LHC Q2.2017 – Q3.2018






- GEM production at CERN

- 144 GEMs of each type: IROC, OROC 1, 2, 3
- 720 individual GEMs (including 10 % spares) = 2 x 180 sheets (IROC + OROC3, OROC1 + OROC2)
- Each type has 4 flavours (G1, G2, G3, G4), which are unique

GEM cumulative production chart IROC, status 2018-02-18





GEM Production Progress




ROC GEM Foils	Total (produced)	QA-B done	QA-B passed	failed	failed (w/o 5)	Sliding Yield	Sliding Yield (w/o 5)
IROC	129	109	88	23	17	0.807	0.844
OROC1	124	124	107	17	13	0.863	0.895
OROC2	115	115	107	8	5	0.930	0.957
OROC3	132	111	94	17	15	0.847	0.865
Total	500	459	396	65	50	0.863	0.891

- February 2018: 500 foils produced (target: 720 = 640+80 spares)
- GEM production: Original end of production was planned end of april, now in may
- Projected yield: ~ 90% (constantly monitored)
- Yield might be too tight → 720 produced GEM foils might not be sufficient to finish ROC production
- 80 GEM foils on top of the 720 → 800 (need 640 GEMs for 40+40 ROCs)
- Very powerful database system is in place
- Keeps track of all GEMs, components and QA results


2018-02-15	IROC					OROC1					OROC2					OROC3				
flavor	G1	G2	G3	G4	sum	G1	G2	G3	G4	sum	G1	G2	G3	G4	sum	G1	G2	G3	G4	sum
QA-B done	30	30	29	31	120	34	30	31	29	124	29	31	30	26	116	32	29	27	33	121
produced	30	27	27	25	109	34	30	31	29	124	28	31	30	26	115	29	25	26	31	111
QA-B passed	20	25	25	16	86	29	25	26	27	107	25	30	30	23	108	23	21	24	26	94
QA-B yield	0.67	0.93	0.93	0.64	0.79	0.85	0.83	0.84	0.93	0.86	0.89	0.97	1.00	0.88	0.94	0.79	0.84	0.92	0.84	0.85
QA-A done	29	25	24	24	102	30	27	29	25	111	26	27	24	23	100	26	20	24	26	96
QA-A passed	19	23	22	15	79	25	22	24	23	94	23	26	24	20	93	20	16	22	21	79
QA-A yield	0.66	0.92	0.92	0.62	0.77	0.83	0.81	0.83	0.92	0.85	0.88	0.96	1.00	0.87	0.93	0.77	0.80	0.92	0.81	0.82
framed, ok	18	20	21	15	74	21	21	23	22	87	22	23	23	19	87	16	17	19	18	70

- GEM flavours are unique G1, G4 (S) and G2, G3 (LP) can not be exchanged (rotation)
- Lowest number of GEM flavours defines the number of chambers, that can be build
- Information from database and personal communication helps to equalize the flavours.
- Close contact to CERN PCB workshop allows to react on the flavor mismatch from batch to batch
- Keeping track of all GEM flavours is crucial

GEM cumulative production chart IROC, status 2018-02-18




GEM cumulative production chart IROC, status 2018-02-18




- February 2018: ~ 400 foils tested for Advanced QA, ~ 86 % of all GEM tested at CERN
- Advanced QA consists of
 - high definition optical scan,
 - Small part of GEM foils test gain uniformity
 - long term leakage current measurement
- Classification according an extended traffic light system
- So far all GEM foils except **Red** are used
- Connect performance of single GEMs and chamber gain uniformity (ongoing), see next slides


Traffic Light					
IROC	48	25	6	23	102
OROC1	28	56	10	17	111
OROC2	45	26	9	8	88
OROC3	20	50	9	17	96
Total	141	157	34	65	397






Gain uniformity I-G1-007 measured




Gain uniformity I-G1-007 simulated




Gain uniformity I-G1-007 measured





GEM cumulative production chart IROC, status 2018-02-18



GEM cumulative production chart IROC, status 2018-02-18



- February 2018: ~ 340 GEM foils glued on frame
- For all GEM foils I_{Leak} has been measured twice (before and after framing glueing)
- ~ 74 % of all GEMs tested at CERN already glued to a GEM frame
- Quality of the glueing procedure constantly monitored at the framing and the assembly centres (feedback to the framing centres)
- Also GEM framing enters in the database



- **Production of 40x IROCs and 40x OROCs chambers is ongoing**
 - Almost all components in hand
 - GEM production continues until May 2018
 - All chambers assembled until Q4.2018



ROC components	Needed	Produced	Fraction (%)
Al-bodies	80	65	81
Padplanes	160	160	100
FEC connectors	15'000	15'000	100
HV cables	1'300	1'300	100
GEMs*	720 (10% spares)	500	69
GEM frames**	640	590	92

* PCB workshop will continue GEM production, if needed (manpower booked)

** Extra spare frames ordered recently

Assembly step	Goal	Assembled	Fraction (%)
Chamber bodies (IROC/OROC)	40/40	21/15	45
Padplane + FEC connectors (IROC/OROC)	40/120	40/120	100
GEM framing	640	340	53
Assembled Chambers (IROC/OROC)	40/40	11/9***	25

*** 10/7 fully commissioned





TPCU Production Status



	2017		2018																																																							
	51	52	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49							
			Jan.18				Feb.18				Mar.18				Apr.18				May.18				Jun.18				Jul.18				Aug.18				Sep.18				Oct.18				Nov.18															
Batch	DB	#27						#25	#28	#30					#32	#34					#36	#38																																				
IROC	99	109						119	129	139					149	159							179																																			
QA at CERN [20/w]			(10)					WGC	(10)	(10)	(10)					(10)	(10)					WGC	(10)	(10)																																		
Transportation [+1 w]						(10)	-->				18	12		18			18																																									
QA BUDAPEST [25/m]	18	18						10						18			18																																									
Transportation to US [+1 w]						18				10				18			18					18																																				
IROC framing [4/w]	68					18				10				18			18					18																																				
Transportation in US [+1 w]							18				10						18																																									
GEMs	6/9/9/5						4x GEM4				3x GEM4				#27 1x GEM4			#25 and #28 has 10 GEM4s																																								
IROC Assembly [2/3w]	7			8+9		10+11			12+13		14+15		16+17		18+19		20+21+22		23+24		25+26+27		28+29		30+31+32		33+34		35+36+37		38+39+40																											
IROC to CERN																																																										



TPCU Production Status



		2017		2018																																																
		51	52	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
				Jan.18				Feb.18				Mar.18				Apr.18				May.18				Jun.18				Jul.18				Aug.18				Sep.18				Oct.18				Nov.18								
Batch	DB	--> #26		#29				#31				#33				#35				#37				#39																												
OROC1	114	124		134				144				154				164				174				184																												
QA at CERN [20/w]	5			(10)		WGC		(10)		WGC		(10)		WGC		(10)		WGC		(10)		WGC		(10)		WGC		(10)																								
Transportation [+1 w]				(3)		(7)				9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9				
QA HELSINKI [25/m]	16	8		(8)		3 avail.		6		(4)		6		(9)		9		(9)		9		(9)		9		(9)		9		(10)																						
Transportation in EUR [+1 w]		9		-->		9		8		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9						
OROC framing [4/w] (per site)	68+6	9		5		10		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		10		10						
Transportation in EUR [0-1 w]		9-GSI		-->		9-HPD		9-GSI		6-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		10-HPD										
Batch	DB	--> #26		#29				#31				#33				#35				#37				#39																												
OROC2	106	116		126				136				146				156				166				176																												
QA at CERN [20/w]				9				(10)		WGC		(10)		WGC		(10)		WGC		(10)		WGC		(10)		WGC		(10)																								
Transportation [+1 w]				9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9						
QA BUDAPEST [25/m]	21	1		9		5		15		9		12		9		18		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9						
Transportation in EUR [+1 w]				9		6		9		6		9		6		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9						
OROC framing [4/w] (per site)	71+9	9		9		9		6		9		6		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		WGC		9		6										
Transportation in EUR [0-1 w]		8-HPD		-->		9-GSI		9-HPD		6-GSI		6-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		6-HPD												
Batch	DB	#27		#25				#28				#30				#32				#34				#36				#38																								
OROC3	103	113		123				133				143				153				163				173				183																								
QA at CERN [20/w]	8			(10)		WGC		(10)		(20)		WGC		(10)		WGC		(10)		WGC		(10)		WGC		(10)		WGC																								
Transportation [+1 w]				(6)		(11)		9		9		18		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9								
QA HELSINKI [25/m]	18	9		(9)		5		9		(8)		12		(9)		9		(9)		9		(9)		9		(15)		(11)		(5)																						
Transportation in EUR [+1 w]		9		-->		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9								
OROC framing [4/w] (per site)	58+7	7		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		9		7										
Transportation in EUR [0-1 w]		7-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		9-HPD		9-GSI		7-GSI																
GEMs (GSI)	16/16/16	17/15/18		26/24/18		35/30/27		35/30/27		35/39/36		44/39/36		44/48/45		53/48/45		53/57/54		62/57/54		62/66/63																														
OROC (GSI)		3		4		5		6		7		8		9		10		11		12		13		14		15		16		17		19		20																		
GEMs (HPD)	8/8/8	20/25/19		29/34/28		35/34/28		44/40/37		44/40/37		44/49/46		53/49/46		53/58/55		62/58/55		62/67/64		72/73/71																														
OROC (HPD)		1		2		3		4		5		6		7		8		9		10		11+12		13+14		15+16		17+18		19+20																						

1. Chamber commissioning at the assembly sites
2. Stability tests at LHC



LIST OF TESTS





1. Gas tightness (< 0.5 ml/h)
2. Gain curve
3. Gain uniformity (< 20 %)
4. IBF uniformity (IBF = 0.7%, $\Delta\epsilon < 20\%$)
5. Full X-ray irradiation (10 nA/cm²) for 6h

Gas: Ne-CO₂-N₂ (90-10-5)

HV: resistor chain

Settings: GEM1/2/3/4 = 270/230/288/359 V T1/T2/T3/IND = 4/4/0.1/4 kV/cm



Readout: single channel pre-amplifier + shaper + ADC, amperemeters



- Effective gain ($G_{eff} = \frac{I_{anode}}{eN_{ion}R}$)
- Performance within specs:
 - gain uniformity < 20%
- 10 IROCs within specs






IROC

Gain distribution (anode current)



- Low-gain bins not included in 1D distribution
- spacer
 - measurement edges (non-active area)


OROC




- Gain uniformity RMS well below $\leq 20\%$ (within the specs)
- OROC3 non-uniformity correlates with a single foil hole-size distribution – investigation ongoing

IROC

Distribution of ion backflow








IBF distribution



- Ion Backflow ($G_{eff} = \frac{I_{anode}}{e N_{ionR}}$, $IB = \frac{I_{cathode}}{I_{anode}} = \frac{(1+\epsilon)}{G_{eff}}$)
- Performance within specs. $IB < 1 \%$
- Mean value in agreement with $IB < 0.7\%$ measured with $10 \times 10 \text{ cm}^2$ GEMs at $G_{eff} = 2000$
- For the final TPC performance (space charge distortions) $\rightarrow \epsilon$ uniformity!
- 18 segments means 18 times $10 \times 10 \text{ cm}^2$ detectors (In total 206 individual measurements)
- Mean value in good agreement with the R&D results


X-scan_11.24.2017-12.56.30-AM/scan.txt




- Ion Backflow ($G_{eff} = \frac{I_{anode}}{e N_{ionR}}$, $IB = \frac{I_{cathode}}{I_{anode}} = \frac{(1+\epsilon)}{G_{eff}}$)
- Performance within specs. $IB < 1 \%$
- Mean value in agreement with $IB \sim 0.7\%$ measured with $10 \times 10 \text{ cm}^2$ GEMs at $G_{eff} = 2000$
- This is the area of 66 times $10 \times 10 \text{ cm}^2$ detectors (in total ~ 900 individual measurements)




Eps parameter XY



Epsilon parameter




- Epsilon proportional to the cathode current:
- $G_{eff} = \frac{I_{anode}}{e N_{ion} R}$, $IB = \frac{I_{cathode}}{I_{anode}} = \frac{(1+\epsilon)}{G_{eff}}$, $\epsilon = \frac{I_{cathode}}{(e N_{ion} R)} - 1$
- Performance within specs:
 - gain uniformity RMS < 20%; epsilon RMS < 20%
- The calibration procedure has been demonstrated to work for effective non-uniformities of $\epsilon \sim 25\%$



IROC

- Induce 10 nA/cm² current (expected in Run 3) at the pad plane after amplification $G = 2000$ for 6h
- Cathode/Anode current read with pA-meter
- Cathode/anode currents go directly to zero after X-ray off
- No energy resolution deterioration after the test
- Leakage current of all foils <0.5 nA after the test
- no discharge recorded during 6 hours of full irradiation




















- Well established acceptance criteria
- Similar setups in all three assembly sites (Uni Yale, GSI Darmstadt, HPD Bucharest)
- Possible to assemble and commission 2-3 IROCs/month and 4 OROCs/month

- Acceptance criteria upon arrival at CERN:
 - Capacitance, resistance measurements
 - Leakage current at 350 V in dry gas
 - Full voltage in dry gas
 - Part of the chambers will be tested at LHC
 - All tests documented in the database

part	item	batch	sent from	to	date	location	QA status	link	comment
IROC chamber	IROC/01					Yale		X	
IROC chamber	IROC/03					CERN		X	
IROC chamber	IROC/04					CERN		X	
IROC chamber	IROC/05					CERN		X	
IROC chamber	IROC/06					Yale		X	
IROC chamber	IROC/07					Yale		X	
IROC chamber	IROC/08					Yale		X	
IROC chamber	IROC/09					Yale		X	
IROC chamber	IROC/10					Yale		X	
IROC chamber	IROC/11					Yale		X	
IROC chamber	IROC/12					Yale		X	
IROC chamber	IROC/13					Yale		X	
IROC chamber	IROC/14					Yale		X	
IROC chamber	IROC/15					Yale		X	



14 items

part	item	batch	sent		date	location	QA status	link	comment
			from	to					
OROC chamber	OROC/01					CERN		X	PRR (aka FINAL) OROC
OROC chamber	OROC/02					GSI		X	At the beginning of commissioning, 2 kV applied by mistake to pads.
OROC chamber	OROC/03					Bucharest		X	former OROC 23
OROC chamber	OROC/04					Bucharest		X	repaired HV-cable GEM 4 TOP (-1160V) tested at -3500V --> 75pA
OROC chamber	OROC/05					GSI		X	two discharges during HV-wire irradiation (at a wrong position), no discharges in a second test
OROC chamber	OROC/06					GSI		X	O3-G1-012 touched, replaced with O3-G1-016
OROC chamber	OROC/07					Bucharest		X	
OROC chamber	OROC/08					Bucharest		X	
OROC chamber	OROC/09					Bucharest		X	
OROC chamber	OROC/10					GSI		X	bump in gain map
OROC chamber	OROC/11					GSI		X	
OROC chamber	OROC/12					GSI		X	
OROC chamber	OROC/13					HD		X	
OROC chamber	OROC/14					HD		X	
OROC chamber	OROC/15					HD		X	
OROC chamber	OROC/16					HD		X	
OROC chamber	OROC/17					HD		X	

17 items

Goals:

- Test IROCs and OROCs under radiation conditions that are comparable to Run 3
- Practice HV hardware and control tools – complex system
- Optimize operational point: HV settings, decoupling resistors, trip settings





- IROC and OROC are placed in a miniframe, close to the beam pipe, between PMD and compensator magnet
- In 150kHz pp, **direct** load on ROCs in this position is comparable to that on ROCs installed in the TPC in Run 3
- HV supply in CR4, control from ALICE Control Room

- We have come a long way from R&D to full production
- Intensive R&D lead to the 4-GEM configuration, fulfilling all requirements
- We are in full production mode now, but the end of production is already near
- Results from R&D ($10 \times 10 \text{ cm}^2$) phase in good agreement with the results of the final chambers
- Full production:
 - GEM production and QA-B on track 500 out of 720 produced (more than 2/3)
 - GEM QA-A 400 out of 720 (55 % done already)
 - GEM framing 340 out of 640 (~ 50 %)
- ROC production/qualification on schedule, until Q3.2018
- OROC at LHC running stable. More chambers to be tested in the upcoming months
- LHC Long Shutdown 2 in 2019-2020: chamber and FEE installation, commissioning will be soon the crucial challenge
- RD51 and CERN PCN workshop were with us and part of everything during the whole time
- Your are/were gratefull for all you advice, comments and criticism
- Thank you all a lot that you contributed in such an active way !!!

Backup





- Ion Backflow suppression of a MWPC with a Gating grid $\sim 10^{-5}$
- 100 μs electron drift time + 200 μs to neutralise all ions
- Total cycle time $\sim 300 \mu\text{s}$ limits the maximal readout rate to $\sim 3 \text{ kHz}$ (in p-p)
- Trigger Rate $\sim 600 \text{ Hz}$ for Pb-Pb (300 Hz in Run 1)

00:00 -- 00:20 1. Chamber body assembly

body assembly 27...

⌚ 20m

00:20 -- 00:40 2a. HV cables and HV plugs assembly

Feedthroughs 27.D...

⌚ 20m

00:40 -- 01:00 2b. Padplane test

padplane 2702201...

⌚ 20m

01:00 -- 01:20 3. Working with GEMs

Savoir Vivre 27.08.2...

01:20 -- 01:40 4. Optiguard frame installation

optiguard 27.08.20...

01:40 -- 02:00 5. GEM packing/unpacking

Packing-Unpacking ...

02:00 -- 02:20 6. Coarse optical check

coarse optical chec...

02:20 -- 02:40 7. HV test

GEM HV test 23.10...

02:40 -- 03:00 7a. HV test in the PCB workshop

GEM HV test in PC...

03:00 -- 03:20 8. Optical scanning

GEM_OSS_test_v1...

03:20 -- 03:40 9. GEM frame assembly

frame assembly 27...

03:40 -- 04:00 10. GEM framing

gem framing 27.08...

04:00 -- 04:20 11. ROC assembly

ROC assembly 23.1...

04:20 -- 04:40 12. ROC commissioning

ROC commissionin...

⌚ 20m

04:40 -- 05:00 13. ROC acceptance

ROC acceptance 28...

⌚ 20m


FRAME ASSEMBLY FRAME LEDGES CLEANING

1. Check ledges under the microscope
2. Document possible damages
3. Remove overhanging glass fibers with sand paper (see picture)
4. Clean in an ultrasonic bath for at least 5 minutes. For example:
 - Bath 1 with isopropanol for pre-cleaning – 5' (or pre-clean with iso-propanol manually)
 - Bath 2 with isopropanol for final cleaning – 3'-5' and let isopropanol drain
 - Bath 3 with distilled water – 3' and let water drain
5. Blow dry with nitrogen
6. Check ledges again under the microscope
7. Put ledges into the dry cabinet. Leave them (at least) over night for drying before the final assembly.






Offse






Simulation vs. measurement



(1) Simulation



(2) Measurement




GEM foils geometries

Double-mask technique:

- *“Standard” for small areas ($\leq 40 \times 40 \text{ cm}^2$)*
- *Gives a perfect bi-conical shape*

Diameters	cross section optical microscopy	
Hole location	Diam. [μm]	Err. [μm]
Top	70.1	± 0.2
Middle	49.1	± 1.2
Bottom	69.4	± 0.8

Preliminary








Single-mask technique:

- *Suitable for large areas*
- *Gives a “asymmetric” bi-conical shape*


Diameters	digital microscopy		cross section optical microscopy	
Hole location	Diam. [μm]	Err. [μm]	Diam. [μm]	Err. [μm]
Top	73.8	± 3.3	71.0	± 2.1
Middle	51.3	± 2.7	52.8	± 5.4
Bottom	85.5	± 4.1	86.1	± 4.9

- **How does this asymmetry affect the operation of the detectors ?**









- Strong non linear humidity dependent > 0.6 % abs. humidity. Problematic if room air conditions are not under control. Typical room air conditions (0.8-1.5 %) abs humidity
- Variance of leakage current between segments is large in humid conditions. Reason unknown.
- I_{leak} variations of different segments could not be related to optical or stability measures
- After additional HV cleaning in humid condition most sectors show lower leakage currents
- Constant QA threshold in uncontrolled humidity conditions can not be used as a quality criteria.





- Strong non linear humidity dependent > 0.6 % abs. humidity. Problematic if room air conditions are not under control. Typical room air conditions (0.8-1.5 %) abs humidity
- Variance of leakage current between segments is large in humid conditions. Reason unknown.
- I_{leak} variations of different segments could not be related to optical or stability measures
- After additional HV cleaning in humid condition most sectors show lower leakage currents
- Constant QA threshold in uncontrolled humidity conditions can not be used as a quality criteria.



- Number of discharges rise with humidity
- Has also be observed in “M. C. Altunbas et al. Construction, test and commissioning of the triple-GEM tracking detector for COMPASS. Nucl. Instrum. Meth., A490:177-203, 2002.”
- Observation contradicts expectation from gas properties GEM is not parallel plate capacitor → electrode quantities change e.g. dielectric constant, surface conductivity → behaviour not fully understood
- GEMs show some training effect (breakdown voltage increasing with number of tries). So far a clear quality criteria could not be derived. Currently sparks are detected. Foils are excluded if sparking continues after long term tests and sparks appear at the same position (red light)
- Avoid sparking → avoid humidity





- Ions from 8000 events pile up in the drift volume at 50 kHz Pb-Pb collisions ($t_{d,ion} = 160$ ms)
- Total number of ions in drift volume strongly depends on IB: $n_{tot} = n_{ion} * IB * G_{eff}$; $\epsilon = IB * G_{eff}^{-1}$
- 1% of IB at $G_{eff} = 2000$ ($\epsilon = 20$)
 - distortions up to $dr \approx 20$ cm and $d\phi \approx 8$ cm (at small r and z)
 - well below 10 cm for the largest part of drift volume
- Corrections to $\mathcal{O}(10^3)$ are required for final calibration (to the level of intrinsic resolution, $\sigma_{r\phi} \sim 200$ μ m)
- 2-stage calibration and reconstruction scheme



Testing limits of calibration procedure at up to twice the nominal ion density ($\epsilon=40$)



- tracking efficiency not compromised
- slight decrease in p_t resolution at low momenta
 - does not compromise physics program




- ▶ Effective gain independent of hole alignment
- ▶ Ion backflow highly dependent on hole alignment

Foils rotated 1°


Foils rotated 90° to each other




- ▶ Effect of rotation of GEM to each other
- ▶ Ion backflow distributed uniform and reproducible



Foils not rotated





Foils rotated 90° to each other



- ▶ Effective gain independent of hole alignment
- ▶ Ion Backflow highly dependent on hole alignment

- ▶ Effect of rotation of GEM to each other
- ▶ Ion backflow distributed uniform and reproducible

CERN-LHCC-2013-020



Asymmetric field configuration can be repeated in a GEM stack !

$$E_{\text{drift}} < E_{T1}, E_{T2} < E_{\text{ind}}, \Delta U_{G1} < \Delta U_{G2} < \Delta U_{G3}$$

Limitations of a triple GEM setup

- ▶ Ion Backflow was measured with triple GEM stack. Best value achieves was around 2.5 % at a gain of 2000 $\rightarrow \epsilon \sim 50$
- ▶ Asymmetric field configuration separates Gain of GEM₃ from Gain of GEM₁ + GEM₂ \rightarrow higher discharge probability


Electron transport properties for IB optimised HV settings

ϵ_{coll} = collection efficiency

ϵ_{extr} = extraction efficiency

M = gas multiplication factor

$G_{\text{eff}} = \epsilon_{\text{coll}} \times M \times \epsilon_{\text{extr}} = \text{effective gain}$



	ϵ_{coll}	$n_{e,\text{in}}$	M	$n_{e-\text{ion}}$	ϵ_{extr}	$n_{e,\text{out}}$	G	$n_{\text{ion,back}}$	fraction of total IBF (sim.)	fraction of total IBF (meas.)
GEM1 (S)	1	1	14	13	0.65	9.1	9.1	3.6 (28%)	40%	31%
GEM2 (LP)	0.2	1.8	8	12.7	0.55	8	0.88	3.3 (26%)	37%	34%
GEM3 (LP)	0.25	2	53	104	0.12	12.7	1.6	1.3 (1.3%)	14%	11%
GEM4 (S)	1	12.7	240	3053	0.6	1830	144	0.84 (0.03%)	9%	24%
Total				3183		1830	1830	9 (0.28%)		

Electron transport properties for IB optimised HV settings

ϵ_{coll} = collection efficiency

ϵ_{extr} = extraction efficiency


M = gas multiplication factor

$G_{\text{eff}} = \epsilon_{\text{coll}} \times M \times \epsilon_{\text{extr}}$ = effective gain

$n_{\text{e-ion}}$ = number of produced e-ions pairs

$n_{\text{ion,back}}$ = number of ions drifting back into the drift volume (ϵ)

$$IB = (1 + \epsilon) / G_{\text{eff}}$$



	ϵ_{coll}	$n_{\text{e,in}}$	M	$n_{\text{e-ion}}$	ϵ_{extr}	$n_{\text{e,out}}$	G	$n_{\text{ion,back}}$	fraction of total IBF (sim.)	fraction of total IBF (meas.)
GEM1 (S)	1	1	14	13	0.65	9.1	9.1	3.6 (28%)	40%	31%
GEM2 (LP)	0.2	1.8	8	12.7	0.55	8	0.88	3.3 (26%)	37%	34%
GEM3 (LP)	0.25	2	53	104	0.12	12.7	1.6	1.3 (1.3%)	14%	11%
GEM4 (S)	1	12.7	240	3053	0.6	1830	144	0.84 (0.03%)	9%	24%
Total				3183		1830	1830	9 (0.28%)		

Electron transport properties for IB optimised HV settings

ϵ_{coll} = collection efficiency

ϵ_{extr} = extraction efficiency


M = gas multiplication factor

$G_{\text{eff}} = \epsilon_{\text{coll}} \times M \times \epsilon_{\text{extr}}$ = effective gain

$n_{\text{e-ion}}$ = number of produced e-ions pairs

$n_{\text{ion,back}}$ = number of ions drifting back into the drift volume (ϵ)



fraction of total IB: **simulation** vs. **experiment**



	ϵ_{coll}	$n_{\text{e,in}}$	M	$n_{\text{e-ion}}$	ϵ_{extr}	$n_{\text{e,out}}$	G	$n_{\text{ion,back}}$	fraction of total IBF (sim.)	fraction of total IBF (meas.)
GEM1 (S)	1	1	14	13	0.65	9.1	9.1	3.6 (28%)	40%	31%
GEM2 (LP)	0.2	1.8	8	12.7	0.55	8	0.88	3.3 (26%)	37%	34%
GEM3 (LP)	0.25	2	53	104	0.12	12.7	1.6	1.3 (1.3%)	14%	11%
GEM4 (S)	1	12.7	240	3053	0.6	1830	144	0.84 (0.03%)	9%	24%
Total				3183		1830	1830	9 (0.28%)		

discharge probability (S-S-S)

Triple GEM stack in standard settings



Optimisation of two parameters at the same time is conflicting:



- ▶ ^{220}Rn source, randomly distributed in the detector
- ▶ Measurement for TPC gas mixtures: Ar- CO_2 (90-10), Ne- CO_2 (90-10), Ne- CO_2 - N_2 (90-10-5)
- ▶ Different slopes for Ar- and Ne-based gas mixture
- ▶ Clear influence of additional quencher

- QA of the CERN workshop:
 - Deliver GEM foils within specification agreed upon in collaboration document
- Basic QA (CERN):
 - Reject malfunctioning GEM foils at the earliest possible stage
 - Give fast feedback to the producer (CERN)
 - First reference (to identify e.g. defects coming from transport)
- Advanced QA:
 - Additional quality selection (hole size distributions, defect classification, gain uniformity prediction, long term stability)
 - Provide additional criteria to select the best foils
 - Provide additional information for the producer to improve/optimize the production process
- Basic QA (Framing-, Assembly sites)
 - Continuous quality monitoring
 - Shows if the basic HV stability is kept after each additional production step

- **Red Light:**
 - GEM did not pass Basic QA (most important HV stability) → Reprocessed
 - Not (necessarily) permanent
- **Orange Light**
 - Basic QA passed → HV stability ok
 - Hole size distributions: both inner or outer holes show an asymmetry
 - Target design values for hole (inner outer deviate more than 10 μm)
- **Yellow Light:**
 - Basic QA passed → HV stability ok
 - Hole size distributions: either inner or outer holes show an asymmetry
 - Predicted gain spread larger than 10 % (RMS), long term HV stability acceptable
- **Green Light**
 - Passed all basic and advanced QA criteria
 - Basic HV stability is kept after all processing steps

Advanced QA consists of:

- High definition optical scan including the determination of 1-dim and 2-dim hole size distributions and map of optical defects
- Gain uniformity measurements of statistically significant sample of GEM foils
- Correlation of gain uniformity and hole size distribution is used to predict the gain uniformity of each GEM foil
- $I_{leakage}$ measurements for at least five hours, data is stored in a leakage current file with common data format
- Determination and classification of defects (in preparation)


10	QA-B	I_leak histo data	01_O2-G1-001_N2_corrected.txt evaluate	2	2017-08-11 16:22:15	no comment avg all segments 10.7, sparks: 0 ok	Viktor	file
12	12	hole size distribution	02-G1-001_1D.txt evaluate 1D		2017-06-09 11:44:02	no comment avg all segments 10.7, sparks: 0	Marton	file txt
13	13	hole size data 2D	02-G1-001_2D.txt evaluate 2D		2017-06-09 11:44:43	no comment avg all segments 10.7, sparks: 0	Marton	file txt
15	QA-A	long term leakage current data	02-G1-001-20170504-15-42_sectors.txt evaluate	2	2017-06-29 14:11:17	no comment avg all segments 3.4, sparks: 0 sticky rolled after shorted sector, looks better although many sparks	Marton	file txt
20	20	frame glueing comment if not perfect (wrinkels?)						eq
25	25	quality	B	2	2017-06-10 23:01:47	Also slight problems from the HV, had to sticky roll it, but came back alive.	Marton	le C

All values in μm

Green GEM foil:

Segmented Side			Unsegmented Side		
inner (RMS)	outer (RMS)	rim (RMS)	inner (RMS)	outer (RMS)	rim (RMS)
56.6 (1.54)	74.7 (1.54)	9.0 (0.58)	56.6 (1.57)	73.9 (1.94)	8.7 (1.94)

I-G2-003




- Long term I_{leak} ok
- Hole size distribution uniform
- Mean values of the inner, outer holes close to the target values

All values in μm

Yellow GEM foil:

Segmented Side			Unsegmented Side		
inner (RMS)	outer (RMS)	rim (RMS)	inner (RMS)	outer (RMS)	rim (RMS)
54.6 (1.72)	80.5 (1.57)	13.0 (0.49)	54.3 (1.67)	79.1 (2.64)	12.4 (0.68)

O3-G2-008




- Long term I_{leak} ok
- Hole size distribution not (always) uniform
- Mean values of the inner, outer holes within 5-10 μm of batch average

All values in μm

Orange GEM foil:

Segmented Side			Unsegmented Side		
inner (RMS)	outer (RMS)	rim (RMS)	inner (RMS)	outer (RMS)	rim (RMS)
53.9 (3.14)	77.3 (2.92)	11.7 (0.52)	53.8 (3.16)	81.0 (4.02)	13.6 (0.71)

O3-G3-005




- Long term I_{leak} ok
- Hole size distribution of segmented and unsegmented side not uniform
- Mean values of the inner, outer holes bigger than $10 \mu\text{m}$ of batch average

All values in μm



Orange GEM foil:

Segmented Side			Unsegmented Side		
inner (RMS)	outer (RMS)	rim (RMS)	inner (RMS)	outer (RMS)	rim (RMS)
53.9 (3.14)	77.3 (2.92)	11.7 (0.52)	53.8 (3.16)	81.0 (4.02)	13.6 (0.71)



O3-G3-005




- Long term I_{leak} ok
- Hole size distribution of segmented and unsegmented side not uniform
- Mean values of the inner, outer holes bigger than $10 \mu\text{m}$ of batch average



- ▶ Repeat coarse optical inspection and cross-check with known defects from the database



- ▶ Repeat coarse optical inspection and cross-check with known defects from the database
- ▶ We have to monitor the I_{leak} for each individual HV segment to fall below a specific value (0.5 nA/segment). I_{leak} will be measured before and after the framing



New FE ASIC “SAMPA” (130 nm TSMC CMOS)


- Positive or negative input
- Programmable conversion gains and peaking times
- Different readout modes: triggered, continuous with DSP, continuous with DSP by-pass

For required Signal-to-Noise ratio excellent noise figure of $670e^-$ (as currently) is needed

All ADC values are read out: data output for 50 kHz Pb-Pb collisions ≈ 6.55 TByte/s


Baseline correction and data compression off detector

Use CERN developed GBT and Versatile Link for readout



Two-stage reconstruction scheme:

- Cluster finding, cluster to track association: 1 TB/s \rightarrow 50 GB/s, scaled averaged space charge distortion map
- Tracking, ITS-TRD track matching, high-resolution space-charge corrections for full distortion calibration \rightarrow $O(200 \mu\text{m})$ in $r\phi$



Gas	v_d (cm/ μ s)	D_L ($\sqrt{\text{cm}}$)	D_T ($\sqrt{\text{cm}}$)	$\omega\tau$	W_1 (eV)	N_p (cm ⁻¹)	N_i (cm ⁻¹)
Ne-CO ₂ -N ₂ (90-10-5)	2.58	0.0221	0.0209	0.32	37.3	14.0	36.1
Ne-CO ₂ (90-10)	2.73	0.0231	0.0208	0.34	38.1	13.3	36.8
Ne-CF ₄ (90-10)	8.02	0.0152	0.0131	1.77	37.7	15.7	42.7
Ne-CF ₄ (80-20)	8.41	0.0131	0.0111	1.84	37.3	20.5	54.1
Ar-CO ₂ (90-10)	3.31	0.0262	0.0221	0.43	28.8	26.4	74.8

Gas Choices of the ALICE TPC:

- ▶ **RUN 1:** Ne-CO₂ (90-10)
TPC with gating grid, space charges only from the primary ions produced in the drift volume
- ▶ **Run 2:** Ar-CO₂ (90-10)
TPC with gating grid, focus on stability of operation
- ▶ **RUN 3:** Ne-CO₂-N₂ (90-10-5)
TPC with GEM amplification system, focus on fast ion drift velocity $v_{\text{ion}}(\text{Ar}) \sim 600$ cm/s, $v_{\text{ion}}(\text{Ne}) \sim 1600$ cm/s, E_{trans} is in ~ 4 kV/cm (Townsend coefficient), increases probability for traversing discharges, limits the field settings