



- **1.** Introduction
- 2. CMS GE1/1 triple-GEM Detectors Slice Test
- 3. CMS GE1/1 triple-GEM Detectors Construction and Certification
- 4. CMS GE1/1 triple-GEM Detectors Electronics
- 5. CMS ME0 triple-GEM Long-term Operation Study

### 6. Conclusion

# **CMS Forward Muon System Upgrade**

### Present CMS endcap muon detectors:

- CSC + RPC covering 0. 9 < |η| < 1.6</li>
- Only CSC covering 1. 6 <  $|\eta| < 2.4$

### From 2026: High - Luminosity LHC

→ Increase luminosity to  $5 \times 10^{34} s^{-1} cm^{-2}$ (5 × nominal value)

→ Upgrade current Muon Forward System:

- Increase redundancy in endcaps
- Improve p<sub>T</sub> measurements in low B field (solenoid)
- Reduce the trigger rates

#### Future GEM installation 1.5 < $|\eta|$ < 2.8

- GE1/1 project and GE2/1 project
- ME0 project







Slice Test = commissioning of 5 GE1/1 detectors in CMS

1 out of 5 with final readout electronics and HV Installation of GE1/1 during Long Shutdown 2

144 chambers in two endcaps GE1/1: 1. 5 <  $|\eta|$  < 2. 2

GE2/1 and ME0 installed by the end of Long Shutdown 3

 $\begin{array}{l} \mbox{GE2/1: } 1.5 < |\eta| < 2.2 \\ \mbox{ME0: } 2.0 < |\eta| < 2.8 \end{array}$ 

## **Gas Electron Multiplier Technology**

## **GEM foils:**

- 50 μm thick copper/cladded polyimide foils
- Holes (diameter = 70  $\mu$ m) in hexagonal pattern (pitch = 140  $\mu$ m)

## **GEM chamber:**

- Gas detectors: charged particles ionize gas
- One or multiple GEM- foils (e.g. triple GEM = 3 foils)
- HV applied: amplification process inside holes (E ~ 60 kV/cm)

## **Performance:**

- Rate capability: up to O(MHz/cm<sup>2</sup>)
- Triple-GEM chamber efficiency > 97% for MIPs
- No aging effects after 3000  $fb^{-1}$  (and even up to 875 mC/cm<sup>2</sup>)







# **CMS GEM GE1/1 Project**

## The 1<sup>st</sup> project of the CMS GEM Collaboration GEM Endcap Ring 1 Station 1

- GE1/1 chamber
- Triple-GEM chambers
- Gas mixture Ar/CO<sub>2</sub> (70/30%)
- Large area  $O(m^2)$
- Covering 1. 5 < |η| < 2.2</li>
- 144 trapezoidal Long and Short chambers
- 24 readout sectors per chamber
- 128 radial strips for each sector
- Digital readout
- 72 Super Chambers (2 coupled chambers)
- Each Super Chamber covers 10. 15° (overlap)





# CMS GE1/1 triple-GEM Detectors Slice Test

## Co-authors Martina Ressegotti and Ilaria Vai

## **GE1/1 Slice Test Overview**

- A demonstrator with 5 SuperChambers (or *GEMINI*) took place in 2017-18 with the goals to:
- Proving the system's operational conditions
- Developing the integration into the CMS online system
- Start acquiring installation and commissioning expertise

#### **SLOT - 1** $\rightarrow$ 4 *GEMINI*:

- High Voltage supplied with a single HV channel per detector (8 HV channels in total)
- The HV is distributed to the detector's electrodes through a voltage divider
- Readout system based on VFAT2 ASICs

Slot 1

#### **SLOT - 2** $\rightarrow$ 1 *GEMINI*:

- High Voltage supplied with a multichannel power supply realized specifically for triple-GEM detectors (CAEN A1515TG)
- The HV module provides 7 × 2 voltage channels to power independently all detector's electrodes
- Readout system based on VFAT2 ASICs in 2017, moved to VFAT3 ASICs in 2018

## **GE1/1 Slice Test - System Stability**

The activity of 2017 included a study of stability of triple-GEM detectors into the CMS environment

Single HV channel

→ high voltage fluctuations < 1% observed in a period of 7 hours during LHC collisions  $(L_{max} \approx 1.1 \times 10^{34} cm^{-2} s^{-1})$ 

## Multichannel HV

 $\rightarrow$  high voltage fluctuations <1% observed for all 7 HV channels in a period of 12 hours during LHC collisions

 $(L_{max} \approx 9.3 \times 10^{33} cm^{-2} s^{-1})$ 

## LV channels

 $\rightarrow$  LV channels showed the same stability both with and without beam



# **GE1/1 Slice Test - Integration into CMS**

### **Detector Control System (DCS)**

- The Detector Control System (DCS) was locally developed to control the HV and LV system and to monitor the gas system and environmental parameters.
- A Finite State Machine (FSM) was then added in order to prepare the system for the operation in central DCS.
- The final integration of the GEM DCS in CMS was reached at the end of 2017.

## **Data Quality Monitoring (DQM)**

 The inclusion of GEMs into the global runs entails also the need of monitoring the quality of data collected as well as the performance of the detectors.





## **GE1/1 Slice Test - First Results**

#### **GE1/1 Slice Test: Success!**

#### First results of reconstructing collision data with GEMs in muon reconstruction 2017/2018



20/02/2019

CMS Experiment at the LHC, CERN Data recorded: 2018-Jul-08 19:55:40.193536 GMT Run / Event / LS: 319347 / 36141749 / 46



LHC run2 2018C p-p collision event display showing two muons (red lines), associated with hits on one of the five GE1/1 slice test super-chambers (blue trapezoidal boxes) at station 1 of the endcap muon system. The antimuon ( $p_T = 30.11 \text{ GeV}/c^2, \eta = -1.956$ ) and muon ( $p_T = 53.597 \text{ GeV}/c^2, \eta = -1.993$ ) has a combined invariant mass of  $3.011 \text{ GeV}/c^2$  ( $J/\Psi$  meson particle).



LHC run2 2018C p-p collision event display showing two muons (red lines), associated with hits on one of the five GE1/1 slice test super-chambers (blue trapezoidal boxes) at station 1 of the endcap muon system. The antimuon ( $p_T = 34.01 \ GeV/c^2, \eta = -0.540$ ) and muon ( $p_T = 37.63 \ GeV/c^2, \eta = -1.985$ ) has a combined invariant mass of 91. 141  $GeV/c^2$  ( $Z^0$  boson particle).



# CMS GE1/1 triple-GEM Detectors Construction and Certification

## Co-authors Mohsin Abbas, Michele Bianco, Jeremie Merlin and Archana Sharma

# **GE1/1 Production Sites**

- $\rightarrow$  Distribution of the production in various sites:
- Share the effort with CMS GEM institutes
- Generate a large community of GEM experts
- Equip production sites with infrastructure, tooling and knowledge for GE2/1 and ME0 productions
- $\rightarrow$  2-years training program
- Using same procedure
- Using same infrastructure
- All Quality Control deliverables validated by the production community



# **GE1/1 Detector Assembly**

## **GE1/1 Detector Assembly Procedure**

## **Preparation of the components (in laboratory)**

- Cleaning of the components
- Preparation of the HV circuit
   Mounting of the pull-outs
   Selection of the O-ring

#### Assembly (in clean room)

- Fast test of the GEM-foils
- 2<sup>n<sup>r</sup></sup> Mounting of the stack Closing of the chamber

## **1** day is sufficient to fully assemble a GE1/1 detector







D. Abbaneo et al., Layout and assembly technique of the GEM chambers for the upgrade of the CMS first muon endcap station, Nucl. Instrum. Methods Phys. Res., A 918 (2019) 67 - 75



20/02/2019

R

CERN

Production sites

CERN

15

# **GE1/1 Detector Production Status**

## **Super Chamber Assembly:**









## **On-time production:**

(last update 9<sup>th</sup> Feb. 2019)

- 160 detectors already assembled
- 151 detectors fully validated up to QC5
- 6 Quality Control on-going
- 3 chamber need to be repaired
- 13 detectors fully equipped with electronics and services (6 Super Chamber + 1 chamber)



# CMS GE1/1 triple-GEM Detectors Electronics

### **Co-authors**

Brian Dorney, Francesco Ivone, Gilles de Lentdecker and Federica Simone



# **GE1/1 Electronics: VFAT3 Front-end**

## VFAT3 chip on hybrid:

- Binary output, CFD
- 320 MHz
- L1 latency: up to 25. 6 μs
- Slow control: ePort, GBT compatible
- Trigger data:

 $\rightarrow$  1bit = OR of 2 strips (+DDR option)



VFAT3 chip on hybrid



- Trigger path: 8 sLVDS pairs @ 320Mbps 64b/bx (128b/bx DDR)
- Fast OR: Each pair of channels, lossless
- SPZS: Full granularity, up yo 6 partitions /bx
- DDR: Full granularity, lossless.
- Data path: Full granularity after LV1 + time tag LV1 latency extended to 25us LV1 rate extended to 1MHz.
- Communication interface to GBT: Comm-Port allows bi-directional communication of control commands, CMB (calibration, bias and monitoring) and data readout through a single port to the GBT.

# VFAT hybrid for GE1/1: input protection circuit studies

The GEM collaboration is carrying out an R&D campaign to improve the input protection and robustness of front-end electronics preventing possible discharge damage

HV3b - V3

**Ext. input protection** 

HV3b - V2 Initial baseline

Internal input protection only (diode). Channels burnt with  $E > 28 \ \mu J/disc$ 

8 ohm



 $(R = 330 \ \Omega)$  OK after 500 ESD 470 µJ/disc X-talk +15%; Noise +20%

No radiation issues expected

HV3b - V4 Ext. Input protection (diodes)

OK after 540 ESD 470µJ/disc No increase of noise observed Rad Hard studies OK (10 Mrad)









# CMS ME0 triple-GEM Detectors Long-term Operation

## Co-authors Davide Fiorina and Jeremie Merlin

## **Aging of Gaseous Detectors**

## **Classica Aging:**

- Chemical processes occurring in the plasma avalanches release free radicals chemically active
- Radicals → Monomers → Polymers
- Polymers deposit on sensible surfaces (anode, cathode, insulations, etc.)



### Detector performances loss!

CMS needs to validate triple-GEM technology for the ME0 project

- Expected hit flux in the ME0 muon detectors: ~ 50 kHz/cm<sup>2</sup>
- Constraints on the technology for the upgrade:
  - Longevity > 10 HL-LHC years (× safety factor 3!)
  - Accumulated charge ( 10 HL–LHC years ):

 $\rightarrow Q_{tot} = Rate \times Primaries \times Gain \times Time \times q_e \sim 283 \ mC/cm^2 \ (at \ Gain = 2 \times 10^4)$ 

850 mC/cm<sup>2</sup> of integrated charge (safety factor 3!) needed to fully validate the triple-GEM technology for the new ME0 project

## **Longevity Studies at GIF++ facility**

**GIF++ facility:** 

- The facility consists of an intense 14 TBq (in 2015) <sup>137</sup>Cs source emitting 662 keV photons and lower energetic scattered photons
- Particle flux: ~ 10<sup>8</sup> Hz/cm<sup>2</sup>

**Detector under test:** 

- CMS GE1/1 triple-GEM detector ( similar to the final design )
- Effective Gas Gain: 2 × 10<sup>4</sup>
- Gas Mixture: Ar/CO<sub>2</sub> (70/30)
- Measured parameter:
- Monitoring of the anode current (representative of the detector gas gain)



NO aging observed up to  ${\sim}182~mC/cm^2$  (  ${\sim}~64\%$  of ME0 operation at the HL-LHC )

Additional 5 - 5.5 years are needed in order to validate the MEO project with the safety factor 3

# Longevity Studies at CMS-GEM Production Lab.

#### Source:

 22 keV X-ray photons from X-rays generator

#### **Detector under test:**

- CMS GE1/1 triple GEM detector ( final design and material )
- Effective Gas Gain: 2 × 10<sup>4</sup>
- Gas Mixture: Ar/CO<sub>2</sub> (70/30)

#### Measured parameter:

- Monitoring of the anode current during the irradiation test
- Weekly effective gas gain meas.
- Weekly energy resolution meas.



#### X-ray Aging Test at CMS-GEM Lab.

20/02/2019 (4000 hours of continuous tests)

#### ( $\sim 31$ years of ME0 operation at the HL-LHC )

NO aging observed up to  $\sim 875 \ mC/cm^2$ 

# **Longevity Studies at CMS-GEM Production Lab.**



## Conclusions (1/2)

- 1. CMS GE1/1 triple-GEM Detectors Slice Test
  - A Slice Test composed of 5 Super-Chambers installed at beginning of 2017
    - High Voltage and Low Voltage systems: functional and stable
    - DCS and DAQ system: functional and successfully calibrated
    - **Operation:** successfully detected cosmic muons and muons from p-p collisions
    - Other aspects not covered here: gas system, cooling system, cable routing and other necessary services have been installed/performed and worked properly
  - Slice Test removed at the end of January 2019 in preparation for the final installation of the GE1/1 station

### **2.** CMS GE1/1 triple-GEM Detectors Construction and Certification

- Successful production of 144/144 (100%) detectors in 10 production sites
  - All tested detectors are within specifications ( with uniform performances )
  - Full production has been completed in December 2018
  - Production of Super-Chambers and final certification are in a full swing

## Conclusions (2/2)

- 3. CMS GE1/1 triple-GEM Detectors Electronics
  - GE1/1 Slice Test has observed irreversible channel loss in the VFAT-V2
  - R&D campaign launched this summer to understand:
    - The origin of the channel loss: discharges propagating to the anode plane
    - The weakness in GE1/1 front-end protection: new hybrids have been designed with diode protection

### 4. CMS ME0 triple-GEM Longevity Studies

- Longevity test ongoing at GIF++ facility ( γ ray exposure )
  - NO aging observed up to  $\sim 182 \ mC/cm^2$
  - $\sim 64\%$  of *MEO* operation at the HL-LHC
- Longevity test ongoing at CMS-GEM QA/QC facility (X ray exposure)
  - NO aging observed up to  $\sim 875 \ mC/cm^2$
  - 10 years of *MEO* operation at the HL-LHC (safety factor 3.1)
- Advanced Longevity Studies ( preliminary results )
  - Aging issues originated by particles with different ionization powers
- 20/02/2019 Clear correlation between specific ionization power and polymer creation rate 27



## VCI2019

# Vienna Conference on Instrumentation



## The author is grateful to co-authors for their support of this work:

- Moshin Abbas, Institut für Experimentelle Teilchenphysik, Karlsruhe, Germany
- Michele Bianco, CERN European Organization for Nuclear Research
- Brian Dordey, Université libre de Bruxelles, Belgium
- Davide Fiorina, University of Pavia and Pavia INFN, Italy
- Francesco Ivone, University of Bari and Bari INFN, Italy
- Gilles de Lentdecker, Université libre de Bruxelles, Belgium
- Jeremie A. Merlin, CERN European Organization for Nuclear Research
- Martina Ressegotti, University of Pavia and Pavia INFN, Italy
- Archana Sharma, CERN European Organization for Nuclear Research
- Federica Simone, University of Bari and Bari INFN, Italy
- Ilaria Vai, University of Pavia and Pavia INFN, Italy





#### **Comments:**

- More than 5 years of R&D to optimize the performance, reliability and construction
- Production of 10 Slice Test chambers → installed in CMS in January 2017

(\*) Installation of a new GEM production facility at CERN (904 Lab.)





## **GE1/1 Detector Design**

## **GE1/1 Detector Construction**

- GE1/1 detectors introduced a novel technique of GEM chambers construction, which avoid the usage of glue
- GE1/1 detectors are realizing using GEM foils stretched by means of moveable FR4 frame (internal). Cathode and Readout electrode made by standard single layer PCB. Electrical signal extracted by "vias" on PCB trough 130 pins Panasonic connectors
- The internal frames are controlled by "stretching screws"
- The tightness of the chambers is assured by an external FR4 frame sealed with O-ring
- Chamber assembly have to be performed in clean room (at least class 1000) to avoid GEM foils contamination
- GE1/1 chamber production distributed in several production sites
- GE1/1 Mass production started in April 2017



CERN







## **QC1 - Detectors Components Inspection and Qualification**

All the GE1/1 detector components produced by industrial companies are delivered to CERN where they are immediately verified for defects and tested

### $\rightarrow$ Internal / external frames

- Optical inspection to identify possible cracks, mechanical unconformities and manufacturing defects on the epoxy glass structure
- Measurements of the width and depth of the grooves along periphery of the external frame that will accommodate the Viton O-ring in order to ensure greater degree of the gas-tightness of the detector

#### → Viton O-ring

20/02/2019

 Measurements of the external diameter in order to ensure a correct coupling between the O-ring and the external frame and ensure a correct gas-tightness





32







# QC1 - Detectors Components Inspection and Qualification

### $\rightarrow$ Drift Board

 Optical inspection to identify possible mechanical damage and surface anomalies on the drift electrode and its planarity

#### → Readout Board

- Optical inspection to check the planarity of the readout board and possible macroscopic scratches and defects on the readout strips or Panasonic adopters for signal readout
- Connectivity test in order to inspect the readout board for possible shorts between strips or open strip-readout connections
- The readout board under test is rejected if:
  - short circuit ≥ 4
     (in the whole readout board)
  - *faulty channels* ≥ 3
     (inside the same Panasonic adapter)







Microscopy photos of the readout strips showing some examples of defects and short circuits between the readout strips.





## **QC2 - Leakage Current Test**

The QC2 - leakage current test aims to determine the quality of a GEM-foil by measuring the maximum leakage current flowing on the surface of the GEM-holes.

GEM-foils produced in the CERN PCB workshop are delivered to CMS GEM clean room, where they undergo to dedicated QA/QC test:

- Optical inspection to identify macroscopic defects on the copper or Kapton layers, which could increase the probability of electrical breakdown and/or short circuit
- Dedicated quality control test (QC2 - Leakage Current test) to measure the leakage current and possible discharge

When a voltage is applied across the GEM-foil, a current flows from its top to bottom due to the surface conductivity of the Kapton which is known as **leakage current** 

CERN



Presence of dust, pollution or defects could provoke an increase the leakage current flowing through the polyimide surface

It is possible determinate the integrity of the GEM-foils by measuring this leakage current and/or possible discharge





## **QC2 - Leakage Current Test**

#### $\rightarrow$ QC2 Fast Term Stability

- The first step consists of applying 550 V to the GEM-foil and measure the leakage current between the top and the bottom electrodes and the number of possible discharge
- QC2 Fast Term Stability is performed both in CERN PCB workshop before the foils delivered and as soon as the foils arrive in the CMS - GEM QA/QC lab.
- The QC2 Fast Term Stability is performed with a Multi Mega-ohmmeter (Megger) over a period of 10 min. in air
- The GEM-foil is accepted if:
  - *impedance*  $\geq$  **10** *G* $\Omega$
  - *number of discharge* ≤ 2 (during the last two/three minutes of test)
- If the number of discharges exceed the limit, the GEMfoils have to be re-cleaned with antistatic roll or, in the worst case, with *DI water* in ultrasonic baths



FR







## QC2 - Leakage Current Test



Schematic view of the QC2 long term stability setup



### $\rightarrow$ QC2 Long Term Stability

- Goal of the QC2 Long Term Stability test is the ultimate certification of the GEM-foils before the installation in the GE1/1 detectors
- QC2 Long Term Stability test is conducted using CAEN HV module with 50 *pA* of current resolution acquired through *LabView* based software
- The GEM-foils are kept at low humidity level  $(\sim 7 \%)$  in a dedicated box by flushing in pure dry Nitrogen ( $N_2$  flow rate  $\approx 50 L/hr$ )
- GEM-foils are rejected if the test is failed more than three times (see next slide)
- GEM-foils fails the test are promptly sent back to the CERN-PCB workshop for cleaning




### **QC2 - Leakage Current Test**

#### $\rightarrow$ QC2 Long Term Stability

The Long test is divided into preliminary characterization phase and 3 steps with data monitoring:

- During the "first gas flushing period"  $\sim 36/48 hr$ , needed to reduce the relative humidity up to  $\sim 7\%$ , the GEM-foils are kept at 500/550 Volts, (Current limit 100 nA, trip time 1 sec)
- Step 1: Slow rump up to 500 V, plateau monitor at 500 and 550 Volts; step is passed if no discharges occurred for 10 min. for each HV value
- Step 2: HV fixed at 600 Volts, current and discharges are monitored; step is passed if no discharges occurred for 15 min. or no more than two discharges during the last 6 hr (Current limit 50 nA, Trip Time 0 sec)
- Step 3: Voltage switches between 100 Volts and 600 Volts, to evaluate a possible off-set in the current measurement



FR







**Step 1:** all the tools are prepared and carefully organized for the assembly (left). The working table, made of PolyMethyl MethAcrylate (PMMA), is cleaned with an anti-static paper and ethanol (right).



**Step 2**: the internal frames, responsible of holding the GEM stack, are cleaned with an anti-static roll (left) and placed on working table thanks to guiding pins (right).









#### **Step 3:** the first GEM foil is tested at 550 *V* and cleaned again with the adhesive roll.



**Step 4:** the first GEM is placed on the first layer of internal frames (left). The foils is stretched by hand and attached to the working table to ensure the flatness and stability of the structure (right).







# **GE1/1 Detector**





**Step 5:** the second layer of internal frames is placed on top of the first GEM (left). After testing and cleaning, the second GEM is added to the stack (right).



**Step 6:** same operation as before, the second GEM is stretched manually (left) and tested at 550 *V* (right).









**Step 7:** after the third layer of internal frames is in position, metallic nuts are inserted in the dedicated housing of the frames. Then, the last GEM foils is added to the structure.



**Step 8**: the last layer of internal frames is added to close the stack (left), the GEM stack is protected by a PMMA cover placed fixed to the top of the internal frames.









**Step 9**: vertical screws are inserted into the frames in order to attach all the frame layers and GEM together.



**Step 10:** the excess of polyimide foil is cut and detached from the GEM stack.









**Step 11:** after being cleaned with the anti-static roll (left), the drift plane is positioned below the GEM stack (right).



**Step 12:** lateral screws are inserted in the stainless steel pull-outs attached to the drift board until it reaches the embedded nuts (left). Then, torque control tools are used to stretch the foils, for a tension about  $8 - 10 cN \cdot cm$ .





**GE1/1 Detector** Assembly



**Step 13:** the possible dust produced during the stretching step is removed with an anti-static roller (left) and the three GEM foils are tested once again at 550 *V*.



**Step 14:** The external frames is equipped with the O-rings (left) and it is placed around the GEM stack (right).









**Step 15:** after being cleaned (left), the readout board is placed on top of the external frame to close the chamber.



**Step 16:** finally, washers are inserted in the dedicated housings of the readout board before the last screws are used to attach all the elements together and close the gas volume (left). Picture of a last generation GE1/1 detector just after the assembly (right).







### QC3 - Gas Leak Test

#### Identify the Gas Leak Rate of the detector by monitoring the drop of the internal over-pressure as a function of time and check the gas tightness $\frac{1}{2} \frac{32}{GE1/1 \text{ Detector Production (LS2)}} \frac{1}{2} \frac{1}{2}$

The detector is pressurized at 25 - 30 mbar in pure CO<sub>2</sub>



- The pressure drop is measured during one hour after closing the gas volume
- The experimental data are modeled by the function:  $P_m = P_0 \times e^{-t/\tau}$  to extract the gas leak time constant  $\tau$



FR

Typical *Pressure* vs *Time* curve obtained during the QC3 gas leak test. The parameter  $\tau$  obtained by fitting is the Gas Leak Time Constant.







### QC3 - Gas Leak Test

#### → Acceptance criteria

The detector under test is validated if the pressure drop in the detector + gas system does not exceed:

#### $\Delta P \leq 7 \ mbar/hr$

at initial over-pressure of  $25 \ mbar$ , which corresponds to a gas leak time constant:

#### $\tau \geq 3.04 hr$

### Examples of damage assembly components identified as potential gas leak sources in the GE1/1 detectors











Assembly

**GEM-foils Test (fast)** 

#### QC3 - Gas Leak Test

- $\rightarrow$  Pressurize the detectors at 25 mbar
- $\rightarrow$  Measure the pressure drop during one hour after closing the gas volume
- $\rightarrow$  Fit the results to extract the time constant of the system

**Statistics:** (mean ± std.)

#### Time Constant = $16.2 \pm 11.8 hr$







## <u>QC4 - High Voltage Test</u>

# Determine Current vs Voltage curve of the detector and identify possible malfunctions, defects in the HV circuit

- The detector is ramped up to 3.0 kV in step of 200 V and up to 4.9 kV in step of 100 V in pure CO<sub>2</sub> using a resistive HV divider
- For each step, the current through the HV circuit of the detector is recorded
- The experimental data are modeled by the function:  $I_{mon.} = \left(\frac{1}{R_{equiv.}}\right) \times V_{mon.}$
- → Acceptance criteria

 $\frac{|R_{measured} - R_{expected}|}{R_{expected}} \times 100\% \le 2\%$ 





FR

Typical *I* vs *V* curve obtained during the QC4 HV test.  $I_{mon.}$  represents the current flowing through the HV divider to provide power to the detector electrodes.





## <u>QC4 - High Voltage Test</u>

# Determine Intrinsic Noise Rate (i.e. pulses not produced by ionizing particle) over the entire detector surface

- The detector is ramped up to 3.0 kV in step of 200 V and up to 4.9 kV in step of 100 V in pure CO<sub>2</sub> using a resistive HV divider
- For each step, the intrinsic noise rate R<sub>noise</sub> of the detector is recorded from the bottom of the third GEM-foil



#### → Acceptance criteria

 $R_{noise} \leq 0.02 \ Hz/cm^2 \ (at \ 4.9 \ kV)$ 



Typical Intrinsic Noise Rate as a function of the applied voltage obtained during the QC4 HV test:  $R_{noise} \approx 6.4 \times 10^{-3} Hz/cm^2$  at 4.9 kV.







QC4 - High Voltage Test

- $\rightarrow$  Measure the I vs. V characteristics
- $\rightarrow$  Measure the spurious signal rate over the entire detector surface

### Statistics: (mean ± std.)

 $R/R_{expected} = 0.65 \pm 0.23 \%$ 



Spurious Signal Rate =  $19.5 \pm 11.2$  Hz











#### **QC5 - Gas Gain Measurement**

#### A 2-steps procedure to measure the Effective Gas Gain

10<sup>5</sup> UNOC

STEP 1 Effective Gas Gain Measurement

- → First operation in  $Ar/CO_2$  (70/30) at high particle flux
- → Get the effective gas gain versus HV in one readout sector

Angelek Mini-XX-Ray Tube Angelek Mini-XX-Ray Tube Target Silver Voltage Tube 10 kV min. / 50 kV max Current Tube 5 µA min. / 200 µA max Output Cone Angle 120°

Both tests performed inside a copper box using an X-ray generator ( $\sim 22 \ keV \ X - rays$ )

STEP 2 Response Uniformity Measurement

- → Get "internal" gas gain variations map
- → Get average gas gain and std. deviation after compiling with eff. gas gain meas.





20/02/2019



**GE1/1 QC Overview** 

### **QC5 - Effective Gas Gain Meas.**

Measure the Effective Gas Gain as a function of the voltage applied on the resistive high voltage divider

- Effective gas gain of GE1/1 detector is measured in a single readout sector (η = 4, φ = 2)
- The Effective gas gain is defined as:





ER







## **QC5 - Response Uniformity Meas.**

#### Measure the internal gas gain variations maps for each detector

- Detector fully irradiated with X-rays
- RO based on analog electronics (APV25)
- Measure the copper fluorescence for every readout channels
- Compare ionization peak position (2D map)
- The uniformity map is used to calculate the average effective gas gain and the standard deviation for each detector













#### Variations of GEM thickness

- Producers claims  $50 \pm 0.1 \ \mu m$
- i.e. Gain variations:

Electron Multiplication  $\pm 2.4\%$  for single-GEM ( $\sigma_{total}/G_{total} = \sqrt{3} \times \sigma_{single}/G_{single}$ )

- $\pm$  4.2% for triple-GEM
- + Second order variations
  - Thickness of GEM copper layers  $(\pm 0.5\%)$

#### Variations of GEM hole diameter

- Outer diameter: 70  $\pm$  5  $\mu m$
- *i.e. Gain variations:*  $\pm$  **15%** for single-GEM  $\pm$  26% for triple-GEM
- + Second order variations
  - Variations of the inner hole diameter
  - Variations of the hole asymmetry



S. Bachmann et al., ERN-EP/99-48, 1999







#### **Bending of Drift and RO PCBs**

- Initial bending from fabrication process
- Induced by GEM stretching
- GEM Transparency Induced by mechanical stress on O-ring and internal frames
- Bending due to gas over-pressure
- Slice test production team worked a lot on chamber design and assembly procedures to mitigate the bending effect









GEM

#### **Bending of Drift and RO PCBs**

- $Gap_{Drift} = 3 + 0.6 mm / Gap_{induction} = 1 + 0.4 mm$
- i.e. Electric fields + 20% (drift) and + 40% (RO)
- Transparency i.e. Gain variations: +7.5% (drift) and +25% (RO)

(May also change by few % depending on the internal pressure)



#### + Second order variations

- Thickness of the internal frame PU coating ( $\pm 0.5\%$ )
- Height of the pull-outs  $(\pm 0.7\%)$







Environmental Parameters

#### **Gas temperature and pressure**

• Known effect in gaseous detectors

 $Gain \sim Exp(\alpha_{Townsend}) \sim Exp\left(\frac{E}{\rho_{gas}}\right) \sim Exp\left(\frac{E \times T}{P}\right)$ 

Corrections on Detector HV

 $Gain_{measured} \sim Exp(HV) \rightarrow Exp(HV \times {^{T}/_{P}} \times {^{P_{0}}/_{T_{0}}})$ 



#### + Second order variations

- Variations of the internal pressure (i.e. gas flow rate)
- Variations of the gas composition ( "second order" because under control in GEM QC setups)
- 20/02/2019





#### **Total gain variations**

 $\sigma_{total} = \sqrt{\sigma_{GEM \ thickness}^{2} + \sigma_{hole \ diameter}^{2} + \sigma_{bending \ drift}^{2} + \sigma_{bending \ RO}^{2}}$  $\sigma_{total} = 37.1 \ \% \ (relative \ error - first \ order \ approximation)$ 

From B2B test beam (data provided by I. Vai and M. Ressegotti - Jan 2017)



Individual chamber average gain can be within 50% of the other chamber without affecting the global performances





stituto Nazionale di Fisica Nucleare



#### QC5 – Step 2

#### **Response Uniformity Test**

- $\rightarrow$  Detector fully irradiated with X-rays
- $\rightarrow$  RO based on analog electronics (APV25)
- $\rightarrow$  Measure the internal gain variations map

#### Statistics: (mean ± std.)

- Long  $\rightarrow \sigma/\mu = 15.35 \pm 6.17 \%$
- **Short**  $\rightarrow \sigma/\mu = 11.77 \pm 3.89\%$







CFR

#### **Chamber selection for SC assembly**

- Define the detector pool (not already paired, QCs passed and validated, physically present at CERN)
- Compile the QC data to select the chambers with the most similar characteristics







 $10^{3}$ 

Average Effective Gas Gain

 $10^{4}$ 

#### **Statistics before/after HV optimization:**

 $10^{4}$ 

ሰቬ

 $10^{2}$ 

Before  $\rightarrow G_{eff} = 8705.0 \pm 3246.2 (37.3\%)$ After  $\rightarrow G_{eff} = 10006.6 \pm 364.9 (3.6\%)$ 

Round 1: 34 selected chambers (17 SCL)

ەلتىك

 $10^{2}$ 

 $10^{3}$ 

Average Effective Gas Gain



## **GE1/1 Super Chamber Matching**



R

CERN

Production sites

CERN

## **GE1/1 Super Chamber Matching**



R

CERN

Production sites

CERN

## **GE1/1 Detector Production Status**

### **On-time production**

- 160 detectors already assembled
- 148 detectors fully validated up to QC5
- 7 validation on-going
- 5 QC on-going
- 3 chamber rejected (need intervention)





- Successful production of 160 detectors in 10 Production Sites
- All tested chambers within specifications

Full production of 144 detectors (2 full endcaps) completed in December 2018

## **GE1/1 Super Chamber Matching**

**GE1/1** Detector Production

CMS

45 Long Chambers 40 Gas = Ar/CO<sub>2</sub> (70/30)

Bound 1 Selection 35 Optimized HV After SC Pairing

----- G<sub>avg</sub> +/- 50 %

CERN

Ghent

Pakistan

+-G<sub>ava</sub>

 $10^{2}$ 

G<sub>avg</sub> +/- 37 %

50

Serial Number

Detector

#### **Before Optimization**



#### $\langle G \rangle_{eff} \sim 5786.9 ~\pm~ 2108.8 \rightarrow \sigma/\langle G \rangle_{eff} \sim \mathbf{36.4\%} \qquad \langle G \rangle_{eff} \sim 10011.2 ~\pm~ 376.2 \rightarrow \sigma/\langle G \rangle_{eff} \sim \mathbf{4.8\%}$



#### **After Optimization**

Preliminary

Average Effective Gas Gain



 $\langle G \rangle_{eff} \sim 7980.0 \pm 2893.0 \rightarrow \sigma / \langle G \rangle_{eff} \sim 36.2\% \quad \langle G \rangle_{eff} \sim 10006.0 \pm 364.9 \rightarrow \sigma / \langle G \rangle_{eff} \sim 3.6\%$ 20/02/2019





**Longevity Studies** 



#### **Aging of Gaseous Detectors:**

#### **Radiation hardness**

modifications of the physical, chemical and electrical properties of the detector materials

#### Long-term damages/variation of the structure

- modifications of the stretching strength with time inducing non-uniformity
- discharges-induced damages

#### **Classical Aging**

 production of polymers in the plasmas during the amplification (gain losses, non-uniformity, selfsustained discharges, increase of the dark current, degradation of the space/time/energy resolutions, lower rate capability, etc.)



#### Complex phenomenon

- Many input parameters (technology, geometry, mode of operation, charge, gas mixture, etc.)
- Several possible processes ( plasma conditions )
- Various results ( type of polymers, physical state, electrical properties, etc. )





**Longevity Studies** 



### **Aging of Gaseous Detectors:**

How to measure longevity of gaseous detectors?

- $\rightarrow$  Measure various properties of the detector at different accumulated doses
- $\rightarrow$  Monitor gas gain fluctuations during the irradiation

**Requirements:** 

- ightarrow Accelerate aging with strong radiation
- $\rightarrow$  High acceleration factors reduce polymer production rate ( so aging effects )
- → Recommendations:
  - Acceleration factor << 100 × real operation (realistic conditions)</li>
  - Accumulate expected dose with safety factor
- → Monitor the environmental parameters:
  - Temperature
  - Pressure
  - Gas purity / gas flow rate
- → High Purity Systems:
  - Aging mostly enhanced by pollution in the gas mixture





**MEO Longevity Studies** 

### at GIF++ facility



### Gamma Irradiation Facility (GIF++)

*How to reproduce the aging effects*?

- The facility consists of an intense 14 TBq (in 2015) <sup>137</sup>Cs source emitting 662 keV photons and lower energetic scattered photons
- The GIF++ photons have an energy fairly representative of the energy of LHC/HL-LHC photons seen by the muon detectors





The GE1/1 detector under test is placed at  $\sim 1m$  from the source point (  $D_1$  position ):

- upper half of the detector is operating under a particle flux just below 10<sup>8</sup> Hz/cm<sup>2</sup>
- lower half receive a flux lower by four orders of magnitude (  $10^4 Hz/cm^2$  )

20/02/2019





MEO Longevity Studies at GIF++ facility



### **Experimental Setup at GIF++ facility**

**Detector Under Test and Conditions of Operation:** 

- CMS GE1/1 triple-GEM detector 4<sup>th</sup> generation (representative of the detectors that will be installed in the CMS Muon end-caps)
- Effective Gas Gain: 2 × 10<sup>4</sup>
- Gas Mixture: Ar/CO<sub>2</sub> (70/30) Gas Flow Rate: 5.0 L/h

**Irradiated chamber** @ GIF++ during the aging studies 2015/2016:  $\sim 55 mC/cm^2$  collected in about 6 months of continuous tests.





- New setup designed in aluminium bosh-profiles and assembled to host the triple-GEM chambers
- The DAQ electronics placed below the detector structure and protected inside the lead shielding box




at GIF++ facility



## Installation inside the GIF++ facility



CMS-GEM1 setup inside the GIF++ bunker ( back view )

### CMS-GEM1 setup inside the GIF++ bunker ( front view )



20/02/2019





# at GIF++ facility



# Data Acquisition System at GIF++ facility

How to identify the aging effect?

- Impossible to measure all performance and characteristics during the irradiation test.
  - $\rightarrow$  Requires specific experimental condition ( beam, low energy X-ray, etc. )
  - $\rightarrow$  Probability to disturb the system during the irradiation test







# at GIF++ facility



# **Analysis Procedure at GIF++ facility**

*How to extract the aging effect from the raw data*?

 The anode current, which reflects the effective gas gain of the detector, depends on the gas density, function itself of the temperature and pressure:

 $I_{real} = I_{measured} \times \left(P_i \times \left(\frac{1}{P_i}\right)\right)^{F_1} \times \left(\frac{\langle T_i \rangle}{T_i}\right)^{F_2}$ 

Environmental fluctuations can hide the aging effect









# at GIF++ facility



# **Accumulated Charge and Anode Current Measurement**



### NO aging observed up to $\sim 182 \ mC/cm^2$

(  $\sim 64\%$  of ME0 operation at the HL-LHC )

- The longevity studies will continue at the GIF++ until the detector accumulates a total charge of about ~ 850 mC/cm<sup>2</sup>
- This will take additional 5-5.5 years of exposure due to the duty factor of the GIF++
- To overcome this extremely long time, an additional longevity test has been setup in summer 2017 exposing a GE1/1 triple-GEM detector to ~ 22 keV X - rays photons at CMS-GEM QA/QC facility (904 Lab.)



# Interview MEO Longevity Studies Interview CMS-GEM QA/QC facility



# **Experimental Setup at CMS-GEM facility**

- QA/QC X-ray station adapted for longevity studies
- Source: 22 keV X-ray photons from Xrays generator
- Detector: LS2-GE1/1 detector with the final geometry and materials







### *X-ray configuration:*

The X-Ray gun has been placed at 12cm from the detector in order to:

- Maximize anode current and accelerate aging studies (5 months instead 5.5 years at GIF++ facility)
- Irradiate the GEM-foils, external / internal frame, O-ring, etc.

# MEO Longevity Studies CMS-GEM QA/QC facility

### **Data Acquisition and Analysis Procedure**





FRN

#### **Readout System:**

*3 pico-ammeters on the irradiated zone to monitor the anode current during the irradiation test* 

1 pico-ammeter on the non-irradiated zone as a reference during the irradiation test

#### **Meteo Station:**

Arduino Meteo Station inside the X-ray copper box to monitor environmental parameters.

During the irradiation test, in addition to the monitoring of the anode current:

- The effective gas gain and the energy resolution have been continuously measured every week on the readout sectors under test.
- The gas gain map uniformity measurements have been performed every month to check for the gas gain variation between the irradiated and non irradiated detector active area.

# Initial State MEO Longevity Studies Initial State CMS-GEM QA/QC facility





ERN





### **MEO Longevity Studies** INFŃ **CMS-GEM QA/QC facility** Istituto Nazionale di Fisica Nucleare

### **Monthly Response Uniformity Measurement**

 $(i. e. every \sim 100 - 120 \text{ mC/cm}^2)$ 

- Gas gain map uniformity measurements to check for the gas gain variation between the irradiated and nonirradiated detector active area.
- uniformity Standard QC5 response measurement developed for the LS2 GE1/1 detector qualification.
- 2D normalized ADC peak position shows similar pattern up to  $875 \ mC/cm^2$ .

The results of the response uniformity measurements demonstrated that the detector remains fully operational after  $875 mC/cm^2$  of accumulated charge







E 400 -

5 300

200

100

-100

-200

-300 -

-400 -

10 300

200

100

0

-100

-200

-300

400

-150 -100 -50 0

50 100 150

Width (mm)

50 100 150

Width (mm)

0







ERN

 $\sim 400 \ mC/cm^2$ 





20/02/2019

1.0 0

# **Advanced Longevity Studies**

**Advanced Longevity Studies:** 

 Investigate aging issues originated by particles with different ionization powers to properly represent the long-term gaseous detector behavior in real experiments:

<sup>241</sup>Am: 5.6 *MeV* α - particle and <sup>55</sup>Fe: 5.9 *keV* X-rays

Detector under test:

GEM 10 × 10 cm<sup>2</sup> prototype irradiated in two different sectors

Method to accelerate the aging:

Contaminate the gas mixture with pollutants (hydrocarbons and Si - based molecules)

SEM and EDS analysis to study polymer density around GEM holes

### X - rays irradiated hole



 Perfectly clean surface on the bottom side

### lpha - particles irradiated hole



Si deposits on the entire top and bottom surface with larger structure in a strip of  $10 - 15 \,\mu m$  around the holes

### NO degradation of the effective gas gain and energy resolution



GEM 10x10 prototype